

model_CA_MM.R

atchirc

Mon May 22 22:49:50 2017

```
library(MASS)
library(car)
library(DataCombine)  # Pair wise correlation
library(stargazer)
library(dplyr)        # Data aggregation
library(glmnet)
source('../atchircUtils.R')

data <- read.csv('../intrim/eleckart.csv')

# KPI selection
# units, product_mrp, list_mrp, COD, Prepaid are factors
# Insig : Affiliates corr OnlineMarketing
# Insig : Radio corr Other
# Insig : Digital, ContentMarketing corr SEM
# delivery(b/c)days are corr, lets choose deliverydays
# will use marketing levers rather TotalInvestment

# Filter significant KPIs
model_data <- subset(data, product_analytic_sub_category=='CameraAccessory',
  select = -c(product_analytic_sub_category,product_mrp,
    units,COD,Prepaid,deliverybdays,
    TotalInvestment,Affiliates,Radio,Digital,
    ContentMarketing,sla,procurement_sla))

model_data_org <- model_data
model_data[,c(8:12)] <- model_data[,c(8:12)]*10000000

# # *****
# #           FEATURE ENGINEERING -PASS2  ----
# # *****
#
# # . . . . List Price Inflation ----
model_data$chnglist <- c(0,diff(model_data$list_mrp))
#
# # . . . . Discount Inflation ----
model_data$chngdisc <- c(0,diff(model_data$discount))
#

model_data$chngdisc <- min(model_data$chngdisc)*-1+model_data$chngdisc
model_data$chnglist <- min(model_data$chnglist)*-1+model_data$chnglist
model_data <- log(model_data+0.01)
```

*

****PROCs:****

Linear, Ridge and Lasso Model are wrapped with abstract functions. This would facilitate readable code for model building and Model optimization. Set Class definitions

```
setOldClass('elnet')
setClass(Class = 'atcglmnet',
  representation (
    R2 = 'numeric',
    mdl = 'elnet',
    pred = 'matrix'
  )
)
```

```
setOldClass('lm')
setClass(Class = 'atclm',
  representation (
    R2 = 'numeric',
    mdl = 'lm',
    pred = 'matrix'
  )
)
```

Finding min lambda from 1000 iterations Function to find Min Lambda using bootstrap method. minlambda identified over 1000 cross validation trails. observed minlambda used for Ridge and Lasso regression.

```
findMinLambda <- function(x,y,alpha,folds) {
  lambda_list <- list()
  for (i in 1:1000) {
    cv.out <- cv.glmnet(as.matrix(x), as.vector(y), alpha=alpha,
                       nfolds=folds)
    lambda_list <- append(lambda_list, cv.out$lambda.min)
  }
  return(min(unlist(lambda_list)))
}
```

Linear Model with Regularization Wrapper function for Ridge and Lasso regression. functions performs Ridge/Lasso regression and returns R2, Model and Predicted values as **atcglmnet** object

```
atcLmReg <- function(x,y,l1l2,folds) {
  # l1l2 = 0 for L1, 1 for L2

  if (l1l2) { # Lasso/L2
    min_lambda <- findMinLambda(x,y,1,folds)
  } else { # Ridge/L1
    min_lambda <- findMinLambda(x,y,0,folds)
  }
  mdl <- glmnet(x,y,alpha=l1l2,lambda = min_lambda)
```

```

pred      <- predict(mdl,s= min_lambda,newx=x)

# MSE
mean((pred-y)^2)
R2 <- 1 - (sum((y-pred )^2)/sum((y-mean(pred))^2))
return(new('atcglmnet', R2 = R2, mdl=mdl, pred=pred))
}

```

*

MODELING

```
# Prune KPI as part of model optimization
model_data <- na.omit(model_data)
model_data <- subset(model_data,select=-c(list_mrp,discount))
```

Linear Model:

```
mdl <- lm(gmv~., data=model_data)
step_mdl <- stepAIC(mdl,direction = 'both',trace = FALSE)

stargazer(mdl,step_mdl, align = TRUE, type = 'text',
           title='Linear Regression Results', single.row=TRUE)
```

```
##
## Linear Regression Results
## =====
##                               Dependent variable:
##                               -----
##                               gmv
##                               (1)           (2)
## -----
## week                -0.235 (0.285)
## deliverycdays       -0.119 (0.084)        -0.136** (0.057)
## n_saledays          -0.001 (0.060)
## TV                  -0.643** (0.313)       -0.653** (0.283)
## Sponsorship         0.588** (0.261)       0.526*** (0.179)
## OnlineMarketing     1.995*** (0.395)       1.914*** (0.358)
## SEM                 -0.335 (0.433)
## Other               -0.003 (0.015)
## NPS                 9.869** (4.818)       11.530*** (3.969)
## chnglist            0.058 (0.042)         0.071* (0.038)
## chngdisc            0.209 (0.139)         0.260** (0.124)
## Constant            -213.925** (104.158)  -252.450*** (83.660)
## -----
## Observations                52                52
## R2                        0.847                0.842
## Adjusted R2                0.804                0.817
## Residual Std. Error    0.910 (df = 40)        0.881 (df = 44)
## F Statistic            20.079*** (df = 11; 40) 33.462*** (df = 7; 44)
## =====
## Note:                      *p<0.1; **p<0.05; ***p<0.01
```

```
knitr::kable(viewModelSummaryVIF(step_mdl))
```

var	Estimate	Std.Error	t-value	Pr(> t)	Significance	vif
chngdisc	0.26042	0.12420	2.097	0.04180	*	1.365202
chnglist	0.07073	0.03778	1.872	0.06782	.	1.372248
deliverycdays	-0.13582	0.05695	-2.385	0.02145	*	1.487389
NPS	11.53024	3.96942	2.905	0.00573	**	6.204565
OnlineMarketing	1.91367	0.35832	5.341	3.11e-06	***	17.883660

var	Estimate	Std.Error	t-value	Pr(> t)	Significance	vif
Sponsorship	0.52639	0.17902	2.940	0.00521	**	2.682262
TV	-0.65322	0.28275	-2.310	0.02563	*	10.383976

```
pred_lm <- predict(step_mdl, model_data)
```

Regularized Linear Model:

```
x = as.matrix(subset(model_data, select=-gmv))
y = as.vector(model_data$gmv)


ridge_out <- atcLmReg(x,y,0,3) # x, y, alpha, nfolds
lasso_out <- atcLmReg(x,y,1,3) # x, y, alpha, nfolds
```

*

PLOTTING MODEL RESULTS

Plot Model prediction and base sales:

```
plot(model_data$gmvs, main = 'CameraAccessory Multiplicative Model - Final',
     xlab='week', ylab='PredictGMV')
lines(model_data$gmvs)
lines(pred_lm, col='red', lwd=2)
lines(ridge_out@pred, col='green', lwd=2)
lines(lasso_out@pred, col='blue', lwd=2)
lines(step_md1$coefficients['(Intercept)'] + step_md1$coefficients['week'] * model_data$week,
     lty=2, lwd=2, col='red')
lines(ridge_out@mdl$a0 + ridge_out@mdl$beta['week', 1] * model_data$week,
     lty=2, lwd=2, col='green')
lines(lasso_out@mdl$a0 + lasso_out@mdl$beta['week', 1] * model_data$week,
     lty=2, lwd=2, col='blue')
legend('topright', inset=0, legend=c('GMV', 'LM', 'LM+L1', 'LM+L2'), horiz = TRUE,
     lwd = 2, col=c(1:4), cex = 0.5)
```



*

*Model Coefficients:**

```
coeff_lm <- as.data.frame(as.matrix(coef(step_md1)))
coeff_l1 <- as.data.frame(as.matrix(coef(ridge_out@mdl)))
coeff_l2 <- as.data.frame(as.matrix(coef(lasso_out@mdl)))
```

```
lm_df=data.frame('x'=rownames(coeff_lm),'y'=coeff_lm)
colnames(lm_df) = c('coeff','lm')
l1_df=data.frame('x'=rownames(coeff_l1),'y'=coeff_l1)
colnames(l1_df)= c('coeff','l1')
l2_df=data.frame('x'=rownames(coeff_l2),'y'=coeff_l2)
colnames(l2_df) <- c('coeff','l2')
```

```
smry <- merge(lm_df,l1_df,all = TRUE)
smry <- merge(smry,l2_df,all=TRUE)
```

```
print(smry)
```

##		coeff	lm	l1	l2
## 1	(Intercept)	-252.44951515	2.4421263441	-2.079449e+02	
## 2	chnghdisc	0.26041855	0.3366289752	2.106677e-01	
## 3	chnghlist	0.07072628	0.0912928979	5.821151e-02	
## 4	deliverycdays	-0.13581758	-0.0274385679	-1.140778e-01	
## 5	n_saledays	NA	0.0212336244	0.000000e+00	
## 6	NPS	11.53023534	0.0311621679	9.596589e+00	
## 7	OnlineMarketing	1.91367470	0.6715420291	1.955293e+00	
## 8	Other	NA	-0.0008964057	-2.923578e-03	
## 9	SEM	NA	-0.1929148456	-3.235943e-01	
## 10	Sponsorship	0.52639403	0.3781702734	5.747898e-01	
## 11	TV	-0.65321728	0.1197003060	-6.125896e-01	
## 12	week	NA	-0.0275379571	-2.334996e-01	

```
print(paste0('Ridge regression R2 : ',ridge_out@R2))
```

```
## [1] "Ridge regression R2 : 0.799735454911694"
```

```
print(paste0('Lasso regression R2 : ',lasso_out@R2))
```

```
## [1] "Lasso regression R2 : 0.846611423521393"
```

```
print(paste0('Linear Mode R2 : ',getModelR2(step_md1)))
```

```
## [1] "Multiple R-squared: 0.8419,\tAdjusted R-squared: 0.8167 "
```

```
## [1] "Linear Mode R2 : Multiple R-squared: 0.8419,\tAdjusted R-squared: 0.8167 "
```

*

Significant KPI

Lasso(LM+L1) regression results a simple explainable model with significant KPIs as Discount Inflation, Deliverycday, sale days, Sponsorship Discount, week, NPS

Model Optimization

```
# coeff      lm          l1          l2
# 1      (Intercept) -291.1095142 -1.156524e+02 -3.247125e+02
# 2      chngdisc    0.2976528  4.529978e-01  3.005713e-01
# 3      chnglist      NA  4.156542e-02 -1.160978e-02
# 4      deliverycdays      NA  5.492330e-02  3.127685e-02
# 5      discount      NA -1.493296e+00 -1.307761e-02
# 6      list_mrp     3.4394110  2.980721e+00  3.721846e+00
# 7      n_saledays      NA  2.042750e-02  6.727983e-03
# 8      NPS      10.0904759  2.763048e+00  1.133940e+01
# 9      OnlineMarketing  1.3481222  4.963282e-01  1.269501e+00
# 10     Other      NA  8.074312e-03  1.067699e-02
# 11     SEM      NA  5.195209e-02  2.492818e-01
# 12     Sponsorship  0.2671538  2.217135e-01  1.930656e-01
# 13     TV      -0.2953724  1.322017e-01 -1.901196e-01
# 14     week      NA  6.922926e-02 -4.158001e-02
# [1] "Ridge regression R2 : 0.907781713555186"
# [1] "Lasso regression R2 : 0.92785868141555"
# [1] "Multiple R-squared:  0.9245,\tAdjusted R-squared:  0.9145 "
# [1] "Linear Mode      R2 :
#      Multiple R-squared:  0.9245,\tAdjusted R-squared:  0.9145 "
```

```
# coeff      lm          l1          l2
# 1      (Intercept) -252.44951515 -2.209457934 -2.079449e+02
# 2      chngdisc    0.26041855  0.335460607  2.106677e-01
# 3      chnglist    0.07072628  0.090937642  5.821151e-02
# 4      deliverycdays -0.13581758 -0.029507054 -1.140778e-01
# 5      n_saledays      NA  0.021263335  0.000000e+00
# 6      NPS      11.53023534  0.248190242  9.596589e+00
# 7      OnlineMarketing  1.91367470  0.701215112  1.955293e+00
# 8      Other      NA -0.001003973 -2.923578e-03
# 9      SEM      NA -0.204127587 -3.235943e-01
# 10     Sponsorship  0.52639403  0.385357456  5.747898e-01
# 11     TV      -0.65321728  0.105757500 -6.125896e-01
# 12     week      NA -0.035989462 -2.334996e-01
# [1] "Ridge regression R2 : 0.802021944242947"
# [1] "Lasso regression R2 : 0.846611423521393"
# [1] "Multiple R-squared:  0.8419,\tAdjusted R-squared:  0.8167 "
# [1] "Linear Mode      R2 :
#      Multiple R-squared:  0.8419,\tAdjusted R-squared:  0.8167 "
```