SALES QUOTATION

TO **PARTIDO STATE UNIVERSITY**
GOA CAMARINES SUR

ATTENTION : ENGR. KIER P. GASGA
RESEARCH AND DEVELOPMENT COORDINATOR

DATE : JANUARY 4, 2022

REFERENCE NUMBER: 2022-001

DEAR ENGR. GASGA

Please find below my formal quotation for one-unit **VARIOUS LABORATORY EQUIPMENT**

NO.	DESCRIPTION	QTY.	UNIT PRICE	TOTAL PRICE IN PESO
1	**PN: 840-341400** **BRAND: THERMO SCIENTIFIC** **ORIGIN: USA** **MODEL: EVOLUTION ONE UV-VIS SPECTROPHOTOMETER**  **Features:** ~ Up to 100 Hz data acquisition for single cell kinetics ~ Complete line of Peltier temperature control accessories ~ Adjustable cell holder for optimum cell positioning ~ Numerous accessories for liquid and solid sampling ~ Performance Verification and optional software and documentation for regulated laboratories **INSIGHT Software Features:** ~ Software control available in English, French, German, Italian, Spanish, Polish, Portuguese, Russian, Japanese and Chinese language ~ Live Display offers walk-up simplicity for real time single wavelength measurements or quick identification of a sample		**PHP. 800,888.00**	**PHP. 800,888.00**

	peak ~ Next-generation Quantification package makes quantitative analysis straightforward ~ Advanced Fixed wavelength analysis with graphical data display and user defined limits ~ Integrated calculations provide more data per measurement in Scan, Fixed and Quant ~ Wavelength scanning application with advanced tools for peak analysis and spectral processing ~ Advanced kinetics features including multi-stage measurement, temperature ramping and comprehensive data fitting options ~ Automated file export and e-mailing of data ~ Seamless paper-based reporting with user defined parameters ~ Workbook and template scheme makes data organization easy ~ CUE software for customized user interface and workflows **TECHNICAL SPECIFICATIONS** **Instrument Specifications:** **Optical Design:** Double Beam with sample and reference cuvette positions; Czerny-Turner Monochromator **Spectral Bandwidth:** 1 nm **Light Source:** Xenon flash lamp, 3-year warranty **Detector:** Dual Silicon Photodiodes **Scan Ordinate Modes:** Absorbance, % Transmittance, % Reflectance, Kubelka-Munk, log (1/R), log (Abs), Abs*Factor, Intensity **Resolution:** >1.8 (Toluene in Hexane) **Wavelength Range:** 190 –1100 nm **Wavelength Accuracy:** ± 0.5 nm (541.9, 546.1 nm mercury line) ± 0.8 nm (full range) **Wavelength Reproducibility**: ≤ 0.05 nm (546.1 nm mercury line, SD of 10 measurements) **Scanning Speed:** <1 to 6000 nm/min; continuously variable **Slew Speed:** 31,000 nm/min **Data Intervals:** 10, 5, 2, 1, 0.5, 0.2, 0.1 nm **Photometric Range:** > 3.5 Abs **Photometric Accuracy:** 1A: ± 0.006A; 2A: ± 0.010A; (440 nm; traceable neutral density filters) **Photometric Repeatability:** ± 0.0002A **Noise:** 0A: ≤ 0.00015 A; 1A: ≤ 0.00025 A; 2A: ≤ 0.00080 A; (260 nm, 1.0 nm SBW, RMS) **Drift**: < 0.0005 A/hr (500 nm, 1.0 nm SBW, 1 hour warm-up) **Stray light:** ≤ 1% T at 198 nm (KCl), ≤ 0.05% T at 220 nm (NaI), ≤ 0.05% T at 340 nm (NaNO2) **Baseline flatness**: ±0.0010 A (200-800 nm; 1.0 nm SBW, smoothing) **Keypad:** Sealed Membrane			

	Operating System: Microsoft Windows 7, Windows 8, Windows 10 **Dimensions:** 62.2 x 48.6 x 27.9 cm (24 x 19 x 11 in) L x W x H **Weight:** 14.4 kg (32 lb) **Electrical Supply:** 100 – 240 V, 50 – 60 Hz, Selected Automatically; 150 W maximum **Includes the following accessories** ITS PH PC and Printer ITS PH Pair of Cuvette			
2	**PN: HH35000300** **BRAND: PERKINELMER** **ORIGIN: USA** **MODEL: VICTOR NIVO 3F MULTI-LABEL MICROPLATE READERS, CAPABLE OF LUMINESCENCE, FLUORESCENCE INTENSITY (TOP & BOTTOM) & ABSORBANCE READING**  Building on our family of benchtop multimode plate readers, the VICTOR Nivo™ system packs all popular detection modes into the industry's smallest multimode reader footprint. The perfect microplate reader for everyday biochemical and cell-based assays, it measures at any wavelength, with top and bottom reading of all technologies. Its software interface is easy to learn and use, and lets you control the instrument from almost any device – perfect for multiuser environments. Combine with our assays and reagents to get you started right away.	**1**	**PHP. 2,500,888.00**	**PHP. 2,500,888.00**

	Following items are already included with the instrument configuration (for more technical features, please refer to the seller's guide): • **Standard Filter Set** • 405/10nm for Absorbance (HH35000**901**) • 480/30nm Excitation (HH35000**902**) & 530/30nm Emission (HH35000**903**) for FITC Fluorescence Intensity • 700nm IR-cut-off for Luminescence (HH35000**904**) • 50/50 general beam splitter (HH35000**970**) • Browser-based control software • WiFi router and network LAN cable for remote control • MyAssays Desktop data analysis software (Standard license, 1 Seat) (HH3500**1720**)* The VICTOR Nivo™ is a high-performance filter-based multimode plate reader system equipped with all major detection technologies – absorbance, luminescence, fluorescence intensity, time-resolved fluorescence and fluorescence polarization. It is a compact, light-weight instrument designed for life science research laboratories performing routine low-throughout assays, or assay development work, and with diverse application requirements. The system's software has a modern, workflow-oriented user interface which is easy to learn and includes pre-defined application protocols to get users productive quickly. In addition, MyAssays Desktop Standard software is provided for data analysis. The browser-based control software is independent of operating system, so it can be controlled via a laptop, PC or touchscreen device, for example Windows or Mac OS PCs or Android tablets. The system can be operated via Wi-Fi or a network connection, enabling experiments to be set-up, run and monitored remotely, such as from outside a biosafety cabinet or from a neighboring lab. **Detection Technologies** The system incorporates a dynamic wheel system with space for storage of up to 32 filters, providing ready access to filters for a large number of dyes. Filters are exchanged between the inner and outer filter wheels, so any individual filter can serve either excitation or emission lightpaths. As a result, there's no need to install new filters when switching between assays, and filters can be locked within the system so they can't be mislaid in the lab – ideal for multi-user environments.			

	When fully-loaded, the filter system provides the flexibility to detect many dyes with better sensitivity and greater cost-effectiveness compared to a monochromator. When fully-loaded, the filter system provides the flexibility to detect many dyes with better sensitivity and greater cost-effectiveness compared to a monochromator. For absorbance measurements, there is a choice of either a filter- or a spectrometer-based system. Full spectrum absorbance measurements are ultra-fast – 230 to 1000 nm at selectable resolutions (2.0 nm, 5.0 nm, 10 nm) in less than one second per well. The spectrometer system also allows for the detection of a wide range of dyes or measurement of samples with unknown absorbance spectra. **Key Features** • Top and bottom reading of all standard technologies for plate formats from 1- to 1536-wells • Compact, lightweight instrument which frees-up bench space and is easy to move into a biosafety cabinet or another lab • Internal dynamic filter wheel system, with space for up to 32 filters • For absorbance, choice of filter-based detection for best sensitivity or spectrometer for wavelength flexibility • Browser-based software enables control from a variety of devices – PC, laptop, or tablet • Can be controlled via network or Wi-Fi to facilitate remote working and data access • Optional dispenser for applications such as fast kinetics, flash luminescence, or dual addition assays • Integrated temperature control and optional gas control unit to keep cells healthy during long term kinetic assays			

	GENERAL SPECIFICATIONS Dimensions: Width: 20 cm (8 in), Depth: 50 cm (19.5 in), Height (without dispenser): 26.5 cm (10.5 in) Weight: 13 kg (29 lbs) without dispenser, 15 kg (33 lbs) with dispenser Plate Formats: 1- to 1536-wells Environmental Control: Temperature: 3 °C above ambient up to 65 °C (0.1 °C increments); Gas (*optional*): CO_2: 0% – 20% (<0.1% accuracy), O_2: 1% – 20% (<0.1% accuracy) Shaking: Linear, orbital and double orbital modes Dispenser (*optional*): 2 Injectors, 500 µl each syringe, manual rinsing and priming control Operation: Operating environment: 15 °C – 35 °C, < 80 % humidity; Power supply: 110 – 230 V, 50/60 Hz; Power consumption: 100 W Connections: Connection: LAN, USB; Remote Control: Wi-Fi (modem included); LAN network Operating System: Windows (Laptop / PC) ; iOS (Mac) ; Android (tablet) Spectrometer: Absorbance only; Wavelength range: Filter or Spectrometer for Absorbance; Variable bandwidth: 230 nm – 1000 nm (1.0 nm increments), 2.0 nm, 5.0 nm, 10 nm Detector: Flexible measurement height: 0 mm – 16 mm; Wavelength range (Emission): 230 nm – 850 nm Flash Lamp: Wavelength range (Excitation): 230 nm – 1000 nm **PERFORMANCE SPECIFICATIONS** / **96-well Microplate** / **384-well Microplate** Absorbance Filter: OD range: 0 – 4 OD / 0 – 4 OD; OD accuracy: < 2.0 % (OD 2) / < 2.0 % (OD 2) Absorbance Spectrometer: OD range: 0 – 2 OD / 0 – 2 OD; OD accuracy: < 2.0 % (OD 2) / < 2.0 % (OD 2) Luminescence: Sensitivity (Top Reading): 50 amol* / —; Dynamic range: 6 log / 6 log Fluorescence Intensity: Sensitivity (Top Reading): 0.5 fmol / 0.01 fmol; Sensitivity (Bottom Reading): — / 0.06 fmol Time-resolved Fluorescence: Sensitivity (Top Reading): 2.25 amol / 0.5 amol Fluorescence Polarization: Sensitivity (Top Reading): 3 mP / 3 mP *ATP detected by VICTOR Nivo with dispenser **DETECTION MODALITY** / **VICTOR Nivo 3F/3S** / **VICTOR Nivo 5F/5S** / **Standard Features** / **Optional Extras** Absorbance: Filter-based (F) or Spectrometer (S): • / • Luminescence: • / • Fluorescence Intensity: • / • Time-resolved Fluorescence: / • Fluorescence Polarization: / • Standard Features: Top and bottom detection of all technologies for plate formats up to 1,536-wells; Temperature control up to 65°C; Shaker with three modes (linear, orbital, and double orbital); Browser-based control software; Wi-Fi modem for remote control; MyAssays Desktop Standard analysis software Optional Extras: Dispenser (dual injectors); Gas control (CO_2 and O_2); 15-in. laptop or 12-in. tablet; MyAssays Desktop Pro analysis software; Test plate for alignment and system check			
3	**PN: 560-91309-20** **BRAND: HEIDOLPH** **ORIGIN: GERMANY** **MODEL: HEI-VAP SILVER 6 PACKAGE WITH VACUUM PUMP** **The Hei-VAP Value Digital rotary evaporators with hand lift are optimally suited for all standard applications with a digital display for set and actual heating bath temperature.** ✓ The convenience of large dial controls for adjustment of rotation speed and bath temperature ✓ Adjust the required angle of the evaporating flask individually according to your needs ✓ Limit the height of your evaporating flask in just seconds	**1**	**PHP. 500,888.00**	**PHP. 500,888.00**

	✓ The patented flask clamp Easy-Clip allows a simple and safe removing of the evaporating flask due to the force of unscrewing the Easy-Clip ✓ For your protection, the detachable operating panel is located below the bath and outside ✓ the danger zone. To conveniently run your unit from outside a fume hood, detach your panel and place it in your preferred location Intelligent evaporation with Heidolph rotary evaporators: overheat protection design that prevents water baths running dry, provides a detachable panel for superior ease of use from outside closed fume hoods and offers a proven vacuum seal and vapor tube system guaranteed for years of operation! **TECHNICAL SPECIFICATIONS** **Rotation speed indicator** scale / digital **Permissible ambient conditions** 5 – 31 °C at 80 % rel. humidity 32 – 40 °C decreasing lineary up to max 50% rel. humidity **Protection class DIN EN 60529** IP 20 **Lift** Hand lift **Height adjustment** speed manual **Height adjustment** 155 mm **Drive** brushless DC motor with electronic speed control **Heating capacity** 1,300 W **Temp. range heating bath** 20 - 210 °C **Temperature accuracy bath** ±1 K **Overheat protection bath cut-off** at 5 °C over set temperature via separate PT 1000 **Bath temperature setting** scale / digital **Heating bath temperature** control electronic / digital **Secondary overtemp**. cut off 250 °C **Material heating bath** stainless steel AISI 316L **Diameter heating bath** 255 mm **Volume heating bath** 4.5 liters **Display vapor temperature** - **Required accessories for display vapor Temperature** - **Integrated vacuum controller** - **Timer** 1 **Vacuum program SET pressure** - **Vacuum program AUTOeasy** - **Vacuum program AUTOaccurate requires** – AUTOaccurate sensor Remote control function Lift - **Remote control function** - Start rotation 1 **Remote control function** - Start vacuum - **Remote control function** - Start heating bath 1			

	Programmable ramps - **Supply Power** 1,400 W **Weight without glassware assembly** 16 kg **Dimensions with glassware set G3 (l/w/h)** (l) 477 mm x (w) max. 739 mm x (h) 845 mm **Dimensions with glassware set G3 XL** (l/w/h) (l) 477 mm x (w) max. 739 mm x (h) 920 mm **Condensing surface** 1,400 cm² **Condensing surface XL condenser** 2,200 cm² **Max. size evaporating flask** 5 liters **Display** yes **Rotation speed range** 10 - 280 rpm For Hei-VAP Precision Vacuum Pump **Recommended for solvents with low or medium boiling points**			
4	**PN: ABJ-220-4NM** **BRAND: KERN** **ORIGIN: GERMANY** **MODEL: ABJ-220-4NM, ANALYTICAL BALANCE WITH TYPE APPROVAL, CLASS I 0,0001 G; 220 G**  **TECHNICAL SPECIFICATIONS** **Max Capacity:** 220g **Readout** 0.1 mg **Min. load:** 10 mg **Reproducibility:.**1mg **Linearity:** ± 0.3mg **Permissible Ambient Temp.:**10-30°C **Permissible Ambient Humidity:** 80%Rh **Display Type:** LCD with backlight **Display digit height:** 14mm **Weighing Space(w x d x h)mm:** 190 x 155 x 225mm **Material Casing:** Plastic **Net Weight:** 6kg **Material weighing plate:** stainless steel **Internal Calibration control.** Quick setting of the balances accuracy with internal adjusting weight (motor-driven). **-External Calibration.** For quick setting of the balance	**1**	**PHP. 95,888.00**	**PHP. 95,888.00**

	accuracy. External adjusting weight required. **-Piece Counting.** Reference quantities selectable. Display can be switched from piece to weight. **-Metal housing robust and sturdy** **-Percentage determination.** Displays the deviation from the reference weight (100%) in % instead of grams.			
5	**PN: 3581200** **BRAND: IKA** **ORIGIN: GERMANY** **MODEL: C-MAG HS 7**  **Technical Specifications** **New magnetic stirrer with heating and ceramic heating plate which offers excellent chemical resistance.** - Powerful motor for stirring quantities of up to 10 l (H2O) - Fixed safety circuit of 550 °C - Hot Top indicator >> hot surface warning to prevent burns! - Exact temperature setting via digital display (LED) - Bushing according to DIN 12878 for connecting a contact thermometer, e.g. ETS-D5, enables precise temperature control - Digital error code display - Elevated control panel for protection against leaking liquids Accessories: ETS-D5, H 38 Holding rod, H 44 Boss head clamp, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 15 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 40 Magnetic stirring bar, IKAFLON® 50 Magnetic stirring bar, IKAFLON® 80 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, TRIKA® 40 Magnetic stirring bar, RS 1 Set of magnetic stirring bars, RSE Stirring bar remover, H 16 V Support rod **Technical Specifications** **Number of stirring positions** 1	**2**	**PHP. 38,888.00**	**PHP. 77,776.00**

	Stirring quantity max. per stirring position (H2O) [l] 10 **Stirring quantity max**. (H2O) [l] 10 **Motor rating input** [W] 15 **Motor rating output** [W] 1.5 **Speed display** scale **Speed range** [rpm] 100 - 1500 **Stirring bar length max**. [mm] 80 **Heat output** [W] 1000 **Heating rate** (1 l H2O in H15) [K/min] 5 **Heating temperature range** [°C] 50 - 500 **Heat control** LED **Heat control accuracy** [±K] 10 **Speed control scale** 0 - 6 **Fixed safety circuit** [°C] 550 **Connection for ext. temperature sensor** ETS-D5 **Control accuracy with sensor** [±K] 3 **Temperature constancy in medium** [±K] 3 **Set-up plate material** ceramic **Set-up plate dimensions [mm]** 180 x 180 **Dimensions (W x H x D) [mm]** 220 x 105 x 330 **Weight** [kg] 5 **Permissible ambient temperature** [°C] 5 - 40 **Permissible relative moisture** [%] 80 **Protection class according to DIN EN 60529** IP 21 **Voltage [V]** 230 **Frequency [Hz]** 50/60 **Power input [W]** 1020			
6	**PN: 1401** **BRAND: HETTICH** **ORIGIN: GERMANY** **MODEL: HETTICH UNIVERSAL 320 CENTRIFUGE**  The UNIVERSAL 320 is particularly easy to use: • The operating and display elements of the centrifuge are of ergonomic design • The current status of all parameters is displayed while the centrifuge is running • 10 programmable memories • Switching between the display of speed and the RCF (relative centrifugal force) after entry of the rotor radius in mm	**1**	**PHP. 475,888.00**	**PHP. 475,888.00**

	• Parameters can be quickly and easily entered and changed using the rotary button The UNIVERSAL 320 contributes to safe working procedures in the laboratory. It has the following features: • Lid locking • Emergency lid release • Motor overheating protection • Imbalance shut off • Automatic rotor recognition • Lid dropping protection • Chamber overheating protection The UNIVERSAL 320 is a practical benchtop centrifuge with an ergonomic design. It is manufactured from high-quality components and has the following features: • Metal casing • Metal lid • Centrifugation chamber of rust-free stainless steel • View port in the lid **TECHNICAL SPECIFICATIONS:** **Max. Capacity** 4 x 100 mL -or- 32 x 15 mL **Max. RPM/RCF** 15,000/21,382 **Temperature Control** N/A **Dimensions** 346 x 401 x 695 mm 13.5" x 15.75" x 27.25" **Weight** 53 kg (117 lbs) **Cat. No. 240V** 1401			
7	**PN: 1406** **Brand: HETTICH** **Origin: GERMANY** **Model: UNIVERSAL 320R REFRIGERATED CENTRIFUGE** 	**1**	**PHP. 650,888.00**	**PHP. 650,888.00**

	The UNIVERSAL 320 R is particularly easy to use: • The operating and display elements of the centrifuge are of ergonomic design • The current status of all parameters is displayed while the centrifuge is running • 10 programmable memories • Switching between the display of speed and the RCF (relative centrifugal force) after entry of the rotor radius in mm • Parameters can be quickly and easily entered and changed using the rotary button The UNIVERSAL 320 R contributes to safe working procedures in the laboratory. It has the following features: • Lid locking • Emergency lid release • Motor overheating protection • Imbalance shut off • Automatic rotor recognition • Lid dropping protection • Chamber overheating protection The UNIVERSAL 320 R is a practical benchtop centrifuge with an ergonomic design. It is manufactured from high-quality components and has the following features: • Metal casing • Metal lid • Centrifugation chamber of rust-free stainless steel • View port in the lid **TECHNICAL SPECIFICATIONS:** **Max. Capacity** 4 x 100 mL -or- 32 x 15 mL **Max. RPM/RCF** 15,000/21,382 **Temperature Control** -20 °C to +40 °C **Dimensions** 346 x 401 x 695 mm 13.5" x 15.75" x 27.25" **Weight** 53 kg (117 lbs) **Cat. No. 240V** 1406 **CENTRIFUGE SYSTEM COMES WITH FF:**			

	Speed Range: Fixed Angle: 15,200 x g (with 30 x 2 mL rotor), Swing-Out: 6000 x g (with BIOShield 1000A rotor) Maximum RCF: Fixed Angle: 25830 x g (with 30 x 2 mL rotor), Swing-Out: 7164 x g (with BIOShield 1000A rotor) Capacity: Max in TX-1000: 196 5/7mL blood tubes, 148 9/10 mL blood tubes, 96 15mL conical tubes, 40 50mL conical tubes, 6 microplates; 4 x 1000 mL BioBottles (with TX-1000 rotors)			
8	**PN: 543-22332-00** **BRAND: HEIDOLPH** **ORIGIN: GERMANY** **MODEL: PROMAX 1020 INCUBATOR 1000**  **TECHNICAL SPECIFICATIONS** Incubator 1000 This truly unique system enables you to perform a number of functions simultaneously - shaking, mixing and heating with visual reaction control. The incubating model The Promax 1020 is a medium-sized model and accepts load capacities of 5 kg Wide range of accessories, attachments and clamps for separatory funnels available With a stroke length of 32 mm the Promax model performs an ideal motion for separatory funnels Set and continuously adjust the variable speed on the digital display from 30 to 250 rpm This model is suitable for the modular incubator system and is recommended for applications which require variable temperature control up to 65 °C A digital process timer allows for unattended operation and can be set from 1 to 999 minutes. When the set time has elapsed **High hood** Recommended especially for large flasks and media bottles, Erlenmeyer flasks up to 500 ml and mediumsized or large common vessels. The high incubator hood has a total height of 267 mm. **Heating module** Heating capacity of 300 W allows for quick temperature adjustments	**1**	**PHP. 250,888.00**	**PHP. 250,888.00**

	Digital temperature settings up to 65 °C and separate display for actual temperature To protect your sample from thermal damages this unit features a safety circuit to prevent overheating Electrical heater comes with low-noise blower and provides accuracy of ± 2 °C up to 50 °C and ± 4 °C over 50 °C **Motion** reciprocating **Rotation speed range** 30 - 250 rpm **Operating** Modetimer or continous **Orbit / Stroke** 32 mm **Timer** Yes **Power input** 50 W **Platform size** 290 x 258 mm **Max. Load** 5 kg **Overheat protection** self-resetting **Protection class DIN EN 60529** IP 40			
9	**PN: UN55** **BRAND: MEMMERT** **ORIGIN: GERMANY** **MODEL: UNIVERSAL OVEN, 55 LITERS**  **TECHNICAL SPECIFICATIONS** **Control of standard components** **Temperature** : 1 Pt100 sensor DIN class A in 4-wire-circuit **Control COCKPIT:** adaptive multifunctional digital PID-microprocessor controller with high-definition TFT-colour display **Timer**: Digital backwards counter with target time setting, adjustable from 1 minute to 99 days **Temperature** **Set temperature range in °C** : min. 5°C above ambient up to +300°C resolution of display for set point values 0.1°C up to 99.9°C, 0.5°C from 100°C and for actual values 0.1°C (LED) **Control technology** **Function Set point WAIT** : the process time does not start until the set temperature is reached **Language Setting**: German/English/Spanish/French **Calibration:** three freely selectable temperature values adjustable parameters temperature (Celsius or Fahrenheit), air flap position, programmed time, time zones, summertime/wintertime **Ventilation**	**1**	**PHP. 180,888.00**	**PHP. 180,888.00**

	Natural convection **Fresh Air admixture**: adjustment of pre-heated fresh air admixture by air flap control in 10 % steps **Vent**: vent connection with restrictor flap **Communication** **Documentation**: programmed stored in case of power failure **Programming** : Atmo CONTROL software for reading out, managing and organizing the data logger via Ethernet interface (temporary trial version can be downloaded). USB stick with Atmo CONTROL software available as accessory (on demand). **Safety** **Temperature control** : adjustable electronic over temperature monitor and mechanical temperature limiter TB, protection class 1 according to DIN 12880 to switch off the heating approx. 20°C above nominal temperature **Auto diagnostic:** system for fault analysis **Standard equipment** **Scope of delivery**: incl. works calibration certificate for +160°C **Door**: fully insulated stainless steel door with 2-point locking (compression door lock) **Housing:** rear zinc-plated steel I**nterior**: easy-to-clean interior ,made of stainless steel, reinforced by deep drawn ribbing with integrated and protected large-area heating on four sides **Internals:** 1 stainless steel grid **Stainless steel interior** **Max. Loading of chamber:** 80 kg **Dimensions W x H x D in mm w(A) x h(B) x d(C):** 400 x 400 x 330 mm **Volume** 53 **Textured stainless steel casing** **w(D) x h(E) x d(F):** 585 x 784 x 514 mm **Electrical data** **Voltage Electrical load** 230 V, 50/60 Hz **approx.** 2000 W **Voltage Electrical load** 115 V, 50/60 Hz **approx.** 1700 W			
10	**PN: BSC-1500IIA2-X** **BRAND: BIOBASE** **ORIGIN: CHINA** **MODEL: MODEL: BIOLOGICAL SAFETY CABINET CLASS II A2** 	**1**	**PHP. 400,888.00**	**PHP. 400,888.00**

TECHNICAL SPECIFICATIONS

Model	BSC-1500IIA2-X
Internal size(mm)n (W*D*H)	1300*700*630
External size(mm) (W*D*H)	1500*840*2280
Tested Opening	Safety Height ≤ 200mm
Working Opening	400mm
Inflow Velocity	0.53±0.025 m/s
Down Flow Velocity	0.33±0.025 m/s
HEPA Filter	Two , efficiency 99.999%@0.3 microns
Front Window	Motorized, Two-layer toughened glass >5mm
Noise	EN12469≤58dB / NSF≤61dB
UV lamp	30W*1
Fluorescent Lamp	28W*2
Illumination	≥1000Lux
Consumption	1300W
Water and Gas Tap	Water Tap*1, Gas Tap*1.(Optional)
Socket	Two, total consumption:500W
Display	LCD Display
Control System	Microprocessor
Airflow System	70% air recirculation,30% air exhaust
Material	Work table: 304 stainless steel
	Main body: Cold-rolled steel with anti-bacteria powder
Work Surface Height	750mm
Caster	Universal wheel with brake and leveling feet
Power Supply	100/220V±10%, 50/60Hz
Standard Accessory	Fluorescent lamp, UV lamp*2,Base stand, Remote control, Foot switch, Drain valve, Waterproof socket

11	**PN: HV85** **BRAND: HIRAYAMA** **ORIGIN: JAPAN** **MODEL: HIRAYAMA AUTOCLAVE**	**1**	**PHP. 585,888.00**	**PHP. 585,888.00**



- ✓ 85L free standing
- ✓ Self-contained autoclave that can be run manually
- ✓ Using preprogrammed cycles (including an Agar cycle)

TECHNICAL SPECIFICATIONS

MODEL	**HV-85**
TEMPERATURE	
Operating Range	105ºC to 135ºC
Display Range	137ºC
Warming Range	45ºC to 60ºC
Agar Dissolution	Heating at 60ºC to 100ºC for up to 1 hour (temperature and time programmable), followed by 45ºC to 60ºC (programmable for up to 20 hours to prevent coagulations)
GAUGE PRESSURE	
Operating Range	3 to 30 psi (0.021 to 0.206MPa)
Maximum Allowable	38 psi (0.26MPa)

	TIMER				
	Sterilization	1 to 250 minutes			
	Delayed Auto-start	Program autoclave to start 1 minute to 7 days later			
	DIMENSIONS				
	Overall (W x D x H)	26.0" x 25.6" x 39.4" (66 cm x 65 cm x 100 cm)			
	Chamber (Diameter x Height)	85 liters 16.5" x 24.2" (42.0 cm x 61.5 cm)			
	SAFETY DEVICES	Dual-sensing lid interlock, over-pressure power cutoff, over-temperature power cutoff, low-water power cutoff, mechanical pressure relief valve, microprocessor-controlled pressure relief valve, lid-closure detector, over-current detector and circuit breaker			
	PROGRAMS				
	1. For agar	Heating -> Sterilization -> Exhaust (from no exhaust to slow, programmable) -> Warming -> Completion			
	2. For liquids	Heating -> Sterilization -> Exhaust (from no exhaust to slow, programmable) -> Completion			
	3. For solids	Heating -> Sterilization -> Exhaust (fast, default) -> Completion			
	4. For melting agar or for faster start-up	Rapid melting at 60°C to 100°C (temperature and time programmable) -> Maintain at 45°C to 60°C (temperature programmable) ->			

		Completion			
	POWER				
	Source	208V/220V/240V, 50/60 Hz, single phase			
	Consumption	3000 watts (3000VA)			
	SHIPPING WEIGHT	282 lb (128 kg)			
	INCLUSIVE OF VAT (F.O.B. GOA CAMARINES SUR			**PHP.**	**PHP.**

Terms and Conditions:

1. **Validity of Quotation**: *30 days from the date of quotation*.
2. **Terms of Payment***: Net 30 days*
3. **Delivery***: 8-12 Weeks upon receipt of Purchase Order.*
4. **Warranty**: *One (1) year on parts and services.*
5. **Price offered is Inclusive of 12% VAT, Taxes & Duties and Commissioning**

NOTE:

1. We shall now implement a 25% of restocking fee for cancelled or returned orders, likewise product exchanges can only be done 7 days upon placing conforme. Otherwise ITS Science has the right to revise quotation if necessary.

2. Price quoted for forward sale is subject to acceptance due to peso/dollar exchange rate fluctuation.

Prepared By:

JOHN MARLON P. BUBAN
PRODUCT SPECIALIST
Tel no. (032) 640-1363
Fax no. (032) 641-3186
Mobile: +63 922.711.3803 (SUN)
+63 917.585.2267 (GLOBE)
Email: jm.buban@its-sciencephils.com