Gryke Scientific Instruments Trading
237-B Worth Drive, Savvy 25 Subdivision,
Severina Km. 18, Parañaque City, Philippines
Tel: +632 8776-7140 /8822-2376
8245-7969/ 7358-0858
Fax:+632 8824-5367
E-mail: jo2pob@gryke.com.ph
sales@gryke.com.ph

QUOTATION

Reference No. : 005-22F-LAG

Date: January 11, 2022

Company: **PARTIDOSTATE UNIVERSITY**
Camarines Sur
Attention: **Engr. Kier P. Gasca**

Supplier:
Biobase
China

ITEM	QTY.	ITEM DESCRIPTION	UNIT PRICE
1	1 Unit	**DOUBLE BEAM SCANNING UV/VIS SPECTROPHOTOMETER** Model:**BK-D590** Brand: **BIOBASE**  Optical System: Double Beam,Grating 1200 lines/mm Wavelength Range: 190-1100nm Spectral Bandwidth:05,1,2,4,5nm Wavelength Accuracy±0.3nm Wavelength Repeatabilly ≤0.2nm Photometric Accuracy ±0.002A (0-0.5 abs). ±0.3% T (0-100% T) Photometric Repeatability ±0.001Abs (0-0.5Abs)0.002Abs (0.5-1.0Abs), ≤0.2% T (0-100% T) Stray light:≤0.04 T@ 360nm; 220nm Stability ±0.0003A/h@500nm Baseline Flatness: ±0.0005A Noise: ±0.0002Abs Display: 65 thousand true color 7 inch TFT LCD (480*800) Photometer Mode: T,A,C,E Photometric Range:0-200% T,-0.301-3.0A Detector Slicon photodiode Light Source:Deuterium Lamp, Tingsten Lamp Input: Membrane keypad Output USB print and data output, Connect PC Standard accessories:10mm glass cuvette*4 units 10 mm quarts cuvette *2 units,software Power Supply: AC110V/220±10%,60/50Hz Package Size (W*D*H) mm 7408570*440 Gross Weight (kg) Oprional Accessories:Single cell holder, General cell holder, solid sample holder, Deuterium lamp,Halogen Lamp,4-place Cell holder, Printer, Water-jacketedcell holder,Reflection accessory 5°, Auto8-cell changer, micro cell holder, Water –jacketed cell holder, Constant-temperature system **Features:** *Environmental Deuterium lamp,preventing from ozone inhalation *Real time monitoring the lifetime of Deuterium lamp and tungsten lamp *Socket-type of Deuterium lamp and tungsten lamp *GLp self-check function:check the wavelength accuracy and photometer Accuracy,provide test report and power-off protection *Wavelength calibration,wavelenght setting,change lamp source and dark current calibration automatically *SiO2 coating optical mirror,reudces the influence from outside	**₱ 493,500.00**

2	1 Unit	**MICROPLATE READER** Brand: Biobase Model: **BK-EL10C** Measurement channel: Vertical 7 optical channels Wavelength range: 400-800nm Filter: standard 4 wavelengths of 405, 450, 492, 630nm; can be installed up to 10 filters (optional) Reading range: 0.000 – 4.000 Abs Linear range: 0.000 – 3.000 Abs Repeatability: CV≤1.0% Stability: ≤±0.003 Abs Vibration plate function: 3 kinds of vibration plate function, adjustable 0-255 seconds Display: 10.1 inch large touch screen Power supply: AC110/220V, 60/50Hz Net weight: 11kg Gross weight: 13kg Instruments size: W450 x D320 x H300mm Packing size: W535 x D395 x H395mm 	**₱ 350,845.00**
3	1 Set	**ROTARY EVAPORATOR**  Brand: Biobase Model: **RE 100-PRO** Evaporating flask: 1L (NS 29/32, 18300120) Receiving flask: 1L (KS 35/20, 18300110) Display: LCD Rotating speed: 20-280rpm Temp. range: RT-180°C Temp. accuracy: Water bath: ±1°C; Oil bath: ±3°C Lift: Motor Stroke height: 150mm Timing range: 1-999min Motor: DC brushless motor Heating power: 1300 W Stroke displacement: Automatic 150mm Protection class: IP20 Rotation: Reversible direction Interface: USB Power: 1400W Power supply: AC110/220V±10%, 50/60Hz (Customizavle) External size: W465 x D457 x H583mm Package size: W640 x D1100 x H650mm Net weight: 15kg Gross weight: 36kg Standard: Condenser (1700cm^2)*1 1L Evaporator flask*1, 1L Receiving flask*1, 5L pot *1 ***With Accessories*** **VACUUM PUMP** Model: **SHZ-DIII** Pump head: 4 Speed of evacuation: 10L/min Vaccum: -0.098MPa Circulating pump flow: 40L/min Pump lift: 12m Material: Anti-corrosion Consumption: 370W Capacity: 15L Power supply: AC220/110V±10%, 50/60Hz Package size: W435 x 340 x 500mm Gross weight: 12kg 	**₱ 343,455.00**

		RECIRCULATING CHILLER Model: **CCA-420** Temp. display: LED Tank volume: 4L Matching reaction kettle (steam): 1-2L Tank material: 304 stainless steel Tank size: 250 x 130 x 130mm Temp. control accuracy: ±0.1°C Display temp. resolution: 0.1°C Pump lift: 1.5 – 2.7m Circulating pump flow: 8-16L/min Refrigerant: R134A Refrigerating capacity: 1550 – 500W Pressure: ≤0.4MPa Ambient relative humidity: 60-80% ventilation Instruments temp. control range: -20°C RCT Optimum ambient temp.: 5-35°C Unload min. temp: -20°C Circulation pump power: 100W Circulating pump: Magnetic pump Circulating water mouth interface: Outer diameter 11mm/Inner diameter 7mm Sensor: PT100 Power Supply: AC220V±10%, 50/60Hz  	
4	1 Unit	**ANALYTICAL BALANCE** Brand: Biobase Model: **BA3003C** Capacity: 0-300g Readability: 1mg Scale size: ϕ90mm Stable time: 1s Repeat ability: 1mg Liner: 1mg N.W: 6.8kg External size: 350 x 215 x 340mm Package size: 480 x 375 x 515mm G.W 8.5kg Work space height: 240mm Calibration: Internal cal 	**₱ 100,180.00**
5	1 Unit	**HOTPLATE MAGNETIC STIRRER** Brand: Biobase Model: **MS7-H550-Pro** Work plate size: 184x184mm Work plate material: Glass ceramic Max. stirring capacity: 20L Motor type: Brushless DC Speed range: 100-1500rpm Speed display accuracy: ±1rpm Heating output: 1000W Heating temp.: RT-500°C, increment 1 Control temp. precision: ±1(<100°C), ±1%(>100°C) Max. temp.: 580°C **Please see brochure for full specification**  	**₱ 79,568.00**
6	1 Unit	**REFRIGERATED CENTRIFUGE** Brand: Biobase Model: **BKC-TL21RL**	**₱ 253,498.00**

		Max. capacity: 4*750ml Max. speed: 21000rpm Max RCF: 30700xg Speed precision: ±20rpm Temp. range: -20 – 40°C Temp. accuracy: ±1°C Timing range: 0-99h 59 min 59 sec Noise: ≤65dB Consumption: 2.5Kw Power supply: AC110/220V, 50/60Hz External size: W800 x D700 x H400mm Package size: W810 x D770 x H500mm Net weight: 110kg Gross weight: 140kg 	
7	1 Unit	**SHAKING INCUBATOR**  Brand: Biobase Model: **BJPX-1002D** Controller: PID Display: LCD Circulation mode: Forced convection Shaking mode: Rotary shaking Drive mode: Multidimensional drive Rotating speed: 20-350rpm (static culture, reverse rotation or alternate operation) Rotating accuracy: ±1rpm Vibration range: ϕ26mm (can customize ϕ35 (20-250rpm/min); ϕ50 (20-200rpm/min) Temp. range: 0-9999h/min (can run continuously from time to time) Shaking plate size: 500 * 360mm Shaking plate quantity: 2 pcs Max. capacity: 100ml*60 or 250ml*38 or 500ml * 22 or 1000ml – 16 (flask clamp) 100ml*60 or 250ml*36 or 500ml * 24 or 1000ml – 16 (Haftplate) Standard capacity: 250ml*24 Internal material: Stainless steel Heating consumption: 500W Consumption: 600W Power supply: AC220V±10%, 50/60HZ (Standard); AC110±10%, 60HZ (Optional) Internal size: W600 x D410 x H630mm External size: W700 x D580 x H1280mm Package size: W825 x D720 x H1490mm Gross weight: 220kg Safety function: - Audio and visual alarm for over-tempertaure - Alarm for over-speeds - Independent over-temperature protector - Shutdown protection for door opening (optional accessory) - Leakage or over-current protection - Ultraviolet disinfection function (optional accessory) - Calibration of monitoring temperature and ambient temperature	**₱ 265,000.00**
8	1 Unit	**FORCED AIR DRYING OVEN**  Model: **BOV-T50F** Capacity: 54L Temp. Range: 50-200°C Temp. Precision: 0.1°C Temp. Fluctuation: ±1°C Ambient Temp: 5-40°C Timing Range: 1-9999min Shelves No.: 2 pcs Consumption: 1000w	**₱ 185,585.00**

		Power Supply: AC100V/220±10%, 50/60Hz Internal Size (W*D*H)mm: 420*332*348 External Size (W*D*H)mm: 708*595*532 Package Size (W*D*H)mm: 840*690*620 Gross Weight (kg): 66 *Features:* - *External material: cold-rolled steel with anti-bacteria powder coating.* - *Stainless steel inner chamber, round angle structure, adjustable shelves* - *Double layer glass observation window, adjustable airtight buckle lock.* - *PID control with LED display.* - *Over-temperature protection*	
9	1 Unit	**FUMEHOOD**  Brand: Biobase Model: **FH1800(E)** External size: W1800 x D800 x H2515mm Internal size: W1590 x D600 x H870mm Work surface height: 900mm Max opening: 750mm Air velocity: 0.3 – 0.8m/s System exhaust volume: 1140 m^3/h Noise: ≤68dB Exhaust duct: PVC, standard length, 4.3 meters, ϕ300mm Pipe strap: 2 pcs LED Lamp: 16W*1 Blower: Built-in PP Centrifugal blower Fron window: Manual, 5mm toughened glass, height adjustable Power supply: 220V±10%, 60/50Hz; 110V±10%, 60Hz Consumption: 500W Material: - 1.0mm cold-rolled steel with bacteria power coating - Compact laminate board with good acid and alkali resistance function - Chemical resistant phenolic resin Gross weight: 365kg Package: - Main body: 1940 x 940 x1900mm - Base cabinet: 1940 x 940 x 1050mm	**₱ 395,554.00**
10	1 Unit	**VERTICAL AUTOCLAVE**  Brand: Biobase, China Model: **BKQ-B75II** Chamber size: 386 x 694mm Consumption: 4.7W SS basket: 2 pcs External size: W640 x D550 x H1070mm Packaging size: W750 x D745 x H1240 Gross weight: 112 Chamber Material: SUS304 Designed pressure: 0.28Mpa Designed temp.: 150°C Working pressure.: 0.22Mpa Working temp.: 105 - 136°C Temp. display accuracy: ±0.1°C Timing range: 0-999min Dynamic pulse exhaust times: 0-9 times Dynamic pulse exhaust temp.: 105 - 134°C Dissolution. Temp range: 60-100°C (optional) Temp. holding range: 40-60°C (optional) Power supply: AC110/220V±10%, 50/60Hz	**₱ 388,455.00**

TERMS and CONDITIONS:

Price	:	DDP Manila/in **PESO**
Validity	:	30 days
Terms of Payment	:	COD
Delivery Period	:	Approx.: 8 – 10 working weeks upon receipt of Purchase Order

Looking forward to your reply, we remain
GRYKE SCIENTIFIC INSTRUMENTS TRADING

CONFORME:

By : _____
LYRA A. GO

By:_____
PARTIDO STATE UNIVERSITY

OTHER TERMS & CONDITIONS:

- Please indicate the Quote Ref. Number in your Purchase Order as acceptance of product specifications.
- **Calibration** is chargeable and not included in the offer unless stated.
- **Certificate of Conformity** (if applicable) must be advised at the time of order. If this certificate is ordered after the unit has been shipped or delivered, certificate will be chargeable.
- We Warrant that all offered goods are in good quality and free from any physical/manufacturing defects.
- **NO Cancellation** of products once order is entered or acknowledged. Otherwise, a minimum *cancellation charge of 20% of Total Amount Due* **OC** *Consequential Cost* related to the same shall be charged whichever is higher.

THIS IS AN ELECTRONICALLY APPROVED AND GENERATED DOCUMENT.
NO SIGNATUES REQUIRED.