Republic of the Philippines
PARTIDO STATE UNIVERSITY
Camarines Sur

REQUISITION AND ISSUE SLIP

Fund Cluster: 05

3GX COMPUTERS & IT SOLUTIONS TECHNOSHOP

Office:	R. Artiaga		Reference	25-12-964	Date:	12/9/2025	RIS No.:	2026-01-049
Stock Number	Qty	Unit	Item Description				Unit Cost	Total Cost
	1	unit	R. Artiaga Tower Server unit Application System Server Processor 1 x Intel Xeon E-2456 3.30 GHz Form Factor - Tower Server Chipset Intel® C260 Series Chipsets Memory (Min/MAx) 16 GB RAM 3200 MHz or 32 GB Hardware Interface 12Gb/s SAS Controller Hard Disk 1TB SAS 12Gb Hot Swap HDD Operating System Microsoft Windows Server with Hyper-V Power Supply 800W; DELL T160 SN; 2S93PD4				106,053.00	106,053.00
	1	unit	FDM (Fused Deposistion Modeling) 3D Printer; Build Volume: 220 x 220 x 250 mm; Max Print Speed: 600 mm/s; Max Nozzle Temperature: 300 ℃; Max Bed Temperature: 100℃; Extruder Type: All-metal direct-drive; Nozzle Type: Tri-metal quick-swap (0.4 mm standard); Supported Filament Types: PLA, ABS, PETG, TPU, PC, Nylon 3D Printing filament included Filament Diameter: 1.75 mm; Automatic Bed Leveling: Yes; Enclosure: Fully enclosed with glass panels; Connectivity: USB, Wi-Fi, LAN Touchsceen: 4.3-inch color display; AI Camera: Built-in for print monitoring and error detection; Software Compatibility: Creality Print, Cura, and others: BAMBU LAB P1S COMBO SN; 01P00C590900174				59,000.00	59,000.00
	1	unit	Split-type 1.5 HP Inverter Type Aircondition Unit (inclusive of installation services); Aircon Type: Split; Cooling Capacity (HP): 1.5 HP; Length cm: Indoor: 20.8 |Outdoor: 27; Width (cm): Indoor: 83.5 | Outdoor: 72; Height (cm): Indoor: 29.5 Outdoor: 49.5; Gross Weight (kg): Indoor: 11.9; Outdoor: 23.8; Net Weight (kg): indoor: 9 | Outdoor: 21.8; Turbo, Silent Mode, Follow Me Function, Fast Cooling, Wind Avoid Me, Gear Operation, Emergency Function, Eco Mode, Do Not Disturb, Sleep Mode, Louver Position Memory, Gold Fin, Silver Ion Filter, Clean Function, EER Rating: 4.5 (CSPF); Color: White; 1030 watts; HYUNDAI HAC-DC12C/D OUTDOOR SN: 5400A367504AB170170016; INDOOR SN: 5400A367503AB170130058				50,190.00	50,190.00
	1	unit	2KVA ON-LINE Double Conversion UPS; Capacity 2000VA / 2000W UPS Type: On-Line Double Conversion (Zero Transfer Time) Input Voltage: 220-240 VAC ; Output Voltage: 220-240 VAC, Pure SIne Wave Frequency: 50/60 Hz (Auto-sensing); Output Power Factor: 0.9 or 1.0 (model-dependent) Battery Backup Time: Approx. 4-5 minutes @ full load Recharge Time: ~5 hours to 90%; Battery Type: Sealed Lead- Acid (VRLA), Internal Display: LCD Display Panel; Outlets: 6-8 x IEC C13 (typical) Communication Ports: USB, RS-232, SNMP (optional) Form Factor: Tower; Surge Protection: Built-in EMI/RFI Filter; Certifications: CE, RoHS; VERTIV 2K DOUBLE CONVERSION TOWER SN: 2402700013GE03Z ** nothing follows **				50,010.00	50,010.00
						Total		265,253.00

Purpose :	**Procurement of ICT Equipment for the Establishment of Digital System and Instrumentation (Phase 1) for CEC		
Signature :	Approved by:	Issued by:	Requested & Received by:
Printed Name :	**MARICRIS L. MAGAT**	**JHONNA SALVE J. BUENAFLOR**	**ROWELL JOHN B. ARTIAGA**
Designation:	Admin. Officer V-Supply Office	Admin. Officer III	End-User
Date:			

Republic of the Philippines
PARTIDO STATE UNIVERSITY
Camarines Sur

PROPERTY ACKNOWLEDGMENT RECEIPT

Fund Cluster: 05 PAR No.: 2026-01-003

Quantity	Unit	Description	Property Number	Date Acquired	Cost	Total Cost	Remarks
1	unit	Tower Server unit Application System Server Processor 1 x Intel Xeon E-2456 3.30 GHz Form Factor - Tower Server Chipset Intel® C260 Series Chipsets Memory (Min/MAx) 16 GB RAM 3200 MHz or 32 GB Hardware Interface 12Gb/s SAS Controller Hard Disk 1TB SAS 12Gb Hot Swap HDD Operating System Microsoft Windows Server with Hyper-V Power Supply 800W; DELL T160 SN; 2S93PD4		1/27/2026	106,053.00	106,053.00	25-12-964
1	unit	FDM (Fused Deposistion Modeling) 3D Printer; Build Volume: 220 x 220 x 250 mm; Max Print Speed: 600 mm/s; Max Nozzle Temperature: 300 °C; Max Bed Temperature: 100°C; Extruder Type: All-metal direct-drive; Nozzle Type: Tri-metal quick-swap (0.4 mm standard); Supported Filament Types: PLA, ABS, PETG, TPU, PC, Nylon 3D Printing filament included Filament Diameter: 1.75 mm; Automatic Bed Leveling: Yes; Enclosure: Fully enclosed with glass panels; Connectivity: USB, Wi-Fi, LAN Touchsceen: 4.3-inch color display; AI Camera: Built-in for print monitoring and error detection; Software Compatibility: Creality Print, Cura, and others: BAMBU LAB P1S COMBO SN; 01P00C590900174			59,000.00	59,000.00	3GX COMPUTERS & IT SOLUTIONS TECHNOSHOP

**Procurement of ICT Equipment for the Establishment of Digital System and Instrumentation (Phase 1) for CEC

Received By:	Issued by:
ROWELL JOHN B. ARTIAGA Signature over Printed Name of End User **End-User** Position/Office _____ Date	**MARICRIS L. MAGAT** Signature over printed Name of Supply and/or Property Custodian **Admin. Officer V/Supply** Position/Office _____ Date

Republic of the Philippines

PARTIDO STATE UNIVERSITY

Camarines Sur

PROPERTY ACKNOWLEDGMENT RECEIPT

Fund Cluster: 05 PAR No.: 2026-01-004

Quantity	Unit	Description	Property Number	Date Acquired	Cost	Total Cost	Remarks
1	unit	Split-type 1.5 HP Inverter Type Aircondition Unit (inclusive of installation services); Aircon Type: Split; Cooling Capacity (HP): 1.5 HP; Length cm: Indoor: 20.8 |Outdoor: 27; Width (cm): Indoor: 83.5 | Outdoor: 72; Height (cm): Indoor: 29.5 Outdoor: 49.5; Gross Weight (kg): Indoor: 11.9; Outdoor: 23.8; Net Weight (kg): indoor: 9 | Outdoor: 21.8; Turbo, Silent Mode, Follow Me Function, Fast Cooling, Wind Avoid Me, Gear Operation, Emergency Function, Eco Mode, Do Not Disturb, Sleep Mode, Louver Position Memory, Gold Fin, Silver Ion Filter, Clean Function, EER Rating: 4.5 (CSPF); Color: White; 1030 watts; HYUNDAI HAC-DC12C/D OUTDOOR SN: 5400A367504AB170170016; INDOOR SN: 5400A367503AB170130058		1/27/2026	50,190.00	50,190.00	25-12-964
1	unit	2KVA ON-LINE Double Conversion UPS; Capacity 2000VA / 2000W UPS Type: On-Line Double Conversion (Zero Transfer Time) Input Voltage: 220-240 VAC ; Output Voltage: 220-240 VAC, Pure SIne Wave Frequency: 50/60 Hz (Auto-sensing); Output Power Factor: 0.9 or 1.0 (model-dependent) Battery Backup Time: Approx. 4-5 minutes @ full load Recharge Time: ~5 hours to 90%; Battery Type: Sealed Lead- Acid (VRLA), Internal Display: LCD Display Panel; Outlets: 6-8 x IEC C13 (typical) Communication Ports: USB, RS-232, SNMP (optional) Form Factor: Tower; Surge Protection: Built-in EMI/RFI Filter; Certifications: CE, RoHS; VERTIV 2K DOUBLE CONVERSION TOWER SN:			50,010.00	50,010.00	3GX COMPUTERS & IT SOLUTIONS TECHNOSHOP

**Procurement of ICT Equipment for the Establishment of Digital System and Instrumentation (Phase 1) for CEC

Received By:	Issued by:
ROWELL JOHN B. ARTIAGA	**MARICRIS L. MAGAT**
Signature over Printed Name of End User	Signature over printed Name of Supply and/or Property Custodian
End-User	**Admin. Officer V/Supply**
Position/Office	Position/Office
Date	Date