

INDEX

Note: Page numbers followed by *f* indicate figures and *t* indicate tables.

A

- Ackerman angle, 279
- Acoustic/ultrasonic sensors
 - advantages, 10
 - data collection, 10
 - disadvantages, 10
 - parking sensor, 9-10
 - pedestrian/vehicle and sensor distance, 9-10
- Aerial/satellite imaging
 - advantages, 11
 - data collection, 11
 - disadvantages, 11
 - manned/unmanned helicopters, 10-11, 11*f*
 - vehicle counts, vehicle speeds and traffic density, 10-11
- AIMSUN, 245-247

B

- Bernoulli model
 - compressible fluid mechanics, 267
 - empirical comparison, 268
 - fluid velocity, 265-266
 - ideal gas law, 266
 - principle, 262, 265-266
- Boltzmann equation
 - conservation law, 370
 - initial and boundary conditions, 370-371
 - longitudinal control model, 370

C

- California Vehicle Code, 183, 185-186
- Car-following models
 - CARSIM model, 239-240
 - Forbes model, 187-188
 - macroscopic benchmarking, 191-193
 - microscopic benchmarking, 188-191
 - microscopic models, taxonomy of, 246*f*

- neural network model
 - artificial neural networks, 241-242
 - back-propagation neural network, 242
 - data collection, 243
 - driver's operational control, 242
 - first input-output pattern, 243
 - neurons, 241-242
 - training process, 243
- Pipes model, 183-187
- psychophysical model (*see* VISSIM)
 - driver's operational control, 237
 - driving regimes, 239
 - illustration of, 238*f*
 - operating point, 239
 - psychological activities and physical behavior, 239
 - vehicles collision, 237
- rule-based model, 240-241
- Cell transmission model (CTM)
 - divergence scenario, 146-147
 - mainline scenario, 140-142
 - merger scenario
 - demand exceeds supply, both upstream
 - links congestion, 145
 - demand exceeds supply, one upstream
 - link congestion, 144
 - freeway merge, 142*f*
 - queuing model, 142
 - supply exceeds demand, 143
 - minimum principle, 139-140
 - taxonomy of, 170*f*
- 1964 Chevrolet Corvair, 268-269
- Connected vehicle technology (CVT), 261-262
- Conservation law
 - continuity equation
 - finite difference, derivation I, 72-74
 - finite difference, derivation II, 74-75
 - fluid dynamics, derivation III, 75-77
 - roadway traffic, 72

Conservation law (*Continued*)
 scalar conservation law, derivation IV, 77-78
 three-dimensional representation of traffic flow, derivation V, 78
 first-order dynamic model, 79-80
 flow-speed-density relationship/identity, 71
 mass conservation, 72
 one-dimensional compressible fluid, 72
 pairwise relationships/equilibrium models, 71
 PDE, 92
 traffic flow theory, 71-72
 traffic states, 72

Continuum flow models
 Kerner and Konhäuser's model, 166
 LWR model, 166
 Michalopoulos et al. model, 166
 Phillips's model, 166
 PW model, 166
 relative merits of, 167-168
 Treiber et al. model, 167
 Zhang's model, 166

Control theory, 360, 363
 CORQ, 362
 CORSIM, 245-247
 Coulomb's law, 207, 287-288, 341-342
 CTM. *See* Cell transmission model (CTM)
 CVT. *See* Connected vehicle technology (CVT)

D

d'Alembert solution, 88-89
 Del Castillo model, 332
 Desired measure model, 245-247
 Deterministic models, 360-361
 Discrete choice model
 lane-changing model, 175
 lateral direction, 178
 route-choice model, 173-175
 Drake et al. model, 203, 205, 332
 Drew model, 204, 205
 Dynamic interactive vehicle (DIV) model
 automotive engineering, 275
 brake pedal position, 275-276
 calibration and validation, 279-280

high computational efficiency and modeling fidelity, 275
 modeling lateral movement, 278-279
 modeling longitudinal movement
 aerodynamic drag, 277
 braking performance, 277
 grade resistance, 278
 modeling acceleration performance, 276
 Newton's second law of motion, 276
 steering angle, 275-276
 throttle position, 275-276

DynaMIT, 361-362
 DYNASMART, 361-362

E

Edie model, 59-62
 Energy conservation, 164, 168, 371-372
 Engine modeling
 accessibility, 262
 accuracy, 262
 calibration, 262
 computational efficiency, 262
 cross-comparison of, 273
 CVT, 261-262
 existing engine models
 direct-injection spark-ignition engine model, 263
 filling and emptying method, 263
 hybrid vehicle modeling, 263
 IC engines, 262-263
 linear engine model, 263-264
 spark-ignition engine, 263
 teaching purpose, 263-264
 formulation, 262
 internal combustion engines, 261-262
 mathematical engine models
 Bernoulli model, model III, 265-268
 parabolic model, model II, 265
 polynomial model, model I, 264
 parameter values, 273
 validation and comparison of
 automotive engines, 268-269
 1964 Chevrolet Corvair engine, 268-269, 271f
 empirical engine power and torque curves, 268-269

- 2006 Honda Civic engine, 268–269, 270*f*
 - MAPE, 271–272
 - 2008 Mercedes CLS engine, 268–269, 270*f*
 - model I, 269
 - model II, 269
 - model III, 269
 - 2006 Pagani Zonda engine, 268–269, 270*f*
 - technical specifications, 269*t*
 - Equilibrium traffic flow models
 - multiregime models, 59–62, 62*t*, 64*f*
 - single-regime models
 - comparison of, 61*f*
 - equilibrium/steady-state relationship, 51–52
 - flow, speed and density, 52–55
 - free-flow speed, 58–59
 - Georgia NaviGATOR, 51
 - Greenshields model, 55–58
 - one-equation models, 59
 - point sensor, 51, 53*f*
 - traffic speed, 51–52
 - video images, 51
 - speed-density relationship
 - observed mean and standard deviation, 62–63, 65*f*
 - scattering effect, 62–63
 - three-dimensional representation, 65*f*
- F**
- Federal Motor Carrier Safety Administration, 280
 - Field theory
 - congestion, 301–302
 - driver's interaction, 294–295
 - driver's responsiveness, 292–293
 - driver's strategy, 295–296
 - existing knowledge base
 - engineering disciplines, 302–303
 - physical science, 304
 - traffic flow theories, 302
 - mobility, 301
 - motivation, 283–284
 - physical field, 291–292
 - simplification of
 - decouples equations, 297
 - directional response, 297–300
 - forces, 297
 - generic theory, 296
 - lateral direction, 299–300
 - longitudinal direction, 297–299
 - Occam's razor, 296
 - traffic flow, physical basis of
 - electromagnetic phenomena, 287–288
 - mechanics phenomena, 285–287
 - physical laws and social rules, 284
 - statistical mechanics phenomena, 289–291
 - three systems, 285*f*
 - transportation system, 284
 - wave phenomena, 288–289
 - Forbes model
 - applications (*see* Pipes model)
 - macroscopic benchmarking, 191–193
 - perception-reaction time, 187–188
 - properties (*see* Pipes model)
 - safety rule, 187
 - steady-state model, 331–332
 - FREFLO
 - numerical solutions
 - conservation law, 135
 - dynamic speed-density relationship, 136
 - equilibrium speed-density relationship, 137
 - macroscopic traffic simulation model, 135
 - PW model, 163–164
 - FREQ, 137, 362
- G**
- Gap-acceptance models, 245, 360–361
 - General Motors (GM) models
 - development of
 - driver's control maneuver, 195
 - GM1, 196
 - GM2, 196–197
 - GM3, 197
 - GM4, 197–198
 - GM5, 198
 - stimuli and sensitivity, 195–196

General Motors (GM) models (*Continued*)

- limitations of
 - intimate pair, 208–209
 - mechanism of motion, attraction, 207
 - slow start, 208, 208*f*
 - universal car following, 207
 - macroscopic benchmarking, 205
 - microscopic benchmarking, 198–199
 - microscopic-macroscopic bridge
 - Drake et al. model (Northwestern Model), 203
 - Drew model, 204
 - GM5, 201
 - Greenberg model, 201–202
 - Greenshields model, 203
 - macroscopic equilibrium models, 204
 - microscopic car-following models, 204
 - Pipes and Forbes models, 204
 - Pipes-Munjal model, 203
 - single-regime models, 201*t*
 - Underwood model, 203
 - traffic flow theory, 195
 - Wilson, Charles, 195
- Georgia State Route 400 (GA400) data, 13–15
- Gipps model
- fundamental diagram, 219*f*
 - macroscopic benchmarking, 218
 - microscopic benchmarking, 216–218, 217*f*
- model formulation
- car-following scenario, 212*f*
 - Forbes rule, 211
 - free-flow regime, 214
 - perception-reaction process, 212
 - Pipes rule, 211
 - quadratic inequality, 213
 - safe driving rule, 211
 - speed choice model, 214
- properties of, 215–216
- steady-state model, 331–332
- Global positioning system (GPS)
- advantages, 9
 - automotive navigation and traffic time studies, 8
 - cell phones, 8
 - data collection, 9

- disadvantages, 9
- satellite-based navigation system, 8–9
- spatial-temporal points, 9
- triangulation, 8–9
- vehicle's trajectory, 19–21, 21*f*

Gradient catastrophe, 96

Greenberg model, 201–202, 205, 332

Greenshields model

- dynamic traffic flow modeling, 58
- flow-density relationship, 56*f*
- flow-density-speed relationship, 57*f*
- fundamental diagram, 57–58, 60*f*
- highway capacity and LOS, 58
- LWR model, 115–116
- microscopic-macroscopic bridge, 203
- speed-density relationship, 55, 55*f*
- speed-flow relationship, 56*f*, 57
- traffic flow theory, 58
- vehicular traffic flow, 57–58

H

High-order models

- continuum flow models, 166–167
 - first-order partial differential equation, 163
 - Kerner and Konhäuser's model (1993), 164–165
 - Kühne's model (1984), 164
 - macroscopic models, taxonomy of, 168–169, 170*f*
 - mass/vehicle conservation, 163
 - Michalopoulos et al. (1993) model, 165
 - Phillips's model (1979), 164
 - PW model (1971), 163–164
 - Treiber et al. (1999) model, 165–166
 - Zhang's model (1998), 165
- Highway Capacity Manual (HCM), 37
- 2006 Honda Civic, 268–269
- HUTSIM, 245–247

IIDM. *See* Intelligent driver model (IDM)

IF-THEN rules, 244, 245, 360–361

Inductive-loop detectors

- actuated signal controller, 4–5
- advantages, 5
- data collection, 5

- disadvantages, 6
- intersections, 3
- red-light-running camera, 4-5
- resonant frequency, 4
- Integration, 245-247
- Intelligent driver model (IDM)
 - desired spacing, 227
 - fundamental diagram, 232*f*
 - macroscopic benchmarking, 230, 230*t*
 - microscopic benchmarking, 228, 229*f*, 230*t*
 - properties of, 227-228
- Intelligent transportation systems (ITS), 3
- Internal combustion (IC) engines, 261-262

K

- Kalman filter technique, 33
- Kinematic waves model, 362
- Kosonen model, 245, 347*f*
- KRONOS
 - first-order models, 362
 - numerical solutions
 - computerized macroscopic traffic simulation model, 137
 - discretization, 138*f*
 - Greenshields model, 139
 - ramp flows and lane changes, 137

L

- Lane-changing models, 245, 360-361
- LCM. *See* Longitudinal control model (LCM)
- Lennard-Jones potential, 302-303, 303*f*
- Level of service (LOS), 58
- Lighthill, Whitham and Richards (LWR) model
 - conservation law, 114-115
 - dynamic traffic flow model, 113
 - flow-density relationship
 - free-flow, 122
 - kinematic wave, 122
 - moving observer, 122-123, 124*f*
 - shock wave, 122
 - traffic, 122
 - general q - k relationship, 118-120
 - Greenshields model, 115-116
 - RIEMANN problem, 117-118

- shock path and queue tail, 120-121
- shock wave solution
 - characteristics method, 117
 - fast platoon, 117
 - kinematic wave, 116
 - shock path, 116-117
 - slowing down effect, 116-117
 - slow platoon, 117
- traffic flow problems
 - bottleneck, varying traffic demand, 123-126, 124*t*, 125*f*
 - moving bottleneck, 126, 126*t*, 127*f*
- Lincoln tunnel, 80
- Longitudinal control model (LCM)
 - aggressiveness, 332
 - applications
 - commercial simulation packages, 325
 - freeway, 326-327
 - macroscopic approach, graphical solution, 327-329
 - microscopic approach, deterministic simulation, 329-330
 - microscopic approach, random simulation, 330-331
 - service analysis procedure, 325
 - traffic phenomena, 325
 - transportation planners, 325
 - desired spacing, 332
 - driving force, 308-309
 - empirical results
 - Amsterdam data, 321*f*
 - autobahn data, 316-324, 318*f*
 - cloud density, 317
 - congested regime, 316-320
 - facility types, 322*t*
 - free-flow speed and capacity, 316-320
 - GA400 data, 316*f*
 - Highway 401 data, 316-325, 320*f*
 - Interstate 4 data, 316-325, 317*f*
 - Newell model, 316-320
 - optimized model, 319
 - PeMS data, 316-324, 319*f*
 - reverse-lambda shape, 316-320
 - traffic flow data, 316
 - traffic stream models, 316
 - traffic stream models, facility types, 323*t*

Longitudinal control model (LCM)

(Continued)

Underwood model, 316–320

Forbes model, 331–332

General motors models, 331–332

Gipps car-following model, 331–332

intelligent driver model, 331–332

macroscopic model, 310–311

microscopic model, 309–310

model properties

boundary conditions, 313–314

consistent modeling approach,
312–313field theory and Newton's second law
of motion, 311

model flexibility, 314–316

one-equation model, 311

Newell nonlinear car-following model,
331–332

Newton's second law of motion, 308–309

Pipes model, 331–332

single-regime category, 332

steady-state model, 331–332

Van Aerde car-following model, 331–332

vehicle operational control, 308–309

MMAPE. *See* Mean absolute percentage error
(MAPE)

Mass conservation, 164

Mathematical engine models

Bernoulli model, 265–268

parabolic model, 265

polynomial model, 264

MATLAB, 329

Mean absolute percentage error (MAPE),
271–272

2008 Mercedes CLS, 268–269

Microscopic modeling

macroscopic benchmarking, 180–182

microscopic benchmarking

car-following models, 178–179

hypothetical driving regimes, 178

single driving process, 179–180

trial and error, 180

modeling scope and time frame

car-following decision, 175, 177*f*

categories, 175

driver's options, 173

driving decisions, 173

gap-acceptance decision, 175

lane-changing decision, 175

operational decision, 175, 177*f*

route-choice decision, 173–175

strategic level decision, 174*f*tactical decision, 175, 176*f*

notation, 175–177

Modified Greenberg model, 59–62

Momentum conservation, 164

Multiscale traffic flow modeling

consistent multiscale models, 358–359

microscopic modeling

lateral control model, 368–369

longitudinal control, 366–368

macroscopic modeling, 371–372

mesoscopic modeling, 369–371

modeling scales, spectrum of

issues of, 362–363

macroscopic scale, 362

mesoscopic scale, 361–362

microscopic scale, 360–361

picoscopic scale, 360

picoscopic modeling

component fields, 364

driver-vehicle-environment

closed-loop control system, 363

driving strategies, 364

perceived field, illustration of, 365*f*

traffic simulation, 357–358

zoomable simulation, 357–358

N

Navier-Stokes equation of motion, 163–164

NaviGATOR system, 13–14

Neural network model

artificial neural networks, 241–242

back-propagation neural network, 242

data collection, 243

driver's operational control, 242

first input-output pattern, 243

neurons, 241–242

training process, 243

Neuro-fuzzy hybrid models, 360–361

Newell model, 316–320, 332

- Newell nonlinear car-following model, 331–332
 - Newell nonlinear model
 - fundamental diagram, 225*f*
 - macroscopic benchmarking, 224, 226*t*
 - microscopic benchmarking, 222–224, 223*f*, 224*t*
 - Newell nonlinear car-following model, 221
 - properties of, 221–222
 - Newell simplified model, 226–227
 - Newton's law of universal gravitation, 207
 - Next Generation Simulation (NGSIM), 15–17, 245
 - Northwestern model, 203, 205
 - Numerical solutions
 - CTM
 - divergence scenario, 146–147
 - mainline scenario, 140–142
 - merger scenario, 142–146
 - minimum principle, 139–140
 - discretization scheme
 - cell storage, 135
 - free-flow speed, 134
 - time and space, 133, 134*f*
 - FREFLO
 - conservation law, 135
 - dynamic speed-density relationship, 136
 - equilibrium speed-density relationship, 137
 - macroscopic traffic simulation model, 135
 - FREQ, 137
 - KRONOS
 - computerized macroscopic traffic simulation model, 137
 - discretization, 138*f*
 - Greenshields model, 139
 - ramp flows and lane changes, 137
- P**
- 2006 Pagani Zonda, 268–269
 - Paramics, 245–247
 - Partial differential equation (PDE), 83, 102
 - Photoelectric effect, 289
 - Picoscopic modeling
 - applications
 - connected vehicle technology, 258, 258*f*
 - emergency management, 259
 - interactive highway safety design, 257–258
 - transportation forensics, 258–259
 - driver, vehicle and environment
 - closed-loop system, 253, 254*f*
 - driver modeling approach, 253–254, 255*f*
 - environment information, 254–255
 - field theory, 255
 - intelligent agent, 254–255
 - interaction, 253
 - roadway traffic, 256
 - speed, acceleration and yaw velocity, 256–257
 - traffic operation, 256–257
 - transportation system, 253–254, 254*f*
 - vehicle dynamic responses and lateral movement, 255–256
 - vehicle feedback, 254–255
- Pipes model
- applications of
 - automatic driving, 184–185
 - computer simulation, 185–186
 - California Vehicle Code, 183
 - fundamental diagram, 192*f*
 - macroscopic benchmarking, 191–193
 - microscopic benchmarking, 188–191, 190*f*, 191*t*
 - properties of, 186–187
 - steady-state model, 331–332
- Pipes–Munjal model, 203, 205
- Pneumatic tubes
- advantages, 8
 - data collection, 7, 8
 - disadvantages, 8
 - installation of, 7*f*
 - short-term traffic engineering studies, 7
- Poisson arrival pattern, 330–331
- Prigogine's model, 361–362
- Probabilistic models, 360–361
- Psychophysical model
- driver's operational control, 237
 - driving regimes, 239

Psychophysical model (*Continued*)

- illustration of, 238*f*
- operating point, 239
- psychological activities and physical behavior, 239
- vehicles collision, 237

R

Radio-frequency identification (RFID)

- advantages, 12
- data collection, 12
- disadvantages, 13
- electronic toll collection system, 12, 12*f*
- identification and tracking, 12
- transponders, 12

Route-choice models, 173–175, 245

Rule-based model. *see* HUTSIM

- car-following models, 240–241
- human intelligence, 241
- illustration of, 241*f*

S

Simplified theory of kinematic waves

- backward wave propagation, 153–154
- computational algorithm
 - actual departure, 157, 158
 - capacity constraint, 157
 - departure, 157
 - lattice point, 158
 - time and space, 156–157
 - traffic flow, 156–157
 - upstream arrival, 157
- D/D/1 queuing theory, 151
- Derivation V, 151
- forward wave propagation, 152–153
- local capacity, 154
- minimum principle, 155, 155*f*
- on-ramp and off-ramp queuing models, 159
- segments, 159
- single bottleneck, 155–156
- traffic dynamics, 151
- triangular flow-density relationship, 152

Single-regime models

- equilibrium traffic flow models
 - comparison of, 61*f*

- equilibrium/steady-state relationship, 51–52

- flow, speed and density, 52–55

- free-flow speed, 58–59

- Georgia NaviGator, 51

- Greenshields model, 55–58

- one-equation models, 59

- point sensor, 51, 53*f*

- traffic speed, 51–52

- video images, 51

IDM, 227–230

Newell nonlinear model, 221–224

Newell simplified model, 226–227

Van Aerde model, 230–233

Speeds, flow-density relationship

- free-flow, 122

- kinematic wave, 122

- shock wave, 122

- traffic, 122

T

Three-regime model, 59–62

Traffic flow characteristics

desired traffic

- density, point sensor data, 32–33
- field data collection, 31
- HCM, 31
- loop detector/video camera, 31
- space mean speed, point sensor data, 32

generalized definition

- flow, mean speed and density, 42
- HCM, 37
- infinitesimal distance, 38, 38*f*
- infinitesimal duration, 39, 40*f*
- point sensor data, 37
- space sensor data, 37
- time-space rectangle, 40

mobile sensor data

- GPS data, 19, 20*t*
- vehicle's speed, 19
- vehicle's trajectory, 19–21, 21*f*
- vehicle's travel time, 19–21

point sensor data

- electromagnetism, 23–24
- headway, 23, 24
- loop detector data, 23–24, 23*f*

- occupancy, 24
 - on time, 24
 - time mean speed, 24
 - time-space diagram, 22, 22*f*
 - traffic count, 22, 24
 - vehicle speed, 24
 - relationships
 - density and spacing, 28
 - flow and headway, 28
 - flow, speed and density, 27
 - occupancy and density, 30–31
 - time mean speed and space mean speed, 29–30
 - space sensor data
 - density, 25–26
 - space mean speed, 26
 - spacing, 25
 - vehicle speed, 26
 - three-dimensional representation
 - density and space mean speed, 48
 - examples, 44*f*
 - intelligent transportation system, 48
 - N - t diagram, 46*f*
 - N - t - x region, 47*f*
 - N - x diagram, 45*f*
 - vehicle trajectories, 46
 - time-space diagram and characteristics, 26, 27*f*, 27*t*
 - Traffic flow, physical basis of
 - electromagnetic phenomena
 - car following, 287–288
 - shying-away effect, 288
 - tailgating, 288
 - Maxwell-Boltzmann distribution, 290*f*
 - mechanics phenomena
 - directional flow, 285–286
 - free flow, 286
 - Newton's third law of motion, 285
 - red light, 286
 - road barriers, 286–287, 287*f*
 - physical laws and social rules, 284
 - statistical mechanics phenomena, 289–291
 - three systems, 285*f*
 - transportation system, 284
 - wave phenomena
 - harmonic wave, 288
 - signal propagation, 289
 - wave-particle duality, 289
 - Traffic sensing technologies
 - classification
 - intrusive, 13
 - mobile sensor, 13
 - nonintrusive, 13
 - off-roadway, 13
 - point sensor, 13
 - space sensor, 13
 - data sources
 - GA400 data, 13–15
 - NGSIM data, 15–17, 16*f*
 - ITS, 3
 - types
 - acoustic/ultrasonic sensors, 9–10, 10*f*
 - aerial/satellite imaging, 10–11
 - GPS, 8–9, 8*f*
 - inductive-loop detector, 3–6
 - pneumatic tubes, 7–8
 - RFID, 12–13
 - VIPS, 6–7, 6*f*
 - Traffic stream model, 314
 - TRANSIMS, 361–362
 - Two-regime linear model, 59–62
- ## U
- Underwood model, 203, 205, 316–320, 332
 - Unified diagram
 - connections, 351–354
 - field theory, 339–340
 - macroscopic equilibrium models
 - Del Castillo and Benítez model, 350–351
 - Drew model, 349
 - GM-associated models, 351
 - IDM (macroscopic), 348
 - Kosonen model, 347*f*
 - Newell model (macroscopic), 348
 - Pipes-Munjal model, 348–349
 - Van Aerde model (macroscopic), 348
 - Wang et al. model, 349–350
 - microscopic car-following models
 - CARSIM model, 344–345
 - Forbes model, 341
 - Gipps model, 342–343
 - GM models, 341–342

Unified diagram (*Continued*)

- IDM, 343
- Newell model, 340-341
- psychophysical model, 345-346
- rule-based model, 346-347
- Van Aerde model, 344
- motivation
 - acceleration, 338, 339
 - deceleration, 338
 - driver operational control, 338
 - dynamic car-following model, 338
 - gas and brake pedals, 338
 - human factors, 338
 - Newell nonlinear car-following model, 337
 - Newton's second law of motion, 339
 - physics, 338
 - traffic flow models, 337
- picoscopic models, 351
- traffic flow models, 351, 352*f*

V

- Van Aerde car-following model, 331-332
- Van Aerde model
 - fundamental diagram, 235*f*
 - macroscopic benchmarking, 231-233, 233*t*
 - microscopic benchmarking, 231, 233*t*, 234*f*
 - Pipes model and Greenshields model, 230
 - properties of, 230-231
- Video detection system (VDS), 13-14
- Video image processing system (VIPS)
 - advantages, 7
 - data collection, 7
 - detection zone, 6
 - disadvantages, 7
 - roadway traffic, 6
 - video camera, 6
- VISSIM, 245-247

W

Waves

- characteristic method, 92-94
- characteristics
 - characteristic lines/characteristics, 90
 - domain of dependence, 89

- range of influence, 89
- conservation law, 99
- entropy condition, 109-110
- general solution to wave equations, 87-89
- gradient catastrophes
 - break time, 99-101
 - compression wave, 101
 - expansion wave, 101
 - infinite gradient, 99-101
 - solution profile, 101, 101*f*
 - time-space points, 99-101
- mathematical representation
 - homogeneity, 85
 - linearity, 85
 - notation, 84
 - order, 84-85
- PDE, 83
- properties
 - characteristics, 94-96
 - solution, 96
- rarefaction waves
 - characteristics method, 107
 - characteristics without intersection, 105*f*
 - conservation law problem, 107
 - empty area, characteristic filling, 106*f*
 - Rankine-Hugoniot jump condition, 107-108
 - shock wave solution, 108, 108*f*
 - time development of, 106*f*
- shock waves
 - characteristic intersections, 102
 - conservation law, 103
 - kinematic waves, 104
 - piecewise solution, 102*f*
 - Rankine-Hugoniot jump condition, 102, 103-104
 - shock path, 102, 104, 104*f*
- solution, wave equation, 90-92
- surface waves, 84*f*
- traffic waves, 84*f*
- traveling waves, 85-86
- traveling wave solutions, 86
- wave front and pulse, 87
- wave phenomena, 83
- wave terminology, 110-111
- Wiedmann model, 345, 345*f*
- "Wrong-way travel," 165