

```

# Code by Sarah Wiegreffe (saw@gatech.edu)
# Fall 2019

import numpy as np

import torch
from torch import nn
import random

##### Do not modify these imports.

class ClassificationTransformer(nn.Module):
    """
    A single-layer Transformer which encodes a sequence of text and
    performs binary classification.

    The model has a vocab size of V, works on
    sequences of length T, has an hidden dimension of H, uses word
    vectors
    also of dimension H, and operates on minibatches of size N.
    """
    def __init__(self, word_to_ix, hidden_dim=128, num_heads=2,
dim_feedforward=2048, dim_k=96, dim_v=96, dim_q=96, max_length=43):
        '''
        :param word_to_ix: dictionary mapping words to unique indices
        :param hidden_dim: the dimensionality of the output embeddings
that go into the final layer
        :param num_heads: the number of Transformer heads to use
        :param dim_feedforward: the dimension of the feedforward network
model
        :param dim_k: the dimensionality of the key vectors
        :param dim_q: the dimensionality of the query vectors
        :param dim_v: the dimensionality of the value vectors
        '''
        super(ClassificationTransformer, self).__init__()
        assert hidden_dim % num_heads == 0

        self.num_heads = num_heads
        self.word_embedding_dim = hidden_dim
        self.hidden_dim = hidden_dim
        self.dim_feedforward = dim_feedforward
        self.max_length = max_length
        self.vocab_size = len(word_to_ix)

        self.dim_k = dim_k
        self.dim_v = dim_v
        self.dim_q = dim_q

        seed_torch(0)

#####
#####

```

```

        # Deliverable 1: Initialize what you need for the embedding
lookup (1 line). #
        # Hint: you will need to use the max_length parameter above.
#

#####

        self.token_embeddings =
nn.Embedding(num_embeddings=self.vocab_size,embedding_dim=self.hidden_dim
)
        self.positional_embeddings =
nn.Embedding(num_embeddings=self.max_length,embedding_dim=self.hidden_dim
)

#####

#                                     END OF YOUR CODE
#

#####

#####

#####
# Deliverable 2: Initializations for multi-head self-attention.
#
# You don't need to do anything here. Do not modify this code.
#

#####

# Head #1
self.k1 = nn.Linear(self.hidden_dim, self.dim_k)
self.v1 = nn.Linear(self.hidden_dim, self.dim_v)
self.q1 = nn.Linear(self.hidden_dim, self.dim_q)

# Head #2
self.k2 = nn.Linear(self.hidden_dim, self.dim_k)
self.v2 = nn.Linear(self.hidden_dim, self.dim_v)
self.q2 = nn.Linear(self.hidden_dim, self.dim_q)

self.softmax = nn.Softmax(dim=2)
self.attention_head_projection = nn.Linear(self.dim_v *
self.num_heads, self.hidden_dim)
self.norm_mh = nn.LayerNorm(self.hidden_dim)

```

```

#####
#####
# Deliverable 3: Initialize what you need for the feed-forward
layer.      #
# Don't forget the layer normalization.
#

#####
#####

self.ffdlayer1 = nn.Linear(self.hidden_dim,self.dim_feedforward)
self.reluLayer = nn.ReLU()
self.ffdlayer2 = nn.Linear(self.dim_feedforward,self.hidden_dim)
self.norm_ff = nn.LayerNorm(self.hidden_dim)


#####
#####
#                                     END OF YOUR CODE
#

#####
#####


#####
#####
# Deliverable 4: Initialize what you need for the final layer (1-
2 lines).  #

#####
#####

self.finalLayer = nn.Linear(self.hidden_dim,1)
self.sigmoid = nn.Sigmoid()


#####
#####
#                                     END OF YOUR CODE
#

#####
#####

def forward(self, inputs):
    '''
    This function computes the full Transformer forward pass.
    Put together all of the layers you've developed in the correct
order.

```

```
        :param inputs: a PyTorch tensor of shape (N,T). These are integer
lookups.
```

```
        :returns: the model outputs. Should be normalized scores of shape
(N,1).
```

```
        '''
```

```
        outputs = None
```

```
#####
###
```

```
        # Deliverable 5: Implement the full Transformer stack for the
forward pass. #
```

```
        # You will need to use all of the methods you have previously
defined above. #
```

```
        # You should only be calling ClassificationTransformer class
methods here. #
```

```
#####
###
```

```
        embeddings = self.embed(inputs)
```

```
        multi_head_attention = self.multi_head_attention(embeddings)
```

```
        ffd_layer_output = self.feedforward_layer(multi_head_attention)
```

```
        outputs = self.final_layer(ffd_layer_output)
```

```
#####
###
```

```
        #                                     END OF YOUR CODE
```

```
#
```

```
#####
###
```

```
        return outputs
```

```
def embed(self, inputs):
```

```
    """
```

```
    :param inputs: intTensor of shape (N,T)
```

```
    :returns embeddings: floatTensor of shape (N,T,H)
```

```
    """
```

```
    embeddings = None
```

```
#####
###
```

```
        # Deliverable 1: Implement the embedding lookup.
```

```
#
```

```
        # Note: word_to_ix has keys from 0 to self.vocab_size - 1
```

```
#
```

```
        # This will take a few lines.
```

```
#
```

```
#####
###
```



```
#####
####
    return outputs

    def feedforward_layer(self, inputs):
        """
        :param inputs: float32 Tensor of shape (N,T,H)
        :returns outputs: float32 Tensor of shape (N,T,H)
        """
        outputs = None

#####
####
        # Deliverable 3: Implement the feedforward layer followed by add
+ norm.    #
        # Use a ReLU activation and apply the linear layers in the order
you        #
        # initialized them.
#
        # This should not take more than 3-5 lines of code.
#

#####
####

        ffd1Out = self.ffdLayer1(inputs)
        reluOut = self.reluLayer(ffd1Out)
        ffd2Out = self.ffdLayer2(reluOut)
        outputs = self.norm_ff(ffd2Out+inputs)

#####
####
        #                                END OF YOUR CODE
#

#####
####
    return outputs

    def final_layer(self, inputs):
        """
        :param inputs: float32 Tensor of shape (N,T,H)
        :returns outputs: float32 Tensor of shape (N,1)
        """
        outputs = None

#####
####
        # Deliverable 4: Implement the final layer for the Transformer
classifier. #
```

```

        # This should not take more than 2 lines of code.
#
#####
#####

        inputs = inputs[:,0,:].squeeze(1)
        final_o = self.finalLayer(inputs)
        outputs = self.sigmoid(final_o)

#####
#####

        #                                END OF YOUR CODE
#

#####
#####

        return outputs

def seed_torch(seed=0):
    random.seed(seed)
    np.random.seed(seed)
    torch.manual_seed(seed)
    torch.cuda.manual_seed(seed)
    torch.backends.cudnn.benchmark = False
    torch.backends.cudnn.deterministic = True

```