

Assignment 6

Allison Tessman

2024-02-22

1. Use the codes in the slides to plot the ACF of:

- a white-noise that follows the standard normal distribution (using rnorm function)

```
set.seed(30)
```

```
#Create a white-noise time series
```


```
y <- ts(rnorm(100))
```

```
library(ggfortify)
```

```
## Loading required package: ggplot2
```


```
autoplot(y) + ggtitle("White noise of Standard Normal Distribution")
```

White noise of Standard Normal Distribution




```
#plot its ACF  
acf(y)
```

Series y



- a time series with trend


```
y = ts(c(1:100))  
acf(y)
```



- a time series with seasonality


```
set.seed(30)
y = cos(1:100)
y <- ts(y)

acf(y)
```



- a time series with trend and seasonality

```
y = ts(cos(c(1:100))+c(1:100))  
acf(y)
```



Comment on the difference between the ACF of the white-noise and other time series.


- The ACF of the white noise goes both positive and negative between -0.2 and 0.2, except for the first part that jumps to 1.0
- The ACF of the time series with trend shows a steady decline of the ACF from 1.0 to about 0.5, and there are no negative values
- The ACF of the time series with seasonality goes both positive and negative, but there is a pattern to it with positive values 1.0 and 0.5, then -0.5, -1.0, and -0.75, and then the plot returns to positive values of similar height.

2. Use the codes in the slides to simulate a different random walk Y_t and:

- plot the random walk Y_t


```
n = 100
error_mean = 0
c <- rnorm(n, mean = error_mean, sd = 30)
y_0 = 0
y = c(y_0, 2:n)
```

```
for (i in 2:n)
{
  y[i] = y[i-1]+c[i]
}
y = ts(y)
plot(y)
```




- plot the ACF of the random walk

```
acf(y)
```




- plot the differencing of Y_t

```
plot(diff(y))
```

- plot the ACF of the differencing of Y_t

```
acf(diff(y))
```



3. Use the codes in the slides to simulate a different random walk Y_t with drift 2024 and:

- plot the random walk Y_t


```
set.seed(30)
n = 1000
c <- rnorm(n, sd = 20)
y_0 = 0
drift = 5
y = c(y_0, 2:n)
for (i in 2:n)
{
  y[i] = drift + y[i-1] + c[i]
}

library(ggfortify)
library(latex2exp)

plot(ts(y))


title(paste0("A random walk with drift ", drift))
```

A random walk with drift 5




- plot the ACF of the random walk

```
acf(y)
```




- plot the differencing of Y_t

```
plot(diff(ts(y)))
```



- plot th ACF of the differencing of Y_t

```
acf(diff(y))
```



4. Use the codes in the slides to plot the stock of Apple. Also:

- Plot the ACF of the stock

```
library(quantmod)
```

```
## Loading required package: xts
```

```
## Loading required package: zoo
```

```
##
```

```
## Attaching package: 'zoo'
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##   as.Date, as.Date.numeric
```

```
## Loading required package: TTR
```

```
## Registered S3 method overwritten by 'quantmod':
```


```
##   method           from
```

```
##   as.zoo.data.frame zoo
```

```
getSymbols('AAPL', src='yahoo')
```


```
## [1] "AAPL"
```

```
y = Ad(AAPL[index(AAPL)>"2023-01-01",])  
plot(y)
```




- Plot the differencing of the stock

```
plot(diff(y))
```



- Plot the ACF of the differencing of the stock

```
acf(diff(y), na.action = na.pass)
```

Is it reasonable to assume that Apple stock is following the random walk model?

- Yes, it is reasonable to assume that the stock follows the random walk model.
- It follows the same characteristics as the slides for the Microsoft stock example

5. Find other stocks that may be following the random walk model.


- Disney (DIS):

```
library(quantmod)


#Disney stock
getSymbols('DIS', src='yahoo')

## [1] "DIS"

y = Ad(DIS[index(DIS)>"2023-01-01",])
plot(y)
```




```
#plot differencing  
plot(diff(y))
```



```
#acf of differencing  
acf(diff(y), na.action = na.pass)
```

Series diff(y)




- Amazon (AMZN):

```
library(quantmod)


#Amazon stock
getSymbols('AMZN', src='yahoo')

## [1] "AMZN"

y = Ad(AMZN[index(AMZN)>"2023-01-01",])
plot(y)
```



```
#plot differencing  
plot(diff(y))
```



```
#acf of differencing  
acf(diff(y), na.action = na.pass)
```

Series diff(y)

