

Toward Quantum Competitiveness in Adiabatic Quantum Computing: A Comparative Study of Variational and Factoring Algorithms

PHILIPP HANUSSEK

MASTER 2 QUANTUM INFORMATION, SORBONNE UNIVERSITÉ, PARIS, FRANCE

SUPERVISOR: DR HAB. BARTŁOMIEJ GARDAS, IITiS PAN, GLIWICE, POLAND



- 1 Local Context
- 2 Quantum Annealing
- 3 Factoring Problem
- 4 Restricted Boltzmann Machines
- 5 Quantum Ising Models
- 6 Samplers
- 7 Results


1

Local Context

- Institute of Applied and Theoretical Informatics, Polish Academy of Sciences
- Quantum Systems for Informatics group
- Work on Adiabatic Quantum Computing, simulation of many-body quantum systems




- Previous results on *exact solving* were not very promising
- Problems where a wide range of samples, not necessarily the exact solution, can be exploited



(a) Time-to-success, quantum simulation

doi:10.1103/rff3-jm5m



(b) Success rate prime factorization

arXiv:2410.14397

2

Quantum Annealing


Driver Hamiltonian

$$H_D = - \sum_{i=1}^N \sigma_x^{(i)} \text{ with ground state } |+\rangle^{\otimes N}$$


Problem Hamiltonian

$$H_P = \sum_{i=1}^N h_i \sigma_z^{(i)} + \sum_{i=1}^N \sum_{j=1}^{i-1} J_{ij} \sigma_z^{(i)} \otimes \sigma_z^{(j)}$$


Stays in the ground state according to the adiabatic theorem [1, 2]



Annealing schedules $A(s)$, $B(s)$



(a) Pegasus (Advantage)



(b) Zephyr (Advantage2)

Circles: qubits; blue: internal couplers; orange: external couplers.
Zephyr has more couplers per qubit and longer-range links.

3

Factoring Problem

Definition

Given a composite integer N , find its non-trivial factors p and q such that

$$N = p \times q$$

Methods

- Modified multiplication table method — Jiang et al., 2018 [3]
- Controlled full-adder (CFA) method — Ding et al., 2023 [4]

Based on my bachelor's thesis [5]; see also [6]

Modified Multiplication Table Method

	2^6	2^5	2^4	2^3	2^2	2^1	2^0
p					1	p_0	1
q				1	q_1	q_0	1
+					1	p_0	1
+				q_0	$p_0 q_0$	q_0	
+			q_1	$p_0 q_1$	q_1		
+		1	p_0	1			
+	-	-	-	-	-	c_0	-
+							
+			c_2	c_1			
+		c_4	c_3				
+	c_6	c_5					
+	c_7						
N	1	0	1	1	0	1	1

(a) Block size 1: 8 carry bits

	2^6	2^5	2^4	2^3	2^2	2^1	2^0
p					1	p_0	1
q				1	q_1	q_0	1
+					1	p_0	1
+				q_0	$p_0 q_0$	q_0	
+			q_1	$p_0 q_1$	q_1		
+		1	p_0	1			
+	-	-	-	-	-	-	-
+			c_1	c_0			
+							
+	c_3	c_2					
+							
N	1	0	1	1	0	1	1

(b) Block size 2: 4 carry bits

3×4 -bit multiplication table for $N = (1011011)_2 = 91$ [5, 3]

Modified Multiplication Table Method

From block size 2 (b) we obtain one equation per block:

$$\begin{aligned} 2(1 + p_0q_0 + q_1 - (4c_1 + 2c_0)) + p_0 + q_0 &= (01)_2 = 1 \\ 2(q_1 + p_0 + c_1 - (4c_3 + 2c_2)) + q_0 + p_0q_1 + 1 + c_0 &= (11)_2 = 3 \\ 2c_3 + 1 + c_2 &= (10)_2 = 2 \end{aligned}$$

Cost function

$$f(p, q, c) = \sum_k (\text{LHS}_k - \text{RHS}_k)^2, \quad \min f = 0 \iff N = p \times q$$


- **Reduce:** higher-order terms (e.g. $p_0q_0 \cdot p_0q_1$) to quadratic via auxiliary qubits

Source: [5, 3]


CFA gate

$$2 c_{\text{out}} + \text{out} = (\text{enable} \wedge \text{in}_1) + \text{in}_2 + c_{\text{in}}$$

		p_2	p_1	p_0	$*q_0$
	N_{03}	N_{02}	N_{01}	N_{00}	+
	p_2	p_1	p_0		$*q_1$
	N_{14}	N_{13}	N_{12}	N_{11}	+
	p_2	p_1	p_0		$*q_2$
	N_{25}	N_{24}	N_{23}	N_{22}	+
	p_2	p_1	p_0		$*q_3$
	N_{36}	N_{35}	N_{34}	N_{33}	



Implementation of a 3×4 -bit multiplier with CFAs [4, p. 5]; see [5]




Advantage 5.4 QPU: 7×8 -bit multiplier

Source: [5, 4]

- *direct* into the hardware graph
- One CFA per unit cell

Factoring Results



Top: success frequency [6]. Bottom: runs with ground state in samples [5]


4

Restricted Boltzmann Machines

- classical neural network with a layer of visible and hidden units [7, 8, 9]

RBM energy function

$$E_{\theta}(\mathbf{v}, \mathbf{h}) = \mathbf{a} \cdot \mathbf{v} - \mathbf{b} \cdot \mathbf{h} - \mathbf{h} \cdot \mathbf{W}^{\top} \cdot \mathbf{v}$$



Fully connected RBM with 12 visible and 12 hidden units

1. Sampling from the Boltzmann distribution

RBM wavefunction: hidden units traced out

$$|\Psi\rangle = \sum_{\mathbf{v}} \Psi(\mathbf{v}) |\mathbf{v}\rangle, \quad \Psi(\mathbf{v}) = \sqrt{\sum_{\mathbf{h}} e^{-E_{\theta}(\mathbf{v}, \mathbf{h})}}$$

$$\Rightarrow \Psi(\mathbf{v}) = e^{-\mathbf{a} \cdot \mathbf{v} / 2} \prod_{j=1}^{N_h} [2 \cosh(b_j + \sum_i W_{ij} v_i)]^{1/2}$$

closed form [8]

Born-rule marginal

$$\rho(\mathbf{v}) = \frac{|\Psi(\mathbf{v})|^2}{\sum_{\mathbf{v}'} |\Psi(\mathbf{v}')|^2}$$

2. Calculating the local energies

Local energy [9]

$$E_{\text{loc}}(\mathbf{v}) = \frac{\langle \mathbf{v} | H | \Psi \rangle}{\Psi(\mathbf{v})}$$

TFIM local energy [9, 8]

$$E_{\text{loc}}(\mathbf{v}) = -J \sum_{\langle i,j \rangle} v_i v_j - h \sum_i \frac{\Psi(\bar{\mathbf{v}}_i)}{\Psi(\mathbf{v})}$$

3. Calculate the log derivatives

Log-derivatives [9]

with $\phi_j = b_j + \sum_i W_{ij} v_i$

$$\frac{\partial \log \Psi(\mathbf{v})}{\partial \theta_k} = \frac{1}{2} \begin{cases} -v_i, & \theta_k = a_i \\ \tanh(\phi_j), & \theta_k = b_j \\ v_i \tanh(\phi_j), & \theta_k = W_{ij} \end{cases}$$

4. Update the parameters using GD / Stochastic Reconfiguration

5

Quantum Ising Models

TFIM Hamiltonian [10]

$$H = -J \sum_i \sigma_i^z \sigma_{i+1}^z - h \sum_i \sigma_i^x$$

- we already saw something similar earlier ;)




Image: PennyLane Datasets, <https://pennylane.ai/datasets/transverse-field-ising-model>

Heisenberg Hamiltonian [11]


$$H = J_1 \sum_i \boldsymbol{\sigma}_i \cdot \boldsymbol{\sigma}_{i+1} + J_2 \sum_i \boldsymbol{\sigma}_i \cdot \boldsymbol{\sigma}_{i+2}$$

$\boldsymbol{\sigma}_i = (\sigma_i^x, \sigma_i^y, \sigma_i^z)$, so $\boldsymbol{\sigma}_i \cdot \boldsymbol{\sigma}_j = \sigma_i^x \sigma_j^x + \sigma_i^y \sigma_j^y + \sigma_i^z \sigma_j^z$

- main difference to Ising: spin exchange instead of flipping, next nearest neighbor coupling
- goal in both cases: finding the **ground state** (and sampling from it)

TFIM Hamiltonian [10]

$$H = -J \sum_i \sigma_i^z \sigma_{i+1}^z - h \sum_i \sigma_i^x$$




samples from a trained model with 16 spins

6

Samplers

- Classical Markov-Chain-Monte-Carlo samplers (Metropolis [12, 13]/Gibbs [14]) on GPU and FPGA
- quantum samplers: D-Wave Quantum Annealer




The key to any marriage is good communication.


Ben Orlin, *Math with Bad Drawings*,

<https://mathwithbaddrawings.com/2018/10/31/im-going-on-a-random-walk/>

- D-Wave sampler has unknown temperature
- CEM estimates the temperature from samples [15]



(a) Candidate fits vs. observed hidden units.



(b) Matching objective $F(\beta)$.

7

Results

- sample matched framework
- hyperparameter-matched comparison, TFIM ($h = 0.5$), N up to 64


Error per spin

$$\varepsilon(t) = \frac{|\bar{E}_t - E_0|}{N}$$

$\bar{E}_t$: rolling-mean variational energy after cumulative sampling time t ; E_0 : exact ground-state energy

- median and IQR over 20 seeds per solver and size

Results: Error vs. Sampling Time



MERCI POUR VOTRE ATTENTION




- [1] M. Born and V. Fock. Beweis des adiabatensatzes. *Zeitschrift für Physik*, 51(3):165–180, 1928. <https://doi.org/10.1007/BF01343193>.
- [2] Edward Farhi, Jeffrey Goldstone, Sam Gutmann, and Michael Sipser. Quantum computation by adiabatic evolution. *arXiv preprint*, 2000. <https://arxiv.org/abs/quant-ph/0001106>.
- [3] Shuxian Jiang, Keith A. Britt, Alexander J. McCaskey, Travis S. Humble, and Sabre Kais. Quantum annealing for prime factorization, 2018. [arXiv:1804.02733](https://arxiv.org/abs/1804.02733).
- [4] Jingwen Ding, Giuseppe Spallitta, and Roberto Sebastiani. Effective prime factorization via quantum annealing by modular locally-structured embedding, 2023. [arXiv:2310.17574](https://arxiv.org/abs/2310.17574).
- [5] Philipp Hanussek. Comparison of factoring algorithms on the D-Wave quantum annealer. Bachelor's thesis, Fachhochschule Aachen / Jülich Supercomputing Centre, Forschungszentrum Jülich, 2024.
- [6] Dennis Willsch, Philipp Hanussek, Georg Hoever, Madita Willsch, Fengping Jin, Hans De Raedt, and Kristel Michielsen. The state of factoring on quantum computers. In *NIC Symposium 2025*, volume 52 of *NIC Series*, pages 239–250, 2025. Preprint: <https://arxiv.org/abs/2410.14397>.
- [7] Francesco D'Angelo and Lucas Böttcher. Learning the ising model with generative neural networks. *Phys. Rev. Res.*, 2:023266, Jun 2020. <https://doi.org/10.1103/PhysRevResearch.2.023266>.


- [8] Giuseppe Carleo and Matthias Troyer. Solving the quantum many-body problem with artificial neural networks. *Science*, 355(6325):602–606, 2017. <https://doi.org/10.1126/science.aag2302>.
- [9] Bartłomiej Gardas, Marek M. Rams, and Jacek Dziarmaga. Quantum neural networks to simulate many-body quantum systems. *Physical Review B*, 98(18):184304, November 2018. <https://doi.org/10.1103/PhysRevB.98.184304>.
- [10] Alexander Wietek. Theory of quantum magnetism (lecture notes). https://www.pks.mpg.de/fileadmin/user_upload/MPIPKS/group_pages/SMC/quantum_magnetism_lecture_notes/lecture9.pdf. No publication date given in the source; [Accessed 29-06-2026].
- [11] W. Heisenberg. Zur theorie des ferromagnetismus. *Zeitschrift für Physik*, 49(9-10):619–636, 1928. <https://doi.org/10.1007/BF01328601>.
- [12] Nicholas Metropolis, Arianna W. Rosenbluth, Marshall N. Rosenbluth, Augusta H. Teller, and Edward Teller. Equation of state calculations by fast computing machines. *The Journal of Chemical Physics*, 21(6):1087–1092, 1953. <https://doi.org/10.1063/1.1699114>.
- [13] W. K. Hastings. Monte Carlo sampling methods using Markov chains and their applications. *Biometrika*, 57(1):97–109, 1970. <https://doi.org/10.1093/biomet/57.1.97>.

- [14] Stuart Geman and Donald Geman. Stochastic relaxation, Gibbs distributions, and the Bayesian restoration of images. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, PAMI-6(6):721–741, 1984. <https://doi.org/10.1109/TPAMI.1984.4767596>.
- [15] Kentaro Kubo and Hayato Goto. Unlocking the power of Boltzmann machines by parallelizable sampler and efficient temperature estimation, 2025. <https://arxiv.org/abs/2512.02323>.
- [16] Sergey Bravyi, David P. Divincenzo, Roberto Oliveira, and Barbara M. Terhal. The complexity of stoquastic local hamiltonian problems. *Quantum Info. Comput.*, 8(5):361–385, May 2008. <https://arxiv.org/abs/quant-ph/0606140>.
- [17] W. Marshall. Antiferromagnetism. *Proceedings of the Royal Society of London. Series A. Mathematical and Physical Sciences*, 232(1188):48–68, 1955. <https://doi.org/10.1098/rspa.1955.0200>.
- [18] J. Richter, N. B. Ivanov, and K. Retzlaff. On the violation of Marshall-Peierls sign rule in the frustrated J_1 - J_2 Heisenberg antiferromagnet. *Europhysics Letters*, 25(7):545–550, 1994. <https://doi.org/10.1209/0295-5075/25/7/012>.
- [19] Andreas Voigt and Johannes Richter. Marshall-Peierls sign rule in frustrated Heisenberg chains. *Acta Physica Polonica A*, 97(5):979, 2000. <https://arxiv.org/abs/cond-mat/0003207>.




CEM & Sampling Validation




(a) CEM vs. exact ground truth




(b) Bias across training




(c) D_{TV} vs. cooling sweeps




(a) Sparse RBM construction



(b) Sparsity vs. sampler error



(a) Parallel embedding layout



(b) QPU time speedup

Stoquasticity

A Hamiltonian is *stoquastic* if, in the given basis, all off-diagonal elements are real and non-positive [16].

Using $\sigma^x |\uparrow\rangle = |\downarrow\rangle$, $\sigma^y |\uparrow\rangle = i |\downarrow\rangle$, $\sigma^y |\downarrow\rangle = -i |\uparrow\rangle$, the Heisenberg exchange term acts on an antiparallel pair as

$$\left(\sigma_i^x \sigma_j^x + \sigma_i^y \sigma_j^y\right) |\uparrow\downarrow\rangle = |\downarrow\uparrow\rangle + (i)(-i) |\downarrow\uparrow\rangle = 2 |\downarrow\uparrow\rangle$$

Consequently, every antiparallel bond contributes

$$\langle\downarrow\uparrow| H_{ij} |\uparrow\downarrow\rangle = 2J > 0 \implies \text{not stoquastic}$$


Marshall Sign Rule

- Bipartite lattice $A \cup B$: every nearest-neighbour (J_1) bond connects a site in A to a site in B
- Unitary transformation, Pauli convention [17]:


$$U = \prod_{i \in A} \sigma_i^z$$

- Ground-state wavefunction after transformation (only positive amplitudes):

$$U|\psi_0\rangle = \sum_{\sigma} |c_{\sigma}| |\sigma\rangle$$




(a) J_1 : always $A-B$



(b) J_2 : same sublattice $\rightarrow$ breaks bipartiteness









Marshall correction survives moderate frustration [18, 19]

Marshall Sign Correction



Energy error per site vs. J_2/J_1 , with/without correction

RBM Convergence Curves



E/N vs. SR iteration, frustrated Heisenberg chain