

# CIS v3.0.0 (Azure) Level 1 Compliance Report

June 22, 2026 at 9:11:20 AM UTC

Prepared for Volvo Car Sverige Ab - 1108286888690303376

# Table of Contents

00

Executive Summary

[Overview](#)

01

Identity

[Section Overview](#)

[Section Details](#)

02

Security

[Section Overview](#)

[Section Details](#)

03

Storage Accounts

[Section Overview](#)

[Section Details](#)

04

Database Services

[Section Overview](#)

[Section Details](#)

05

Logging and Monitoring

[Section Overview](#)

[Section Details](#)

# Table of Contents (Continued)

## 06

---

**Networking**

[Section Overview](#)

[Section Details](#)

## 08

---

**AppService**

[Section Overview](#)

[Section Details](#)

## 07

---

**Virtual Machines**

[Section Overview](#)

[Section Details](#)

# Executive Summary

## CLOUD ACCOUNT(S)

az-app-7160-corp-prod-218269-9fe2c87c-f018-49df-be82-0a6dc7f0e4dc,  
az-app-6198-corp-prod-001-d00d6090-8f4e-492f-a27a-26f2243b481a,  
az-app-2025-corp-prod-001-456b04d1-daba-473b-b5f1-32c8111a89ab,  
az-app-5229-corp-nonprod-001-96a85512-4b43-4dcb-89a6-2e298863a7bb,  
az-app-2932-online-nonprod-001-c14970b8-a794-4935-aded-afbd0fdca404,  
az-app-8218-corp-dev-001-69e25e86-9814-48a0-8a7a-e20889796837,  
az-app-5612-corp-nonprod-001-c82c756b-b8db-426e-b494-3bcf19d28f40,  
az-app-570-corp-nonprod-001-9b885e19-beb7-4064-a91c-2e0873def30c,  
az-app-6861-corp-prod-001-3872ccdc-af90-43ea-bc72-2d42c0721f16,  
az-app-4567-corp-prod-001-9b4e4a91-568f-407a-8006-3720272e1f55,  
az-app-3700-online-nonprod-001-fd620b49-4821-485f-915a-033e759353f2,  
az-app-5214-corp-prod-002-87c2779f-40c9-46c7-85c5-9040f23c0bfc,  
az-app-2859-corp-nonprod-001-3e4decfb-4c9e-4c3b-8367-7646a1a33b07,  
az-app-6670-corp-dev-001-758a841e-2e75-4240-aac8-7d7d4eb3143e,  
az-app-7399-corp-nonprod-001-03477d0f-111f-43b4-8f03-adad83fc0915,  
az-app-4081-corp-dev-617178-37ace9dc-c14a-43de-9bfa-6daf44a84343,  
az-app-8242-corp-prod-344512-4f1f576b-6a27-4fe5-8fad-cfae5eceb0a9,  
az-app-8282-corp-dev-001-7b643b5b-ff50-45d7-972e-705f72833221,  
az-app-6360-online-nonprod-001-53568cec-9b75-4e2a-87a6-dc15a6cc738e,  
az-app-5981-corp-nonprod-001-fabed079-cde6-4e6c-a17c-823e80caa879,  
az-app-8339-online-prod-001-d75f5134-7492-4548-9eb0-df61b8a1d4ea,  
az-app-2527-corp-dev-001-26a3406a-c106-43ca-8cd8-20b8851c1a14,  
az-app-3506-online-prod-001-41c9ce76-2568-436d-b8ba-fcf8e2dd5922,  
az-app-5648-corp-prod-001-e4336f91-b8d9-4746-a90e-1f995f5263ef,  
az-app-6129-online-test-001-85243d4e-dc28-4919-94eb-ba216cce57f7 and [1595 more](#)

## DATES

Generated on: June 22, 2026, 9:11:20 AM UTC

From: February 29, 2024, 5:50:24 PM UTC  
To: June 22, 2026, 9:10:50 AM UTC

# Executive Summary

| Resources Passed | Resources Failed | Resources Monitored | Accounts Monitored |
|------------------|------------------|---------------------|--------------------|
| 95,494           | 61,061           | 156,555             | 1,620              |

## Compliance Coverage Breakdown

|                                                                                         |                                |                                 |                                                                                    |                                |                                |
|-----------------------------------------------------------------------------------------|--------------------------------|---------------------------------|------------------------------------------------------------------------------------|--------------------------------|--------------------------------|
| <div>Identity</div> <div>4 Policies Enabled</div> <div><div></div></div>                | <div>Passed</div> <div>3</div> | <div>Failed</div> <div>1</div>  | <div>Security</div> <div>9 Policies Enabled</div> <div><div></div></div>           | <div>Passed</div> <div>6</div> | <div>Failed</div> <div>3</div> |
| <div>Storage Accounts</div> <div>7 Policies Enabled</div> <div><div></div></div>        | <div>Passed</div> <div>0</div> | <div>Failed</div> <div>7</div>  | <div>Database Services</div> <div>10 Policies Enabled</div> <div><div></div></div> | <div>Passed</div> <div>1</div> | <div>Failed</div> <div>9</div> |
| <div>Logging and Monitoring</div> <div>12 Policies Enabled</div> <div><div></div></div> | <div>Passed</div> <div>1</div> | <div>Failed</div> <div>11</div> | <div>Networking</div> <div>3 Policies Enabled</div> <div><div></div></div>         | <div>Passed</div> <div>1</div> | <div>Failed</div> <div>2</div> |

## Virtual Machines

5 Policies Enabled

Passed

Failed

3

2



## AppService

6 Policies Enabled

Passed

Failed

1

5





CIS v3.0.0 (Azure) Level 1

| Requirements           | Pass | Fail | Overall |
|------------------------|------|------|---------|
| Identity               | 31K  | 44K  | Fail    |
| Virtual Machines       | 5.7K | 9.2K | Fail    |
| Storage Accounts       | 52   | 3.1K | Fail    |
| Logging and Monitoring | 64   | 3K   | Fail    |
| Security               | 56K  | 1.3K | Fail    |
| AppService             | 274  | 1K   | Fail    |
| Database Services      | 1.1K | 609  | Fail    |
| Networking             | 1.9K | 316  | Fail    |
| Introduction           | 0    | 0    | Pass    |

# 1


## Identity



# Identity Overview

| Section |                                                                        |                                                              | Pass Rate | Failed | Passed |
|---------|------------------------------------------------------------------------|--------------------------------------------------------------|-----------|--------|--------|
| 2.1.1   | Azure Active Directory Security Defaults is disabled                   | <div><div></div><div></div><div></div><div></div></div> Low  | 100%      | 0      | 0      |
| 2.6     | Azure Microsoft Entra ID account lockout threshold greater than 10     | <div><div></div><div></div><div></div><div></div></div> High | 100%      | 0      | 0      |
| 2.7     | Azure Microsoft Entra ID account lockout duration less than 60 seconds | <div><div></div><div></div><div></div><div></div></div> High | 100%      | 0      | 0      |
| 2.23    | Azure subscriptions with custom roles are overly permissive            | <div><div></div><div></div><div></div><div></div></div> High | 41%       | 43,746 | 30,873 |

# Identity / Section 2.1.1



0 Resource(s) Failed

**Compliance Section: 2.1.1** ●●●● Low

**Ensure Security Defaults is enabled on Microsoft Entra ID**

**Azure Active Directory Security Defaults is disabled**


This policy identifies Azure Active Directory which have Security Defaults configuration disabled. Security Defaults contains preconfigured security settings for common identity-related attacks. This provides a basic level of security-enabled by default. It is recommended to enable this configuration as a security best practice.

**First Seen** N/A | **Resource Type** Other

**Recommendations**

- 1. Login to Azure portal.
- 2. Navigate to 'Azure Active Directory'
- 3. Select 'Properties' under 'Manage'
- 4. Click on 'Manage Security defaults' if not selected
- 5. Under 'Enable Security defaults' select 'Yes' for 'Enable Security defaults'
- 6. Click on 'Save'

# Identity / Section 2.6



0 Resource(s) Failed

## Compliance Section: 2.6 ●●● High

Ensure that account 'Lockout Threshold' is less than or equal to '10'

### Azure Microsoft Entra ID account lockout threshold greater than 10

This policy identifies if the account lockout threshold for Microsoft Entra ID (formerly Azure AD) accounts is configured to allow more than 10 failed login attempts before the account is locked out.

A high lockout threshold (greater than 10) increases the risk of brute-force or password spray attacks, where attackers can attempt multiple passwords over time without triggering account lockouts, leaving accounts vulnerable to unauthorized access. Setting the lockout threshold to a reasonable value (e.g., less than or equal to 10) balances usability and security by limiting the number of login attempts before an account is locked, reducing exposure to attacks while preventing frequent unnecessary lockouts for legitimate users.


As a security best practice, it is recommended to configure the account lockout threshold to less than or equal to 10.

**First Seen** N/A | **Resource Type** Other

### Recommendations

1. Log in to Azure Portal and search for 'Microsoft Entra ID'
2. Select 'Microsoft Entra ID'
3. Under Manage, select Security
4. Under Manage, select Authentication methods
5. Under Manage, select Password protection
6. Set the 'Lockout threshold' to 10 or fewer
7. Click 'Save'

# Identity / Section 2.7



0 Resource(s) Failed

## Compliance Section: 2.7 ●●●● High

Ensure that account 'Lockout duration in seconds' is greater than or equal to '60'

### Azure Microsoft Entra ID account lockout duration less than 60 seconds

This policy identifies if the account lockout duration for Microsoft Entra ID (formerly Azure AD) accounts is configured to be less than 60 seconds. The lockout duration determines how long the account remains locked after exceeding the lockout threshold.

A lockout duration of less than 60 seconds increases the risk of brute-force or password spray attacks. Malicious actors can exploit a short lockout period to attempt multiple logins more frequently, increasing the likelihood of gaining unauthorized access. Configuring the lockout duration to be at least 60 seconds helps reduce the frequency of repeated login attempts during a brute-force attack, improving protection against such attacks while ensuring a reasonable delay for legitimate users after exceeding the threshold.

As a security best practice, it is recommended to configure the account lockout duration to greater than or equal to 60 seconds.

**First Seen** N/A | **Resource Type** Other

### Recommendations

1. Log in to Azure Portal and search for 'Microsoft Entra ID'
2. Select 'Microsoft Entra ID'
3. Under Manage, select Security
4. Under Manage, select Authentication methods
5. Under Manage, select Password protection
6. Set the 'Lockout duration in seconds' to 60 or higher
7. Click 'Save'

# Identity / Section 2.23



## 43,746 Resource(s) Failed

PBIMonitor-Owner-LimitAction, devops-contributor, Application owners, Subscription Owner GF v2, Owner-LimitAction, GRIP\_Reader, Managed Offering 3, Subscription owner, Managed Offering, Network management(GF) & 43,736 more

### Compliance Section: 2.23 High

#### Ensure That No Custom Subscription Administrator Roles Exist

##### Azure subscriptions with custom roles are overly permissive

Overly permissive custom roles in Azure subscriptions pose a significant security risk, allowing unauthorized access and potential data breaches. These roles, if not properly configured, grant excessive privileges beyond what's necessary for legitimate operations.

Azure's role-based access control (RBAC) allows creating custom roles, but misconfiguration can grant 'Owner' or other highly privileged roles to users or groups unnecessarily. Attackers exploiting this could gain complete control over resources, leading to data exfiltration, unauthorized modifications, or service disruptions.

The impact of this misconfiguration includes data loss, system compromise, and regulatory non-compliance. Following the principle of least privilege ensures that only the minimum necessary permissions are granted, minimizing the impact of potential compromises. This strengthens the overall security posture by limiting the blast radius of any successful attack.

To mitigate this, regularly review and audit all custom roles. Ensure that each role only includes the absolute minimum required 'permissions' for its intended function. Regularly review user and group assignments to identify and remove any unnecessary permissions. Implement a robust change management process for all role modifications.

**First Seen** June 25, 2024 at 3:29:51 PM UTC | **Resource Type** Other

#### Recommendations

Check the usage of the role identified. Verify impact caused by Updating/deleting the role. Then follow below URL for updating or deleting custom role:

<https://learn.microsoft.com/en-us/azure/role-based-access-control/custom-roles-portal#update-a-custom-role>

# 2


## Security



# Security Overview

| Section |                                                                                         |                                      | Pass Rate | Failed | Passed |
|---------|-----------------------------------------------------------------------------------------|--------------------------------------|-----------|--------|--------|
| 3.1.10  | Azure Microsoft Defender for Cloud system updates monitoring is set to disabled         | <div><div></div></div> Informational | 100%      | 0      | 53,909 |
| 3.1.12  | Azure Microsoft Defender for Cloud email notification for subscription owner is not set | <div><div></div></div> Informational | 97%       | 47     | 1,573  |
| 3.1.13  | Azure Microsoft Defender for Cloud security alert email notifications is not set        | <div><div></div></div> Informational | 100%      | 0      | 1,620  |
| 3.1.13  | Azure Microsoft Defender for Cloud security contact additional email is not set         | <div><div></div></div> Informational | 97%       | 47     | 1,573  |
| 3.1.14  | Azure Microsoft Defender for Cloud security alert email notifications is not set        | <div><div></div></div> Informational | 100%      | 0      | 1,620  |
| 3.3.1   | Azure Key Vault Key has no expiration date (RBAC Key vault)                             | <div><div></div></div> Informational | 100%      | 0      | 1,402  |
| 3.3.2   | Azure Key Vault Key has no expiration date (Non-RBAC Key vault)                         | <div><div></div></div> Informational | 100%      | 0      | 1,402  |
| 3.3.3   | Azure Key Vault secret has no expiration date (RBAC Key vault)                          | <div><div></div></div> Informational | 100%      | 0      | 1,402  |
| 3.3.4   | Azure Key Vault secret has no expiration date (Non-RBAC Key vault)                      | <div><div></div></div> Informational | 100%      | 0      | 1,402  |
| 3.3.5   | Azure Key Vault is not recoverable                                                      | <div><div></div></div> Informational | 9%        | 1,263  | 140    |

# Security / Section 3.1.10



0 Resource(s) Failed

**Compliance Section: 3.1.10** — Informational

**Ensure that Microsoft Defender Recommendation for 'Apply system updates' status is Completed**

**Azure Microsoft Defender for Cloud system updates monitoring is set to disabled**

This policy identifies the Azure Microsoft Defender for Cloud (previously known as Azure Security Center and Azure Defender) policies which have system updates monitoring set to disabled. It retrieves a daily list of available security and critical updates from Windows Update or Windows Server Update Services. The retrieved list depends on the service that's configured for that virtual machine and recommends that the missing updates be applied. For Linux systems, the policy uses the distro-provided package management system to determine packages that have available updates. It also checks for security and critical updates from Azure Cloud Services virtual machines.

**First Seen** N/A | **Resource Type** Other

**Recommendations**

Use CLI command to remediate this.



# Security / Section 3.1.12



**47 Resource(s) Failed**  
default & 37 more

**Compliance Section: 3.1.12** — Informational

**Ensure That 'All users with the following roles' is set to 'Owner'**

**Azure Microsoft Defender for Cloud email notification for subscription owner is not set**

This policy identifies the Azure Microsoft Defender for Cloud (previously known as Azure Security Center and Azure Defender) in which email notification for subscription owners is not set. Enabling security alert emails to subscription owners ensures that they receive security alert emails from Microsoft. This ensures that they are aware of any potential security issues and can mitigate the risk in a timely fashion.

**First Seen** April 24, 2025 at 12:29:15 PM UTC | **Resource Type** Other

**Recommendations**

1. Log in to the Azure portal
2. Go to 'Microsoft Defender for Cloud'
3. Select 'Environment Settings'
4. Click on the subscription name
5. Click on 'Email notifications'
6. In the drop down of the 'All users with the following roles' field select 'Owner'
7. Select 'Save'

# Security / Section 3.1.13



0 Resource(s) Failed

**Compliance Section: 3.1.13** — Informational

**Ensure 'Additional email addresses' is Configured with a Security Contact Email**

**Azure Microsoft Defender for Cloud security alert email notifications is not set**

This policy identifies the Azure Microsoft Defender for Cloud (previously known as Azure Security Center and Azure Defender) which have not set security alert email notifications. Enabling security alert emails ensures that security alert emails are received from Microsoft. This ensures that the right people are aware of any potential security issues and are able to mitigate the risk.

**First Seen** N/A | **Resource Type** Other

**Recommendations**

- 1. Log in to the Azure portal
- 2. Go to 'Microsoft Defender for Cloud'
- 3. Select 'Environment Settings'
- 4. Click on the subscription name
- 5. Click on 'Email notifications'
- 6. Under 'Notification types', check the check box next to Notify about alerts with the following severity (or higher): and select High from the drop down menu
- 7. Select 'Save'

# Security / Section 3.1.13



**47 Resource(s) Failed**  
default & 37 more

**Compliance Section: 3.1.13** — Informational

**Ensure 'Additional email addresses' is Configured with a Security Contact Email**

**Azure Microsoft Defender for Cloud security contact additional email is not set**

This policy identifies the Azure Microsoft Defender for Cloud (previously known as Azure Security Center and Azure Defender) which has not set security contact additional email addresses. Microsoft Defender for Cloud emails the subscription owners whenever a high-severity alert is triggered for their subscription. Providing a security contact email address as an additional email address ensures that the proper people are aware of any potential compromise in order to mitigate the risk in a timely fashion.

**First Seen** October 24, 2025 at 1:08:46 AM UTC | **Resource Type** Other

**Recommendations**

1. Log in to the Azure portal
2. Go to 'Microsoft Defender for Cloud'
3. Select 'Environment Settings'
4. Click on the subscription name
5. Click on 'Email notifications'
6. Enter a valid security contact email address (or multiple addresses separated by commas) in the 'Additional email addresses' field
7. Select 'Save'

# Security / Section 3.1.14



0 Resource(s) Failed

**Compliance Section: 3.1.14** — Informational

**Ensure That 'Notify about alerts with the following severity' is Set to 'High'**

**Azure Microsoft Defender for Cloud security alert email notifications is not set**


This policy identifies the Azure Microsoft Defender for Cloud (previously known as Azure Security Center and Azure Defender) which have not set security alert email notifications. Enabling security alert emails ensures that security alert emails are received from Microsoft. This ensures that the right people are aware of any potential security issues and are able to mitigate the risk.

**First Seen** N/A | **Resource Type** Other

**Recommendations**

1. Log in to the Azure portal
2. Go to 'Microsoft Defender for Cloud'
3. Select 'Environment Settings'
4. Click on the subscription name
5. Click on 'Email notifications'
6. Under 'Notification types', check the check box next to Notify about alerts with the following severity (or higher): and select High from the drop down menu
7. Select 'Save'

# Security / Section 3.3.1



0 Resource(s) Failed

## Compliance Section: 3.3.1 — Informational

### Ensure that the Expiration Date is set for all Keys in RBAC Key Vaults

#### Azure Key Vault Key has no expiration date (RBAC Key vault)

This policy identifies Azure Key Vault keys that do not have an expiration date for the RBAC Key vaults. As a best practice, set an expiration date for each key and rotate your keys regularly.

Before you activate this policy, ensure that you have added the Prisma Cloud Service Principal to each Key Vault: <https://docs.paloaltonetworks.com/prisma/prisma-cloud/prisma-cloud-admin/connect-your-cloud-platform-to-prisma-cloud/on-board-your-azure-account/azure-onboarding-checklist>


Alternatively, run the following command on the Azure cloud shell:  
`az keyvault list | jq '.[].id' | xargs -I {} az role assignment create --assignee "<Object ID of Prisma Cloud Principal>" --role "Key Vault Reader" --scope {}`

**First Seen** N/A | **Resource Type** Other

### Recommendations

1. Log in to the Azure portal.
2. Select 'All services' > 'Key vaults'.
3. Select the Key vault where the key is stored.
4. Select 'Keys', and select the key that you need to modify.
5. Select the current version.
6. Set the expiration date.
7. 'Save' your changes.

# Security / Section 3.3.2



0 Resource(s) Failed

## Compliance Section: 3.3.2 — Informational

**Ensure that the Expiration Date is set for all Keys in Non-RBAC Key Vaults.**

### Azure Key Vault Key has no expiration date (Non-RBAC Key vault)

This policy identifies Azure Key Vault keys that do not have an expiration date for the Non-RBAC Key vaults. As a best practice, set an expiration date for each key and rotate your keys regularly.

Before you activate this policy, ensure that you have added the Prisma Cloud Service Principal to each Key Vault: <https://docs.paloaltonetworks.com/prisma/prisma-cloud/prisma-cloud-admin/connect-your-cloud-platform-to-prisma-cloud/on-board-your-azure-account/azure-onboarding-checklist>

Alternatively, run the following command on the Azure cloud shell:  
`az keyvault list | jq '.[].name' | xargs -I {} az keyvault set-policy --name {} --certificate-permissions list listissuers --key-permissions list --secret-permissions list --spn <prismacloud_app_id>`


**First Seen** N/A | **Resource Type** Other

### Recommendations

1. Log in to the Azure portal
2. Select 'All services' > 'Key vaults'
3. Select the Key vault where the key is stored
4. Select 'Keys', and select the key that you need to modify
5. Select the current version
6. Set the expiration date
7. 'Save' your changes



# Security / Section 3.3.3



0 Resource(s) Failed

**Compliance Section: 3.3.3** — Informational

**Ensure that the Expiration Date is set for all Secrets in RBAC Key Vaults**

**Azure Key Vault secret has no expiration date (RBAC Key vault)**

This policy identifies Azure Key Vault secrets that do not have an expiry date for the RBAC Key vaults. As a best practice, set an expiration date for each secret and rotate the secret regularly.

Before you activate this policy, ensure that you have added the Prisma Cloud Service Principal to each Key Vault: <https://docs.paloaltonetworks.com/prisma/prisma-cloud/prisma-cloud-admin/connect-your-cloud-platform-to-prisma-cloud/on-board-your-azure-account/azure-onboarding-checklist>


Alternatively, run the following command on the Azure cloud shell:  
`az keyvault list | jq '.[].id' | xargs -I {} az role assignment create --assignee "<Object ID of Prisma Cloud Principal>" --role "Key Vault Reader" --scope {}`

**First Seen** N/A | **Resource Type** Other

**Recommendations**

- 1. Log in to the Azure portal.
- 2. Select 'All services' > 'Key vaults'.
- 3. Select the Key vault instance where the secrets are stored.
- 4. Select 'Secrets', and select the secret that you need to modify.
- 5. Select the current version.
- 6. Set the expiration date.
- 7. 'Save' your changes.

# Security / Section 3.3.4



0 Resource(s) Failed

## Compliance Section: 3.3.4 — Informational

### Ensure that the Expiration Date is set for all Secrets in Non-RBAC Key Vaults

#### Azure Key Vault secret has no expiration date (Non-RBAC Key vault)

This policy identifies Azure Key Vault secrets that do not have an expiry date for the Non-RBAC Key vaults. As a best practice, set an expiration date for each secret and rotate the secret regularly.

Before you activate this policy, ensure that you have added the Prisma Cloud Service Principal to each Key Vault: <https://docs.paloaltonetworks.com/prisma/prisma-cloud/prisma-cloud-admin/connect-your-cloud-platform-to-prisma-cloud/on-board-your-azure-account/azure-onboarding-checklist>

Alternatively, run the following command on the Azure cloud shell:  
`az keyvault list | jq '.[].name' | xargs -I {} az keyvault set-policy --name {} --certificate-permissions list listissuers --key-permissions list --secret-permissions list --spn <prismacloud_app_id>`


**First Seen** N/A | **Resource Type** Other

### Recommendations

1. Log in to the Azure portal
2. Select 'All services' > 'Key vaults'
3. Select the Key vault instance where the secrets are stored
4. Select 'Secrets', and select the secret that you need to modify
5. Select the current version
6. Set the expiration date
7. 'Save' your changes



# Security / Section 3.3.5



## 1,263 Resource(s) Failed

kv-5147-sf-vy99739-dev,  
kv-5904-sf-vcgdm-prod, ucp-crossplane-vault,  
ucp-poc-vault, kv-6664-sf-vcgdm-prod,  
vocmock, kv-rest-fusion-gql-prod,  
kv-6640-sf-bu32980-prod, RMSTKeyValut1,  
kv-cc-agentic-pltfm-prod & 1,253 more

### Compliance Section: 3.3.5 Informational

#### Ensure the Key Vault is Recoverable

##### Azure Key Vault is not recoverable

The key vault contains object keys, secrets and certificates. Accidental unavailability of a key vault can cause immediate data loss or loss of security functions (authentication, validation, verification, non-repudiation, etc.) supported by the key vault objects. It is recommended the key vault be made recoverable by enabling the "Do Not Purge" and "Soft Delete" functions. This is in order to prevent loss of encrypted data including storage accounts, SQL databases, and/or dependent services provided by key vault objects (Keys, Secrets, Certificates) etc., as may happen in the case of accidental deletion by a user or from disruptive activity by a malicious user.

**First Seen** April 24, 2025 at 12:25:03 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to the Azure Portal
2. Go to Key vaults service
3. Navigate to reported Azure Key Vault
4. In the left-hand menu, under 'Settings', select 'Properties'
5. Ensure 'Soft-delete' is enabled
6. Set 'Purge protection' to 'Enable Purge Protection'
7. Click 'Save'

# 3


## Storage Accounts



# Storage Accounts Overview

| Section |                                                                 |                                                              |                                                         | Pass Rate | Failed | Passed |
|---------|-----------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------|-----------|--------|--------|
| 4.1     | Azure Storage Account without Secure transfer enabled           | <div><div></div><div></div><div></div><div></div></div> Low  | <div><div></div><div></div><div></div><div></div></div> | 99%       | 16     | 3,152  |
| 4.5     | Azure Storage account not configured with SAS expiration policy | <div><div></div><div></div><div></div><div></div></div> Low  | <div><div></div><div></div><div></div><div></div></div> | 34%       | 2,068  | 1,100  |
| 4.6     | Azure storage account has a blob container with public access   | <div><div></div><div></div><div></div><div></div></div> High | <div><div></div><div></div><div></div><div></div></div> | 97%       | 94     | 3,074  |
| 4.7     | Azure Storage Account default network access is set to 'Allow'  | <div><div></div></div> Informational                         | <div><div></div><div></div><div></div><div></div></div> | 59%       | 1,269  | 1,899  |
| 4.10    | Azure Storage account soft delete is disabled                   | <div><div></div><div></div><div></div><div></div></div> Low  | <div><div></div><div></div><div></div><div></div></div> | 35%       | 2,057  | 1,112  |
| 4.15    | Azure Storage Account using insecure TLS version                | <div><div></div><div></div><div></div><div></div></div> Low  | <div><div></div><div></div><div></div><div></div></div> | 95%       | 137    | 3,031  |
| 4.16    | Azure Storage account with cross tenant replication enabled     | <div><div></div></div> Informational                         | <div><div></div><div></div><div></div><div></div></div> | 81%       | 595    | 2,573  |
| 4.17    | Azure storage account has a blob container with public access   | <div><div></div><div></div><div></div><div></div></div> High | <div><div></div><div></div><div></div><div></div></div> | 97%       | 94     | 3,074  |

# Storage Accounts / Section 4.1



**16 Resource(s) Failed**  
4672corpnnonprod002sa, vidangprod, vidangps, csb19b49303abcex44f7xaf9, vidangtest, stoserilogtest, vidangmrps, stoserilog1prod, ulftest, prodmonitoru314 & 6 more

**Compliance Section: 4.1** ●●●● Low

**Ensure that 'Secure transfer required' is set to 'Enabled'**

**Azure Storage Account without Secure transfer enabled**

Azure Storage accounts without Secure Transfer enabled are vulnerable to data breaches. Disabling this feature allows access via insecure HTTP, exposing sensitive data during transit to interception and unauthorized modification.

The service setting "Secure Transfer Required" in Azure Storage Accounts enforces secure connections (HTTPS) for all data transfers. Disabling it exposes data to man-in-the-middle attacks and eavesdropping, compromising data confidentiality and integrity. Attackers can intercept data transmitted over HTTP, leading to data theft or manipulation.

The impact of this misconfiguration is significant data exposure, potentially leading to data breaches, regulatory non-compliance, and reputational damage. Enforcing HTTPS protects data in transit, ensuring only authorized users can access storage accounts securely. This best practice minimizes the attack surface and strengthens the overall security posture.


Mitigate this risk by enabling "Secure Transfer Required" for all Azure Storage Accounts. Regularly audit storage account configurations to ensure compliance. Consider implementing network segmentation and intrusion detection systems for added protection.

**First Seen** February 26, 2025 at 8:52:03 AM UTC | **Resource Type** Other

**Recommendations**

To enable secure transfer feature on your storage account, follow below URL:  
<https://learn.microsoft.com/en-gb/azure/storage/common/storage-require-secure-transfer#require-secure-transfer-for-an-existing-storage-account>

# Storage Accounts / Section 4.5



**2,068 Resource(s) Failed**  
ecpweuprodpartsecomprod, polyspaceac-  
cess1509, logstashfilesharepoc, stgfingeniedev,  
tlsqastorage, carfinstorageacc, kb8052devst,  
stvccgoldpartspriceprod, dtstoragefw, sapdat-  
aprodsa & 2,058 more

**Compliance Section: 4.5** ●●●● Low

**Ensure that Shared Access Signature Tokens Expire Within an Hour**

**Azure Storage account not configured with SAS expiration policy**

This policy identifies Azure Storage accounts not configured with SAS expiration policy.

A Shared Access Signature (SAS) expiration policy specifies a recommended interval over which the SAS is valid. SAS expiration policies apply to a service SAS or an account SAS. When a user generates service SAS or an account SAS with a validity interval that is larger than the recommended interval, they'll see a warning. If Azure Storage logging with Azure Monitor is enabled, then an entry is written to the Azure Storage logs. It is recommended that you limit the interval for a SAS in case it is compromised.

For more details:  
<https://learn.microsoft.com/en-us/azure/storage/common/sas-expiration-policy>

**First Seen** August 16, 2024 at 12:14:50 PM UTC | **Resource Type** Other

**Recommendations**

To configure an expiration policy for shared access signatures for the reported Storage account, follow bellow URL:  
<https://learn.microsoft.com/en-us/azure/storage/common/sas-expiration-policy>

# Storage Accounts / Section 4.6



## 94 Resource(s) Failed

vidangqa, stpcetfinfraweuprod001, tlsproductionstorage, app3741bookingengine, weuvcwiringdiagrampdfs, pubstoragecdnweu, ndcassets, vcpdolwebstockpublictest, legalpage-sarchive, saweuemitterarcsightprod & 84 more

## Compliance Section: 4.6 High

### Ensure that 'Public Network Access' is 'Disabled' for storage accounts

#### Azure storage account has a blob container with public access

Publicly accessible Azure blob containers pose a significant security risk, enabling unauthorized access to sensitive data stored within. This misconfiguration allows anyone on the internet to read or download data without authentication.

Azure Blob Storage offers granular access control through shared access signatures or private endpoints. However, enabling 'Public access level' for a container bypasses these security measures, exposing the container and its contents to untrusted IPs. Attackers could easily exploit this to exfiltrate sensitive data, potentially leading to data breaches and regulatory violations.

The impact of this misconfiguration includes data breaches, reputational damage, and financial losses. Strict access control is crucial for data protection; allowing public access unnecessarily increases the attack surface. Restricting access to authorized users and entities only minimizes the risk of unauthorized access and data compromise.

To mitigate this, enforce the principle of least privilege. Disable 'Public access level' for all blob containers. Use shared access signatures (SAS) for controlled, time-limited access to specific data. Consider implementing private endpoints to restrict access to authorized networks. Regularly audit storage account configurations for unintended public access settings.


**First Seen** July 31, 2025 at 12:48:10 PM UTC | **Resource Type** Other

### Recommendations

1. Log in to the Azure portal
2. Navigate to 'Storage Accounts' dashboard
3. Select the reported storage account
4. Under 'Data storage' section, Select 'Containers'
5. Select the blob container you need to modify
6. Click on 'Change access level'
7. Set 'Public access level' to 'Private (no anonymous access)'
8. Click on 'OK'



# Storage Accounts / Section 4.7



**1,269 Resource(s) Failed**  
sqlmie4d6dce7, heliossalesdevsa, partsin-ventoryapi, maintenanceblobtest, sflogsvcc-nclqaus6278, strptdevdl, emearcxpopportu-napiqa, stfiletransfernaproduct, blob4d6dce7, im-ageregistrymaximo9tw7d & 1,259 more

**Compliance Section: 4.7** — Informational

**Ensure Default Network Access Rule for Storage Accounts is Set to Deny**

**Azure Storage Account default network access is set to 'Allow'**

Azure Storage accounts with default network access set to 'Allow' are susceptible to unauthorized data access. This misconfiguration exposes storage account resources to any network, increasing the risk of data breaches and unauthorized modifications.

Azure Storage accounts offer a 'Network rules' setting to control inbound traffic. By default, 'Allow' grants access from any IP address. Untrusted IPs can exploit this, leading to data exfiltration, ransomware attacks, or malicious data manipulation. Restricting network access enhances security posture significantly.

The impact of this misconfiguration includes data breaches, unauthorized resource modification, and potential compliance violations. Implementing strong access controls through network rules is crucial to protect sensitive data and maintain regulatory compliance. Restricting access to only authorized networks minimizes the attack surface.

To mitigate this risk, configure your Azure Storage accounts to explicitly allow access only from trusted IP addresses or virtual networks. Utilize the 'Network rules' setting within the storage account configuration to define specific allowed networks. Regularly review and update these rules as your infrastructure evolves.

**First Seen** June 27, 2024 at 3:27:12 PM UTC | **Resource Type** Other

**Recommendations**

To change the default network access rule, follow below URL:  
<https://learn.microsoft.com/en-us/azure/storage/common/storage-network-security?tabs=azure-portal#change-the-default-network-access-rule>

# Storage Accounts / Section 4.10



## 2,057 Resource(s) Failed

cluster33hw8rg9bn, dl servicedatatest, stqi4v7sl6nr6ws, sawus006smblob, ecp-weuprodfacilitysg, saehprod, geten-corp, saeus006smvm, faultmonitoringinsights, st4243prodbootdiag001 & 2.047 more

### Compliance Section: 4.10 ●●●● Low

#### Ensure Soft Delete is Enabled for Azure Containers and Blob Storage

##### Azure Storage account soft delete is disabled

This policy identifies Azure Storage accounts which has soft delete disabled. Azure Storage contains important access logs, financial data, personal and other secret information which is accidentally deleted by a user or application could cause data loss or data unavailability. It is recommended to enable soft delete setting in Azure Storage accounts.


**First Seen** August 16, 2024 at 12:14:50 PM UTC | **Resource Type** Other

#### Recommendations

To enable Soft delete on your storage account, follow below URL:  
<https://learn.microsoft.com/en-gb/azure/storage/blobs/soft-delete-blob-enable?tabs=azure-portal#enable-blob-soft-delete>



# Storage Accounts / Section 4.15



**137 Resource(s) Failed**  
stewamqconnectnonprod, vssmehstorageprod, st7595corpsnoqaweusys, st7595corpsnos-bxweufin, krbtpcsiterecovasrcache, st5214ai-wftpprodcw001, weunetworkscmbdevtest-dia, dtagudraggregatorstorage, fredtest000002, servicejournalprod & 127 more

**Compliance Section: 4.15** ●●●● Low

**Ensure the 'Minimum TLS version' for storage accounts is set to 'Version 1.2'**

**Azure Storage Account using insecure TLS version**

This policy identifies Azure Storage Account which is using insecure TLS version. Azure Storage Account uses Transport Layer Security (TLS) from communication with client applications. As a best security practice, use newer TLS version as the minimum TLS version for Azure Storage Account. Currently, Azure Storage Account supports TLS 1.2 version which resolves the security gap from its preceding versions.


<https://docs.microsoft.com/en-us/azure/storage/common/transport-layer-security-configure-minimum-version?tabs=portal>

**First Seen** August 23, 2024 at 1:05:49 AM UTC | **Resource Type** Other

**Recommendations**

- 1. Log in to Azure Portal
- 2. Go to Storage accounts dashboard and Click on the reported storage account
- 3. Under the 'Settings' menu, click on 'Configuration'
- 4. Under 'Minimum TLS version' select 'Version 1.2' from the drop down
- 5. Click on 'Save'

# Storage Accounts / Section 4.16



## 595 Resource(s) Failed

sauctfstateprod, acmobservabilityprd01, ecp-weudevoblclblob, stdwssnowsinkdid2, geten-corp, testweuinstoresa, hpsurerecoverswe-den, dlswicecn, ecpweudevicoeapimfs, ecp-weuqashmfeqa & 585 more

### Compliance Section: 4.16 — Informational

#### Ensure 'Cross Tenant Replication' is not enabled

##### Azure Storage account with cross tenant replication enabled

This policy identifies Azure Storage accounts that are enabled with cross tenant replication.

Azure Storage account cross tenant replication allows data to be replicated across multiple Azure tenants. Though this feature is beneficial for data availability it also poses a significant security risk if not properly managed. Possible risks include unauthorized access to data, data leaks, and compliance violations. Disabling Cross Tenant Replication reduces the risk of unauthorized data access and prevents the accidental sharing of sensitive information.

As best practice, it is recommended to disable cross tenant replication on your storage accounts.

**First Seen** April 24, 2025 at 12:24:54 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Go to Storage Account dashboard
3. Click on the reported Storage Account
4. Under 'Data management', select 'Object replication'
5. Select 'Advanced settings'
6. Uncheck 'Allow cross-tenant replication'
7. Click on 'OK'

# Storage Accounts / Section 4.17



## 94 Resource(s) Failed

vidangqa, stpcetfinfraweuprod001, tlsproductionstorage, app3741bookingengine, weuvcwiringdiagrampdfs, pubstoragecdnweu, ndcassets, vcpdolwebstockpublictest, legalpage-sarchive, saweuemitterarcsightprod & 84 more

## Compliance Section: 4.17 ●●● High

### Ensure that 'Allow Blob Anonymous Access' is set to 'Disabled'

#### Azure storage account has a blob container with public access

Publicly accessible Azure blob containers pose a significant security risk, enabling unauthorized access to sensitive data stored within. This misconfiguration allows anyone on the internet to read or download data without authentication.

Azure Blob Storage offers granular access control through shared access signatures or private endpoints. However, enabling 'Public access level' for a container bypasses these security measures, exposing the container and its contents to untrusted IPs. Attackers could easily exploit this to exfiltrate sensitive data, potentially leading to data breaches and regulatory violations.

The impact of this misconfiguration includes data breaches, reputational damage, and financial losses. Strict access control is crucial for data protection; allowing public access unnecessarily increases the attack surface. Restricting access to authorized users and entities only minimizes the risk of unauthorized access and data compromise.

To mitigate this, enforce the principle of least privilege. Disable 'Public access level' for all blob containers. Use shared access signatures (SAS) for controlled, time-limited access to specific data. Consider implementing private endpoints to restrict access to authorized networks. Regularly audit storage account configurations for unintended public access settings.

**First Seen** July 31, 2025 at 12:48:10 PM UTC | **Resource Type** Other

### Recommendations

1. Log in to the Azure portal
2. Navigate to 'Storage Accounts' dashboard
3. Select the reported storage account
4. Under 'Data storage' section, Select 'Containers'
5. Select the blob container you need to modify
6. Click on 'Change access level'
7. Set 'Public access level' to 'Private (no anonymous access)'
8. Click on 'OK'


# 4

## Database Services

# Database Services Overview

| Section |                                                                            |                 |             | Pass Rate | Failed | Passed |
|---------|----------------------------------------------------------------------------|-----------------|-------------|-----------|--------|--------|
| 5.1.1   | Azure SQL Server auditing is disabled                                      | ●●●● Low        | <div></div> | 5%        | 238    | 15     |
| 5.1.2   | Azure SQL Server allow access to any Azure internal resources              | — Informational | <div></div> | 69%       | 77     | 176    |
| 5.1.4   | Azure SQL server not configured with Active Directory admin authentication | — Informational | <div></div> | 81%       | 47     | 206    |
| 5.1.5   | Azure SQL database Transparent Data Encryption (TDE) encryption disabled   | ●●●● Low        | <div></div> | 99%       | 2      | 481    |
| 5.1.6   | Azure SQL Server audit log retention is less than 91 days                  | — Informational | <div></div> | 98%       | 3      | 250    |
| 5.1.7   | Azure SQL server public network access setting is enabled                  | ●●●● Medium     | <div></div> | 64%       | 89     | 164    |
| 5.2.1   | Azure PostgreSQL flexible server secure transport parameter is disabled    | ●●●● Medium     | <div></div> | 98%       | 11     | 599    |
| 5.3.1   | Azure MySQL database flexible server SSL enforcement is disabled           | ●●●● Low        | <div></div> | 52%       | 22     | 24     |
| 5.3.2   | Azure MySQL database flexible server using insecure TLS version            | ●●●● Low        | <div></div> | 100%      | 0      | 46     |
| 5.4.3   | Azure Cosmos DB key based authentication is enabled                        | ●●●● Low        | <div></div> | 2%        | 329    | 7      |

# Database Services / Section 5.1.1



**238 Resource(s) Failed**  
crm-vssm-azure-synapse-prod, sql-srv-5410-corp-di-pro-weu, dms-as-dev, asr-prod-db, vcbr-lake-sql-qa, sql-cloud-base-dev, sql-weu-tread-qa, c3aiagent, sqlsrv-insurance-prod, sql-server-pno-translator-prod & 228 more

**Compliance Section: 5.1.1** ●●●● Low

**Ensure that 'Auditing' is set to 'On'**

**Azure SQL Server auditing is disabled**

Audit logs can help you find suspicious events, unusual activity, and trends to analyze database events. Auditing the SQL Server, at the server-level, enables you to track all new and existing databases on the server.

This policy identifies SQL servers do not have auditing enabled. As a best practice, enable auditing on each SQL server so that the database are audited, regardless of the database auditing settings.


**First Seen** August 16, 2024 at 12:29:00 PM UTC | **Resource Type** Other

**Recommendations**

- 1. Log in to the Azure Portal.
- 2. Select 'SQL servers', and select the SQL server instance you want to modify.
- 3. Select 'Auditing', and set the status to 'On'.
- 4. 'Save' your changes.



# Database Services / Section 5.1.2



**77 Resource(s) Failed**  
trapprod, sqlsrv-sap-dev, sqlsrv-sap-prod, sql-scot-nonprod, sql-weu-swdl-datado-main-dev, sqlsrv-5214-onl-aiw-pro-weu, vcc-ncl-we-dev-sql, rules-engine-dev, vcbr-lake-sql-prod, sqlsrv-insurance-nonprod & 67 more


**Compliance Section: 5.1.2** — Informational  
**Ensure no Azure SQL Databases allow ingress from 0.0.0.0/0 (ANY IP)**  
**Azure SQL Server allow access to any Azure internal resources**

This policy identifies SQL Servers that are configured to allow access to any Azure internal resources. Firewall settings with start IP and end IP both with '0.0.0.0' represents access to all Azure internal network. When this settings is enabled, SQL server will accept connections from all Azure resources including other subscription resources as well. It is recommended to use firewall rules or VNET rules to allow access from specific network ranges or virtual networks.

**First Seen** April 24, 2025 at 12:28:56 PM UTC | **Resource Type** Other

- Recommendations**
1. Log in to Azure Portal
  2. Navigate to the 'SQL servers' dashboard
  3. Click on the reported SQL server
  4. Click on 'Networking' under Security
  5. Unselect 'Allow Azure services and resources to access this server' under Exceptions if selected.
  6. Remove any firewall rule which allows access to 0.0.0.0 in startIpAddress and endIpAddress if any.
  7. Click on 'Save'

# Database Services / Section 5.1.4



**47 Resource(s) Failed**  
app-5284-sqlserver, shlm-sql-server-non-prod-dev, app-db-server-dev, vccvclsql-prod, sql-rmb-prod-emea, sqlsrvon-line001, weu-tie-prod-levc, weu-tie-staging-vcc, weu-tie-staging-levc, chatbot-mth & 37 more

**Compliance Section: 5.1.4** — Informational

**Ensure that Microsoft Entra authentication is Configured for SQL Servers**

**Azure SQL server not configured with Active Directory admin authentication**

Azure SQL servers lacking Active Directory admin authentication present a significant security risk. This misconfiguration allows attackers to potentially use weak or default credentials to access sensitive data.

Azure SQL Database and SQL Data Warehouse offer Azure Active Directory authentication, enabling central identity management. Bypassing this feature exposes the database to brute-force attacks and credential stuffing, potentially leading to data breaches or unauthorized access. Attackers could exploit weak passwords or compromised accounts to gain control.

The impact of this misconfiguration includes unauthorized data access, modification, or deletion, resulting in data loss, regulatory non-compliance, and reputational damage. Implementing Active Directory admin authentication enhances security by centralizing identity management and enforcing strong authentication practices.


To mitigate this risk, enforce Active Directory admin authentication on all Azure SQL servers. Regularly review and update user accounts and passwords. Restrict network access to the database using network rules and monitor for suspicious login attempts. Implement multi-factor authentication for added security.

**First Seen** January 6, 2025 at 10:37:09 AM UTC | **Resource Type** Other

- Recommendations**
1. Log in to the Azure Portal.
  2. Navigate to reported Azure SQL server resource in the Azure Portal.
  3. In the left menu under 'Settings', select 'Microsoft Entra ID'.
  4. Click the 'Set admin' button at the top of the pane.
  5. In the search box, find and select the Microsoft Entra user or group you want to assign as the admin.
  6. Click the 'Select' button to confirm your choice.
  7. Click the 'Save' button on the Microsoft Entra ID page to apply the new administrator.



# Database Services / Section 5.1.5



**2 Resource(s) Failed**  
snow-openai-synapse-ws / sonw\_ai\_db\_dev,  
synapse-nonprod-westeuropa-001 / PayrollDW

**Compliance Section: 5.1.5** ●●●● Low

**Ensure that 'Data encryption' is set to 'On' on a SQL Database**

**Azure SQL database Transparent Data Encryption (TDE) encryption disabled**


This policy identifies SQL databases in which Transparent Data Encryption (TDE) is disabled. TDE encryption performs real-time encryption and decryption of the database, related reinforcements, and exchange log records without requiring any changes to the application. It encrypts the storage of an entire database by using a symmetric key called the database encryption key. It is recommended to have TDE encryption on your SQL databases to protect the database from malicious activity.

**First Seen** March 3, 2025 at 10:36:52 AM UTC | **Resource Type** Managed Database

**Recommendations**

- 1. Login to Azure Portal
- 2. Click on SQL databases (Left Panel)
- 3. Choose the reported database
- 4. Under Security, Click on Transparent data encryption
- 5. Set Data encryption to ON
- 6. Click on Save

# Database Services / Section 5.1.6



3 Resource(s) Failed

psl-compound-sqlserver-prod, vssm, digital-cardsdb

**Compliance Section: 5.1.6** — Informational

**Ensure that 'Auditing' Retention is 'greater than 90 days'**

**Azure SQL Server audit log retention is less than 91 days**

Audit Logs can help you find suspicious events, unusual activity, and trends. Auditing the SQL server, at the server-level, allows you to track all existing and newly created databases on the instance.


This policy identifies SQL servers which do not retain audit logs for more than 90 days. As a best practice, configure the audit logs retention time period to be greater than 90 days.

**First Seen** April 24, 2025 at 12:48:33 PM UTC | **Resource Type** Other

**Recommendations**

1. Log in to the Azure Portal
2. Navigate to 'SQL servers' dashboard
3. Select the SQL server instance you want to modify
4. Select 'Auditing', and verify that 'Enable Azure SQL Auditing' is set
5. If Storage is selected, expand 'Advanced properties'
6. Set the Retention (days) setting is greater than 90 days or 0 for unlimited retention.
7. Click on 'Save'

# Database Services / Section 5.1.7



**89 Resource(s) Failed**

crm-vssm-azure-synapse-prod, fipa-dms, rules-engine-dev, dms-as-dev, sql-scot-non-prod, sql-weu-swdl-datadomain-dev, vcc-ncl-ncus-prod-sql, qdfips-prod, sql-srv-5631-onl-sup-poc-weu, vcbr-lake-sql-qa & 79 more

**Compliance Section: 5.1.7** ●●●● Medium

**Ensure Public Network Access is Disabled**

**Azure SQL server public network access setting is enabled**

This policy identifies Azure SQL servers which have public network access setting enabled. Publicly accessible SQL servers are vulnerable to external threats with risk of unauthorized access or may remotely exploit any vulnerabilities. It is recommended to disable public network access to the Azure SQL servers and use private endpoints or virtual network service endpoints to secure connectivity.


**First Seen** April 21, 2025 at 9:47:22 PM UTC | **Resource Type** Other

**Recommendations**

- 1. Navigate to reported SQL Server in the Azure portal.
- 2. Under Security, select Networking.
- 3. Under Public network access, select Disable.
- 4. Click Save.

NOTE: This setting takes effect immediately upon application. Disabling public access without first configuring private endpoints or virtual network service endpoints will result in immediate connection loss.

# Database Services / Section 5.2.1



## 11 Resource(s) Failed

pql-backstage-dev,  
pql-backstage-pre-prod-260326,  
srdbpostgresql, psql-tbj-nonprod-12197,  
psql-5214-corp-aiw-sbx-weu,  
pql-backstage-prod-recovery0,  
az-psql-hpa-ci-ro, dms-as-postgres-server,  
postgresql-icoe-weu-dev-pri-  
vate-db-schema-registry-iilwxl22,  
pql-backstage-staging & 1 more

### Compliance Section: 5.2.1 ●●● Medium

Ensure server parameter 'require\_secure\_transport' is set to 'ON' for PostgreSQL flexible server

#### Azure PostgreSQL flexible server secure transport parameter is disabled

This policy identifies PostgreSQL flexible servers for which secure transport (SSL connectivity) parameter is disabled.

Secure transport (SSL connectivity) helps to provide a new layer of security, by connecting server to client applications using Secure Sockets Layer (SSL). Enforcing SSL connections between server and client applications helps protect against 'man in the middle' attacks by encrypting the data stream between the server and application.


As a security best practice, it is recommended to enable secure transport parameter for Azure PostgreSQL flexible server.

**First Seen** March 11, 2025 at 2:14:37 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to the Azure Portal
2. Navigate to 'Azure Database for PostgreSQL flexible server'
3. Click on the reported PostgreSQL flexible server
4. Navigate to Settings -> Server parameters
5. Search for parameter 'require\_secure\_transport' and set VALUE to 'ON' and You can also set min TLS version by setting 'ssl\_min\_protocol\_version' server parameter as per your business requirement.
6. Click on 'Save'

# Database Services / Section 5.3.1



**22 Resource(s) Failed**

ecp-weu-sbx-vault,  
mysql-sea-6168-dev-001-replicate,  
apex-mysql-flexible,  
ecp-weu-sbx-vault-restore,  
mysql-sea-6168-qa-mid, av-dev-mysql-server,  
mysql-sea-6168-prod-dms-replicate,  
mysql-sea-6168-dev-002,  
mysql-sea-6168-dev-001, mysqldealersites & 12  
more

**Compliance Section: 5.3.1** ●●●● Low

**Ensure server parameter 'require\_secure\_transport' is set to 'ON' for MySQL flexible server**

**Azure MySQL database flexible server SSL enforcement is disabled**


This policy identifies Azure MySQL database flexible servers for which the SSL enforcement is disabled. SSL connectivity helps to provide a new layer of security, by connecting database server to client applications using Secure Sockets Layer (SSL). Enforcing SSL connections between database server and client applications helps protect against 'man in the middle' attacks by encrypting the data stream between the server and application.

**First Seen** January 10, 2025 at 12:42:04 AM UTC | **Resource Type** Other

**Recommendations**

To enable MySQL database flexible server SSL connection, refer below URL:  
<https://docs.microsoft.com/en-us/azure/mysql/flexible-server/how-to-connect-tls-ssl>

# Database Services / Section 5.3.2



0 Resource(s) Failed

**Compliance Section: 5.3.2** ●●●● Low

**Ensure server parameter 'tls\_version' is set to 'TLSv1.2' (or higher) for MySQL flexible server**

**Azure MySQL database flexible server using insecure TLS version**

This policy identifies Azure MySQL database flexible servers which are using insecure TLS version. Enforcing TLS connections between database server and client applications helps protect against 'man in the middle' attacks by encrypting the data stream between the server and application. As a security best practice, it is recommended to use the latest TLS version for Azure MySQL database flexible server.

**First Seen** N/A | **Resource Type** Other

**Recommendations**

- 1. Log in to the Azure portal
- 2. Go to Azure Database for MySQL flexible servers dashboard
- 3. Click on the reported MySQL flexible server
- 4. Click on 'Server parameters' under 'Settings'
- 5. In the search box, type in 'require\_secure\_transport' and make sure VALUE is set to 'ON' if it is not already set.
- 6. In the search box, type in 'tls\_version' and Set VALUE to TLSV1.2 or above for tls\_version.



# Database Services / Section 5.4.3



**329 Resource(s) Failed**  
db-dms-deve,  
ecpweuprod-taxcalccosmosprod,  
ecpweusbx-bd-cosmos-2,  
di-logging-poc-secondattempt-deleteme,  
emea-rdm-snowflake-ingestion-prod,  
cosmos-cdbmarket-prod, db-veds-test,  
emea-coc-logic-qa, aurora-cosmos-db,  
ecpweudev-cds-om-message-manager-cosmos  
& 319 more

**Compliance Section: 5.4.3** ●●●● Low

**Use Entra ID Client Authentication and Azure RBAC where possible**

**Azure Cosmos DB key based authentication is enabled**

Unauthorized access to Azure Cosmos DB can occur if key-based authentication is enabled without proper controls. Improper configuration of key-based authentication exposes sensitive data and allows attackers to alter database settings.

Azure Cosmos DB's key-based authentication allows access using account keys. Disabling metadata write access via account keys enhances security by preventing unauthorized modifications to database resources. Compromised keys could lead to data breaches or service disruptions.

The impact of this misconfiguration includes data loss, unauthorized data modification, and potential service disruption. Restricting key-based access minimizes the blast radius of a compromised key, improving overall security posture and ensuring data integrity.

Implement role-based access control ('RBAC') to manage access to Azure Cosmos DB resources. Regularly rotate account keys and use strong, unique keys. Consider limiting the number of users with 'read' and 'write' permissions to only authorized personnel.

**First Seen** August 15, 2024 at 6:48:10 AM UTC | **Resource Type** Other

**Recommendations**

As of the current Azure Portal design, there is no direct UI switch or setting within the Azure Cosmos DB blade to disable key-based (local) authentication.

This specific security control, can only be managed programmatically. Please use the CLI given below to remediate the misconfiguration:

```
az cosmosdb update --name ${resourceName} --resource-group ${resourceGroup} --disable-key-based-metadata-write-access true
```

# 5

## Logging and Monitoring




# Logging and Monitoring Overview

| Section |                                                                                       |                                      |                        | Pass Rate | Failed | Passed |
|---------|---------------------------------------------------------------------------------------|--------------------------------------|------------------------|-----------|--------|--------|
| 6.1.2   | Azure Monitor Diagnostic Setting does not captures appropriate categories             | <div><div></div></div> Informational | <div><div></div></div> | 100%      | 0      | 1,620  |
| 6.1.4   | Azure Key Vault audit logging is disabled                                             | <div><div></div></div> Informational | <div><div></div></div> | 4%        | 1,339  | 64     |
| 6.2.1   | Azure Activity log alert for Create policy assignment does not exist                  | <div><div></div></div> Informational | <div><div></div></div> | 0%        | 1,620  | 0      |
| 6.2.2   | Azure Activity log alert for delete policy assignment does not exist                  | <div><div></div></div> Informational | <div><div></div></div> | 0%        | 1,620  | 0      |
| 6.2.3   | Azure Activity log alert for Create or update network security group does not exist   | <div><div></div></div> Informational | <div><div></div></div> | 0%        | 1,620  | 0      |
| 6.2.4   | Azure Activity log alert for Delete network security group does not exist             | <div><div></div></div> Informational | <div><div></div></div> | 0%        | 1,620  | 0      |
| 6.2.5   | Azure Activity log alert for Create or update security solution does not exist        | <div><div></div></div> Informational | <div><div></div></div> | 0%        | 1,620  | 0      |
| 6.2.6   | Azure Activity log alert for Delete security solution does not exist                  | <div><div></div></div> Informational | <div><div></div></div> | 0%        | 1,620  | 0      |
| 6.2.7   | Azure Activity log alert for Create or update SQL server firewall rule does not exist | <div><div></div></div> Informational | <div><div></div></div> | 0%        | 1,620  | 0      |
| 6.2.8   | Azure Activity log alert for Delete SQL server firewall rule does not exist           | <div><div></div></div> Informational | <div><div></div></div> | 0%        | 1,620  | 0      |

| Section |                                                                                     |                                     | Pass Rate | Failed | Passed |
|---------|-------------------------------------------------------------------------------------|-------------------------------------|-----------|--------|--------|
| 6.2.9   | Azure Activity log alert for Create or update public IP address rule does not exist | <div><div></div>Informational</div> | 0%        | 1,620  | 0      |
| 6.2.10  | Azure Activity log alert for Delete public IP address rule does not exist           | <div><div></div>Informational</div> | 0%        | 1,620  | 0      |

# Logging and Monitoring / Section 6.1.2



0 Resource(s) Failed

## Compliance Section: 6.1.2 — Informational

### Ensure Diagnostic Setting captures appropriate categories

#### Azure Monitor Diagnostic Setting does not captures appropriate categories


This policy identifies Azure Monitor Diagnostic Setting which does not captures appropriate categories. Capturing appropriate diagnostic setting categories allows proper alerting. It is recommended to select Administrative, Alert, Policy, and Security diagnostic setting categories.

**First Seen** N/A | **Resource Type** Other

### Recommendations

1. Log in to Azure Portal
  2. Navigate to 'Monitor' and select 'Activity log'
  3. Click on 'Diagnostic settings' in top pane
  4. Select 'Add diagnostic setting' if no 'Diagnostic settings' present
- OR
- Click on 'Edit setting' for the existing 'Diagnostic settings'
5. Under 'Category details', select 'Administrative', 'Alert', 'Policy', and 'Security' for 'log'
  6. Add 'Destination details' and other required fields
  7. Click on 'Save'

# Logging and Monitoring / Section 6.1.4



## 1,339 Resource(s) Failed

ps-keyvault-prod, ucp-vault-local-01, weu-piemfg-vck-qa-kv, ddt-prod-kv, kv-4992-sf-vcgdm-dev, kv-pceinfra-01, kv-monitoring-qa, kv-4066-sf-vy99739-sbx, akv6375ibl-prod001, kv-vips-despatchadv-prod & 1,329 more

### Compliance Section: 6.1.4 — Informational

#### Ensure that logging for Azure Key Vault is 'Enabled'

##### Azure Key Vault audit logging is disabled


This policy identifies Azure Key Vault instances for which audit logging is disabled. As a best practice, enable audit event logging for Key Vault instances to monitor how and when your key vaults are accessed, and by whom.

**First Seen** April 24, 2025 at 12:24:54 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure portal
2. Select 'Key vaults'
3. Select the key vault instance to modify
4. Select 'Diagnostic settings' under 'Monitoring'
5. Click on '+Add diagnostic setting'
6. Specify a 'Diagnostic settings name',
7. Under 'Category details' section, Under Log, select 'AuditEvent'
8. Under section 'Destination details',
  - a. If you select 'Send to Log Analytics workspace', set the 'Subscription' and 'Log Analytics workspace'
  - b. If you select 'Archive to storage account', set the 'Subscription', 'Storage account' and 'Retention (days)'
  - c. If you select 'Stream to an event hub', set the 'Subscription', 'Event hub namespace', 'Event hub name' and 'Event hub policy name'
  - d. If you select 'Send to partner solution', set the 'Subscription' and 'Destination'
9. Click on 'Save'

# Logging and Monitoring / Section 6.2.1



## 1,620 Resource(s) Failed

89a5bac3-d242-4466-a8c6-92204a0e7d59,  
89bac60f-beb6-43c2-88b2-acc8c1a01df8,  
94769a2c-88e1-489f-8216-f626cf004840,  
7e305957-4a60-4b34-84f9-39177e1e7af2,  
b42a01c6-beef-4778-a6b2-bb150a213224,  
6cf203f7-dbdb-46ed-8683-7a4d8236d1cf,  
56249305-5fc8-4453-a8e7-13283a7f160b,  
e3552dbc-b83c-45b6-9de1-3aa97ef27bf6,  
bc2fc80e-e6ba-4183-b351-8088218211cc,  
e25e87bb-ff77-49c0-b9a1-ab6e731d3199 &  
1.610 more

### Compliance Section: 6.2.1 Informational

#### Ensure that Activity Log Alert exists for Create Policy Assignment

##### Azure Activity log alert for Create policy assignment does not exist


This policy identifies the Azure accounts in which activity log alert for Create policy assignment does not exist. Creating an activity log alert for Create policy assignment gives insight into changes done in azure policy - assignments and may reduce the time it takes to detect unsolicited changes.

**First Seen** April 24, 2025 at 12:24:54 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Create policy assignment (Microsoft.Authorization/policyAssignments)' and Other fields you can set based on your custom settings.
6. Click on Create

# Logging and Monitoring / Section 6.2.2



## 1,620 Resource(s) Failed

6bfb4917-2885-497a-9877-80283132c037,  
3ec888a0-ddd4-49e3-ad67-044f6662ba8e,  
87492560-33b5-489a-9eab-4034bb87c320,  
3b7e2c53-981f-4ceb-a73f-bbe759e368cd,  
88b7c5be-7500-43de-b1c2-1fedcda0bb2c,  
7cac1cb7-eb1f-4e41-a781-7846b6a5d39f,  
fabed079-cde6-4e6c-a17c-823e80caa879,  
ff402ab5-2ed7-4bc1-bf90-9b92470226ec,  
47d7eb94-b0f5-4f91-8bd3-2f99fb965089,  
0b345a31-b5a0-4b3b-a438-e13bc547a0b4 &  
1.610 more

### Compliance Section: 6.2.2 Informational

#### Ensure that Activity Log Alert exists for Delete Policy Assignment

##### Azure Activity log alert for delete policy assignment does not exist

This policy identifies the Azure accounts in which activity log alert for Delete policy assignment does not exist. Creating an activity log alert for Delete policy assignment gives insight into changes done in azure policy - assignments and may reduce the time it takes to detect unsolicited changes.


**First Seen** April 24, 2025 at 12:24:55 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Delete policy assignment (Microsoft.Authorization/policyAssignments)' and Other fields you can set based on your custom settings.
6. Click on Create



# Logging and Monitoring / Section 6.2.3



## 1,620 Resource(s) Failed

018bdf45-d977-43b4-82a2-6682e821a837,  
f3ce41c1-1857-4593-9a71-fd17efe54945,  
b5126ba4-3470-4998-8625-1d1d69a1f7ae,  
c5728c7c-7cf6-488a-b418-686e022a3c3c,  
b26ee498-efc2-4aae-94a2-22b9c820bc16,  
b358ec75-29d6-4678-b0bd-507e25a23e0f,  
24a15855-09bb-40d5-9bb5-0cbfa0577383,  
0fb8b9b3-35fc-41aa-844f-7fe5e8deb5f4,  
b18caef7-4520-4899-879e-f7bdfb0dc002,  
0c2d14b9-2ad5-4654-bd5d-66578c655fc5 &  
1.610 more

### Compliance Section: 6.2.3 Informational

#### Ensure that Activity Log Alert exists for Create or Update Network Security Group

##### Azure Activity log alert for Create or update network security group does not exist


This policy identifies the Azure accounts in which activity log alert for Create or update network security group does not exist. Creating an activity log alert for Create or update network security group gives insight into network access changes and may reduce the time it takes to detect suspicious activity.

**First Seen** April 24, 2025 at 12:24:53 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Create or Update Network Security Group (Microsoft.Network/networkSecurityGroups)' and Other fields you can set based on your custom settings.
6. Click on Create

# Logging and Monitoring / Section 6.2.4



## 1,620 Resource(s) Failed

a9d9b51b-96a1-4e67-9eae-96dd06284e0f, f3ce41c1-1857-4593-9a71-fd17efe54945, ccc2728a-c602-419e-9284-46dd051a9531, c5728c7c-7cf6-488a-b418-686e022a3c3c, 89b7257f-8b7c-42e0-a7fe-0dacc9ddd5a4, db3b40d2-e1ee-4c81-ae3e-9e96ed6b3736, d48093de-c8fd-4df7-8367-1417634c874f, 3dd67924-53f0-4cf6-819e-fa826c4a7eb3, b18caef7-4520-4899-879e-f7bdfb0dc002, 1f1e82c7-37ac-4445-97de-206cd64812c9 & 1.610 more

### Compliance Section: 6.2.4 Informational

#### Ensure that Activity Log Alert exists for Delete Network Security Group

##### Azure Activity log alert for Delete network security group does not exist

This policy identifies the Azure accounts in which activity log alert for Delete network security group does not exist. Creating an activity log alert for the Delete network security group gives insight into network access changes and may reduce the time it takes to detect suspicious activity.


First Seen April 24, 2025 at 12:24:54 PM UTC | Resource Type Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Delete Network Security Group (Microsoft.Network/networkSecurityGroups)' and Other fields you can set based on your custom settings.
6. Click on Create



# Logging and Monitoring / Section 6.2.5



## 1,620 Resource(s) Failed

bf8cab40-e3bd-42d7-a83c-e69f0205b61d, 479304dd-c5a0-462a-bc75-609fa6108862, e9f9d120-f8cc-4be8-928e-a9a411c7c765, 87117b38-199c-4be6-a9d3-736097b656a3, 70801a5f-4117-4702-b9aa-1f0b21997ecb, 977e7744-0e8b-4f95-9b49-9c1ca5659b7c, e6ade80d-ec83-461c-90c5-c7560990b0ba, b2cb7e46-8d67-4add-9638-93b7179ecad4, 6675dee3-1743-4334-b899-5246c889ca38, e3509464-b996-48da-8a2c-cfa61d745438 & 1.610 more

### Compliance Section: 6.2.5 Informational

#### Ensure that Activity Log Alert exists for Create or Update Security Solution

##### Azure Activity log alert for Create or update security solution does not exist


This policy identifies the Azure accounts in which activity log alert for Create or update security solution does not exist. Creating an activity log alert for Create or update security solution gives insight into changes to the active security solutions and may reduce the time it takes to detect suspicious activity.

**First Seen** April 24, 2025 at 12:24:55 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Create or Update Security Solutions (Microsoft.Security/securitySolutions)' and Other fields you can set based on your custom settings.
6. Click on Create

# Logging and Monitoring / Section 6.2.6



## 1,620 Resource(s) Failed

87833b25-06dd-4329-99ae-b8b09ceb3844,  
b2cb7e46-8d67-4add-9638-93b7179ecad4,  
d6ee44c3-cb3b-43fb-aeda-17109b44661c,  
4cbf244f-ae0e-4cd0-a561-6d55fc91d711,  
d37ee4a6-4106-44b9-968a-b669ac643f27,  
0f27f2a2-d916-4e36-8ec7-54cf8e209c65,  
d7df5d68-c649-442c-8262-c0bf8e758685,  
a12cd6b1-3bad-4038-8c45-0404242a5614,  
7d93a69d-8266-47a1-9507-4ec6708c7f7c,  
ac78052b-86ae-43fc-bed8-f3ea7d70b7c5 &  
1.610 more

### Compliance Section: 6.2.6 Informational

#### Ensure that Activity Log Alert exists for Delete Security Solution

##### Azure Activity log alert for Delete security solution does not exist


This policy identifies the Azure accounts in which activity log alert for Delete security solution does not exist. Creating an activity log alert for Delete security solution gives insight into changes to the active security solutions and may reduce the time it takes to detect suspicious activity.

First Seen April 24, 2025 at 12:24:53 PM UTC | Resource Type Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Delete Security Solutions (Microsoft.Security/securitySolutions)' and Other fields you can set based on your custom settings.
6. Click on Create

# Logging and Monitoring / Section 6.2.7



## 1,620 Resource(s) Failed

7aa649d9-464f-4f29-b15a-7b92aab6bb71,  
a9d9b51b-96a1-4e67-9eae-96dd06284e0f,  
24d8347b-81db-423c-bf17-a05cfc7f9e85,  
95fb2193-276d-4b47-91b4-6bf8fa833e2e,  
0e2652a6-4921-4e79-b06c-f0415bb9a63b,  
960debea-34e2-44b9-8450-f859e69cc0cd,  
a21dc29d-fd69-4966-a8e5-6b46fc137054,  
56114312-44c3-4597-8e7f-856f21ae97d9,  
1f1e82c7-37ac-4445-97de-206cd64812c9,  
dd25ccae-0073-4cc0-80b2-ffade0009646 &  
1.610 more

### Compliance Section: 6.2.7 — Informational

#### Ensure that Activity Log Alert exists for Create or Update SQL Server Firewall Rule

##### Azure Activity log alert for Create or update SQL server firewall rule does not exist


This policy identifies the Azure accounts in which activity log alert for Create or update SQL server firewall rule does not exist. Creating an activity log alert for Create or update SQL server firewall rule gives insight into SQL server firewall rule access changes and may reduce the time it takes to detect suspicious activity.

**First Seen** April 24, 2025 at 12:24:54 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Create/Update server firewall rule (Microsoft.Sql/servers/firewallRules)' and Other fields you can set based on your custom settings.
6. Click on Create

# Logging and Monitoring / Section 6.2.8



## 1,620 Resource(s) Failed

5c5dc4cd-00f1-4b1e-862a-2ea68d875967,  
e0e59d8b-e065-439d-8d02-4478630b8d72,  
bfcead43-4cf0-4594-be85-dfcc49205934,  
a21dc29d-fd69-4966-a8e5-6b46fc137054,  
8f5659ee-a1a2-45e6-aebc-0a1ba9b8be78,  
040e0e91-a3af-4114-b678-8b2680998b7f,  
f3935350-72bd-4735-9785-9d22bfb723ff,  
0deb1e88-b2e5-464e-9578-15745c056f9d,  
f924a410-76dc-4bf4-9618-c4d9725c3a23,  
81b21080-cb2d-4218-989f-7c9af0b2b538 &  
1.610 more

### Compliance Section: 6.2.8 Informational

#### Ensure that Activity Log Alert exists for Delete SQL Server Firewall Rule

##### Azure Activity log alert for Delete SQL server firewall rule does not exist


This policy identifies the Azure accounts in which activity log alert for Delete SQL server firewall rule does not exist. Creating an activity log alert for Delete SQL server firewall rule gives insight into SQL server firewall rule access changes and may reduce the time it takes to detect suspicious activity.

**First Seen** April 24, 2025 at 12:24:55 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Delete server firewall rule (Microsoft.Sql/servers/firewallRules)' and Other fields you can set based on your custom settings.
6. Click on Create

# Logging and Monitoring / Section 6.2.9



## 1,620 Resource(s) Failed

0fbf7810-e15b-466e-8112-75330f52afd5,  
5fef7e98-7388-4405-b773-3637f41a921f,  
81f63773-f55f-4281-8b33-74f1008f7bcb,  
94666186-3eb0-4556-b592-55c41b67bab2,  
8097d022-0632-41bb-8cf0-d7289996ed7a,  
08db722c-7635-41bd-b49c-e17ee2ec58e0,  
b6383fb3-b28f-4c4e-b230-165e5569989a,  
70801a5f-4117-4702-b9aa-1f0b21997ecb,  
977e7744-0e8b-4f95-9b49-9c1ca5659b7c,  
3c01d4c6-410f-42ef-9a10-71f683ddb43a & 1,610  
more

### Compliance Section: 6.2.9 — Informational

#### Ensure that Activity Log Alert exists for Create or Update Public IP Address rule

##### Azure Activity log alert for Create or update public IP address rule does not exist

This policy identifies the Azure accounts in which activity log alert for Create or update public IP address rule does not exist.

Creating an activity log alert for create or update public IP address rule gives insight into network rule access changes and may reduce the time it takes to detect suspicious activity. By enabling this monitoring, you get alerts whenever any changes are made to public IP address rules.


As a best practice, it is recommended to have a activity log alert for create or update public IP address rule to enhance network security monitoring and detect suspicious activities.

**First Seen** April 24, 2025 at 12:24:53 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Create or Update Public Ip Address (Public Ip Address)' and Other fields you can set based on your custom settings.
6. Click on Create

# Logging and Monitoring / Section 6.2.10



## 1,620 Resource(s) Failed

b42a01c6-beef-4778-a6b2-bb150a213224,  
30b30152-a07e-488c-b746-e9f2ff181e8c,  
a01ab935-e930-495b-9da2-87d9fd650310,  
7a915ee8-62a5-4dda-a55c-4d25347e06d7,  
61875675-eed6-4851-863f-12797e2e2f9f,  
f75d50ca-e696-4967-87aa-ab21bbd1abbc,  
0c775c57-33aa-45f6-a5bd-734150b0236c,  
7872fba8-be26-4cf4-97ca-22acf78ed9a3,  
f0b8e36a-8ea7-4465-88c4-6a52a4b9a909,  
ccceb9a9-d45c-4734-8a98-3db174763142 &  
1.610 more

### Compliance Section: 6.2.10 Informational

#### Ensure that Activity Log Alert exists for Delete Public IP Address rule

##### Azure Activity log alert for Delete public IP address rule does not exist

This policy identifies the Azure accounts in which activity log alert for Delete public IP address rule does not exist.

Creating an activity log alert for Delete public IP address rule gives insight into network rule access changes and may reduce the time it takes to detect suspicious activity. By enabling this monitoring, you get alerts whenever any deletions are made to public IP addresses rules.

As a best practice, it is recommended to have an activity log alert for Delete public IP address rule to enhance network security monitoring and detect suspicious activities.

**First Seen** April 24, 2025 at 12:24:55 PM UTC | **Resource Type** Other

#### Recommendations

1. Log in to Azure Portal
2. Click on Monitor (Left Panel)
3. Select 'Alerts'
4. Click on Create > Alert rule
5. In 'Create an alert rule' page, choose the Scope as your Subscription and under the CONDITION section, choose 'Delete Public Ip Address (Public Ip Address)' and Other fields you can set based on your custom settings.
6. Click on Create



# 6


## Networking

# Networking Overview

| Section |                                                                                                   |                                      |                        | Pass Rate | Failed | Passed |
|---------|---------------------------------------------------------------------------------------------------|--------------------------------------|------------------------|-----------|--------|--------|
| 7.1     | Azure Network Security Group allows all traffic on RDP Port 3389                                  | <div><div></div></div> Informational | <div><div></div></div> | 96%       | 85     | 2,178  |
| 7.2     | Azure Network Security Group allows all traffic on SSH port 22                                    | <div><div></div></div> Informational | <div><div></div></div> | 88%       | 264    | 1,999  |
| 7.3     | Azure Network Security Group having Inbound rule overly permissive to all traffic on UDP protocol | <div><div></div></div> Medium        | <div><div></div></div> | 100%      | 0      | 2,263  |



# Networking / Section 7.1



## 85 Resource(s) Failed

monroney-test-1-nsg, matlab-task-win01, dynamic-cand01, vcc-ci-images-windows-mxam\_1fcce8034c27406fbaf03a4754bc14C hightecazurensg739, nsg-shir-vm-conference-system, hightec-azure-nsg, windows-2019-bootstrap-python-admin-no-proxy-vm-nsg, matlab202301, powerBI-VM-nsg & 75 more

### Compliance Section: 7.1 — Informational

#### Ensure that RDP access from the Internet is evaluated and restricted

##### Azure Network Security Group allows all traffic on RDP Port 3389

This policy identifies any NSG rule that allow all traffic on RDP port 3389. Review your list of NSG rules to ensure that your resources are not exposed. As a best practice, restrict RDP solely to known static IP addresses. Limit the access list to include known hosts, services, or specific employees only.


**First Seen** February 26, 2025 at 8:40:56 AM UTC | **Resource Type** Security Group

#### Recommendations

Before making any changes, please check the impact to your applications/services. Evaluate whether you want to edit the rule and limit access to specific users, hosts, and services only, deny access, or delete the rule completely.

1. Log in to the Azure Portal.
2. Select 'All services'.
3. Select 'Network security groups', under NETWORKING.
4. Select the Network security group you need to modify.
5. Select 'Inbound security rules' under Settings.
6. Select the rule you need to modify, and edit it to allow specific IP addresses OR set the 'Action' to 'Deny' OR 'Delete' the rule based on your requirement.
7. 'Save' your changes.

# Networking / Section 7.2



## 264 Resource(s) Failed

linux-d2ds-4301, linux-d2ds-2201, big-mat-lab2-202101, closvl2168-nsg, closvl1535-nsg, nsg-pslgithubrunner-prod, closvl1454-nsg, hightecazurensg739, closvl1449-nsg, dmoller1-testing01 & 254 more

## Compliance Section: 7.2 Informational

### Ensure that SSH access from the Internet is evaluated and restricted

#### Azure Network Security Group allows all traffic on SSH port 22

This policy identifies Network security groups (NSG) that allow all traffic on SSH port 22. Review your list of NSG rules to ensure that your resources are not exposed. As a best practice, restrict SSH solely to known static IP addresses. Limit the access list to include known hosts, services, or specific employees only.

**First Seen** November 20, 2024 at 11:52:44 AM UTC | **Resource Type** Security Group

### Recommendations

Before making any changes, please check the impact to your applications/services. Evaluate whether you want to edit the rule and limit access to specific users, hosts, and services only, deny access, or delete the rule completely.

1. Log in to the Azure Portal.
2. Select 'All services'.
3. Select 'Network security groups', under NETWORKING.
4. Select the Network security group you need to modify.
5. Select 'Inbound security rules' under Settings.
6. Select the rule you need to modify, and edit it to allow specific IP addresses OR set the 'Action' to 'Deny' OR 'Delete' the rule based on your requirement.
7. 'Save' your changes.

# Networking / Section 7.3



0 Resource(s) Failed

**Compliance Section: 7.3** ●●●● Medium

**Ensure that UDP access from the Internet is evaluated and restricted**

**Azure Network Security Group having Inbound rule overly permissive to all traffic on UDP protocol**

This policy identifies Azure Network Security Groups (NSGs) which are overly permissive to all traffic on UDP protocol. A network security group contains a list of security rules that allow or deny inbound or outbound network traffic based on source or destination IP address, port, and protocol. As a best practice, it is recommended to configure NSGs to restrict traffic from known sources, allowing only authorized protocols and ports.

**First Seen** N/A | **Resource Type** Other

**Recommendations**

Before making any changes, please check the impact to your applications/services. Evaluate whether you want to edit the rule and limit access to specific users, hosts, and services only, deny access, or delete the rule completely.

- 1. Log in to the Azure Portal.
- 2. Select 'All services'.
- 3. Select 'Network security groups', under NETWORKING.
- 4. Select the Network security group you need to modify.
- 5. Select 'Inbound security rules' under Settings.
- 6. Select the rule you need to modify, and edit it to allow specific IP addresses and Port ranges OR set the 'Action' to 'Deny' OR 'Delete' the rule based on your requirement.
- 7. 'Save' your changes.


# 7

## Virtual Machines

# Virtual Machines Overview

| Section |                                                                  |                                      |                        | Pass Rate | Failed | Passed |
|---------|------------------------------------------------------------------|--------------------------------------|------------------------|-----------|--------|--------|
| 8.2     | Azure Virtual Machines are not utilising Managed Disks           | <div><div></div></div> Informational | <div><div></div></div> | 99%       | 1      | 4,815  |
| 8.2     | Azure Virtual machine scale sets are not utilising Managed Disks | <div><div></div></div> Informational | <div><div></div></div> | 100%      | 0      | 416    |
| 8.6     | Azure disk data access authentication mode not enabled           | <div><div></div></div> Medium        | <div><div></div></div> | 5%        | 9,211  | 503    |
| 8.11    | Azure Virtual Machine (Windows) secure boot feature is disabled  | <div><div></div></div> Low           | <div><div></div></div> | 100%      | 0      | 4,816  |
| 8.11    | Azure Virtual Machine vTPM feature is disabled                   | <div><div></div></div> Low           | <div><div></div></div> | 100%      | 0      | 4,816  |

# Virtual Machines / Section 8.2



**1 Resource(s) Failed**  
matlab2023

**Compliance Section: 8.2** — Informational

**Ensure Virtual Machines are utilizing Managed Disks**

**Azure Virtual Machines are not utilising Managed Disks**

This policy identifies Azure Virtual Machines which are not utilising Managed Disks. Using Azure Managed disk over traditional BLOB based VHD's has more advantage features like Managed disks are by default encrypted, reduces cost over storage accounts and more resilient as Microsoft will manage the disk storage and move around if underlying hardware goes faulty. It is recommended to move BLOB based VHD's to Managed Disks.


**First Seen** March 18, 2026 at 10:31:11 AM UTC | **Resource Type** Other

**Recommendations**

- 1. Log in to the Azure Portal
- 2. Select 'Virtual Machines' from the left pane
- 3. Select the reported virtual machine
- 4. Select 'Disks' under 'Settings'
- 5. Click on 'Migrate to managed disks'
- 6. Select 'Migrate'



# Virtual Machines / Section 8.2



0 Resource(s) Failed

**Compliance Section: 8.2** — Informational

**Ensure Virtual Machines are utilizing Managed Disks**

**Azure Virtual machine scale sets are not utilising Managed Disks**

This policy identifies Azure Virtual machine scale sets which are not utilising Managed Disks. Using Azure Managed disk over traditional BLOB storage based VHD's has more advantage features like Managed disks are by default encrypted, reduces cost over storage accounts and more resilient as Microsoft will manage the disk storage and move around if underlying hardware goes faulty. It is recommended to move BLOB based VHD's to Managed Disks.

**First Seen** N/A | **Resource Type** Other


**Recommendations**

Currently migrating Virtual machine scale sets VHD disks to Azure Managed Disks is not available. It is recommended that all new future scale sets be deployed with managed disks.

Follow steps given in the URL to create new Virtual machine Scale sets,

<https://docs.microsoft.com/en-us/azure/virtual-machine-scale-sets/quick-create-portal>

# Virtual Machines / Section 8.6



9,211 Resource(s) Failed

closvw1876-disk01, closvl3127-data02, 3dxdatabase-data, closvl4116-datadisk-005, closvw3266-disk00, closvl3288-osdisk, closvw3252-data00, pvc-f8aafe9b-bb54-4248-808c-d27eb9e1fc23, closvw1934-disk01, wvdsea001-1838\_Os-Disk\_1\_16ee272061474b1f88b8bc1bbd1fb22a & 9,201 more

Compliance Section: 8.6 ●●●● Medium

Ensure that 'Enable Data Access Authentication Mode' is 'Checked'

Azure disk data access authentication mode not enabled

This policy identifies if the Data Access Authentication Mode for Azure disks is disabled. This mode is crucial for controlling how users upload or export Virtual Machine Disks by requiring an Azure Entra ID role to authorize such operations.

Without enabling this mode, users can create SAS tokens to export disks without stringent identity-based restrictions. This increases the risk of unauthorized disk access or data exposure, especially in environments handling sensitive data. Enabling the Data Access Authentication Mode ensures that only users with the appropriate Data Operator for Managed Disk role in Azure Entra ID can export or manage disks. This enhances data security by preventing unauthorized disk exports and restricting access to secure download URLs.

As a security best practice, it is recommended to enable data access authentication mode for Azure disks.

First Seen December 12, 2024 at 12:17:50 AM UTC | Resource Type Other


Recommendations

Note: To enable data access authentication mode on disks attached to a VM, you must first stop the VM and detach the disk.

- 1. Log in to Azure Portal and search for 'Disks'
- 2. Select 'Disks'
- 3. Select the reported disk
- 4. Under 'Settings' select 'Disk Export'
- 5. Check the 'Enable data access authentication mode' under 'Data access authentication mode'
- 6. Click on 'Save'
- 7. Re-attach the disk to the virtual machine, and restart it



# Virtual Machines / Section 8.11



0 Resource(s) Failed

**Compliance Section: 8.11** ●●●● Low

**Ensure Trusted Launch is enabled on Virtual Machines**

**Azure Virtual Machine (Windows) secure boot feature is disabled**

This policy identifies Virtual Machines (Windows) that have secure boot feature disabled. Enabling Secure Boot on supported Windows virtual machines provides mitigation against malicious and unauthorised changes to the boot chain. Secure boot helps protect your VMs against boot kits, rootkits, and kernel-level malware. So it is recommended to enable Secure boot for Azure Windows virtual machines.


NOTE: This assessment only applies to trusted launch enabled Windows virtual machines. You can't enable trusted launch on existing virtual machines that were initially created without it.  
To know more, refer [https://docs.microsoft.com/azure/virtual-machines/trusted-launch?WT.mc\\_id=Portal-Microsoft\\_Azure\\_Security](https://docs.microsoft.com/azure/virtual-machines/trusted-launch?WT.mc_id=Portal-Microsoft_Azure_Security)

**First Seen** N/A | **Resource Type** Other

**Recommendations**

- 1. Log in to Azure portal
- 2. Navigate to Virtual machines dashboard
- 3. Click on the reported Virtual machine
- 4. Select 'Configuration' under 'Settings' from left panel
- NOTE: Enabling Secure Boot will trigger an immediate SYSTEM REBOOT.
- 5. On the 'Configuration' page, check 'Secure boot' under 'Security type' section
- 6. Click 'Save'

# Virtual Machines / Section 8.11



0 Resource(s) Failed

**Compliance Section: 8.11** ●●●● Low

**Ensure Trusted Launch is enabled on Virtual Machines**

**Azure Virtual Machine vTPM feature is disabled**

This policy identifies Virtual Machines that have Virtual Trusted Platform Module (vTPM) feature disabled. Virtual Trusted Platform Module (vTPM) provide enhanced security to the guest operating system. It is recommended to enable virtual TPM device on supported virtual machines to facilitate measured Boot and other OS security features that require a TPM.

NOTE: This assessment only applies to trusted launch enabled virtual machines. You can't enable trusted launch on existing virtual machines that were initially created without it.  
To know more, refer [https://docs.microsoft.com/azure/virtual-machines/trusted-launch?WT.mc\\_id=Portal-Microsoft\\_Azure\\_Security](https://docs.microsoft.com/azure/virtual-machines/trusted-launch?WT.mc_id=Portal-Microsoft_Azure_Security)

**First Seen** N/A | **Resource Type** Other

**Recommendations**

- 1. Log in to Azure portal
- 2. Navigate to Virtual machines dashboard
- 3. Click on the reported Virtual machine
- 4. Select 'Configuration' under 'Settings' from left panel
- NOTE: Enabling vTPM will trigger an immediate SYSTEM REBOOT.
- 5. On the 'Configuration' page, check 'vTPM' under 'Security type' section
- 6. Click 'Save'


# 8

## AppService

# AppService Overview

| Section |                                                          |                                                                |                                                                    | Pass Rate | Failed | Passed |
|---------|----------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------------------|-----------|--------|--------|
| 9.1     | Azure App Service Web app doesn't redirect HTTP to HTTPS | <div><div></div><div></div><div></div><div></div></div> Medium | <div><div></div><div></div><div></div><div></div><div></div></div> | 99%       | 10     | 1,268  |
| 9.3     | Azure App Services FTP deployment is All allowed         | <div><div></div><div></div><div></div><div></div></div> Low    | <div><div></div><div></div><div></div><div></div><div></div></div> | 88%       | 152    | 1,126  |
| 9.4     | Azure App Service Web app doesn't use latest TLS version | <div><div></div><div></div><div></div><div></div></div> Low    | <div><div></div><div></div><div></div><div></div><div></div></div> | 99%       | 2      | 1,276  |
| 9.6     | Azure App Service basic authentication enabled           | <div><div></div><div></div><div></div><div></div></div> Medium | <div><div></div><div></div><div></div><div></div><div></div></div> | 31%       | 881    | 397    |
| 9.10    | Azure App Service Web app doesn't use HTTP 2.0           | <div><div></div></div> Informational                           | <div><div></div><div></div><div></div><div></div><div></div></div> | 70%       | 377    | 901    |
| 9.12    | Azure App Services Remote debugging is enabled           | <div><div></div><div></div><div></div><div></div></div> Medium | <div><div></div><div></div><div></div><div></div><div></div></div> | 100%      | 0      | 1,278  |

# AppService / Section 9.1



## 10 Resource(s) Failed

api-vssm-utility-qa, powerbi-embedded-report, app-vccgaid-dev, probas-api-test, digitalcards-qa, api-vssm-softbank-prod, psim-migration, api-vssm-utility-prod, api-vssm-tisp-retryasync-prod, api-vssm-utility-dev

### Compliance Section: 9.1 ●●● Medium

Ensure 'HTTPS Only' is set to `On`

#### Azure App Service Web app doesn't redirect HTTP to HTTPS


Azure Web Apps allows sites to run under both HTTP and HTTPS by default. Web apps can be accessed by anyone using non-secure HTTP links by default. Non-secure HTTP requests can be restricted and all HTTP requests redirected to the secure HTTPS port. It is recommended to enforce HTTPS-only traffic.

**First Seen** February 25, 2025 at 3:06:31 PM UTC | **Resource Type** Other

### Recommendations

1. Log in to the Azure portal
2. Navigate to App Services
3. Click on the reported App
4. Under the Settings section, Click on 'Configuration'
5. In 'General Settings', under 'Platform settings' Set 'HTTPS Only' to 'On'

# AppService / Section 9.3



## 152 Resource(s) Failed

fn-weu-arcsightmonitor-prod,  
emea-vips-orderstatus-logic-test,  
api-vssm-tcu-prod, emea-grip-maintenance,  
emea-grip-ip-prod-apiapp, api-vssm-sim-prod,  
emea-vr-salesbinningresponse-logic-qa,  
func-postmanbackup-test,  
func-fleet-agreement, emea-qw90-logic-qa &  
142 more

### Compliance Section: 9.3 ●●●● Low

Ensure 'FTP State' is set to 'FTPS Only' or 'Disabled'

Azure App Services FTP deployment is All allowed

This policy identifies Azure App Services which has FTP deployment setting as All allowed. Attacker could listen to wifi traffic and get the login credentials to a FTP deployments which could be in plain text and get full control of the code base of the app or service. It is highly recommend to use FTPS if FTP deployment for workflow is essential else disable the FTP deployment for Azure App Services.

First Seen August 21, 2024 at 5:48:21 PM UTC | Resource Type Other

### Recommendations

Following recommendation steps are for resources hosted in App Service, Premium and Windows Consumption plans,

1. Log in to the Azure Portal
2. Select 'App Services' from the left pane
3. Select the reported App Services
4. Go to 'Configurations' under 'Settings'
5. Click on 'General settings'
6. Select 'FTPS only' or 'Disabled' for 'FTP state' under 'Platform settings'
7. Click on 'Save'

If Function App Hosted in Linux using Consumption (Serverless) Plan follow below steps

Azure CLI Command

FTP Disable - \"az functionapp config set --ftps-state Disabled --name MyFunctionApp --resource-group MyResourceGroup\"

FTPS only - \"az functionapp config set --ftps-state FtpsOnly --name MyFunctionApp --resource-group MyResourceGroup\"



# AppService / Section 9.4



**2 Resource(s) Failed**  
aps-ne-prd-cas-static-publ, aps-ne-qa-cas-stat-ic-publ

**Compliance Section: 9.4** ●●●● Low

**Ensure Web App is using the latest version of TLS encryption**

**Azure App Service Web app doesn't use latest TLS version**

This policy identifies Azure web apps that are not configured with the latest version of TLS encryption. Azure Web Apps provide a platform to host and manage web applications securely.

Using the latest TLS version is crucial for maintaining secure connections. Older versions of TLS, such as 1.0 and 1.1, have known vulnerabilities that can be exploited by attackers. Upgrading to newer versions like TLS 1.2 or 1.3 ensures that the web app is better protected against modern security threats.


It is highly recommended to use the latest TLS version (greater than 1.1) for secure web app connections.

**First Seen** February 26, 2025 at 8:38:57 AM UTC | **Resource Type** Other

**Recommendations**

- 1. Log in to the Azure portal
- 2. Navigate to App Services
- 3. Click on the reported App
- 4. Under "Settings" section, Click on "Configuration"
- 5. In "Platform Settings", Set "Minimum Inbound TLS Version" to "1.2" or "1.3"
- 6. Click on "Save" icon at the top
- 7. Click "Continue" to save the changes

# AppService / Section 9.6



## 881 Resource(s) Failed

pds-piereport-function-dev, emea-grip-log-ic-func, func-retailer-agreements-logic-prod, app-backendapi-weu-test, dealer-inspire-dev, webjob-vssm-prod, NCLOwnershipDataUp-dateFunction, emea-vips-orderstatus-log-ic, logicapp-7595-sno-dev-weu-001, on-boardingab3dx9 & 871 more

### Compliance Section: 9.6 ●●● Medium

#### Ensure that 'Basic Authentication' is 'Disabled'

##### Azure App Service basic authentication enabled

This policy identifies Azure App Services which have basic authentication enabled.

Basic Authentication allows local identity management for App Services without using a centralized identity provider like Azure Entra ID, posing a security risk by creating isolated identity systems that lack centralized control and are vulnerable to credential compromise and unauthorized access. Disabling Basic Authentication and integrating with a centralized solution like Azure Entra ID enhances security with stronger authentication, improved access management, and reduced attack risks.

As a security best practice, it is recommended to disable basic authentication for Azure App Services.


**First Seen** December 12, 2024 at 12:02:00 AM UTC | **Resource Type** Other

#### Recommendations

1. Log in to the Azure portal
2. Navigate to App Services
3. Click on the reported App Service
4. Under 'Settings' section, Click on 'Configuration'
5. Under the 'General settings' tab, scroll down to locate the two Basic Auth settings:
  - Set the 'SCM Basic Auth Publishing Credentials' radio button to Off
  - Set the 'FTP Basic Auth Publishing Credentials' radio button to Off
6. At the top, click on 'Save'
7. Click 'Continue' to save the changes



# AppService / Section 9.10



**377 Resource(s) Failed**  
app-backendapi-weu-test, app-sec-suhoda-ta-prod, webapp-bams-be-staging, app-quire-lite-api-prod, api-vssm-tisp-prod, app-test-reporter-frontend-prod-001, cdpweb-cdpeu-qa, api-vssm-cardata01-prod, webapp-nextjs-staging, app-ic-weu-non-prod & 367 more

**Compliance Section: 9.10** — Informational

**Ensure that 'HTTP20enabled' is set to 'true' (if in use)**

**Azure App Service Web app doesn't use HTTP 2.0**

HTTP 2.0 has additional performance improvements on the head-of-line blocking problem of old HTTP version, header compression, and prioritization of requests. HTTP 2.0 no longer supports HTTP 1.1's chunked transfer encoding mechanism, as it provides its own, more efficient, mechanisms for data streaming.

**First Seen** April 24, 2025 at 12:25:03 PM UTC | **Resource Type** Other

**Recommendations**

- 1. Log in to the Azure portal
- 2. Navigate to App Services
- 3. Click on the reported App
- 4. Under Setting section, Click on 'Configuration'
- 5. Under 'General Settings' tab, In 'Platform settings', Set 'HTTP version' to '2.0'

# AppService / Section 9.12



0 Resource(s) Failed

**Compliance Section: 9.12** ●●●● Medium

**Ensure that 'Remote debugging' is set to 'Off'**

**Azure App Services Remote debugging is enabled**

Azure App Services with remote debugging enabled pose a significant security risk. Enabling this feature opens inbound network ports, creating a potential attack vector for unauthorized access.

Remote debugging allows developers to connect to and troubleshoot applications running within Azure App Services. However, leaving this feature enabled after development exposes the application to potential exploitation via these open ports from untrusted IPs. Attackers could exploit this access to gain unauthorized control or steal sensitive data.

The impact of this misconfiguration could range from data breaches and service disruptions to complete application compromise. Disabling remote debugging after development is a crucial security best practice, minimizing the attack surface and protecting the application from external threats.

To mitigate this risk, disable remote debugging on Azure App Services once development and testing are complete. Regularly review App Service configurations to ensure this setting remains disabled unless explicitly required for troubleshooting. Implement robust network security controls, including firewalls and intrusion detection systems, to further enhance protection.

**First Seen** N/A | **Resource Type** Other

**Recommendations**

- 1. Log in to the Azure Portal
- 2. Select 'App Services' from the left pane
- 3. Select the reported App Services
- 4. Go to 'Configurations' under 'Settings'
- 5. Click on 'General settings'
- 6. Select 'Off' for 'Remote debugging' under 'Debugging section'
- 7. Click on 'Save'