Cold Email Infrastructure Setup - Secondary Domain & Warm-Up Blueprint

Multi-Domain Outbound Architecture & Warm-Up Schedule

Architecture: Primary Domain Protected - 2 Secondary Sending Domains - 2 Mailboxes / Domain

---

Primary Root Domain
Configuration Standard: Strict DMARC p=reject - Zero cold outbound traffic permitted
Volume / Threshold: 0 cold sends / day (Isolated)
Verification: Reputation Shielded
Protected

Secondary Sending Domains
Configuration Standard: 301 HTTPS redirect to primary + full SPF, DKIM 2048-bit & DMARC
Volume / Threshold: 2 mailboxes per domain
Verification: MX & Auth Verified
Active

Days 01-14 Warm-Up Ramp
Configuration Standard: Gradual daily increment (+2 sends/day) with 30% conversational replies
Volume / Threshold: 10 - 30 emails / day / box
Verification: 0% Hard Bounce Gate
Ramping

Campaign Readiness Audit
Configuration Standard: Plain-text ratio check, RFC 8058 List-Unsubscribe header, blacklist scan
Volume / Threshold: Max 35-45 sends / day / box
Verification: Pre-Launch Cleared
Ready

Cold Email Infrastructure Setup - Secondary Domain & Warm-Up Blueprint

Domain Architecture Map

Primary domain is never used for cold outreach. Secondary domains carry all sending risk.

Primary Root Domain
Detail: Brand + transactional mail only
Control / Requirement: No cold sending, ever
Verification: Policy

Secondary Domains (-3)
Detail: Look-alike domains registered for outreach
Control / Requirement: SPF/DKIM/DMARC per domain
Verification: DNS verified

Mailboxes (2-3 / domain)
Detail: Named sender personas
Control / Requirement: Profile complete + signature plain-text
Verification: Checklist

Tracking Subdomain
Detail: CNAME to sending platform
Control / Requirement: SSL active before first send
Verification: HTTPS check

Mailbox Distribution Matrix

Volume is spread so no single mailbox or domain carries campaign risk.

Per Mailbox
Detail: Max 30-50 sends/day at full ramp
Control / Requirement: Warm-up tool pacing enabled
Verification: Platform log

Per Domain
Detail: Max 3 mailboxes
Control / Requirement: Domain-level caps respected
Verification: Platform log

Rotation
Detail: Even rotation across mailboxes
Control / Requirement: No mailbox exceeds daily cap
Verification: Weekly review

Bounce Guard
Detail: Campaign pauses above 2% bounce
Control / Requirement: List cleaning before relaunch
Verification: Hard rule

21-Day Warm-Up Schedule

Warm-up runs on peer-network engagement before any live campaign volume.

Days 1-7
Detail: 10-20 / day per mailbox
Control / Requirement: Replies + rescue-from-spam actions
Verification: Week 1 gate

Days 8-14
Detail: 20-35 / day per mailbox
Control / Requirement: Engagement rate > 25% maintained
Verification: Week 2 gate

Days 15-21
Detail: 35-45 / day per mailbox
Control / Requirement: Postmaster signals reviewed
Verification: Week 3 gate

Day 22+
Detail: Controlled campaign start
Control / Requirement: Small segment first, monitor hourly
Verification: Go / no-go

Cold Email Infrastructure Setup - Secondary Domain & Warm-Up Blueprint

Readiness Audit & Handover

Sending starts only after every readiness gate passes. Authentication improves deliverability readiness; it never guarantees inbox placement.

Authentication
Evidence: SPF/DKIM/DMARC all PASS
Owner: SafetyWithAthar
Status: Required

Blacklist Baseline
Evidence: Domain + IP checked against major lists
Owner: SafetyWithAthar
Status: Required

Warm-Up Plan
Evidence: 21-day ramp schedule issued
Owner: Client sender
Status: Required

Handover
Evidence: Configuration sheet + checklist delivered
Owner: SafetyWithAthar
Status: Rev. 0