

Lecture Notes

Monotone Classification with Relative Approximations

Your Name
Your University

March 21, 2026

Abstract

Brief summary of what these notes cover. Replace this with your own abstract or remove this block entirely.

Contents

1	Introduction	2
2	Problem Definitions	2
2.1	Math Conventions	2
2.2	Dominance	3
3	Results	3
4	Algorithms	3
5	Proofs	3

1 Introduction

Write your introductory text here. Below is a quick demo of every reusable box. Copy-paste whichever you need.

Definition 1.1 (Monotone Classifier). A classifier $h : \mathbb{R}^d \rightarrow \{-1, 1\}$ is *monotone* if $h(p) \geq h(q)$ for every $p, q \in \mathbb{R}^d$ satisfying $p \succ q$.

Theorem 1.1 (Upper Bound). For any $\epsilon > 0$, there exists an algorithm that finds a $(1 + \epsilon)$ -approximate monotone classifier using $O\left(\frac{\log n}{\epsilon}\right)$ label queries.

Proof. Write your proof here. The $\square$ is inserted automatically. $\square$

Lemma 1.1. For any input P and monotone classifier $h \in \mathbb{H}_{\text{mon}}$,

$$\text{err}_P(h) \geq k^*.$$

Proof. Proof of the lemma. $\square$

Proposition 1.1. If P is monotone then $k^* = 0$.

Corollary 1.1. Theorem 1.1 implies that the algorithm of ... achieves an error of at most $(1 + \epsilon)k^*$ with high probability.

Problem 1.1 (Monotone Classification with Relative Precision). Given $\epsilon \geq 0$, find a monotone classifier whose error on P is at most $(1 + \epsilon)k^*$. The efficiency of an algorithm is measured by the number of elements probed.

Example 1.1. Let $P = \{p_1, p_2, \dots, p_n\} \subset \mathbb{R}^2$. The optimal monotone classifier h misclassifies only p_1 , so $k^* = 1$.

Remark 1.1. When $\epsilon = 0$ the problem reduces to finding an *optimal* monotone classifier, which is achievable in polynomial time after revealing all labels.

2 Problem Definitions

2.1 Math Conventions

For an integer $x \geq 1$, the notation $[x]$ denotes $\{1, 2, \dots, x\}$. We write $x \leq_{1+\epsilon} y$ to mean $x \leq (1 + \epsilon)y$. For any real $x \geq 1$, define $\text{Log } x = \log_2(1 + x)$.

2.2 Dominance

A point $p \in \mathbb{R}^d$ *dominates* $q \in \mathbb{R}^d$ (written $p \succ q$) if $p \neq q$ and $p[i] \geq q[i]$ for all $i \in [d]$.
The optimal monotone error is

$$k^* = \min_{h \in \mathbb{H}_{\text{mon}}} \text{err}_P(h). \quad (1)$$

The expected cost and error of a randomised algorithm $\mathcal{A}$ are

$$\text{expected cost} = \mathbf{E}[X], \quad (2)$$

$$\text{expected error} = \mathbf{E}[\text{err}_P(h)]. \quad (3)$$

3 Results

Insert your main results here. Use the theorem/lemma boxes from above.

Setting	Upper bound	Lower bound
$\epsilon = 0$	$O(n)$	$\Omega(n)$
$\epsilon \in (0, 1)$	$O(n/\epsilon)$	$\Omega(n/\epsilon)$
$\epsilon \geq 1$	$O(\log n)$	$\Omega(\log n)$

Table 1: Summary of upper and lower bounds.

4 Algorithms

Describe your algorithms here. Use `\begin{enumerate}` for steps.

Step 1. Probe a random element $p \in P$ and observe $\text{label}(p)$.

Step 2. Update the current best classifier h .

Step 3. Repeat until $\text{err}_P(h) \leq (1 + \epsilon)k^*$.

5 Proofs

Place detailed proofs here. Each proof should reference a labelled theorem or lemma, e.g. *Proof of Theorem 1.1*.

References

References

- [1] Y. Tao, “Monotone Classification,” *PODS’18*.
- [2] Y. Tao, “Monotone Classification (Extended),” *PODS’21*.