

Name:Samiksha Sudhir Pingale.

PRN No:202501040041

Division:CS1

Batch:C12

Codetantra practical 2

2.1.1 problem statement

Write a Python program that implements a menu-driven interface for managing a list of integers. The program should have the following menu options:

1. Add
2. Remove
3. Display
4. Quit

The program should repeatedly prompt the user to enter a choice from the menu. Depending on the choice selected, the program should perform the following actions:

- **Add:** Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".

- **Remove:** Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".
- **Display:** Displays the current list of integers. If the list is empty, display "List is empty".
- **Quit:** Exits the program.
- The program should handle invalid menu choices by displaying "Invalid choice". Ensure that the program continues to prompt the user until they choose to quit (option 4).

Code:

```
l1=[]
```

```
while True:
```

```
    print("1. Add")
```

```
    print("2. Remove")
```

```
    print("3. Display")
```

```
    print("4. Quit")
```

```
    n= int(input("Enter choice: "))
```

```
    if n == 1:
```

```
    add = int(input("Integer: "))
    l1.append(add)
    print(f"List after adding: {l1}")
elif n == 2:
    if len(l1) == 0:
        print("List is empty")
    elif len(l1) != 0:
        remove = int(input("Integer: "))
        if remove not in l1 :
            print("Element not found")
        else:
            l1.remove(remove)
            print(f"List after removing: {l1}")
            after removing: {l1}")
elif n == 3:
    if len(l1) == 0:
        print("List is empty")
    else:
        print(l1)
elif n == 4:
```

break

else:

print("Invalid choice")

Output:

Average time
0.054 s
54.33 ms

Maximum time
0.079 s
79.00 ms

✓ 2 out of 2 shown test case(s) passed

✓ 1 out of 1 hidden test case(s) passed

✓ Test case 1
42 ms

Expected output

Actual output

1. · Add

1. · Add

2. · Remove

2. · Remove

3. · Display

3. · Display

4. · Quit

4. · Quit

Enter · choice: · 1

Enter · choice: · 1

Integer: · 11

Integer: · 11

List · after · adding: ·
[11]

List · after · adding: ·
· [11]

1. · Add

1. · Add

2. · Remove

2. · Remove

3. · Display

3. · Display

4. · Quit

4. · Quit

Enter · choice: · 1

Enter · choice: · 1

Integer: · 25

Integer: · 25

List after adding: · [11, ·25] ↵	List after adding: · ·[11, ·25] ↵
1. ·Add ↵	1. ·Add ↵
2. ·Remove ↵	2. ·Remove ↵
3. ·Display ↵	3. ·Display ↵
4. ·Quit ↵	4. ·Quit ↵
Enter choice: · 2	Enter choice: · 2
Integer: · 26	Integer: · 26
Element not found ↵	Element not found ↵
1. ·Add ↵	1. ·Add ↵
2. ·Remove ↵	2. ·Remove ↵
3. ·Display ↵	3. ·Display ↵
4. ·Quit ↵	4. ·Quit ↵
Enter choice: · 2	Enter choice: · 2
Integer: · 11	Integer: · 11
List after removing: ·[25] ↵	List after removing: ·[25] ↵
1. ·Add ↵	1. ·Add ↵
2. ·Remove ↵	2. ·Remove ↵
3. ·Display ↵	3. ·Display ↵
4. ·Quit ↵	4. ·Quit ↵
Enter choice: · 2	Enter choice: · 2
Integer: · 25	Integer: · 25
List after removing: ·[] ↵	List after removing: ·[] ↵
1. ·Add ↵	1. ·Add ↵

2. Remove ↵	2. Remove ↵
3. Display ↵	3. Display ↵
4. Quit ↵	4. Quit ↵
Enter choice: 3	Enter choice: 3
List is empty ↵	List is empty ↵
1. Add ↵	1. Add ↵
2. Remove ↵	2. Remove ↵
3. Display ↵	3. Display ↵
4. Quit ↵	4. Quit ↵
Enter choice: 2	Enter choice: 2
List is empty ↵	List is empty ↵
1. Add ↵	1. Add ↵
2. Remove ↵	2. Remove ↵
3. Display ↵	3. Display ↵
4. Quit ↵	4. Quit ↵
Enter choice: 8	Enter choice: 8
Invalid choice ↵	Invalid choice ↵
1. Add ↵	1. Add ↵
2. Remove ↵	2. Remove ↵
3. Display ↵	3. Display ↵
4. Quit ↵	4. Quit ↵
Enter choice: 4	Enter choice: 4

2. Remove ↵	2. Remove ↵
3. Display ↵	3. Display ↵
4. Quit ↵	4. Quit ↵
Enter choice: 3	Enter choice: 3
List is empty ↵	List is empty ↵
1. Add ↵	1. Add ↵
2. Remove ↵	2. Remove ↵
3. Display ↵	3. Display ↵
4. Quit ↵	4. Quit ↵
Enter choice: 2	Enter choice: 2
List is empty ↵	List is empty ↵
1. Add ↵	1. Add ↵
2. Remove ↵	2. Remove ↵
3. Display ↵	3. Display ↵
4. Quit ↵	4. Quit ↵
Enter choice: 8	Enter choice: 8
Invalid choice ↵	Invalid choice ↵
1. Add ↵	1. Add ↵
2. Remove ↵	2. Remove ↵
3. Display ↵	3. Display ↵
4. Quit ↵	4. Quit ↵
Enter choice: 4	Enter choice: 4

2.1.2 problem statement

Write a Python program to perform insertion, update, deletion, and traversal operations on a dictionary. An initial dictionary containing 10 predefined records is already given in the program.

Operations to be Performed:

1. Insertion – Insert a new key-value pair into the dictionary using user input.
2. Update – Update the value of an existing key using user input.
3. Deletion – Delete a specified key from the dictionary using user input.
4. Traversal – Traverse the final dictionary and display all key-value pairs.

Input and Output Format:

1. Read an integer representing the key to be inserted and a string representing its value. Insert this new key-value pair into the dictionary and display the dictionary after insertion.
2. Read an integer representing the key to be updated and a string representing the new value. Update the value of the specified key (only if it exists) and display the dictionary after the update.
3. Read an integer representing the key to be deleted. Delete the specified key from the

dictionary (only if it exists) and display the dictionary after deletion.

4. Finally, traverse the dictionary and display all key-value pairs.

The program should also display the original dictionary before performing any operations. Each output should be printed with appropriate messages.

Note:

- All operations must be performed using dictionary methods.
- Perform deletion only if possible; leave the dictionary unchanged.
- Refer to the visible test cases for better understanding and strictly match with the input/outputs.

Code:

```
# Initial dictionary with 10 predefined records
```

```
student = {
```

```
    1: "Amit",
```

```
    2: "Riya",
```

```
3: "Kiran",
4: "Neha",
5: "Arjun",
6: "Pooja",
7: "Rahul",
8: "Sneha",
9: "Vikram",
10: "Anjali"
}
print("Original Dictionary:",student)
#step 1
key1=int(input())
value1=input()
student.update({key1:value1})
print("After Insertion:",student)
#step2
key2=int(input())
value2=input()
if(key2 in student.keys()):
student.update({key2:value2})
```

```
print("After Update:",student)
#step3
key3=int(input())
if(key3 in student.keys()):
    student.pop(key3)
print("After Deletion:",student)
#step4
print("Traversing Dictionary:")
for key,value in student.items():
    print(f"{key} : {value}")
```

Output:

Average time

0.016 s

16.00 ms



Maximum time

0.027 s

27.00 ms



✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1

27 ms



Expected output

Actual output

Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}	Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}
11	11
Suresh	Suresh
After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}	After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
3	3
Karthik	Karthik
After Update: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}	After Update: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}

5

After Deletion: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}

Traversing Dictionary:

1: Amit

2: Riya

3: Karthik

4: Neha

6: Pooja

7: Rahul

8: Sneha

9: Vikram

10: Anjali

11: Suresh

5

After Deletion: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}

Traversing Dictionary:

1: Amit

2: Riya

3: Karthik

4: Neha

6: Pooja

7: Rahul

8: Sneha

9: Vikram

10: Anjali

11: Suresh

Test case 2

13 ms

Expected output

Original Dictionary:
 {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}

12

Meera

After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 12: 'Meera'}

6

Divya

After Update: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Divya', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 12: 'Meera'}

1

Actual output

Original Dictionary:
 {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}

12

Meera

After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 12: 'Meera'}

6

Divya

After Update: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Divya', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 12: 'Meera'}

1

After Deletion: {2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Divya', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 12: 'Meera'}	After Deletion: {2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Divya', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 12: 'Meera'}
Traversing Dictionary:	Traversing Dictionary:
2: Riya	2: Riya
3: Kiran	3: Kiran
4: Neha	4: Neha
5: Arjun	5: Arjun
6: Divya	6: Divya
7: Rahul	7: Rahul
8: Sneha	8: Sneha
9: Vikram	9: Vikram
10: Anjali	10: Anjali
12: Meera	12: Meera

Practical Lab Assignments:

2.2.1 problem statement

Write a program to check whether the given element is present or not in the array of elements using linear search.

Input format:

- The first line of input contains the array of integers which are separated by space
- The last line of input contains the key element to be searched

Output format:

- If the element is found, print the index. If the element found multiple times, print the starting index
- If the element is not found, print **Not found**.

Sample Test Case:

Input:

1 2 3 4 3 5 6

3

Output:

2

Code:

#function to perform linear search

def linear_search(arr,key):

```
#iterate through the bytearray
    for i in range(len(arr)):
        if arr[i]==key:
            return i

    return -1

arr=list(map(int, input().split())) #convert the input
string to a list of integers
key=int(input())# the key element to br searched
#perform linear search
result=linear_search(arr,key)
#output the result
if result != -1:
    print(result)
else:
    print("Not found")
```

Output:

Average time
0.009 s
8.75 ms



Maximum time
0.012 s
12.00 ms



✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1
12 ms



Expected output

Actual output

1 2 3 4 3 5 6

1 2 3 4 3 5 6

3

3

2

2

✓ Test case 2
9 ms



Expected output

Actual output

1 2 3 4 5 6 7 8 9

1 2 3 4 5 6 7 8 9

19

19

20

20

Not found

Not found

2.2.2 problem statement

You are provided with the heights of 11 cricket players (in centimeters). Your task is to identify the

tallest player, who will be selected as the captain of the team.

Input Format:

The first line of input will contain 11 integers, each representing the height of a player (in centimeters), each separated by a space.

Output Format

The output should be the height (in centimeters) of the tallest player.

Code:

```
heights = list(map(int, input().split()))  
tallest_player = max(heights)  
print(tallest_player)
```

Output:

Average time

0.006 s

5.67 ms



Maximum time

0.009 s

9.00 ms



✓ 1 out of 1 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1

5 ms



Expected output	Actual output
171 169 185 156 174 191 186 190 187 172 160	171 169 185 156 174 191 186 190 187 172 160
191	191