

Bureau Veritas

Thruster Requirements

Comprehensive Surveyor Catalog

Based on NR467 Rules for Classification of Steel Ships

Sections 7, 14, and 15

Complete Plan Approval Reference Guide

Document Version 1.7
2026

FOR BUREAU VERITAS PLAN APPROVAL SURVEYORS

Contents

Document Purpose and Usage	7
1 General Requirements - All Thrusters $\geq 110\text{kW}$	10
1.1 Applicability	10
1.2 Two Axes to Classify Before Listing Drawings	10
1.2.1 Duty: manoeuvring vs. propulsion	10
1.2.2 Propeller configuration: open vs. ducted (nozzle)	11
1.3 Mandatory Submissions for All Thruster Types	11
2 Transverse Thrusters (Tunnel & Retractable)	13
2.1 Tunnel Thrusters (Fixed Installation)	13
2.1.1 Structural Drawings & Calculations	13
2.1.2 Thruster Unit - Mechanical Components	14
2.1.3 Drive System (Electric or Hydraulic)	15
2.1.4 Control System	16
2.1.5 Additional Calculations & Documentation	17
2.2 Retractable Thrusters	19
2.2.1 Additional Requirements Beyond Fixed Tunnel Thrusters	19
3 Rotating and Azimuth Thrusters	21
3.1 Azimuth Thrusters (Fixed Pitch & Controllable Pitch)	21
3.1.1 General Arrangement & Structure	21
3.1.2 Propeller & Shaft System	22
3.1.3 Vertical Shaft & Column	23
3.1.4 Gear System	24
3.1.5 Slewing (Azimuth) System	25
3.1.6 Power Transmission	26
3.1.7 Control System	27
3.1.8 Additional Calculations & Documentation	28
3.2 Podded Propulsion Units	29
3.2.1 Pod-Specific Structural Components	29
3.2.2 Electric Motor in Pod	29
3.2.3 Power Supply Through Strut	30
3.2.4 Propeller Direct Drive	31
3.2.5 Pod-Specific Testing	31

4	Water-Jet Propulsion Systems	33
4.1	General Arrangement	33
4.2	Water-Jet Unit Components	33
4.3	Inlet Duct System	34
4.4	Steering and Reversing Mechanism	35
4.5	Drive System	36
4.5.1	For Direct Drive from Main Engine	36
4.5.2	For Gearbox Drive	36
4.6	Hydraulic System (for steering/reversing)	37
4.7	Control System	37
4.8	Performance Calculations	38
5	Voith-Schneider (Cycloidal) Propulsion Systems	39
5.1	Description & Classification Basis	39
5.2	VSP-Specific Structural & Mechanical Components	39
5.3	VSP Drive, Servo Control & Steering Function	41
6	Other Thruster Types (Rim-Driven, Pump-Jet, Gill/Jet, Steering Grid)	43
6.1	Rim-Driven Thrusters (Integrated Motor Propulsors)	43
6.2	Pump-Jet & Ducted Rotor-Stator Propulsors	44
6.3	Gill / Hydro-Jet Transverse Thrusters (Pump-Type)	44
6.4	Steering Grid / Steering-Nozzle & Rudder-Propeller Variants	44
7	Prime Mover Considerations — Diesel-Engine vs. Electric-Motor Driven Thrusters	45
7.1	Purpose	45
7.2	Electric-Motor-Driven Thrusters — Additional Submissions	45
7.3	Diesel-Engine-Driven Thrusters — Additional Submissions	47
8	Thrusters as Part of Steering Gear	50
8.1	Applicability	50
8.2	Additional Steering Gear Requirements	50
8.2.1	Steering System Design	50
8.2.2	Redundancy & Reliability	51
8.2.3	Power Supply	51
8.2.4	Control Stations	52
8.2.5	Alarms and Monitoring	52
8.2.6	Hydraulic Systems (if applicable)	53
8.2.7	Testing & Commissioning	53
8.2.8	Operating Manuals	54
8.2.9	SOLAS Compliance Documentation	54
9	Thrusters as Part of Main Shafting	55
9.1	Applicability	55
9.2	Overlap with Thruster Requirements	55
9.2.1	Shaft Design Drawings	55
9.2.2	Shaft Strength Calculations	56
9.2.3	Critical Speed Analysis	57

9.2.4	Bearing Design	57
9.2.5	Couplings	58
9.2.6	Seals	59
9.2.7	Alignment	59
9.2.8	Material Specifications	60
9.2.9	Non-Destructive Testing (NDT)	60
9.2.10	Testing & Commissioning	61
9.3	MON-SHAFT & Shaft-Line Condition-Monitoring Notations	62
10	Hydraulic Systems & Pitch Control Mechanisms	64
10.1	Applicability	64
10.2	Hydraulic Power Unit (HPU)	64
10.3	Hydraulic Circuit Design	65
10.4	Hydraulic Components	66
10.5	Filtration System	67
10.6	Cooling System	68
10.7	Hydraulic Fluid	68
10.8	Piping Design	69
10.9	Hose Assemblies	70
10.10	Safety Devices	70
10.11	Control System	70
10.12	Monitoring & Instrumentation	71
10.13	Controllable Pitch Mechanism (CP Propellers)	71
10.14	Testing & Commissioning	72
10.15	Operating & Maintenance Manuals	73
11	Dynamic Positioning (DP) Thrusters - Additional Requirements	74
11.1	Applicability	74
11.2	Reference	75
12	Ice Class & Cold-Climate (Winterisation) Requirements	76
12.1	Applicability	76
12.2	Ice-Strengthening Submissions	76
13	Additional BV Class Notations Affecting Thruster Packages	79
13.1	Purpose	79
13.2	Notation Impact Matrix	79
14	Ship-Type & Service-Notation Specific Requirements	81
14.1	Purpose	81
14.2	Ship-Type → Thruster Expectation Matrix	81
14.3	Passenger Ships & Safe Return to Port (SRtP)	83
14.4	Tankers & Gas Carriers — Hazardous Areas & Explosion Protection	84
14.5	Offshore & DP-Intensive Vessels	84
14.6	Tugs & Escort Tugs	85
14.7	Thruster Compartment (All Ship Types)	85

15 Testing & Commissioning Requirements	86
15.1 Factory Acceptance Tests (FAT)	86
15.2 Installation Tests	86
15.3 Dock Trials	87
15.4 Sea Trials	87
15.5 Documentation & Reporting	87
16 Surveyor Checklists by Thruster Type	88
16.1 Tunnel Thrusters (Fixed) - Complete Checklist	88
16.1.1 General Information	88
16.1.2 Structural	88
16.1.3 Thruster Unit - Mechanical	88
16.1.4 Drive System	89
16.1.5 Control System	89
16.1.6 Calculations	89
16.1.7 Materials & Welding	89
16.1.8 Testing	89
16.1.9 Manuals	90
16.2 Retractable Thrusters - Complete Checklist	90
16.2.1 Retraction Mechanism	90
16.2.2 Additional Manuals	90
16.2.3 Additional Testing	90
16.3 Azimuth Thrusters (Fixed Pitch) - Complete Checklist	91
16.3.1 General & Structure	91
16.3.2 Propeller & Shaft	91
16.3.3 Gear & Slewing System	91
16.3.4 Drive System & Prime Mover	91
16.3.5 Control, Calculations, Materials & Testing	92
16.3.6 If Steering / DP / Ice / Notations	92
16.4 Azimuth Thrusters (Controllable Pitch) - Complete Checklist	92
16.5 Podded Propulsion Units - Complete Checklist	92
16.6 Voith-Schneider (Cycloidal) Units - Complete Checklist	93
16.7 Water-Jet Systems - Complete Checklist	93
16.8 Prime-Mover Add-On Checklist (apply to any type)	94
16.9 Ice Class / Winterisation Add-On Checklist (apply if notation carried)	94
16.10 DP Thrusters - Additional Checklist Items	95
17 Submission Cover Sheets by Ship Type	96
17.1 Generic Template (any ship / any thruster type)	97
17.2 Harbour / Escort Tug	98
17.3 Offshore Supply / PSV / AHTS (DP)	99
17.4 Passenger Ship / RoPax / Ferry	100
17.5 Cruise Ship	101
17.6 Double-Ended Ferry	102
17.7 Dredger (TSHD / CSD)	103
17.8 Cable / Pipe Layer & Offshore Construction (DP)	104
17.9 Drillship / Semi-Submersible (MODU)	105

17.10	Oil / Chemical Tanker	106
17.11	Gas Carrier (LNG / LPG)	107
17.12	Ice-Class / Polar Trader	108
17.13	Research / Naval / Patrol	109
17.14	Large Yacht	110
17.15	Container / Bulk / General Cargo	111
18	Common Submission Errors & Surveyor Notes	112
18.1	Frequent Documentation Gaps	112
18.1.1	Missing or Incomplete Calculations	112
18.1.2	Inadequate Drawings	112
18.1.3	Steering Gear Overlap Not Addressed	112
18.1.4	DP System Gaps	113
18.1.5	Hydraulic System Issues	113
18.1.6	Prime-Mover Gaps	113
18.1.7	Ice-Class & Notation Gaps	113
18.1.8	Cycloidal (VSP) & Combined Propulsion/Steering Gaps	113
18.2	Surveyor Review Tips	114
18.2.1	Initial Review	114
18.2.2	Calculation Review	114
18.2.3	Drawing Review	114
18.3	Red Flags for Surveyors	114
18.3.1	Immediate Rejection Criteria	114
18.3.2	Require Clarification	115
19	Quick Reference Tables	116
19.1	Thruster Type vs. Applicable Rule Sections	116
19.2	Prime Mover & Additional-Notation Quick Guide	117
19.3	Document Approval Categories Summary	117
20	Regulatory References	118
20.1	Bureau Veritas Rules	118
20.1.1	NR467 - Rules for Classification of Steel Ships	118
20.1.2	Related BV Rule Notes (as applicable)	119
20.2	International Standards	120
20.2.1	ISO Standards	120
20.2.2	IEC Standards	120
20.2.3	IACS Unified Requirements & Codes	120
20.2.4	SOLAS Convention	120
20.2.5	Ship-Type / Service Rule Sets & Codes	121
20.2.6	IMO Resolutions	121
20.3	Online Resources	121
20.3.1	Bureau Veritas Marine & Offshore	121
21	Contact Information & Document Control	122
21.1	For Technical Queries	122
21.2	For Urgent Classification Matters	122
21.3	Document Revision History	123

21.4 Important Disclaimers	124
--------------------------------------	-----

Document Purpose and Usage

This catalog provides a comprehensive overview of thruster requirements per Bureau Veritas Rules for Classification (NR467) and related guidance, designed as a practical reference for plan approval surveyors.

Key Features

- Complete drawing and document lists for all thruster types
- Explicit approval categories (**FA** or **FI**)
- Cross-references for overlapping requirements (steering gear, main shafting, hydraulics)
- Surveyor checklists by thruster type
- Testing and commissioning requirements
- Common submission errors and review tips

Document Structure

The catalog is organized into the following chapters:

1. General Requirements (All Thrusters $\geq 110\text{kW}$)
2. Transverse Thrusters (Tunnel & Retractable)
3. Rotating and Azimuth Thrusters (incl. Podded Units)
4. Water-Jet Propulsion Systems
5. Voith-Schneider (Cycloidal) Propulsion Systems
6. Other Thruster Types (Rim-Driven, Pump-Jet, Gill/Jet, Steering Grid)
7. Prime Mover Considerations — Diesel-Engine vs. Electric-Motor Driven Thrusters
8. Thrusters as Part of Steering Gear
9. Thrusters as Part of Main Shafting
10. Hydraulic Systems & Pitch Control
11. Dynamic Positioning (DP) Thrusters

12. Ice Class & Cold-Climate (Winterisation) Requirements
13. Additional BV Class Notations Affecting Thruster Packages
14. Ship-Type & Service-Notation Specific Requirements
15. Testing & Commissioning
16. Surveyor Checklists by Type
17. Submission Cover Sheets by Ship Type (one-page tick-off)
18. Common Submission Errors
19. Quick Reference Tables
20. Regulatory References
21. Contact Information

How to Use This Catalog (Surveyor Workflow)

1. **Identify the thruster type** (Chapters 2–6) and confirm rated power. Thrusters ≥ 110 kW attract the full Sec. 15 submission set.
2. **Identify the prime mover** — electric motor or diesel engine (Chapter 7) — and add the corresponding drive-train drawings.
3. **Identify the functional role(s)**: propulsion, steering (Chapter 8), main shaft line (Chapter 9), or dynamic positioning (Chapter 11). Each role *adds* to the base package.
4. **Overlay additional notations & service constraints**: ice class / winterisation (Chapter 12), other BV additional class notations (Chapter 13), and the ship-type / service-notation requirements incl. SRtP, hazardous-area and offshore rules (Chapter 14).
5. **Verify hydraulics/pitch** (Chapter 10) and **testing & commissioning** (Chapter 15).
6. **Run the type-specific checklist** (Chapter 16) and screen against common errors (Chapter 18).

Navigating this PDF

This document is fully hyperlinked for quick reference:

- **Bookmarks panel** — open your PDF reader’s bookmarks/outline panel to jump to any chapter or section.
- **Table of contents** — every entry is clickable.
- **Cross-references** — “Chapter X”, “Section Y” and table references in the text are clickable links.
- **Search** — the text is fully selectable and searchable (e.g. search “MON-SHAFT”, “escort tug”, “ice”).

Legend

- **FA** = **For Approval** — Must be reviewed and approved before construction/installation
- **FI** = **For Information** — Submitted for record, not requiring formal approval
- **During Construction** = Certificates/reports generated during manufacturing

Note on rule references: Thruster requirements are found in **NR467, Part C, Chapter 1, Section 15** (“Thrusters”); steering gear in **Section 14**; shaft lines and propellers in **Sections 7–8**. Bracketed sub-references such as [2.3] are structural pointers within this catalog. Ice class, comfort, automation and DP requirements sit in **NR467 Part F** (Additional Class Notations, e.g. DYNAPOS for DP); service notations are in **Part D** (general) and **Part E** (offshore service vessels & tugs). Note **NR216** is the Materials & Welding rule note (not a DP rule). Always confirm the exact article against the rule edition applicable to the vessel’s contract/build date.

Chapter 1

General Requirements - All Thrusters $\geq 110\text{kW}$

1.1 Applicability

All thrusters developing power equal to 110 kW or more ($\geq 110\text{ kW}$) must comply with NR467 Section 15 requirements (NR467 Pt C, Ch.1, Sec.15, [1.1.1]). Thrusters of less than 110 kW are to be built in accordance with sound marine practice and tested per Sec.15 [3.2] to the satisfaction of the Surveyor (NR467 Pt C, Ch.1, Sec.15, [1.1.2]) — verify with surveyor for the exact reduced scope.

1.2 Two Axes to Classify Before Listing Drawings

Before applying any type checklist, fix two attributes of the unit — they change *which* rules and drawings apply as much as the thruster type does:

1.2.1 Duty: manoeuvring vs. propulsion

- **Manoeuvring (auxiliary)** — e.g. a bow/stern tunnel thruster used only for low-speed manoeuvring. Assessed under Sec. 15 as auxiliary machinery; it is *not* part of the main shaft line.
- **Propulsion (main)** — e.g. an azimuth on a tug, a podded unit, a water-jet or a Voith-Schneider that propels the ship. The propeller, shaft and gear are classed as **main propulsion**: the main-shaft-line requirements of Chapter 9 apply, a **torsional vibration calculation is mandatory**, and barred/continuous-speed ranges must be confirmed.
- **Take-me-home / emergency propulsion** — a retractable or auxiliary unit providing get-home capability; assess independence from the main train (cross-reference redundant-propulsion notation, Chapter 13).

The same physical thruster therefore attracts a heavier package when it is the ship's propulsion than when it is purely for manoeuvring.

1.2.2 Propeller configuration: open vs. ducted (nozzle)

- **Open (non-ducted) propeller** — blade and hub strength, cavitation and the usual shaft/bearing package.
- **Ducted (nozzle) propeller** — *adds* the nozzle/duct structure and strength drawing, nozzle profile/geometry with propeller-tip clearance, and the nozzle-to-unit/hull connection. Distinguish:
 - **Fixed nozzle** (Kort-type) — structural item only; improves bollard pull.
 - **Steering nozzle** — the nozzle also steers, so the **steering-gear package** of Chapter 8 applies (actuator, control, redundancy, SOLAS II-1/29 where it is the ship's means of steering).

Surveyor note: record duty and propeller configuration on the submission cover sheet (Chapter 17). The interactive Quick-Reference tool builds the exact drawing list once type, duty, propeller configuration, prime mover, role, ship type and notations are selected.

1.3 Mandatory Submissions for All Thruster Types

Table 1.1: General Requirements - All Thrusters

#	Drawing/Document	Category	Content Requirements	Reference
1	General Arrangement Drawing	FA	• Thruster location on vessel • Installation orientation • Access provisions • Clearances to other equipment • Coordinate system reference	NR467 Sec.15, [1]
2	Technical Specification Sheet	FA	• Rated power (kW) • Rated thrust (kN) • Rated speed (RPM) • Operating voltage/pressure • Weight and dimensions • Operating depth/pressure rating	NR467 Sec.15, [1]
3	Material Specifications	FA	• Material grades for all major components • Compliance with NR467 Part B, Ch.3 • Corrosion protection details • Material certificates (during construction)	NR467 Part B, Ch.3
Continued on next page				

Table 1.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
4	Welding Procedures	FA	• Welding Procedure Specifications (WPS) • Welder qualification records • NDT requirements and extent • Weld inspection plan	NR467 Part B, Ch.4
5	Manufacturer's Quality Plan	FA	• Manufacturing sequence • Inspection and test points • Quality control procedures • Traceability system	NR467 Sec.15
6	Operation & Maintenance Manual	FI	• Operating instructions • Maintenance schedule • Troubleshooting guide • Safety precautions	NR467 Sec.15
7	Spare Parts List	FI	• Recommended spare parts • Critical component identification • Part numbers and suppliers	NR467 Sec.15
8	Installation Manual	FI	• Installation procedure • Alignment requirements • Foundation specifications • Connection details	NR467 Sec.15

Chapter 2

Transverse Thrusters (Tunnel & Retractable)

2.1 Tunnel Thrusters (Fixed Installation)

2.1.1 Structural Drawings & Calculations

Table 2.1: Tunnel Thrusters - Structural Requirements

#	Drawing/Document	Category	Content Requirements	Reference
1	Tunnel Structural Arrangement	FA	• Tunnel diameter and length • Tunnel position relative to baseline/centerline • Plate thickness and material • Reinforcement arrangement • Connection to hull structure	NR467 Sec.15, [2.1]
2	Tunnel Structural Calculations	FA	• Pressure loads (internal/external) • Structural stress analysis • Buckling analysis • Fatigue assessment • FEA results (if applicable)	NR467 Sec.15, [2.1]
3	Tunnel End Grating/Grid Design	FA	• Grating dimensions and material • Attachment method • Structural strength verification • Debris protection	NR467 Sec.15, [2.2]
Continued on next page				

Table 2.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
4	Hull Penetration Details	FA	• Opening dimensions • Reinforcement around opening • Welding details • Watertight integrity provisions	NR467 Part B, Ch.5

2.1.2 Thruster Unit - Mechanical Components

Table 2.2: Tunnel Thrusters - Mechanical Components

#	Drawing/Document	Category	Content Requirements	Reference
5	Thruster Unit General Assembly	FA	• Complete unit cross-section • Component identification • Material specifications • Assembly sequence	NR467 Sec.15, [2.3]
6	Propeller Design Drawing	FA	• Propeller diameter and pitch • Number of blades • Blade profile and geometry • Hub design • Material specification	NR467 Sec.15, [2.4]
7	Propeller Strength Calculations	FA	• Blade root stress analysis • Hub stress analysis • Centrifugal force calculations • Fatigue life assessment • Cavitation analysis	NR467 Sec.15, [2.4]
8	Propeller Shaft Drawing	FA	• Shaft diameter and length • Material specification • Surface finish requirements • Keyway details • Seal locations	NR467 Sec.15, [2.5]
9	Shaft Strength Calculations	FA	• Torsional strength analysis • Bending stress calculations • Combined stress analysis • Deflection calculations • Critical speed analysis • Fatigue assessment	NR467 Sec.15, [2.5]; Sec.7
Continued on next page				

Table 2.2 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
10	Bearing Arrangement Drawing	FA	• Bearing type and manufacturer • Bearing housing design • Lubrication arrangement • Seal design • Cooling provisions (if applicable)	NR467 Sec.15, [2.6]
11	Bearing Load Calculations	FA	• Radial and axial loads • Bearing life calculation (L10) • Lubrication requirements • Temperature analysis	NR467 Sec.15, [2.6]
12	Gearbox Assembly Drawing	FA	• Gear arrangement (bevel, helical, etc.) • Gear ratios • Casing design • Lubrication system • Mounting arrangement	NR467 Sec.15, [2.7]
13	Gear Tooth Calculations	FA	• Gear tooth strength (ISO 6336) • Contact stress analysis • Bending stress analysis • Lubrication film thickness • Efficiency calculations	NR467 Sec.15, [2.7]
14	Gearbox Lubrication System	FA	• Oil type and capacity • Circulation system (if forced) • Cooling arrangement • Filtration system • Oil level and temperature monitoring	NR467 Sec.15, [2.7]

2.1.3 Drive System (Electric or Hydraulic)

For Electric Motor Drive

Table 2.3: Tunnel Thrusters - Electric Drive System

#	Drawing/Document	Category	Content Requirements	Reference
15	Electric Motor Specification	FA	• Motor type (induction, synchronous) • Rated power and speed • Voltage and frequency • Insulation class • Protection class (IP rating) • Cooling method • Mounting arrangement	NR467 Sec.15, [2.8]; IEC 60092-301
16	Motor Foundation Drawing	FA	• Foundation structure design • Vibration isolation details • Bolt arrangement • Alignment provisions • Structural attachment to hull	NR467 Sec.15, [2.8]
17	Motor-Gearbox Coupling	FA	• Coupling type and manufacturer • Alignment tolerances • Torque capacity • Installation procedure	NR467 Sec.15, [2.8]

For Hydraulic Motor Drive

Table 2.4: Tunnel Thrusters - Hydraulic Drive System

#	Drawing/Document	Category	Content Requirements	Reference
18	Hydraulic Motor Specification	FA	• Motor type (axial piston, radial piston, gear) • Displacement and speed range • Rated pressure • Efficiency curves • Mounting details	NR467 Sec.15, [2.9]
19	Hydraulic System Schematic	FA	• Complete hydraulic circuit • Component symbols and identification • Pressure and flow ratings • See Chapter 10 for detailed requirements	NR467 Sec.15, [2.9]

2.1.4 Control System

Table 2.5: Tunnel Thrusters - Control System

#	Drawing/Document	Category	Content Requirements	Reference
20	Control System Block Diagram	FA	- Control architecture - Input/output signals - Control logic overview - Interface with ship systems	NR467 Sec.15, [2.10]; Part C, Ch.4
21	Control Panel Layout	FA	- Panel arrangement - Component locations - Wiring diagram - Protection devices	NR467 Sec.15, [2.10]
22	Electrical Single-Line Diagram	FA	- Power supply arrangement - Circuit breakers and protection - Emergency stop circuit - Monitoring and alarm systems	NR467 Sec.15, [2.10]; IEC 60092-504
23	Control Software Description	FA	- Software functionality - Control algorithms - Safety functions - Software validation documentation	NR467 Part C, Ch.4

2.1.5 Additional Calculations & Documentation

Table 2.6: Tunnel Thrusters - Additional Calculations

#	Drawing/Document	Category	Content Requirements	Reference
24	Thrust Calculation	FA	- Theoretical thrust calculation - Efficiency factors - Operating curves (thrust vs. speed) - Bollard pull prediction	NR467 Sec.15, [2.11]
25	Vibration Analysis	FA	- Natural frequency calculations - Forced vibration analysis - Resonance avoidance verification - Vibration isolation design	NR467 Sec.15, [2.12]

Continued on next page

Table 2.6 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
26	Noise Level Prediction	FA	• Airborne noise prediction • Structure-borne noise analysis • Compliance with IMO noise code • Noise reduction measures	NR467 Sec.15, [2.12]
27	Thermal Analysis	FA	• Heat generation calculations • Cooling requirements • Temperature rise predictions • Ventilation requirements	NR467 Sec.15, [2.13]

2.2 Retractable Thrusters

2.2.1 Additional Requirements Beyond Fixed Tunnel Thrusters

All submissions from Section 2.1 apply, PLUS the following:

Table 2.7: Retractable Thrusters - Additional Requirements

#	Drawing/Document	Category	Content Requirements	Reference
28	Retraction Mechanism Assembly	FA	• Complete mechanism design • Lifting/lowering system • Guide rail arrangement • Travel limits and stops • Position indicators	NR467 Sec.15, [2.14]
29	Hydraulic Cylinder Specifications	FA	• Cylinder bore and stroke • Operating pressure • Rod diameter and material • Seal specifications • Mounting arrangement	NR467 Sec.15, [2.14]
30	Retraction System Calculations	FA	• Lifting force requirements • Hydraulic pressure calculations • Cylinder sizing verification • Retraction/extension time calculations • Dynamic load analysis	NR467 Sec.15, [2.14]
31	Hull Opening & Closure Design	FA	• Opening dimensions • Closure plate/door design • Sealing arrangement (extended position) • Sealing arrangement (retracted position) • Locking mechanism	NR467 Sec.15, [2.15]; Part B, Ch.5
32	Hull Opening Structural Analysis	FA	• Local hull strength calculations • Reinforcement design around opening • Stress concentration analysis • Fatigue assessment • FEA results (typically required)	NR467 Sec.15, [2.15]; Part B, Ch.5
Continued on next page				

Table 2.7 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
33	Watertight Integrity Documentation	FA	• Seal design and material • Pressure testing requirements • Leakage criteria • Compliance with subdivision requirements	NR467 Part B, Ch.5
34	Locking System Design	FA	• Mechanical locks (extended position) • Retracted position locks • Locking force calculations • Fail-safe provisions • Interlock system	NR467 Sec.15, [2.16]
35	Position Indication System	FA	• Position sensors (type and location) • Indication on bridge/control panel • Alarm system (intermediate positions) • Redundancy provisions	NR467 Sec.15, [2.16]
36	Emergency Lowering System	FA	• Emergency power source • Manual lowering provisions • Emergency procedure • Time to deploy	NR467 Sec.15, [2.17]
37	Hydraulic System for Retraction	FA	• HPU specifications • Control valve arrangement • Piping layout • Accumulator sizing (if applicable) • Emergency lowering circuit • See Chapter 10 for detailed requirements	NR467 Sec.15, [2.17]
38	Retraction/Extension Procedures	FI	• Step-by-step operating procedure • Pre-operation checks • Safety precautions • Troubleshooting	NR467 Sec.15, [2.18]
39	Emergency Recovery Procedures	FI	• Emergency lowering procedure • Manual operation instructions • Recovery from failure modes • Contact information for support	NR467 Sec.15, [2.18]

Chapter 3

Rotating and Azimuth Thrusters

3.1 Azimuth Thrusters (Fixed Pitch & Controllable Pitch)

3.1.1 General Arrangement & Structure

Table 3.1: Azimuth Thrusters - General Arrangement

#	Drawing/Document	Category	Content Requirements	Reference
1	General Arrangement Drawing	FA	• Thruster location on vessel • Installation orientation • Azimuth rotation range (typically 360°) • Clearance envelope (rotating) • Access for maintenance	NR467 Sec.15, [3.1]
2	Azimuth Unit Complete Assembly	FA	• Longitudinal and transverse sections • All major components identified • Material specifications • Assembly sequence • Lifting points	NR467 Sec.15, [3.1]
3	Hull Penetration & Foundation	FA	• Hull opening dimensions • Structural reinforcement • Foundation design • Watertight integrity details • Load transfer to hull structure	NR467 Sec.15, [3.2]; Part B, Ch.5
Continued on next page				

Table 3.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
4	Hull Structure Calculations	FA	• Local hull strength analysis • Foundation load distribution • Stress analysis • Fatigue assessment • FEA results (typically required)	NR467 Sec.15, [3.2]; Part B, Ch.5

3.1.2 Propeller & Shaft System

For Fixed Pitch Propellers

Table 3.2: Azimuth Thrusters - Fixed Pitch Propeller

#	Drawing/Document	Category	Content Requirements	Reference
5	Propeller Design Drawing	FA	• Propeller diameter and pitch • Number of blades • Blade geometry (sections) • Hub design • Material specification • Blade attachment method	NR467 Sec.15, [3.3]
6	Propeller Strength Calculations	FA	• Blade stress analysis • Hub stress analysis • Centrifugal forces • Hydrodynamic forces • Fatigue life assessment • Cavitation analysis	NR467 Sec.15, [3.3]

For Controllable Pitch Propellers (ADDITIONAL to Fixed Pitch)

Table 3.3: Azimuth Thrusters - Controllable Pitch Mechanism

#	Drawing/Document	Category	Content Requirements	Reference
7	CP Hub Mechanism Assembly	FA	• Hub internal mechanism • Pitch control rod/linkage • Blade retention system • Bearing arrangement • Seal design	NR467 Sec.15, [3.4]
Continued on next page				

Table 3.3 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
8	Blade Retention Calculations	FA	• Blade root connection strength • Centrifugal force analysis • Hydrodynamic moment analysis • Bolt/pin strength verification • Fatigue assessment	NR467 Sec.15, [3.4]
9	Pitch Control Mechanism	FA	• Hydraulic cylinder (in hub or external) • Control rod design • Linkage system • Pitch range and indicators • Fail-safe position	NR467 Sec.15, [3.4]; Ch.10
10	Pitch Control Hydraulic System	FA	• Hydraulic supply arrangement • Rotary joint/slip ring design • Control valve system • Pitch feedback system • See Chapter 10 for detailed requirements	NR467 Sec.15, [3.4]; Ch.10

3.1.3 Vertical Shaft & Column

Table 3.4: Azimuth Thrusters - Vertical Shaft & Column

#	Drawing/Document	Category	Content Requirements	Reference
11	Vertical Shaft Assembly	FA	• Shaft dimensions and material • Upper and lower bearing locations • Thrust bearing arrangement • Seal system • Coupling details	NR467 Sec.15, [3.5]; Sec.7
12	Vertical Shaft Calculations	FA	• Torsional strength • Bending stress (from propeller forces) • Combined stress analysis • Deflection calculations • Critical speed analysis • Fatigue assessment	NR467 Sec.15, [3.5]; Sec.7
Continued on next page				

Table 3.4 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
13	Thrust Bearing Design	FA	• Bearing type and manufacturer • Load capacity • Lubrication system • Cooling arrangement • Monitoring provisions	NR467 Sec.15, [3.6]
14	Thrust Bearing Calculations	FA	• Axial load analysis • Bearing life calculation • Temperature rise analysis • Lubrication film thickness	NR467 Sec.15, [3.6]
15	Radial Bearing Arrangement	FA	• Upper and lower bearing design • Bearing housing • Lubrication system • Seal arrangement	NR467 Sec.15, [3.7]
16	Column Structure Design	FA	• Column/strut dimensions • Material specification • Hydrodynamic fairing • Structural strength • Corrosion protection	NR467 Sec.15, [3.8]
17	Seal System Design	FA	• Seal type and material • Seal arrangement (upper/lower) • Pressure rating • Leakage monitoring • Replacement procedure	NR467 Sec.15, [3.9]

3.1.4 Gear System

Table 3.5: Azimuth Thrusters - Gear System

#	Drawing/Document	Category	Content Requirements	Reference
18	Gear Train Assembly	FA	• Gear arrangement (bevel, helical, planetary) • Gear ratios • Gear casing design • Lubrication system • Access for inspection	NR467 Sec.15, [3.10]

Continued on next page

Table 3.5 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
19	Gear Tooth Strength Calculations	FA	• Tooth bending stress (ISO 6336) • Contact stress • Pitting resistance • Scuffing analysis • Efficiency calculations	NR467 Sec.15, [3.10]
20	Gear Lubrication System	FA	• Oil type and capacity • Circulation system (forced/splash) • Cooling arrangement • Filtration system • Oil level and temperature monitoring	NR467 Sec.15, [3.10]

3.1.5 Slewing (Azimuth) System

Table 3.6: Azimuth Thrusters - Slewing System

#	Drawing/Document	Category	Content Requirements	Reference
21	Slewing Bearing Design	FA	• Bearing type and manufacturer • Internal/external gear (if applicable) • Load capacity (axial, radial, moment) • Mounting arrangement • Lubrication provisions	NR467 Sec.15, [3.11]
22	Slewing Bearing Calculations	FA	• Load analysis (static and dynamic) • Bearing life calculation • Bolt preload calculations • Overturning moment analysis	NR467 Sec.15, [3.11]
23	Azimuth Drive Mechanism	FA	• Drive motor (electric or hydraulic) • Gear/pinion arrangement • Drive ratio • Brake system • Locking mechanism (if required)	NR467 Sec.15, [3.12]

Continued on next page

Table 3.6 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
24	Azimuth Drive Calculations	FA	• Torque requirements • Acceleration/deceleration analysis • Motor sizing verification • Brake sizing • Response time calculations	NR467 Sec.15, [3.12]
25	Position Feedback System	FA	• Position sensor type and location • Accuracy and resolution • Signal processing • Redundancy (if required for DP/steering)	NR467 Sec.15, [3.13]

3.1.6 Power Transmission

For Electric Drive

Table 3.7: Azimuth Thrusters - Electric Power Transmission

#	Drawing/Document	Category	Content Requirements	Reference
26	Electric Motor Specification	FA	• Motor type and rating • Voltage and frequency • Cooling method • Insulation and protection class • Mounting arrangement	NR467 Sec.15, [3.14]; IEC 60092-301
27	Power Cable Routing	FA	• Cable route from switchboard • Cable support and protection • Penetrations through bulk-heads • Cable sizing calculations	NR467 Sec.15, [3.14]; IEC 60092-352
28	Slip Ring or Rotary Joint	FA	• Type and manufacturer • Current rating • Maintenance requirements • Cooling provisions	NR467 Sec.15, [3.14]

For Hydraulic Drive

Table 3.8: Azimuth Thrusters - Hydraulic Power Transmission

#	Drawing/Document	Category	Content Requirements	Reference
29	Hydraulic Motor Specification	FA	• Motor type and displacement • Rated pressure and speed • Efficiency curves • Mounting details	NR467 Sec.15, [3.15]
30	Hydraulic System Schematic	FA	• Complete hydraulic circuit • HPU specifications • Piping arrangement • Control valve system • See Chapter 10 for detailed requirements	NR467 Sec.15, [3.15]; Ch.10

3.1.7 Control System

Table 3.9: Azimuth Thrusters - Control System

#	Drawing/Document	Category	Content Requirements	Reference
31	Control System Architecture	FA	• Overall control system topology • Propulsion control • Azimuth control • Pitch control (CP thrusters) • Interface with ship systems	NR467 Sec.15, [3.16]; Part C, Ch.4
32	Bridge Control Console	FA	• Control panel layout • Joystick/lever arrangement • Display and indication • Alarm system • Emergency stop provisions	NR467 Sec.15, [3.16]
33	Local Control Station	FA	• Local control panel design • Control mode selection • Indication and monitoring • Interlock with bridge control	NR467 Sec.15, [3.16]
34	Control Software Description	FA	• Software architecture • Control algorithms • Safety functions • Software validation documentation • Version control	NR467 Part C, Ch.4
Continued on next page				

Table 3.9 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
35	Electrical Single-Line Diagram	FA	• Power supply arrangement • Circuit breakers and protection • Emergency power provisions • Monitoring and alarm circuits	NR467 Sec.15, [3.16]; IEC 60092-504

3.1.8 Additional Calculations & Documentation

Table 3.10: Azimuth Thrusters - Additional Calculations

#	Drawing/Document	Category	Content Requirements	Reference
36	Thrust and Torque Calculations	FA	• Propeller thrust curves • Torque requirements • Power absorption • Efficiency analysis • Bollard pull prediction	NR467 Sec.15, [3.17]
37	Vibration Analysis	FA	• Natural frequency calculations • Forced vibration analysis • Resonance avoidance • Foundation vibration isolation • Acceptable vibration levels	NR467 Sec.15, [3.18]
38	Noise Analysis	FA	• Airborne noise prediction • Structure-borne noise analysis • Compliance with noise regulations • Noise reduction measures	NR467 Sec.15, [3.18]
39	Hydrodynamic Analysis	FA	• Propeller hydrodynamic design • Cavitation analysis • Efficiency optimization • Interaction effects with hull	NR467 Sec.15, [3.19]
40	Thermal Analysis	FA	• Heat generation in gears, bearings, seals • Cooling system capacity • Temperature rise predictions • Ventilation requirements	NR467 Sec.15, [3.20]

3.2 Podded Propulsion Units

Podded propulsion units include all requirements from Section 3.1 (Azimuth Thrusters), with the following **ADDITIONAL** or **MODIFIED** requirements:

3.2.1 Pod-Specific Structural Components

Table 3.11: Podded Propulsion - Pod Structure

#	Drawing/Document	Category	Content Requirements	Reference
41	Pod Housing Design	FA	• Pod shell structure • Material specification • Hydrodynamic fairing • Structural strength analysis • Corrosion protection system	NR467 Sec.15, [3.21]
42	Pod Housing Calculations	FA	• Pressure loading analysis • Structural stress analysis • Fatigue assessment • Impact resistance • FEA results	NR467 Sec.15, [3.21]
43	Strut Structure Design	FA	• Strut dimensions and material • Hydrodynamic profile • Connection to pod and hull • Internal cable/pipe routing • Access provisions	NR467 Sec.15, [3.22]
44	Strut Structural Calculations	FA	• Bending stress analysis • Torsional stress • Combined loading • Fatigue analysis • Vibration analysis	NR467 Sec.15, [3.22]

3.2.2 Electric Motor in Pod

Table 3.12: Podded Propulsion - In-Pod Motor

#	Drawing/Document	Category	Content Requirements	Reference
45	In-Pod Motor Design	FA	• Motor type (permanent magnet, induction) • Rated power and speed • Voltage and frequency • Insulation system (marine environment) • Rotor and stator assembly • Bearing arrangement	NR467 Sec.15, [3.23]; IEC 60092-301
46	Motor Thermal Design	FA	• Heat generation calculations • Cooling system design • Temperature limits • Thermal monitoring • Insulation life assessment	NR467 Sec.15, [3.23]
47	Motor Cooling System	FA	• Cooling method (water-cooled, oil-cooled) • Heat exchanger design • Coolant circulation system • Pump specifications • Temperature monitoring	NR467 Sec.15, [3.24]
48	Motor Mounting & Support	FA	• Motor mounting arrangement in pod • Alignment provisions • Vibration isolation • Thermal expansion accommodation	NR467 Sec.15, [3.23]

3.2.3 Power Supply Through Strut

Table 3.13: Podded Propulsion - Power Supply

#	Drawing/Document	Category	Content Requirements	Reference
49	Power Cable Routing	FA	• Cable route through strut • Cable support and protection • Cable entry into pod • Sealing arrangements • Cable sizing calculations	NR467 Sec.15, [3.25]; IEC 60092-352
Continued on next page				

Table 3.13 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
50	Slip Ring or Rotary Transformer	FA	• Type and manufacturer • Current and voltage rating • Cooling provisions • Maintenance access • Reliability data	NR467 Sec.15, [3.25]
51	Power Distribution in Pod	FA	• Internal switchgear/junction boxes • Protection devices • Monitoring systems • Watertight/waterproof rating	NR467 Sec.15, [3.25]

3.2.4 Propeller Direct Drive

Table 3.14: Podded Propulsion - Direct Drive

#	Drawing/Document	Category	Content Requirements	Reference
52	Direct Drive Arrangement	FA	• Motor shaft to propeller connection • Coupling or direct mounting • Bearing arrangement • Seal system • Alignment procedure	NR467 Sec.15, [3.26]
53	Shaft Seal System	FA	• Seal type and material • Seal arrangement • Pressure rating • Leakage monitoring • Emergency sealing provisions	NR467 Sec.15, [3.26]

3.2.5 Pod-Specific Testing

Table 3.15: Podded Propulsion - Testing Requirements

#	Drawing/Document	Category	Content Requirements	Reference
54	Pressure Testing Procedure	FA	• Test pressure and duration • Test setup • Acceptance criteria • Leakage limits	NR467 Sec.15, [3.27]
Continued on next page				

Table 3.15 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
55	Motor Insulation Testing	FA	• Insulation resistance tests • High voltage tests • Partial discharge tests • Test conditions and acceptance criteria	IEC 60092-301

Chapter 4

Water-Jet Propulsion Systems

4.1 General Arrangement

Table 4.1: Water-Jets - General Arrangement

#	Drawing/Document	Category	Content Requirements	Reference
1	Water-Jet General Arrangement	FA	• Installation location on vessel • Inlet and outlet positions • Nozzle orientation • Access for maintenance • Clearances	NR467 Sec.15, [4.1]
2	Hull Integration Drawing	FA	• Inlet duct design • Hull penetration details • Structural integration • Hydrodynamic considerations • Reinforcement arrangements	NR467 Sec.15, [4.2]; Part B, Ch.5

4.2 Water-Jet Unit Components

Table 4.2: Water-Jets - Unit Components

#	Drawing/Document	Category	Content Requirements	Reference
3	Water-Jet Unit Assembly	FA	• Complete unit cross-section • Pump assembly • Inlet duct • Nozzle and steering/reversing mechanism • Material specifications	NR467 Sec.15, [4.3]
Continued on next page				

Table 4.2 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
4	Impeller Design	FA	• Impeller geometry • Number of blades • Material specification • Blade profile • Hub design	NR467 Sec.15, [4.4]
5	Impeller Strength Calculations	FA	• Blade stress analysis • Hub stress analysis • Centrifugal forces • Hydrodynamic forces • Fatigue assessment • Cavitation analysis	NR467 Sec.15, [4.4]
6	Pump Shaft Design	FA	• Shaft dimensions and material • Bearing locations • Seal arrangements • Coupling details	NR467 Sec.15, [4.5]
7	Pump Shaft Calculations	FA	• Torsional strength • Bending stress • Combined stress analysis • Deflection • Critical speed • Fatigue assessment	NR467 Sec.15, [4.5]; Sec.7
8	Bearing Arrangement	FA	• Bearing types and locations • Bearing housing • Lubrication system • Seal design • Cooling provisions	NR467 Sec.15, [4.6]
9	Bearing Load Calculations	FA	• Radial and axial loads • Bearing life calculation • Lubrication requirements • Temperature analysis	NR467 Sec.15, [4.6]

4.3 Inlet Duct System

Table 4.3: Water-Jets - Inlet Duct

#	Drawing/Document	Category	Content Requirements	Reference
10	Inlet Duct Design	FA	• Duct geometry and dimensions • Material specification • Structural design • Hydrodynamic profile • Debris protection (grating/screen)	NR467 Sec.15, [4.7]
11	Inlet Duct Calculations	FA	• Structural strength analysis • Pressure loading • Flow analysis • Cavitation assessment	NR467 Sec.15, [4.7]
12	Hull Penetration & Reinforcement	FA	• Opening dimensions • Reinforcement design • Watertight integrity • Structural attachment	NR467 Sec.15, [4.7]; Part B, Ch.5

4.4 Steering and Reversing Mechanism

Table 4.4: Water-Jets - Steering & Reversing

#	Drawing/Document	Category	Content Requirements	Reference
13	Steering Nozzle Design	FA	• Nozzle geometry • Deflection range • Actuator arrangement • Structural design • Material specification	NR467 Sec.15, [4.8]
14	Reversing Bucket Design	FA	• Bucket geometry • Deployment mechanism • Actuator system • Structural strength • Material specification	NR467 Sec.15, [4.9]
15	Steering/Reversing Actuators	FA	• Hydraulic cylinder specifications • Operating pressure • Force requirements • Position feedback • Emergency provisions	NR467 Sec.15, [4.10]
Continued on next page				

Table 4.4 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
16	Steering/Reversing Calculations	FA	• Actuator force requirements • Structural strength of nozzle/bucket • Response time analysis • Hydraulic system sizing	NR467 Sec.15, [4.10]

4.5 Drive System

4.5.1 For Direct Drive from Main Engine

Table 4.5: Water-Jets - Direct Drive

#	Drawing/Document	Category	Content Requirements	Reference
17	Drive Shaft Arrangement	FA	• Shaft line from engine to water-jet • Bearing locations • Coupling arrangements • Alignment provisions	NR467 Sec.15, [4.11]; Sec.7
18	Drive Shaft Calculations	FA	• Torsional strength • Bending stress • Critical speed analysis • Alignment calculations • See Chapter 9 for full requirements	NR467 Sec.15, [4.11]; Sec.7

4.5.2 For Gearbox Drive

Table 4.6: Water-Jets - Gearbox Drive

#	Drawing/Document	Category	Content Requirements	Reference
19	Gearbox Assembly	FA	• Gear arrangement • Gear ratios • Casing design • Lubrication system • Mounting arrangement	NR467 Sec.15, [4.12]

Continued on next page

Table 4.6 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
20	Gear Calculations	FA	• Gear tooth strength • Contact stress • Bending stress • Lubrication analysis • Efficiency	NR467 Sec.15, [4.12]

4.6 Hydraulic System (for steering/reversing)

Table 4.7: Water-Jets - Hydraulic System

#	Drawing/Document	Category	Content Requirements	Reference
21	Hydraulic System Schematic	FA	• Complete hydraulic circuit • HPU specifications • Control valves • Piping arrangement • See Chapter 10 for detailed requirements	NR467 Sec.15, [4.13]; Ch.10

4.7 Control System

Table 4.8: Water-Jets - Control System

#	Drawing/Document	Category	Content Requirements	Reference
22	Control System Architecture	FA	• Control system topology • Steering control • Reversing control • Engine/pump speed control • Interface with ship systems	NR467 Sec.15, [4.14]; Part C, Ch.4
23	Bridge Control Console	FA	• Control panel layout • Joystick/lever arrangement • Display and indication • Alarm system • Emergency stop	NR467 Sec.15, [4.14]
24	Electrical Single-Line Diagram	FA	• Power supply • Protection devices • Monitoring circuits • Emergency power provisions	NR467 Sec.15, [4.14]; IEC 60092-504

4.8 Performance Calculations

Table 4.9: Water-Jets - Performance Calculations

#	Drawing/Document	Category	Content Requirements	Reference
25	Thrust and Performance Calculations	FA	• Thrust curves • Power absorption • Efficiency analysis • Speed predictions • Bollard pull	NR467 Sec.15, [4.15]
26	Cavitation Analysis	FA	• Cavitation inception speed • Cavitation patterns • Erosion risk assessment • Mitigation measures	NR467 Sec.15, [4.15]
27	Vibration Analysis	FA	• Natural frequency calculations • Forced vibration analysis • Resonance avoidance • Foundation design	NR467 Sec.15, [4.16]
28	Noise Analysis	FA	• Airborne noise prediction • Structure-borne noise • Compliance with regulations • Noise reduction measures	NR467 Sec.15, [4.16]

Chapter 5

Voith-Schneider (Cycloidal) Propulsion Systems

5.1 Description & Classification Basis

The Voith-Schneider Propeller (VSP), or cycloidal propeller, is a vertical-axis propulsor in which a set of vertical blades projects below a rotating casing (rotor). Each blade oscillates about its own vertical axis through a kinematic control gear linked to a movable control (steering) centre. By displacing the control centre, the unit produces thrust of *any magnitude in any horizontal direction* at constant rotor speed. A VSP therefore combines **propulsion and steering in a single unit**; the steering function makes **NR467 Part C, Ch 1, Sec 14 (Steering Gear) and SOLAS II-1 Reg. 29 requirements applicable** (see Chapter 8). Typical applications: Voith Water Tractors, double-ended ferries, buoy tenders, mine-countermeasure vessels.

VSP units are assessed under **NR467 Pt C, Ch 1, Sec 15** for the mechanical thruster elements, **Sec 14** for the steering/control function, and **Sec 7** where the drive forms part of the propulsion shaft line.

5.2 VSP-Specific Structural & Mechanical Components

Table 5.1: Voith-Schneider Propeller — Mechanical & Structural Requirements

#	Drawing/Document	Category	Content Requirements	Reference
1	VSP Unit General Assembly	FA	• Complete unit cross-section (rotor casing, blades, gear) • Number of blades and blade circle diameter • Rotor speed and orbit geometry • Material list and lifting arrangement	NR467 Sec.15, [5.1]
Continued on next page				

Table 5.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
2	Blade (Wing) Design Drawing	FA	• Blade profile, chord, span • Blade shaft dimensions and material • Blade root / shaft connection • Surface finish and corrosion protection	NR467 Sec.15, [5.2]
3	Blade Shaft & Blade Strength Calculations	FA	• Hydrodynamic blade loads (thrust + side force) • Bending + torsion of blade shaft • Centrifugal loads at max rotor speed • Fatigue assessment (reversing loads)	NR467 Sec.15, [5.2]; Sec.7
4	Blade Bearing Arrangement	FA	• Upper/lower blade bearings, seals • Bearing load and L10 life • Lubrication path from oil system	NR467 Sec.15, [5.3]
5	Kinematic Control Gear (Steering Mechanism)	FA	• Control-centre / eccentric arrangement • Control rods, links, crank geometry • Servo actuator interface • Strength of linkage members and pins • Fail-safe / neutral-thrust behaviour	NR467 Sec.15, [5.4]; Sec.14
6	Rotor Casing & Main Bevel Gear	FA	• Rotor casing structure and thrust path • Input bevel gear (horizontal drive → vertical rotor) • Gear tooth calculations (ISO 6336) • Main thrust bearing design and life • Lubrication and oil monitoring	NR467 Sec.15, [5.5]
Continued on next page				

Table 5.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
7	Bottom Cover / Guard Plate Structure	FA	- Guard plate below blade circle - Structural strength (grounding/impact) - Attachment to unit and hull - Detachment / fail-safe considerations	NR467 Sec.15, [5.6]; Part B, Ch.5
8	Hull Seat, Foundation & Well Structure	FA	- Foundation ring and bolting - Local hull reinforcement / FEA - Watertight integrity of installation well - Load transfer (thrust, steering moment)	NR467 Sec.15, [5.6]; Part B, Ch.5
9	Seal System (Rotor & Blade Shafts)	FA	- Seal type, arrangement and material - Leakage monitoring / oil-in-water prevention - EAL fluid if CLEANSHIP (see Ch.13)	NR467 Sec.15, [5.7]

5.3 VSP Drive, Servo Control & Steering Function

Table 5.2: Voith-Schneider Propeller — Drive & Control

#	Drawing/Document	Category	Content Requirements	Reference
10	Prime Mover Interface	FA	- Diesel engine or electric motor input (see Ch.7) - Input coupling / clutch / cardan shaft - Torsional vibration calculation of the complete drive train	NR467 Sec.15; Sec.7
11	Servo / Hydraulic Control Unit	FA	- Control (steering) hydraulic schematic - Two independent power/servo systems where used for steering (redundancy) - Pressure ratings, relief, accumulators - See Chapter 10	NR467 Sec.14; Ch.10

Continued on next page

Table 5.2 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
12	Steering Control System & Bridge Console	FA	- Control transmitter (tiller/joystick) to control centre - Thrust magnitude & direction indication - Follow-up / non-follow-up control - Alarms, emergency stop, mode changeover	NR467 Sec.14; Part C, Ch.4
13	Steering Function Compliance Package	FA	- FMEA of steering function - Single-failure / duplication analysis - Response time, hard-over to hard-over - SOLAS II-1 Reg.29 demonstration (see Ch.8)	NR467 Sec.14; SOLAS II-1/29

Surveyor note (VSP): A VSP is simultaneously a propeller, a gear unit *and* a steering gear. Do not approve the mechanical package in isolation — confirm that the steering-function documentation of Chapter 8 (redundancy, control stations, alarms, response time, SOLAS compliance) has also been submitted. The blade guard/bottom plate and its hull attachment are frequently under-documented; require structural substantiation against grounding loads.

Chapter 6

Other Thruster Types (Rim-Driven, Pump-Jet, Gill/Jet, Steering Grid)

This chapter addresses less-common propulsor arrangements recognised by BV. Each follows the **general submissions of Chapter 1** plus the requirements of the *nearest analogous conventional type*, with the additional type-specific items below. Confirm the intended notation and service (propulsion, take-me-home, DP, steering) before fixing the package.

6.1 Rim-Driven Thrusters (Integrated Motor Propulsors)

Rim-driven / hubless thrusters integrate a permanent-magnet (or induction) motor whose rotor forms the propeller-blade tip ring inside the duct. There is no mechanical shaft line or reduction gear; excitation and speed are set by a frequency converter. Assessment shifts from gearing toward **electrical machine, converter and duct-bearing** substantiation.

Table 6.1: Rim-Driven Thruster — Type-Specific Requirements

#	Drawing/Document	Category	Content Requirements	Reference
1	Integrated Motor & Duct Assembly	FA	- Motor type (PM / induction), pole/winding data - Rotor rim / blade-tip ring construction - Duct structure and stator support - Cooling (seawater / freshwater path)	NR467 Sec.15; Pt C, Ch.2; IEC 60092-301
2	Frequency Converter / Drive Package	FA	- Converter rating and topology - Harmonic / power-quality analysis - Protection, cooling, EMC - See Chapter 7 (electric drive)	NR467 Pt C, Ch.2; IEC 60092-101
Continued on next page				

Table 6.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
3	Bearing & Seal Arrangement	FA	• Water-lubricated / magnetic bearing design • Bearing load and wear-life basis • Gap / air-gap control, seal design	NR467 Sec.15, [6.1]
4	Blade & Rim Strength Calculations	FA	• Blade + rim stress (hydro + magnetic + centrifugal) • Fatigue and corrosion allowance • Cavitation assessment	NR467 Sec.15, [6.1]; Sec.7

6.2 Pump-Jet & Ducted Rotor-Stator Propulsors

Pump-jet units (ducted rotor with stator vanes, often for low-signature or shallow-draught craft) are treated as a ducted propeller + shaft line. Submit the **duct/stator structure and strength, rotor blade design and strength, shaft line (Chapter 9), bearings, seals** and the relevant drive package. Where the unit also steers (deflector/vectoring), add the steering function package of Chapter 8.

6.3 Gill / Hydro-Jet Transverse Thrusters (Pump-Type)

Pump-type transverse thrusters draw water through a hull inlet and discharge through athwartship outlets, providing side thrust without an open tunnel. Submit as for a tunnel thruster (Chapter 2) but replace the tunnel structure items with: **inlet grating and duct, internal pump/impeller design and strength, discharge outlet and directional-valve arrangement, hull penetration and watertight integrity**, plus the pump drive package.

6.4 Steering Grid / Steering-Nozzle & Rudder-Propeller Variants

Fixed-nozzle (Kort-type) units with a steering grid or a steerable nozzle behave as combined propulsion + steering devices. Submit the **nozzle/grid structure and strength, propeller in nozzle, shaft line, steering actuator and control**, and the full steering-gear compliance package of Chapter 8 (SOLAS II-1 Reg.29 where the device is the ship's means of steering).

Surveyor note (other types): For any novel or hybrid propulsor, apply the *function-based* approach — decompose the unit into propeller/impeller, structure, shaft line, gear (if any), drive (electric/diesel/hydraulic), bearings/seals and control — and require the corresponding chapter's submissions for each function. Novel technology may additionally require an Approval-in-Principle (AiP) or risk-based/alternative-design assessment.

Chapter 7

Prime Mover Considerations — Diesel-Engine vs. Electric-Motor Driven Thrusters

7.1 Purpose

The preceding type chapters split the drive into *electric* or *hydraulic*. This chapter consolidates the **additional package elements driven by the choice of prime mover** so the surveyor can confirm the correct drive-train documentation is present. A thruster may be driven by:

- an **electric motor** (constant- or variable-speed, converter-fed), typical of diesel-electric ships, DP vessels, cruise ships and pods; or
- a **diesel engine** (direct/geared mechanical drive), typical of tugs, OSVs and workboats with inboard engines driving Z-drive azimuth or tunnel thrusters via shafting, clutches and gearboxes; or
- a **hydraulic motor** (covered per type chapter and Chapter 10), common on retractable and smaller units.

7.2 Electric-Motor-Driven Thrusters — Additional Submissions

Table 7.1: Electric-Motor Prime Mover — Additional Requirements

#	Drawing/Document	Category	Content Requirements	Reference
1	Propulsion/Drive Motor Data Sheet	FA	• Type (induction / PM / synchronous) • Rated & overload power, torque-speed curve • Voltage, frequency, insulation & IP class • Cooling method, temperature rise (IEC 60034)	NR467 Pt C, Ch.2; IEC 60092-301
Continued on next page				

Table 7.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
2	Frequency Converter (VFD) Specification & Arrangement	FA	• Converter topology and rating • Output torque ripple at thruster • Protection, redundancy, bypass • Cooling and heat load to space	NR467 Pt C, Ch.2
3	Harmonic & Power-Quality Analysis	FA	• THD at main switchboard (limits per rules) • Effect on generators/other consumers • Mitigation (multi-pulse, active front end, filters)	NR467 Pt C, Ch.2
4	Supply Transformer & Switchboard Interface	FA	• Transformer rating, vector group, cooling • Feeder protection and discrimination • Short-circuit & earth-fault co-ordination	NR467 Pt C, Ch.2; IEC 60092-201
5	Power Cable Sizing & Routing	FA	• Current rating, voltage drop, derating • Routing, support, bulkhead penetrations • Segregation (DP redundancy where relevant)	IEC 60092-352 / -352
6	Motor Protection, Monitoring & Cooling	FA	• Winding/bearing temperature monitoring • Overload, earth-fault, differential protection • Space heaters, forced cooling, condensation control	NR467 Pt C, Ch.2 / Ch.3
7	Torque-Ripple / Torsional Interaction Note	FA	• Converter harmonics vs. shaft-line torsionals • Barred-speed / avoidance ranges if any • Cross-reference shaft TVC (Chapter 9)	NR467 Sec.7
8	Integration with PMS / Black-out Recovery	FI	• Load-dependent start/stop, load shedding • Blackout and thruster restart sequence	NR467 Pt C, Ch.3

7.3 Diesel-Engine-Driven Thrusters — Additional Submissions

Where a thruster (typically a Z-drive azimuth on a tug/OSV, or a directly driven tunnel/CP unit) is driven by a diesel engine, the **engine and its auxiliary systems become part of the approvable package** under **NR467 Pt C, Ch 1, Sec 2 (Diesel Engines)** in addition to the thruster under Sec 15. A **torsional vibration calculation (TVC) of the complete engine-clutch-shafting-thruster system is mandatory.**

Table 7.2: Diesel-Engine Prime Mover — Additional Requirements

#	Drawing/Document	Category	Content Requirements	Reference
1	Diesel Engine Approval / Type Data	FA	• Engine general arrangement & rating (MCR) • Type Approval / unit certification status • Crankshaft & main running-gear data • Safety devices (overspeed, LO low-pressure shutdown)	NR467 Pt C, Ch.1, Sec.2
2	Torsional Vibration Calculation (TVC)	FA	• Complete engine-coupling-gear-thruster model • Barred/critical speed ranges • Stresses in shafts, coupling, gear at criticals • Clutch-in/out and misfiring conditions	NR467 Sec.2; Sec.7
3	Clutch & Flexible Coupling	FA	• Clutch type, torque & engagement control • Flexible coupling stiffness/damping data • Alignment and vibration decoupling	NR467 Sec.2; Sec.7
4	Engine Foundation & Chocking	FA	• Seating structure and holding-down bolts • Resilient mounts / chocking arrangement • Alignment provisions and thrust transmission	NR467 Sec.2; Part B, Ch.5
Continued on next page				

Table 7.2 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
5	Fuel Oil System	FA	• FO service/settling tanks, transfer, filtration • Piping, valves, quick-closing valves • Leakage containment, high-pressure line shielding	NR467 Pt C, Ch.1 (Piping)
6	Lubricating Oil System	FA	• LO pumps, cooler, filters, sump • Pressure/temperature monitoring & alarms	NR467 Pt C, Ch.1
7	Cooling Water System	FA	• Jacket & charge-air cooling circuits • Sea-water / central cooling, pumps, expansion	NR467 Pt C, Ch.1
8	Starting & Control Air / Starting System	FA	• Air receivers, compressors, capacity for starts • Or electric-start battery capacity	NR467 Pt C, Ch.1
9	Exhaust Gas System	FA	• Piping, expansion, lagging, silencer • Back-pressure, boundary insulation (fire) • SCR/EGR arrangement if fitted	NR467 Pt C, Ch.1; SOLAS II-2
10	Engine Control, Safety & Monitoring	FA	• Governor / speed control, over-speed trip • Alarms & safeguards, local/remote control • Integration with thruster & bridge controls	NR467 Pt C, Ch.1 / Ch.3
11	Emissions / NOx Documentation	FI	• EIAPP certificate & NOx Technical File • MARPOL Annex VI Tier compliance	MARPOL Annex VI
12	Engine-Room Ventilation & Air Supply	FI	• Combustion air and space ventilation • Heat balance / temperature rise	NR467 Pt C, Ch.1

Surveyor note (prime mover): The single most common gap for diesel-driven Z-drive tugs is a **missing or incomplete TVC for the whole train** (engine + clutch + cardan/shaft + azimuth

gears + propeller). For electric drives, the recurring gaps are the **harmonic/power-quality study** and **cable-sizing/segregation**. Hybrid PTI/PTO arrangements must document *every* driving path and the mode-changeover logic. Cross-reference the shaft-line torsional/alignment package in Chapter 9.

Chapter 8

Thrusters as Part of Steering Gear

8.1 Applicability

CRITICAL: When thrusters (azimuth, podded, or water-jets) are used as the PRIMARY or AUXILIARY steering system, they MUST comply with ALL steering gear requirements in addition to thruster requirements.

This applies to:

- Azimuth thrusters used for steering
- Podded propulsion units providing steering
- Water-jet systems providing steering
- Any thruster configuration that replaces or supplements rudder steering

8.2 Additional Steering Gear Requirements

All applicable thruster drawings from Chapters 2-4 apply, PLUS the following steering-specific submissions:

8.2.1 Steering System Design

Table 8.1: Steering Gear - System Design

#	Drawing/Document	Category	Content Requirements	Reference
1	Steering System General Arrangement	FA	• Complete steering system layout • Main and auxiliary steering provisions • Control stations • Power supply arrangements • Emergency steering provisions	NR467 Sec.14, [1]
Continued on next page				

Table 8.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
2	Steering Gear Capacity Calculations	FA	• Maximum steering torque • Time to move from 35° port to 35° starboard • Time to move from 35° to 30° on opposite side • Compliance with SOLAS requirements • Redundancy analysis	NR467 Sec.14, [2]; SOLAS Ch.II-1, Reg.29
3	Steering Control System	FA	• Control system architecture • Main control station (bridge) • Auxiliary control provisions • Emergency control • Autopilot integration • Manual override provisions	NR467 Sec.14, [3]

8.2.2 Redundancy & Reliability

Table 8.2: Steering Gear - Redundancy Requirements

#	Drawing/Document	Category	Content Requirements	Reference
4	Main and Auxiliary Steering Systems	FA	• Main steering arrangement • Auxiliary steering arrangement • Independence of systems • Changeover provisions • Simultaneous operation capability	NR467 Sec.14, [4]; SOLAS Ch.II-1, Reg.29
5	Failure Mode and Effects Analysis (FMEA)	FA	• All potential failure modes • Effects on steering capability • Single failure tolerance • Redundancy verification • Mitigation measures	NR467 Sec.14, [5]
6	Reliability Analysis	FA	• System reliability calculations • Component failure rates • Mean time between failures (MTBF) • Availability analysis • Compliance with steering gear standards	NR467 Sec.14, [5]

8.2.3 Power Supply

Table 8.3: Steering Gear - Power Supply

#	Drawing/Document	Category	Content Requirements	Reference
7	Steering Gear Power Supply	FA	• Main power supply arrangement • Emergency power supply • Independent power sources for main/auxiliary • Switchboard arrangements • Circuit protection	NR467 Sec.14, [6]; SOLAS Ch.II-1, Reg.29
8	Power Supply Calculations	FA	• Load analysis • Cable sizing • Protection device coordination • Voltage drop calculations • Short circuit analysis	NR467 Sec.14, [6]; IEC 60092-352

8.2.4 Control Stations

Table 8.4: Steering Gear - Control Stations

#	Drawing/Document	Category	Content Requirements	Reference
9	Bridge Control Console	FA	• Main steering control layout • Steering wheel or joystick • Rudder angle indicator (or thruster angle) • Rate of turn indicator • Alarm and monitoring displays • Autopilot controls	NR467 Sec.14, [7]
10	Emergency Steering Station	FA	• Emergency control location • Control equipment • Communication with bridge • Indication and monitoring • Access provisions	NR467 Sec.14, [8]; SOLAS Ch.II-1, Reg.29
11	Local Control Station	FA	• Local control panel (if applicable) • Control mode selection • Indication and monitoring • Interlock with other control stations	NR467 Sec.14, [9]

8.2.5 Alarms and Monitoring

Table 8.5: Steering Gear - Alarms & Monitoring

#	Drawing/Document	Category	Content Requirements	Reference
12	Alarm System Design	FA	• Power supply failure alarms • Control system failure alarms • Actuator failure alarms • Position deviation alarms • Alarm display on bridge	NR467 Sec.14, [10]
13	Monitoring System	FA	• Position monitoring • Rate monitoring • Torque/thrust monitoring • Temperature monitoring • Data logging	NR467 Sec.14, [10]

8.2.6 Hydraulic Systems (if applicable)

Table 8.6: Steering Gear - Hydraulic System

#	Drawing/Document	Category	Content Requirements	Reference
14	Steering Gear Hydraulic System	FA	• Main hydraulic system • Auxiliary hydraulic system • Independence of systems • Accumulator provisions • See Chapter 10 for detailed requirements	NR467 Sec.14, [11]; Ch.10

8.2.7 Testing & Commissioning

Table 8.7: Steering Gear - Testing Requirements

#	Drawing/Document	Category	Content Requirements	Reference
15	Steering Gear Testing Procedures	FA	• Factory acceptance tests • Installation tests • Sea trial procedures • Performance verification • Redundancy testing • Emergency steering tests	NR467 Sec.14, [12]; SOLAS Ch.II-1, Reg.29
16	Steering Gear Test Records	FI	• FAT reports • Installation test reports • Sea trial results • Performance verification • As-built documentation	NR467 Sec.14, [12]

8.2.8 Operating Manuals

Table 8.8: Steering Gear - Operating Manuals

#	Drawing/Document	Category	Content Requirements	Reference
17	Steering Gear Operating Manual	FI	• Normal operating procedures • Changeover procedures (main/auxiliary) • Emergency procedures • Troubleshooting guide • Safety precautions	NR467 Sec.14, [13]
18	Maintenance Manual	FI	• Maintenance schedule • Inspection procedures • Lubrication requirements • Spare parts list • Overhaul procedures	NR467 Sec.14, [13]

8.2.9 SOLAS Compliance Documentation

Table 8.9: Steering Gear - SOLAS Compliance

#	Drawing/Document	Category	Content Requirements	Reference
19	SOLAS Compliance Statement	FA	• Demonstration of compliance with SOLAS Ch.II-1, Reg.29 • Steering gear capacity verification • Redundancy verification • Emergency steering capability • Testing and commissioning compliance	NR467 Sec.14, [14]; SOLAS Ch.II-1, Reg.29

Chapter 9

Thrusters as Part of Main Shafting

9.1 Applicability

When thruster shafts (propeller shafts, intermediate shafts, vertical shafts in azimuth thrusters, or water-jet drive shafts) are considered part of the main propulsion shafting system, they **MUST** comply with shafting requirements in NR467 Section 7.

This typically applies to:

- Azimuth thruster vertical and horizontal shafts
- Podded propulsion shafts
- Water-jet drive shafts
- Tunnel thruster propeller shafts (for high-power units)
- Any shaft transmitting significant propulsion power

9.2 Overlap with Thruster Requirements

NOTE: Many shaft-related drawings and calculations are already covered in Chapters 2-4. This chapter identifies **ADDITIONAL** requirements or **ENHANCED** detail levels required when shafts are classified as "main shafting."

9.2.1 Shaft Design Drawings

Table 9.1: Main Shafting - Design Drawings

#	Drawing/Document	Category	Content Requirements	Reference
1	Shaft Line General Arrangement	FA	• Complete shaft line layout • All shaft sections identified • Bearing locations • Coupling locations • Seal locations • Coordinate system	NR467 Sec.7, [1]
2	Shaft Detail Drawings	FA	• Dimensional drawings of each shaft section • Diameter changes and transitions • Keyway details • Thread details • Surface finish requirements • Material specifications • Heat treatment requirements	NR467 Sec.7, [2]
3	Shaft End Connections	FA	• Flange designs • Coupling designs • Bolt specifications • Fit tolerances • Assembly procedures	NR467 Sec.7, [3]

9.2.2 Shaft Strength Calculations

Table 9.2: Main Shafting - Strength Calculations

#	Drawing/Document	Category	Content Requirements	Reference
4	Shaft Diameter Calculations	FA	• Minimum diameter calculations per BV formula • Torsional strength verification • Bending strength verification • Combined stress analysis • Safety factors applied	NR467 Sec.7, [4]
5	Shaft Stress Analysis	FA	• Detailed stress calculations at critical sections • Stress concentration factors • Keyway effects • Thread effects • FEA results (if applicable)	NR467 Sec.7, [4]
Continued on next page				

Table 9.2 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
6	Fatigue Analysis	FA	• Fatigue life calculations • S-N curves for materials • Stress range analysis • Cumulative damage assessment • Compliance with fatigue criteria	NR467 Sec.7, [5]
7	Deflection Calculations	FA	• Shaft deflection under load • Bearing alignment effects • Seal clearance verification • Acceptable deflection limits	NR467 Sec.7, [6]

9.2.3 Critical Speed Analysis

Table 9.3: Main Shafting - Critical Speed Analysis

#	Drawing/Document	Category	Content Requirements	Reference
8	Torsional Vibration Analysis	FA	• Natural frequencies calculation • Forced vibration analysis • Resonance identification • Barred speed ranges • Damping analysis • Compliance with acceptable vibration levels	NR467 Sec.7, [7]
9	Lateral Vibration Analysis	FA	• Critical speed calculations • Campbell diagram • Operating speed verification • Margin to critical speeds • Bearing stiffness effects	NR467 Sec.7, [7]
10	Whirling Analysis	FA	• Whirling speed calculations • Forward and backward whirl • Operating range verification • Stability analysis	NR467 Sec.7, [7]

9.2.4 Bearing Design

Table 9.4: Main Shafting - Bearing Design

#	Drawing/Document	Category	Content Requirements	Reference
11	Bearing Arrangement Drawing	FA	• Bearing types and locations • Bearing housing design • Lubrication system • Seal arrangements • Cooling provisions • Mounting details	NR467 Sec.7, [8]
12	Bearing Load Calculations	FA	• Radial loads • Axial loads (thrust bearings) • Moment loads • Load distribution among bearings • Dynamic load factors	NR467 Sec.7, [8]
13	Bearing Life Calculations	FA	• L10 life calculations • Operating conditions • Load and speed effects • Lubrication effects • Minimum acceptable life	NR467 Sec.7, [8]
14	Bearing Lubrication System	FA	• Lubrication method (oil bath, forced circulation, grease) • Oil type and properties • Oil flow rate (forced systems) • Cooling arrangements • Filtration system • Oil level and temperature monitoring	NR467 Sec.7, [9]

9.2.5 Couplings

Table 9.5: Main Shafting - Couplings

#	Drawing/Document	Category	Content Requirements	Reference
15	Coupling Design Drawing	FA	• Coupling type (rigid, flexible) • Dimensions and material • Bolt specifications • Fit tolerances • Assembly procedure	NR467 Sec.7, [10]
Continued on next page				

Table 9.5 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
16	Coupling Strength Calculations	FA	• Torque capacity • Bolt strength verification • Flange strength • Fit stress analysis • Fatigue assessment	NR467 Sec.7, [10]
17	Flexible Coupling Characteristics	FA	• Torsional stiffness • Damping properties • Misalignment capacity • Effect on torsional vibration	NR467 Sec.7, [10]

9.2.6 Seals

Table 9.6: Main Shafting - Seals

#	Drawing/Document	Category	Content Requirements	Reference
18	Seal System Design	FA	• Seal type and material • Seal arrangement • Pressure rating • Leakage monitoring provisions • Emergency sealing (if applicable)	NR467 Sec.7, [11]
19	Seal Performance Data	FA	• Operating pressure and temperature • Shaft speed limitations • Expected leakage rates • Service life • Maintenance requirements	NR467 Sec.7, [11]

9.2.7 Alignment

Table 9.7: Main Shafting - Alignment

#	Drawing/Document	Category	Content Requirements	Reference
20	Shaft Alignment Calculations	FA	• Alignment procedure • Bearing reactions • Shaft sag calculations • Thermal growth considerations • Acceptable alignment tolerances	NR467 Sec.7, [12]
21	Alignment Procedure	FI	• Step-by-step alignment procedure • Measurement methods • Adjustment provisions • Verification methods • Documentation requirements	NR467 Sec.7, [12]

9.2.8 Material Specifications

Table 9.8: Main Shafting - Material Specifications

#	Drawing/Document	Category	Content Requirements	Reference
22	Shaft Material Specifications	FA	• Material grades (steel, stainless steel, etc.) • Mechanical properties • Heat treatment requirements • Surface treatment (if applicable) • Corrosion protection • Compliance with BV approved materials	NR467 Sec.7, [13]; Part B, Ch.3
23	Material Certificates	FA	• Material test certificates (during construction) • Chemical composition • Mechanical properties • Heat treatment records • Traceability	NR467 Part B, Ch.3

9.2.9 Non-Destructive Testing (NDT)

Table 9.9: Main Shafting - NDT Requirements

#	Drawing/Document	Category	Content Requirements	Reference
24	NDT Plan	FA	• NDT methods (UT, MT, PT, RT) • Extent of testing • Acceptance criteria • Inspector qualifications • Testing stages	NR467 Sec.7, [14]; Part B, Ch.4
25	NDT Reports	FI	• NDT test reports (during construction) • Test results • Defect identification and disposition • Inspector certification	NR467 Part B, Ch.4

9.2.10 Testing & Commissioning

Table 9.10: Main Shafting - Testing & Commissioning

#	Drawing/Document	Category	Content Requirements	Reference
26	Shaft Testing Procedures	FA	• Dimensional verification • Material testing • NDT • Balance testing (if applicable) • Assembly testing • Acceptance criteria	NR467 Sec.7, [15]
27	Vibration Monitoring Plan	FA	• Vibration measurement locations • Measurement methods • Acceptance criteria • Monitoring during sea trials • Long-term monitoring provisions	NR467 Sec.7, [16]
28	Test Reports	FI	• Factory test reports • Installation test reports • Sea trial vibration measurements • Alignment verification • As-built documentation	NR467 Sec.7, [15]

9.3 MON-SHAFT & Shaft-Line Condition-Monitoring Notations

Where the thruster forms part of the propulsion shaft line (azimuth, podded, water-jet or high-power tunnel units with oil-lubricated stern-tube/lower-unit bearings), the owner may request the **MON-SHAFT** additional class notation. MON-SHAFT allows the classical periodic *tailshaft withdrawal / complete shaft survey* to be replaced by a survey regime based on **continuous monitoring and condition assessment** of the oil-lubricated shaft/bearing/seal arrangement. It therefore *adds documentation* to the shaft-line package and interacts directly with the thruster's lower-unit bearing, seal and oil systems.

Table 9.11: MON-SHAFT — Additional Shaft-Line Monitoring Submissions

#	Drawing/Document	Category	Content Requirements	Reference
1	Oil-Lubricated Bearing & Seal Arrangement	FA	• Approved stern-tube / lower-unit oil-lubricated bearing & seal design • Wear-down measurement provisions • Compatibility with monitoring notation	NR467 Pt E (MON-SHAFT) Sec.7;
2	Lube-Oil Monitoring & Analysis Programme	FA	• Oil temperature (and pressure where applicable) monitoring • Periodic oil-analysis programme (contamination, wear metals, water) • Sampling points and acceptance/alert criteria	NR467 Pt E (MON-SHAFT)
3	Bearing Wear-down / Sensor Instrumentation	FA	• Bearing temperature sensors and locations • Wear-down/liner-wear measurement method & trending • Alarm set-points and data logging	NR467 Pt E; Pt C, Ch.3
4	Survey Arrangement & Data-Management Plan	FI	• Monitoring-based survey scheme replacing shaft withdrawal • Record keeping, trend review, thresholds for action • Interface with planned maintenance / class survey	NR467 Pt A (surveys); Pt E

Surveyor note (MON-SHAFT): MON-SHAFT is only compatible with **oil-lubricated** shaft/bearing arrangements of an approved type. For azimuth and podded units the “shaft line” extends into the lower gear/pod; confirm the seal, bearing and oil-monitoring documentation of the thruster lower unit (Chapters 3) is consistent with the MON-SHAFT scheme, and that the

oil-analysis and wear-down-trending programme, sensors and acceptance criteria are all submitted. Related shaft-line notations (e.g. oil-lubricated stern-tube monitoring / **TIGHT**-type arrangements) follow the same principle — verify the exact notation and its rule article in the current NR467 Part E.

Chapter 10

Hydraulic Systems & Pitch Control Mechanisms

10.1 Applicability

Hydraulic systems are used in thrusters for:

- Hydraulic motor drive (alternative to electric motor)
- Retractable thruster lifting/lowering mechanism
- Controllable pitch propeller pitch control
- Azimuth slewing drive (if hydraulic)
- Water-jet steering and reversing actuation
- Voith-Schneider control (steering) servo system

Rule basis: Thruster hydraulic systems are assessed under **NR467 Pt C, Ch 1** — the thruster/water-jet requirements of Sec. 15, the **pipng-system rules** (design pressure, materials, testing, relief), and, where the hydraulics actuate a *steering* function, the more stringent **steering-gear requirements of Sec. 14** (duplication, single-failure, power supply, response time). Recognised standard **ISO 4413** applies to general hydraulic-system design. Steering-critical hydraulics attract the redundancy and control provisions of Chapter 8; pitch-control hydraulics must define the *fail-safe* pitch position.

10.2 Hydraulic Power Unit (HPU)

Table 10.1: Hydraulic Systems - HPU

#	Drawing/Document	Category	Content Requirements	Reference
1	HPU General Arrangement	FA	• Complete HPU layout • Pump arrangement • Motor/drive arrangement • Reservoir design • Valve manifold • Accumulator location • Filtration system • Cooling system • Mounting arrangement	NR467 Sec.15
2	Hydraulic Pump Specification	FA	• Pump type (gear, piston, vane) • Displacement • Rated pressure and flow • Drive motor specifications • Efficiency curves • Manufacturer and model	NR467 Sec.15
3	Hydraulic Reservoir Design	FA	• Reservoir capacity • Material and construction • Baffle arrangement • Oil level indication • Breather and filler • Drain provisions • Heating elements (if applicable)	NR467 Sec.15
4	HPU Calculations	FA	• Flow requirements • Pressure requirements • Pump sizing verification • Reservoir sizing • Heat generation and cooling capacity • Accumulator sizing (if applicable)	NR467 Sec.15

10.3 Hydraulic Circuit Design

Table 10.2: Hydraulic Systems - Circuit Design

#	Drawing/Document	Category	Content Requirements	Reference
5	Hydraulic System Schematic	FA	• Complete hydraulic circuit • All components identified with symbols • Pressure ratings • Flow ratings • Control logic • Safety devices • Monitoring points	NR467 Sec.15
6	Piping and Instrumentation Diagram (P&ID)	FA	• Detailed piping layout • Pipe sizes and materials • Valve locations and specifications • Instrument locations • Pressure and temperature monitoring • Drain and vent points	NR467 Sec.15
7	Hydraulic Piping Arrangement	FA	• 3D piping layout (or isometric) • Pipe routing • Pipe supports • Flexibility analysis • Penetrations through bulk-heads • Accessibility for maintenance	NR467 Sec.15

10.4 Hydraulic Components

Table 10.3: Hydraulic Systems - Components

#	Drawing/Document	Category	Content Requirements	Reference
8	Hydraulic Motor Specification	FA	• Motor type and displacement • Rated pressure and speed • Torque and power curves • Efficiency • Mounting details • Manufacturer and model	NR467 Sec.15
Continued on next page				

Table 10.3 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
9	Hydraulic Cylinder Specification	FA	• Cylinder bore and stroke • Operating pressure • Rod diameter and material • Seal specifications • Mounting arrangement • Position sensors • Manufacturer and model	NR467 Sec.15
10	Control Valve Specifications	FA	• Valve types (directional, pressure, flow) • Valve ratings • Actuation method (solenoid, manual, pilot) • Response time • Manufacturer and model	NR467 Sec.15
11	Pressure Relief Valve	FA	• Set pressure • Flow capacity • Type (direct-acting, pilot-operated) • Mounting location • Manufacturer and model	NR467 Sec.15
12	Accumulator Specification	FA	• Accumulator type (bladder, piston, diaphragm) • Volume • Pre-charge pressure • Operating pressure range • Gas type (nitrogen) • Mounting arrangement • Safety provisions	NR467 Sec.15
13	Accumulator Sizing Calculations	FA	• Volume requirements • Pre-charge pressure calculation • Energy storage capacity • Response time analysis	NR467 Sec.15

10.5 Filtration System

Table 10.4: Hydraulic Systems - Filtration

#	Drawing/Document	Category	Content Requirements	Reference
14	Filtration System Design	FA	• Filter types and locations • Filtration rating (micron) • Flow capacity • Pressure drop • Filter change indicators • Bypass provisions	NR467 Sec.15
15	Filter Specifications	FA	• Filter element type • Filtration rating • Collapse pressure • Manufacturer and model • Replacement schedule	NR467 Sec.15

10.6 Cooling System

Table 10.5: Hydraulic Systems - Cooling

#	Drawing/Document	Category	Content Requirements	Reference
16	Hydraulic Oil Cooling System	FA	• Cooling method (air, water) • Heat exchanger specifications • Cooling capacity • Temperature control • Monitoring provisions	NR467 Sec.15
17	Thermal Analysis	FA	• Heat generation calculations • Heat dissipation calculations • Temperature rise predictions • Cooling capacity verification • Operating temperature range	NR467 Sec.15

10.7 Hydraulic Fluid

Table 10.6: Hydraulic Systems - Fluid Specification

#	Drawing/Document	Category	Content Requirements	Reference
18	Hydraulic Fluid Specification	FA	- Fluid type (mineral oil, synthetic, biodegradable) - Viscosity grade - Operating temperature range - Fire resistance properties (if applicable) - Compatibility with system materials - Approved manufacturer and grade	NR467 Sec.15

10.8 Piping Design

Table 10.7: Hydraulic Systems - Piping

#	Drawing/Document	Category	Content Requirements	Reference
19	Pipe Sizing Calculations	FA	- Flow velocity calculations - Pressure drop calculations - Pipe diameter selection - Compliance with velocity limits	NR467 Sec.15
20	Pipe Material Specifications	FA	- Pipe material (steel, stainless steel, copper-nickel) - Wall thickness - Pressure rating - Corrosion protection - Compliance with BV approved materials	NR467 Sec.15; Part B, Ch.3
21	Pipe Support Design	FA	- Support locations and types - Support spacing - Vibration isolation - Thermal expansion accommodation - Load calculations	NR467 Sec.15
22	Piping Stress Analysis	FA	- Pressure stress - Thermal stress - Vibration analysis - Support reaction forces - Compliance with stress limits	NR467 Sec.15

10.9 Hose Assemblies

Table 10.8: Hydraulic Systems - Hoses

#	Drawing/Document	Category	Content Requirements	Reference
23	Hydraulic Hose Specifications	FA	• Hose type and construction • Pressure rating • Temperature rating • End fittings • Length and routing • Fire resistance (if required) • Manufacturer and model	NR467 Sec.15
24	Hose Installation Drawing	FA	• Hose routing • Bend radius verification • Support and protection • Accessibility for inspection/replacement	NR467 Sec.15

10.10 Safety Devices

Table 10.9: Hydraulic Systems - Safety Devices

#	Drawing/Document	Category	Content Requirements	Reference
25	Pressure Relief System	FA	• Relief valve locations • Set pressures • Discharge routing • Capacity verification	NR467 Sec.15
26	Emergency Shutdown System	FA	• Emergency stop provisions • Valve actuation • System depressurization • Safe state definition	NR467 Sec.15
27	Leak Detection System	FA	• Leak detection method • Alarm provisions • Automatic shutdown (if required)	NR467 Sec.15

10.11 Control System

Table 10.10: Hydraulic Systems - Control

#	Drawing/Document	Category	Content Requirements	Reference
28	Hydraulic Control System	FA	• Control architecture • Manual/automatic control modes • Valve actuation signals • Feedback systems • Safety interlocks	NR467 Sec.15; Part C, Ch.4
29	Control Panel Layout	FA	• Panel arrangement • Control devices • Indication and monitoring • Alarm displays • Emergency stop	NR467 Sec.15

10.12 Monitoring & Instrumentation

Table 10.11: Hydraulic Systems - Monitoring

#	Drawing/Document	Category	Content Requirements	Reference
30	Instrumentation List	FA	• Pressure gauges/transmitters • Temperature sensors • Flow meters (if applicable) • Level indicators • Position sensors • Filter condition indicators • Specifications for each instrument	NR467 Sec.15
31	Alarm and Monitoring System	FA	• Parameters monitored • Alarm setpoints • Alarm display location • Data logging (if applicable)	NR467 Sec.15

10.13 Controllable Pitch Mechanism (CP Propellers)

Table 10.12: Hydraulic Systems - CP Mechanism

#	Drawing/Document	Category	Content Requirements	Reference
32	CP Mechanism Assembly	FA	• Hub internal mechanism • Pitch control rod/linkage • Hydraulic cylinder (in hub or external) • Blade retention system • Bearing arrangement • Seal design	NR467 Sec.15, [3.4]
33	CP Mechanism Calculations	FA	• Pitch control forces • Hydraulic cylinder sizing • Linkage strength • Blade retention strength • Seal pressure rating	NR467 Sec.15, [3.4]
34	Pitch Control Hydraulic System	FA	• Hydraulic supply to hub • Rotary joint/slip ring design • Control valve system • Pitch feedback system • Emergency pitch setting	NR467 Sec.15, [3.4]
35	Pitch Feedback System	FA	• Position sensor type and location • Signal transmission (rotary joint) • Accuracy and resolution • Redundancy (if required)	NR467 Sec.15, [3.4]

10.14 Testing & Commissioning

Table 10.13: Hydraulic Systems - Testing

#	Drawing/Document	Category	Content Requirements	Reference
36	Hydraulic System Test Procedures	FA	• Pressure testing • Functional testing • Leak testing • Performance verification • Safety device testing • Acceptance criteria	NR467 Sec.15
Continued on next page				

Table 10.13 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
37	Hydraulic System Test Reports	FI	• Pressure test results • Functional test results • Leak test results • Performance data • As-built documentation	NR467 Sec.15

10.15 Operating & Maintenance Manuals

Table 10.14: Hydraulic Systems - Manuals

#	Drawing/Document	Category	Content Requirements	Reference
38	Hydraulic System Operating Manual	FI	• System description • Operating procedures • Normal operation • Emergency procedures • Troubleshooting guide • Safety precautions	NR467 Sec.15
39	Hydraulic System Maintenance Manual	FI	• Maintenance schedule • Inspection procedures • Fluid sampling and analysis • Filter replacement • Component overhaul • Spare parts list	NR467 Sec.15

Chapter 11

Dynamic Positioning (DP) Thrusters - Additional Requirements

11.1 Applicability

Thrusters that are part of a Dynamic Positioning (DP) system must comply with ALL applicable requirements from Chapters 2-10, PLUS the additional DP-specific requirements in this chapter.

DP systems are classified into three classes:

- **DP-1:** Basic DP capability, no redundancy required
- **DP-2:** Redundant systems, single failure tolerance
- **DP-3:** Enhanced redundancy with fire/flood separation

The DP-specific submissions below are *in addition to* the full type package for each thruster used in the DP system (structure, propeller, shaft, gear, drive, control). They focus on redundancy, power segregation, control and failure analysis, and are assessed principally under **NR467 Part F** (Additional Class Notation **DYNAPOS**).

Key DP-Specific Documents Required (FA):

1. DP System General Arrangement
2. Thruster Configuration Drawing
3. DP Capability Plot
4. FMEA Documentation (comprehensive)
5. Redundancy Concept (DP-2/DP-3)
6. Power Supply Segregation
7. Fire Zone Arrangement (DP-3)
8. Watertight Subdivision (DP-3)
9. DP Control System Architecture
10. Thruster Allocation Logic

11. Position Reference System Configuration
12. Environmental Sensor Configuration
13. Power Management System (PMS) Configuration
14. UPS Configuration
15. DP FMEA Proving Trials Plan
16. DP Annual Trials Plan

Key DP-Specific Documents Required (FI):

1. DP Operations Manual
2. DP Maintenance Manual
3. DP Trials Reports
4. DP Training Requirements

11.2 Reference

All DP (DYNAPOS) requirements per **NR467 Part F (Additional Class Notations)**; see also IMO MSC.1/Circ.1580 and IMCA guidance.

Chapter 12

Ice Class & Cold-Climate (Winterisation) Requirements

12.1 Applicability

When a vessel carries a BV ice-class or polar notation, thrusters and their drive trains must be strengthened and winterised in addition to all base requirements of the preceding chapters. Two families apply:

- **Baltic / Finnish-Swedish Ice Classes** — notations **ICE CLASS IA SUPER, IA, IB, IC** (and **ID**), based on the Finnish-Swedish Ice Class Rules (FSICR / TRAFICOM), adopted in **NR467 Part E**. Intended for first-year Baltic-type ice with icebreaker assistance.
- **Polar Classes** — notations **POLAR CLASS PC1–PC7** (IACS Polar Class / IMO Polar Code), addressed in **NR467 Part E** and Rule Note **NR527**. Machinery strengthening follows **IACS UR I3**.

Cold-climate service without ice loads is covered by winterisation notations such as **COLD** (e.g. **COLD(Ht_{DH} , Et_{DE})**), addressing design ambient temperatures rather than ice impact.

Key principle: ice class primarily drives *ice-load strengthening* of the propeller, shaft line, gears and thruster body, plus *winterisation* of exposed and seawater systems. The surveyor overlays these on the type package.

12.2 Ice-Strengthening Submissions

Table 12.1: Ice Class — Additional Thruster Requirements

#	Drawing/Document	Category	Content Requirements	Reference
1	Ice Class Notation Basis & Design Conditions	FA	- Declared notation (IA Super/IA/... or PC1–PC7) - Design ice thickness / ice-load basis - Applicable rule edition and lower design temperature	NR467 Part F; NR527
2	Propeller Ice-Load Strength Calculation	FA	- Ice interaction loads (milling, impact) on blades - Blade root and blade tip strength vs. ice bending - Blade material and thickness increase - Open vs. ducted / nozzle ice loads	NR467 Part E; IACS UR I3
3	Shaft Line & Ice Torque Verification	FA	- Maximum ice-induced torque and thrust - Propeller shaft, intermediate shaft, couplings - Overload/peak-torque capacity of gears - Blade-loss / one-blade-milling scenarios	NR467 Part E; Sec.7; IACS UR I3
4	Gear & Azimuth/Nozzle Ice-Load Substantiation	FA	- Bevel/reduction gears vs. ice peak torque - Azimuth slewing bearing/gear vs. ice-block impact on lower unit - Nozzle/steering-grid ice-impact strength	NR467 Part E; Sec.15
5	Thruster Body / Lower Unit Ice Protection	FA	- Lower gearbox/pod shape vs. ice interaction - Ice knife / deflector where required - Local structural strengthening	NR467 Part E
6	Tunnel / Inlet Ice & Grid Arrangement	FA	- Tunnel thruster grid ice/debris protection - De-icing / anti-blocking provisions - Ice-load on grid bars	NR467 Part E; Sec.15
Continued on next page				

Table 12.1 – continued from previous page

#	Drawing/Document	Category	Content Requirements	Reference
7	Winterisation of Systems (Hydraulic, Cooling, Seals)	FA	• Low-temperature grades of oils/greases/seals • Heating/insulation of exposed hydraulics & sensors • Sea-chest/cooling anti-icing (recirculation) • Materials for low-temperature toughness (Charpy)	NR467 Part E (COLD); Part B, Ch.3
8	Materials Low-Temperature Certification	FA	• Impact testing at design temperature • Grade selection for exposed & load-bearing parts	NR467 Part B, Ch.3; Part E
9	Retraction/Deployment in Ice (if retractable)	FI	• Operating limits and procedures in ice • Protection of opening/seals from ice ingress	NR467 Part E

Surveyor note (ice): The governing case for ice-classed propulsion is usually the **ice peak torque / blade-milling load** propagating through propeller → shaft → gear → prime mover, *not* the open-water rating. Verify the ice-load calculation explicitly and check that it is carried consistently into the shaft (Chapter 9) and gear strength checks. For azimuth/podded units in ice, confirm lower-unit and slewing-gear substantiation against ice-block impact — a frequent omission. Match the rule edition to the declared notation.

Chapter 13

Additional BV Class Notations Affecting Thruster Packages

13.1 Purpose

Beyond ice class, several BV **additional class notations** and **service notations** impose extra requirements on the thruster package. This chapter summarises the ones most often encountered so the surveyor can confirm the client has submitted the corresponding documents. Requirements here *add to* the type package; they do not replace it.

13.2 Notation Impact Matrix

Table 13.1: Additional Notations — Impact on Thruster Submissions

Notation (family)	Concern	Additional thruster submissions	Reference
DYNAPOS (AM / AT / AM-AT / AM-AT R / AM-AT RS / SAM); DP-1/2/3	Dynamic positioning	Full DP package — see Chapter 11: FMEA, redundancy, power segregation, capability plot, thruster allocation, proving trials.	NR467 Pt F, Ch.11 (DYNAPOS)
AUT-UMS, AUT-CCS, AUT-PORT	Automated / unattended machinery	Extended alarm & monitoring of thruster (bearing temps, oil, vibration), remote & safe control, fail-safe on power/control loss, integration with alarm system.	NR467 Pt C, Ch.3; Pt F, Ch.3 (AUT)
COMF-NOISE / COMF-VIB (Comfort)	Noise & vibration on board	Structure-borne & airborne noise prediction, vibration levels at thruster excitation (blade-rate), resilient mounting, cavitation-noise control, source data.	NR467 Pt F, Ch.6 (COMF)
Continued on next page			

Table 13.1 – continued from previous page

Notation (family)	Concern	Additional thruster submissions	Reference
CLEANSHIP / environmental	Pollution prevention	Environmentally Acceptable Lubricants (EAL) for stern-tube/thruster seals & hydraulics, leakage monitoring, oil-to-sea interface documentation.	NR467 Pt F, Ch.9 (environmental); VGP/EAL
Redundant Propulsion (AVM-DPS)	Propulsion availability	Independence/segregation of propulsion trains, single-failure analysis, take-me-home capability, redundant thruster arrangement. Related: HEADING CONTROL-DS / HEADING CONTROL-IS for heading-keeping with redundant propulsion/steering.	NR467 Pt F, Ch.2 (AVM-DPS); Ch.11 (HEADING CONTROL)
MON-SHAFT (shaft-line monitoring)	Shaft survey by condition monitoring	Oil-lubricated bearing/seal of approved type; lube-oil monitoring & analysis programme; bearing temperature & wear-down instrumentation; monitoring-based survey scheme (see Section 9.3).	NR467 Pt F, Ch.5; Sec.7
TUG / ESCORT TUG / AHT (service)	High steering & towing loads	Escort/indirect-towing loads on azimuth & steering system, structural substantiation of unit & foundation, stability interaction, uprated steering duty.	NR467 Pt E, Ch.1 (Tugs) / Ch.2 (AHT)
SPS (Special Purpose Ship)	Personnel / mission systems	Higher survivability & redundancy expectations may extend to propulsion/steering arrangement.	NR467 Pt D/E
Electric hybrid / battery	Hybrid power	Documentation of every driving path (PTI/PTO), energy-storage interface, mode changeover, converter data.	NR467 Pt F, Ch.14 (Electric Propulsion)

Surveyor note (notations): Always cross-check the vessel's *requested class notation string* against the thruster package. A DP or comfort notation in particular pulls in substantial extra documentation (FMEA/proving trials; noise & vibration studies) that clients frequently omit from the initial thruster submission. Where a notation adds a steering-critical duty (escort tug), confirm the steering-gear package (Chapter 8) reflects the *uprated* loads, not just the open-water condition.

Chapter 14

Ship-Type & Service-Notation Specific Requirements

14.1 Purpose

The base thruster package (Chapters 1–6) and the prime-mover, ice and notation overlays (Chapters 7, 12, 13) define *what a thruster needs*. This chapter answers the complementary question the surveyor must also ask: **“given the ship type / service notation, what *extra* do I expect in the thruster package, and which *additional ship rules* apply?”**

BV assigns each ship a **service notation** (NR467 Part D) — e.g. tug, supply, oil tanker, passenger ship — plus **additional class notations** (Part E). Together these pull in requirements beyond NR467 Sec.15, and sometimes bring in *separate rule sets* (offshore units, naval ships, high-speed craft). The matrix below is the surveyor’s “what else to demand” guide; the subsequent sections expand the cases with the most rule impact.

14.2 Ship-Type → Thruster Expectation Matrix

Table 14.1: Ship Type / Service — Typical Arrangement & Additional Requirements

Ship type / service	Typical thruster arrangement	Additional requirements & notations to expect	Reference
Harbour / escort tug	Azimuth Z-drive or VSP (main propulsion + steering)	Escort/indirect-towing steering & structural loads; uprated slewing duty; steering redundancy; stability interaction; full steering-gear package.	NR467 Pt E, Ch.1 (tug/escort tug); Sec.14
Offshore supply / PSV / AHTS	Bow tunnel(s) + retractable + stern azimuth; DP	DYNAPOS/DP (usually DP-2): FMEA, redundancy, power segregation, capability plot; FiFi where fitted; station-keeping.	NR467 Pt F, Ch.11 (DYNAPOS); Pt E, Ch.2–3
Continued on next page			

Table 14.1 – continued from previous page

Ship type / service	Typical thruster arrangement	Additional requirements & notations to expect	Reference
Dredger (TSHD / CSD)	Bow tunnels; azimuth; sometimes DP	DREDGING service; DP for some; robust manoeuvring; abrasion/duty considerations.	NR467 Pt D, Ch.13
Passenger ship / RoPax / ferry	Bow (+ stern) tunnels; azimuth/pods on some	SOLAS steering (II-1/29); Safe Return to Port survivability & redundancy for ships ≥ 120 m / 3 fire zones; COMF.	SOLAS II-1/II-2; Pt D, Ch.11–12
Cruise ship	Podded propulsors + multiple bow/stern tunnels	SRtP; COMF-NOISE/VIB; propulsion/steering redundancy; sometimes DP.	SOLAS II-2 Reg.21/22; Pt D, Ch.11
Double-ended ferry	Azimuth or VSP at both ends	Steering redundancy <i>at each end</i> ; control-station changeover; response time both directions.	Sec.14; SOLAS II-1/29
Cable / pipe layer, offshore construction	Retractable + azimuth + tunnels; DP	DYNAPOS DP-2/DP-3: FMEA, fire/flood separation (DP-3), redundancy, proving trials.	NR467 Pt F, Ch.11 (DYNAPOS); Pt E, Ch.6 / Ch.12
Diving support vessel (DSV)	Multiple azimuth/tunnel thrusters; DP-2/DP-3	DYNAPOS (usually DP-2/DP-3): FMEA, redundancy, power segregation, capability plot, proving trials; interfaces with the diving system itself (see NR610 for the diving system, distinct from the ship's NR467 class).	NR467 Pt E, Ch.7; Pt F, Ch.11 (DYNAPOS); NR610
Lifting unit / heavy-lift & crane vessel	Multiple azimuth/tunnel thrusters; often DP	DYNAPOS where fitted: FMEA, redundancy, capability plot; crane/lift loads interact with stability & thruster foundation loads.	NR467 Pt E, Ch.8; Pt F, Ch.11 (DYNAPOS) where DP fitted
Fire-fighting ship	Bow/stern tunnels or azimuth; FiFi pumps often share prime mover with thrusters	FiFi pump/thruster power-sharing and mode-changeover documentation; station-keeping during fire-fighting duty.	NR467 Pt E, Ch.4
Continued on next page			

Table 14.1 – continued from previous page

Ship type / service	Typical thruster arrangement	Additional requirements & notations to expect	Reference
Oil-recovery ship	Bow tunnel(s); sometimes azimuth	Station-keeping during recovery operations; hazardous-area considerations for recovered-oil handling spaces near the thruster room.	NR467 Pt E, Ch.5
Standby rescue vessel	Bow tunnel(s); sometimes azimuth	Manoeuvring/station-keeping close to platforms or vessels in distress; base Sec.15 package typically applies.	NR467 Pt E, Ch.10
Drillship / semi-sub (MODU)	Multiple azimuth thrusters; DP-3	DP-3 station keeping; offshore-unit rules; fire/flood zone separation; extensive FMEA.	NR467 Pt F, Ch.11 (DYNA-POS); NR445
Oil / chemical tanker	Bow thruster (manoeuvring)	Hazardous-area / explosion protection where equipment is in or adjacent to dangerous zones; thruster-room zoning; certified-safe (Ex) equipment.	SOLAS II-2; IEC 60079; Pt C; Pt D, Ch.7–8/10
Gas carrier (LNG/LPG)	Bow thruster; sometimes azimuth	As tanker <i>plus</i> IGC Code hazardous-zone requirements; gas-safe equipment.	IGC Code; IEC 60079; Pt D, Ch.9
Ice-class / polar trader	Ice-strengthened tunnel/azimuth	Ice-load strengthening & winterisation (see Chapter 12).	NR467 Pt F, Ch.8; NR527
Research / naval / patrol	Rim-driven / pods / azimuth	Low underwater-noise & signature; COMF/silent; naval ships follow dedicated naval rules.	Naval rules (e.g. NR483); Pt D, Ch.16 (patrol)
Large yacht	Bow/stern tunnels; pods	Comfort (noise/vibration); yacht-specific rules; retractable/stabiliser interfaces.	NR500 (yacht rules)
Container / bulk / general cargo	Bow tunnel thruster (manoeuvring)	Base Sec.15 package; typically electric drive; no special service overlay.	NR467 Sec.15; Pt C; Pt D, Ch.2/4

14.3 Passenger Ships & Safe Return to Port (SRtP)

For passenger ships to which SOLAS SRtP applies (broadly, ships ≥ 120 m in length or having three or more main vertical fire zones), the ship must retain, after a defined casualty (fire in one zone or flooding of one watertight compartment), a set of **essential systems** — **including**

propulsion and steering. Where thrusters/pods/steering thrusters form part of the propulsion or steering means, the surveyor must confirm:

- redundancy and physical/functional separation so a single casualty does not disable all propulsion & steering;
- power supply, control and cooling for the retained thruster(s) surviving the casualty (fire zone / flooded compartment);
- consistency with the ship's SRtP systems-availability documentation and casualty-threshold analysis.

This typically *adds* redundancy/segregation drawings and a systems availability analysis to the base thruster package. (*Ref. SOLAS II-2 Reg.21/22; NR467 passenger-ship requirements.*)

14.4 Tankers & Gas Carriers — Hazardous Areas & Explosion Protection

On oil tankers, chemical tankers and gas carriers, the bow-thruster room and any electrical/rotating equipment located in or adjacent to **hazardous (gas-dangerous) zones** must meet explosion-protection requirements. The surveyor should verify:

- hazardous-area classification of the thruster space and boundaries;
- **certified safe-type (Ex) equipment** for motors, sensors and junction boxes where required, with certificates;
- cable entries, penetrations and ventilation preserving zone integrity;
- for gas carriers, compliance with the **IGC Code** zoning in addition to SOLAS II-2.

(*Ref. SOLAS II-2; IEC 60079 series; IGC Code; NR467 Pt C electrical in hazardous areas.*) A tanker bow thruster is often electric; confirm the motor's location relative to the cargo/hazardous zone *before* accepting standard (non-Ex) equipment.

14.5 Offshore & DP-Intensive Vessels

OSVs, construction, cable/pipe-lay units, diving support vessels, lifting units and MODUs are defined by their DP capability. Beyond the DP package of Chapter 11, expect: multiple independent thruster trains, power-plant segregation, DP-3 fire/flood separation where notated, worst-case-failure design intent, and comprehensive FMEA and proving-trials programmes. Diving support vessels (NR467 Pt E, Ch.7) additionally require the thruster/DP package to be reviewed alongside the diving system's own classification (**NR610**) where the two interact (e.g. shared power, station-keeping during diving operations). Mobile offshore units are additionally governed by **offshore-unit / MODU rules**, which may modify hull, machinery and location (hazardous-area) requirements relative to NR467.

14.6 Tugs & Escort Tugs

For tugs the thruster *is* the main propulsion and steering means (Z-drive or VSP). Escort tugs generate very high **indirect steering and towing loads**; the surveyor must confirm the azimuth/steering system, unit structure and hull foundation are substantiated for these loads (not merely free-running thrust), together with the full steering-gear package (Chapter 8) and stability interaction. (*Ref. NR467 Pt D tug / escort-tug service notations.*)

14.7 Thruster Compartment (All Ship Types)

Independent of ship type, the thruster room / bow-thruster compartment carries its own requirements the surveyor should not overlook: watertight boundaries and subdivision, bilge/drainage, fire protection and boundary insulation, ventilation and (for tankers/gas carriers) hazardous-area integrity, plus safe access and escape. Confirm these are reflected in the general arrangement and hull/piping documentation. (*Ref. NR467 Part B, Ch 5; Part C fire & piping; SOLAS II-2.*)

Surveyor note (ship type): Read the *requested notation string* first — it tells you the ship type, service and additional notations, and therefore which overlays of Chapters 7–13 and which *separate rule sets* (SRtP, hazardous-area/IGC, offshore/MODU, naval, HSC) apply. The most common ship-type gaps are: SRtP redundancy on passenger ships, Ex/hazardous-area equipment on tankers and gas carriers, and DP-3 separation on offshore units.

Chapter 15

Testing & Commissioning Requirements

15.1 Factory Acceptance Tests (FAT)

Required for All Thrusters:

- Dimensional verification
- Material verification
- Non-destructive testing
- Assembly inspection
- Mechanical running test
- Hydraulic system test (if applicable)
- Electric motor test (if applicable)
- Control system test
- Retraction mechanism test (retractable)
- CP mechanism test (CP propellers)
- Azimuth slewing test (azimuth thrusters)

15.2 Installation Tests

On-Site Verification:

- Foundation inspection
- Alignment verification
- Piping inspection
- Electrical installation inspection
- Control system integration test
- Hydraulic system commissioning

15.3 Dock Trials

Pre-Sea Trials:

- Static thrust test
- No-load running test
- Control system functional test
- Retraction/extension test (retractable)
- Azimuth rotation test (azimuth)
- CP pitch control test (CP propellers)

15.4 Sea Trials

Performance Verification:

- Performance verification
- Maneuverability trials
- Vibration measurements
- Noise measurements
- Thermal performance
- Steering gear trials (if steering function)
- DP trials (for DP systems)
- DP FMEA proving trials (for DP systems)

15.5 Documentation & Reporting

Required Reports (FI):

- FAT Report
- Installation Report
- Sea Trial Report
- DP Trials Report (for DP systems)
- As-Built Documentation

Chapter 16

Surveyor Checklists by Thruster Type

16.1 Tunnel Thrusters (Fixed) - Complete Checklist

16.1.1 General Information

- ☐ Thruster power rating ≥ 110 kW (Section 15 applies)
- ☐ Thruster manufacturer and model
- ☐ Installation location (bow/stern)

16.1.2 Structural

- ☐ General Arrangement Drawing (**FA**)
- ☐ Tunnel Structural Arrangement (**FA**)
- ☐ Tunnel Structural Calculations (**FA**)
- ☐ Tunnel End Grating/Grid Design (**FA**)
- ☐ Hull Penetration Details (**FA**)

16.1.3 Thruster Unit - Mechanical

- ☐ Thruster Unit General Assembly (**FA**)
- ☐ Propeller Design Drawing (**FA**)
- ☐ Propeller Strength Calculations (**FA**)
- ☐ Propeller Shaft Drawing (**FA**)
- ☐ Shaft Strength Calculations (**FA**)
- ☐ Bearing Arrangement Drawing (**FA**)
- ☐ Bearing Load Calculations (**FA**)
- ☐ Gearbox Assembly Drawing (**FA**)
- ☐ Gear Tooth Calculations (**FA**)
- ☐ Gearbox Lubrication System (**FA**)

16.1.4 Drive System

If Electric:

- ☐ Electric Motor Specification (**FA**)
- ☐ Motor Foundation Drawing (**FA**)
- ☐ Motor-Gearbox Coupling (**FA**)

If Hydraulic:

- ☐ Hydraulic Motor Specification (**FA**)
- ☐ Hydraulic System Schematic (**FA**)
- ☐ See Chapter 10 for complete hydraulic requirements

16.1.5 Control System

- ☐ Control System Block Diagram (**FA**)
- ☐ Control Panel Layout (**FA**)
- ☐ Electrical Single-Line Diagram (**FA**)
- ☐ Control Software Description (**FA**)

16.1.6 Calculations

- ☐ Thrust Calculation (**FA**)
- ☐ Vibration Analysis (**FA**)
- ☐ Noise Level Prediction (**FA**)
- ☐ Thermal Analysis (**FA**)

16.1.7 Materials & Welding

- ☐ Material Specifications (**FA**)
- ☐ Welding Procedures (**FA**)
- ☐ Material Certificates (during construction)
- ☐ NDT Plan (**FA**)

16.1.8 Testing

- ☐ FAT Procedures (**FA**)
- ☐ Installation Test Procedures (**FA**)
- ☐ Sea Trial Procedures (**FA**)
- ☐ Test Reports (**FI** - after testing)

16.1.9 Manuals

- ☐ Operation & Maintenance Manual (FI)
- ☐ Spare Parts List (FI)
- ☐ Installation Manual (FI)

16.2 Retractable Thrusters - Complete Checklist

All items from Section 10.1 (Tunnel Thrusters), PLUS:

16.2.1 Retraction Mechanism

- ☐ Retraction Mechanism Assembly (FA)
- ☐ Hydraulic Cylinder Specifications (FA)
- ☐ Retraction System Calculations (FA)
- ☐ Hull Opening & Closure Design (FA)
- ☐ Hull Opening Structural Analysis (FA)
- ☐ Watertight Integrity Documentation (FA)
- ☐ Locking System Design (FA)
- ☐ Position Indication System (FA)
- ☐ Emergency Lowering System (FA)
- ☐ Hydraulic System for Retraction (FA)

16.2.2 Additional Manuals

- ☐ Retraction/Extension Procedures (FI)
- ☐ Emergency Recovery Procedures (FI)

16.2.3 Additional Testing

- ☐ Retraction mechanism FAT
- ☐ Seal integrity testing
- ☐ Emergency lowering test
- ☐ Dock trials - retraction/extension
- ☐ Sea trials - retraction under way (if applicable)

16.3 Azimuth Thrusters (Fixed Pitch) - Complete Checklist

16.3.1 General & Structure

- ☐ General Arrangement Drawing incl. 360° clearance envelope (**FA**)
- ☐ Azimuth Unit Complete Assembly (**FA**)
- ☐ Hull Penetration & Foundation (**FA**)
- ☐ Hull Structure Calculations / FEA (**FA**)

16.3.2 Propeller & Shaft

- ☐ Propeller Design Drawing (**FA**)
- ☐ Propeller Strength Calculations (**FA**)
- ☐ Vertical Shaft Assembly & Calculations (**FA**)
- ☐ Thrust Bearing Design & Calculations (**FA**)
- ☐ Radial Bearing Arrangement (**FA**)
- ☐ Column Structure Design (**FA**)
- ☐ Seal System Design (**FA**)

16.3.3 Gear & Slewing System

- ☐ Gear Train Assembly (**FA**)
- ☐ Gear Tooth Strength Calculations — ISO 6336 (**FA**)
- ☐ Gear Lubrication System (**FA**)
- ☐ Slewing Bearing Design & Calculations (**FA**)
- ☐ Azimuth Drive Mechanism & Calculations (**FA**)
- ☐ Position Feedback System (**FA**)

16.3.4 Drive System & Prime Mover

- ☐ Electric or hydraulic power-transmission package (**FA**)
- ☐ Slip ring / rotary joint (electric) (**FA**)
- ☐ **Prime-mover add-on** — electric or diesel (Chapter 7)

16.3.5 Control, Calculations, Materials & Testing

- ☐ Control System Architecture & Bridge Console (**FA**)
- ☐ Local Control Station (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Material Specifications, Welding, NDT Plan (**FA**)
- ☐ FAT / dock trial (azimuth slewing) / sea-trial procedures (**FA**)
- ☐ O&M and Installation Manuals (**FI**)

16.3.6 If Steering / DP / Ice / Notations

- ☐ If steering function → Chapter 8 package (SOLAS II-1/29, FMEA)
- ☐ If part of main shaft line → Chapter 9 package
- ☐ If DP → Section 16. (DP add-on below)
- ☐ If ice class → Chapter 12 add-on
- ☐ Overlay applicable notations → Chapter 13

16.4 Azimuth Thrusters (Controllable Pitch) - Complete Checklist

All items from Azimuth FP, PLUS:

- ☐ CP Hub Mechanism Assembly (**FA**)
- ☐ Blade Retention Calculations (**FA**)
- ☐ Pitch Control Mechanism (**FA**)
- ☐ Pitch Control Hydraulic System incl. rotary joint (**FA**) — Chapter 10
- ☐ Pitch feedback & fail-safe position (**FA**)

16.5 Podded Propulsion Units - Complete Checklist

All items from Azimuth (FP or CP), PLUS:

- ☐ Pod-specific structural components & strut (**FA**)
- ☐ Electric motor in pod — specification, cooling, monitoring (**FA**)
- ☐ Power supply through strut / slip-ring (**FA**)
- ☐ Propeller direct-drive arrangement (**FA**)
- ☐ Pod-specific FAT/testing (**FA**)
- ☐ **Electric prime-mover add-on** (Chapter 7)

16.6 Voith-Schneider (Cycloidal) Units - Complete Checklist

- ☐ VSP Unit General Assembly (**FA**)
- ☐ Blade (wing) design + blade-shaft/blade strength calculations (**FA**)
- ☐ Blade bearing arrangement (**FA**)
- ☐ Kinematic control gear / steering mechanism strength (**FA**)
- ☐ Rotor casing & main bevel gear + gear calculations (**FA**)
- ☐ Main thrust bearing design & life (**FA**)
- ☐ Bottom cover / guard plate structure (**FA**)
- ☐ Hull seat, foundation & well structure / FEA (**FA**)
- ☐ Seal system (rotor & blade shafts) (**FA**)
- ☐ Servo / hydraulic control unit (**FA**) — Chapter 10
- ☐ Steering control system & bridge console (**FA**)
- ☐ **Steering-function package** — Chapter 8 (FMEA, redundancy, SOLAS II-1/29)
- ☐ Prime-mover add-on (Chapter 7) + drive-train TVC

16.7 Water-Jet Systems - Complete Checklist

- ☐ Water-jet general arrangement & installation (**FA**)
- ☐ Impeller/rotor design & strength calculations (**FA**)
- ☐ Shaft line & bearings (**FA**) — Chapter 9
- ☐ Inlet duct & transom structure / hull penetration (**FA**)
- ☐ Steering & reversing (bucket) mechanism (**FA**)
- ☐ Steering/reversing hydraulic system (**FA**) — Chapter 10
- ☐ Control system & bridge interface (**FA**)
- ☐ Drive package (direct-from-engine or via gearbox) + TVC (**FA**)
- ☐ Performance / thrust calculations (**FA**)
- ☐ Materials, welding, NDT (**FA**)
- ☐ FAT / trials procedures (**FA**); O&M manuals (**FI**)
- ☐ If steering means of ship → Chapter 8; if DP → DP add-on

16.8 Prime-Mover Add-On Checklist (apply to any type)

If **ELECTRIC**-motor driven:

- ☐ Drive-motor data sheet (**FA**)
- ☐ Frequency converter (VFD) specification & arrangement (**FA**)
- ☐ Harmonic / power-quality analysis (**FA**)
- ☐ Supply transformer & switchboard interface (**FA**)
- ☐ Power cable sizing, routing & segregation (**FA**)
- ☐ Motor protection, monitoring & cooling (**FA**)

If **DIESEL**-engine driven:

- ☐ Diesel engine approval / type data (**FA**)
- ☐ **Torsional vibration calculation of the complete train** (**FA**)
- ☐ Clutch & flexible coupling (**FA**)
- ☐ Engine foundation & chocking (**FA**)
- ☐ Fuel oil / lube oil / cooling water systems (**FA**)
- ☐ Starting system & exhaust gas system (**FA**)
- ☐ Engine control, safety & monitoring (**FA**)
- ☐ NOx Technical File / EIAPP (**FI**)

16.9 Ice Class / Winterisation Add-On Checklist (apply if notation carried)

- ☐ Ice-class notation basis & design conditions (**FA**)
- ☐ Propeller ice-load strength calculation (**FA**)
- ☐ Shaft line & ice-torque verification (**FA**)
- ☐ Gear & azimuth/nozzle ice-load substantiation (**FA**)
- ☐ Thruster lower-unit ice protection (**FA**)
- ☐ Tunnel/inlet grid ice arrangement (**FA**)
- ☐ Winterisation of hydraulic/cooling/seal systems (**FA**)
- ☐ Low-temperature material certification (**FA**)

16.10 DP Thrusters - Additional Checklist Items

For ANY thruster type used in DP system, add:

- ☐ DP System General Arrangement (**FA**)
- ☐ Thruster Configuration Drawing (**FA**)
- ☐ DP Capability Plot (**FA**)
- ☐ FMEA Documentation (**FA**)
- ☐ Redundancy Concept (**FA**)
- ☐ Power Supply Segregation (**FA**)
- ☐ DP Control System Architecture (**FA**)
- ☐ Position Reference System Configuration (**FA**)
- ☐ PMS Configuration (**FA**)
- ☐ UPS Configuration (**FA**)
- ☐ DP FMEA Proving Trials Plan (**FA**)
- ☐ DP Trials Reports (**FI**)
- ☐ DP Operations Manual (**FI**)

Chapter 17

Submission Cover Sheets by Ship Type

How to use: one cover sheet per page. Pick the sheet matching the vessel’s service notation, complete the identification block, then tick each line as the corresponding drawing/document is received and found acceptable. Every sheet shares a *common core* (base package, type-specific package, prime mover, testing, manuals) and then lists the **ship-type-specific extras** — the items most often missing for that service. Use together with the detailed checklists of Chapter 16 and the overlays of Chapters 7–14. Legend: **FA** = For Approval, **FI** = For Information.

17.1 Generic Template (any ship / any thruster type)

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

Core package (all thrusters ≥ 110 kW):

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Functional overlays — tick those applicable:

- ☐ Steering function → Chapter 8 (FMEA, redundancy, SOLAS II-1/29)
- ☐ Part of main shaft line → Chapter 9 (+ MON-SHAFT, Section 9.3, if notated)
- ☐ Dynamic positioning → Chapter 11 (FMEA, capability plot, proving trials)
- ☐ Hydraulic actuation → Chapter 10

Additional-notation & ice overlays — tick those in the notation string:

- ☐ Ice class / Polar / COLD → Chapter 12
- ☐ DP / COMF / AUT / CLEANSHIP / RP / MON-SHAFT → Chapter 13

17.2 Harbour / Escort Tug

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (tug):

- ☐ Azimuth (Z-drive) or Voith-Schneider unit — full type package (**FA**)
- ☐ **Full steering-gear package** — Chapter 8: FMEA, redundancy, control stations, response time, SOLAS II-1/29 (**FA**)
- ☐ **Escort / indirect-towing loads** on steering & structure; unit & foundation substantiation for these loads, not free-running only (**FA**)
- ☐ Uprated slewing duty & brake/locking; stability interaction documentation (**FA**)
- ☐ Drive-train torsional vibration calculation (diesel Z-drive) (**FA**)

17.3 Offshore Supply / PSV / AHTS (DP)

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (OSV / DP):

- ☐ Bow tunnel(s) + retractable + stern azimuth — type packages (**FA**)
- ☐ **DYNAPOS / DP (usually DP-2)** — Chapter 11: FMEA, redundancy concept, power segregation, capability plot, thruster allocation, proving-trials plan (**FA**)
- ☐ Retractable/take-me-home thruster package incl. emergency lowering (**FA**)
- ☐ FiFi and other service systems interfaces where fitted (**FI**)
- ☐ Steering-function compliance for azimuth units (**FA**)

17.4 Passenger Ship / RoPax / Ferry

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (passenger):

- ☐ Bow (+ stern) tunnel thrusters / azimuth — type packages (**FA**)
- ☐ **Safe Return to Port** redundancy & segregation of propulsion/steering (ships ≥ 120 m or 3 fire zones); systems-availability analysis (**FA**)
- ☐ SOLAS steering-gear compliance (II-1/29) where thrusters steer (**FA**)
- ☐ COMF-NOISE / COMF-VIB noise & vibration prediction (**FA**)
- ☐ Emergency/standby power to retained thruster after casualty (**FA**)

17.5 Cruise Ship

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (cruise):

- ☐ Podded propulsors + multiple bow/stern tunnels — type packages (**FA**)
- ☐ **Safe Return to Port** redundancy & systems availability (**FA**)
- ☐ **COMF-NOISE / COMF-VIB** — blade-rate excitation, cavitation noise, resilient mounting (**FA**)
- ☐ Pod electrical-machine, cooling & monitoring; slip-ring/power-through-strut (**FA**)
- ☐ DP package if DP-notated (**FA**)

17.6 Double-Ended Ferry

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (double-ended):

- ☐ Azimuth or Voith-Schneider unit *at each end* — type packages (**FA**)
- ☐ **Steering redundancy at both ends** + control-station changeover logic (**FA**)
- ☐ Response time / manoeuvring in both running directions (**FA**)
- ☐ COMF noise & vibration (passenger comfort) (**FA**)

17.7 Dredger (TSHD / CSD)

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (dredger):

- ☐ Bow tunnels / azimuth — type packages (**FA**)
- ☐ DREDGING service duty; robust manoeuvring provisions (**FA**)
- ☐ DP package where station-keeping/tracking notated (**FA**)
- ☐ Duty-cycle / abrasion considerations in bearing & seal life (**FI**)

17.8 Cable / Pipe Layer & Offshore Construction (DP)

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (construction / DP):

- ☐ Retractable + azimuth + tunnel thrusters — type packages (**FA**)
- ☐ **DYNAPOS DP-2 / DP-3** — Chapter 11: FMEA, redundancy, power segregation, capability plot, proving trials (**FA**)
- ☐ DP-3 **fire / flood zone separation** of thruster groups & power (**FA**)
- ☐ Worst-case-failure design intent documentation (**FA**)

17.9 Drillship / Semi-Submersible (MODU)

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (MODU / DP-3):

- ☐ Multiple azimuth thrusters — type packages (**FA**)
- ☐ **DYNAPOS DP-3** station keeping — full FMEA, redundancy, proving trials (**FA**)
- ☐ **Fire & flood separation** of thruster/power groups (DP-3) (**FA**)
- ☐ Compliance with **offshore-unit / MODU rules** (hull, machinery, hazardous-area) (**FA**)

17.10 Oil / Chemical Tanker

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (tanker):

- ☐ Bow thruster (usually electric) — type package (**FA**)
- ☐ **Hazardous-area classification** of thruster room & boundaries (**FA**)
- ☐ **Certified safe-type (Ex) equipment** for motor/sensors/junction boxes where in or adjacent to dangerous zones, with certificates (**FA**)
- ☐ Cable entries, penetrations & ventilation preserving zone integrity (**FA**)
- ☐ Confirm motor location vs. hazardous zone *before* accepting non-Ex equipment (**FA**)

17.11 Gas Carrier (LNG / LPG)

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (gas carrier):

- ☐ Bow thruster / azimuth — type package (**FA**)
- ☐ **IGC Code** hazardous-zone requirements in addition to SOLAS II-2 (**FA**)
- ☐ Gas-safe / certified (Ex) electrical equipment & certificates (**FA**)
- ☐ Hazardous-area drawings for thruster space & boundaries (**FA**)

17.12 Ice-Class / Polar Trader

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (ice) — Chapter 12:

- ☐ Ice-class notation basis & design conditions (**FA**)
- ☐ **Propeller ice-load strength** calculation (**FA**)
- ☐ **Shaft line & gear ice-torque** verification (blade-milling / blade-loss) (**FA**)
- ☐ Azimuth/pod lower-unit & slewing gear vs. ice-block impact (**FA**)
- ☐ Winterisation (low-temp oils, materials, sensor heating; anti-icing) (**FA**)
- ☐ Low-temperature material certification (**FA**)

17.13 Research / Naval / Patrol

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (research / naval):

- ☐ Rim-driven / podded / azimuth units — type packages (**FA**)
- ☐ **Low underwater-noise / signature** & COMF (silent) documentation (**FA**)
- ☐ Cavitation-noise control measures (**FA**)
- ☐ Naval vessels: compliance with applicable **naval ship rules** (**FA**)

17.14 Large Yacht

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (yacht):

- ☐ Bow/stern tunnel thrusters and/or pods — type packages (**FA**)
- ☐ **Comfort** (noise & vibration) documentation (**FA**)
- ☐ Retractable-thruster & stabiliser interface where fitted (**FA**)
- ☐ Applicable yacht-specific rules (**FA**)

17.15 Container / Bulk / General Cargo

Vessel / Yard No		Class notation	
IMO number		Thruster type / qty	
Prime mover		Reviewer / date	

- ☐ General Arrangement + Technical Specification sheet (**FA**)
- ☐ **Type-specific mechanical/structural package** — attach the matching Chapter 16 checklist (**FA**)
- ☐ Materials, welding procedures, NDT plan (**FA**)
- ☐ Thrust / vibration / noise / thermal calculations (**FA**)
- ☐ Control system package + electrical single-line diagram (**FA**)
- ☐ **Prime-mover package** (Chapter 7): if *electric* — motor + VFD + harmonic study + cabling/segregation + protection; if *diesel* — engine approval + **full-train TVC** + clutch/coupling + FO/LO/cooling/starting/exhaust + controls (**FA**)
- ☐ FAT / dock-trial / sea-trial procedures (**FA**); test reports (**FI**)
- ☐ O&M, spare-parts & installation manuals (**FI**)

Ship-type-specific extras (cargo):

- ☐ Bow tunnel thruster for manoeuvring — type package (**FA**)
- ☐ Typically electric drive — confirm motor, cabling & protection (**FA**)
- ☐ No special service overlay unless ice class / other notation carried (verify string) (**FA**)

Chapter 18

Common Submission Errors & Surveyor Notes

18.1 Frequent Documentation Gaps

18.1.1 Missing or Incomplete Calculations

- Shaft strength calculations missing fatigue analysis
- Bearing life calculations without proper load factors
- Gear calculations not per recognized standards (ISO 6336)
- Vibration analysis incomplete or missing
- Hydraulic system calculations (accumulator sizing, pressure drop)

18.1.2 Inadequate Drawings

- General arrangements without sufficient detail
- Material specifications not clearly indicated
- Welding details missing or incomplete
- Foundation drawings without load specifications
- Control system diagrams without protection details

18.1.3 Steering Gear Overlap Not Addressed

- Azimuth or podded thrusters used for steering without steering gear compliance documentation
- Missing FMEA for steering function
- Inadequate redundancy analysis
- Missing emergency steering provisions
- SOLAS compliance not demonstrated

18.1.4 DP System Gaps

- FMEA not covering all failure modes or worst-case scenarios
- Inadequate power segregation for DP-2/DP-3
- Missing fire/flood zone analysis for DP-3
- Thruster interaction effects not analyzed
- Incomplete proving trials procedures

18.1.5 Hydraulic System Issues

- Undersized accumulators
- Inadequate pressure relief provisions
- Missing filtration specifications
- Incomplete piping stress analysis
- Emergency provisions not clearly defined

18.1.6 Prime-Mover Gaps

- Diesel-driven Z-drive submitted *without* a torsional vibration calculation for the complete engine-clutch-shaft-thruster train (most common tug/OSV gap)
- Missing barred-speed range or clutch-in/misfiring conditions in the TVC
- Electric-driven thruster without harmonic / power-quality study or cable-sizing & segregation
- Hybrid PTI/PTO arrangements with undocumented driving paths or mode-changeover logic

18.1.7 Ice-Class & Notation Gaps

- Ice-classed vessel with propeller/shaft/gear checked only for open-water rating, not ice peak-torque / blade-milling loads
- Azimuth/pod lower unit and slewing gear not substantiated against ice-block impact
- Winterisation (low-temperature oils, materials, sensor heating) not addressed
- Comfort (COMF) notation carried but no thruster noise/vibration prediction
- Requested notation string not reconciled with the submitted thruster package

18.1.8 Cycloidal (VSP) & Combined Propulsion/Steering Gaps

- VSP mechanical package submitted without the steering-function compliance set (FMEA, redundancy, SOLAS II-1/29, response time)
- Blade guard/bottom plate and its hull attachment not substantiated for grounding/impact
- Steerable water-jet / nozzle / grid units missing steering-gear documentation

18.2 Surveyor Review Tips

18.2.1 Initial Review

1. Verify thruster power ≥ 110 kW → Section 15 applies
2. Identify thruster type → Apply appropriate checklist (Chapters 2–6)
3. Identify the prime mover (electric / diesel / hydraulic) → Add Chapter 7 submissions
4. Check for steering function → Add Chapter 8 requirements
5. Check for main shafting classification → Add Chapter 9 requirements
6. Check for DP application → Add Chapter 11 requirements
7. Check ice class / winterisation notation → Add Chapter 12 requirements
8. Reconcile the full class-notation string → Add Chapter 13 requirements

18.2.2 Calculation Review

- Verify all calculations use BV-approved formulas or recognized standards
- Check safety factors applied
- Verify material properties used in calculations match specifications
- Ensure all loading conditions considered (normal, extreme, emergency)

18.2.3 Drawing Review

- Check for consistency between drawings
- Verify dimensions and tolerances
- Ensure material specifications clearly indicated
- Check for proper welding symbols and details
- Verify accessibility for maintenance

18.3 Red Flags for Surveyors

18.3.1 Immediate Rejection Criteria

- Missing critical calculations (shaft strength, bearing life, gear strength)
- Material specifications not compliant with BV rules
- Welding procedures not approved
- Control system without adequate safety provisions
- Steering gear requirements not addressed when applicable
- DP FMEA incomplete or inadequate

18.3.2 Require Clarification

- Ambiguous material specifications
- Incomplete or unclear drawings
- Calculations without clear assumptions
- Testing procedures without acceptance criteria
- Manuals not in working language of crew

Chapter 19

Quick Reference Tables

19.1 Thruster Type vs. Applicable Rule Sections

Table 19.1: Applicability Matrix

Thruster Type	Sec.15	Sec.14	Sec.7	DP (Pt F)	Hydraulics
Tunnel (Fixed)	✓	Optional	Optional	Optional	If hydraulic
Retractable	✓	Optional	Optional	Optional	✓ Required
Azimuth FP	✓	Often ✓	Typically ✓	Optional	If hydraulic
Azimuth CP	✓	Often ✓	Typically ✓	Optional	✓ Required
Podded	✓	Often ✓	Typically ✓	Optional	If CP
Water-Jet	✓	Often ✓	✓ Required	Optional	✓ Required
Voith-Schneider	✓	✓ Required	Typically ✓	Optional	✓ Required
Rim-Driven	✓	Optional	Optional	Optional	Rarely
Pump-Jet / Ducted	✓	If steering	✓ Required	Optional	If steering
Gill / Hydro-Jet	✓	Optional	Optional	Optional	If hydraulic
Steering Grid / Nozzle	✓	✓ Required	✓ Required	Optional	✓ Required

Sec.15 = Thrusters; Sec.14 = Steering Gear; Sec.7 = Shaft lines/propellers (NR467 Pt C, Ch 1). “Often/Typically ✓” means applicable when the unit provides steering or forms part of the main shaft line. Overlay Chapter 7 (prime mover), Chapter 12 (ice class) and Chapter 13 (notations) on every row as applicable.

19.2 Prime Mover & Additional-Notation Quick Guide

Table 19.2: Prime Mover — Key Additional Submissions

Prime mover	Headline additional submissions (see Chapter)
Electric motor	Motor data sheet; frequency converter (VFD); harmonic/power-quality study; transformer & switchboard interface; cable sizing & segregation; motor protection/monitoring/cooling.
Diesel engine	Engine approval (Sec.2); full-train torsional vibration calculation ; clutch & flexible coupling; foundation/chocking; FO/LO/cooling/starting/exhaust systems; engine safety & controls; NOx file.
Hydraulic motor	Per Chapter 10 (HPU, circuit, accumulators, relief, filtration, monitoring).

Table 19.3: Additional Notations — Trigger Reference

Notation carried	Adds
DP / DYNAPOS	Chapter 11: FMEA, redundancy, power segregation, capability plot, proving trials (NR467 Pt F, DYNAPOS).
Ice class / Polar / COLD	Chapter 12: ice-load propeller/shaft/gear strengthening, winterisation, low-temp materials (NR467 Pt E, NR527, IACS UR I3).
COMF-NOISE / COMF-VIB	Chapter 13: noise & vibration prediction, blade-rate excitation, resilient mounting.
AUT-UMS / AUT-CCS	Chapter 13: extended alarms/monitoring, safe remote control, fail-safe.
CLEANSHIP	Chapter 13: EAL seal/hydraulic fluids, leakage monitoring.
MON-SHAFT	Section 9.3: oil-lubricated bearing/seal, lube-oil analysis & wear-down monitoring, condition-based shaft survey.
TUG / ESCORT TUG	Chapter 13: uprated steering & structural loads.

19.3 Document Approval Categories Summary

Table 19.4: Approval Categories

Category	Meaning	Timing	Surveyor Action
FA	Must be reviewed and approved before construction	Submit before construction	Detailed technical review
FI	Submitted for record, not requiring formal approval	Submit as specified	Review for completeness
During Construction	Certificates/reports generated during manufacturing	Submit as work progresses	Verify during surveys

Chapter 20

Regulatory References

20.1 Bureau Veritas Rules

20.1.1 NR467 - Rules for Classification of Steel Ships

Part A: Classification and Surveys — Chapter 1 (“Principles of Classification and Class Notations”) is where every **service notation** and **additional class notation** is formally *listed and defined* (the master index of ship types and notations), together with the principles of assignment/maintenance of class (Ch.2) and survey scope (Ch.3–5). The *detailed technical requirements* for each notation then sit in Parts D/E (service notations) and F (additional class notations) as set out below — Part A tells the surveyor *which* notations exist and apply; Parts D/E/F tell the surveyor *what to demand* for each one.

Part B: Hull and Stability

- Chapter 2: Subdivision and Stability
- Chapter 3: Materials
- Chapter 4: Welding
- Chapter 5: Hull Structure

Part C: Machinery, Electricity, Automation and Fire Protection

- Chapter 1 — Machinery:
 - Section 2: Diesel Engines (prime-mover-driven thrusters)
 - Sections 7–8: Shaft Lines and Propellers
 - Section 14: Steering Gear
 - Section 15: Thrusters (and water-jets)
- Chapter 2 — Electrical Installations (drive motors, converters, cables)
- Chapter 3 — Automation (control, alarms, AUT notations)
- Chapter 4 — Fire Protection

Note: exact section numbering varies with rule edition — always confirm against the current NR467 in Rules Explorer.

Part D: Service Notations — general ship-type service notations (e.g. passenger ship, oil tanker, dredger, container ship). Determines the ship-type requirements overlaid on the thruster package.

Part E: Service Notations for Offshore Service Vessels and Tugs — e.g. *tug*, *escort tug*, *supply*, anchor-handling. Source of the uprated escort/towing steering & structural loads for tug/OSV thrusters.

Part F: Additional Class Notations — the additional (voluntary) notations, in multiple chapters:

- Ice class (IA Super / IA / IB / IC) and Polar Class (PC1–PC7); COLD winterisation
- Comfort on board — COMF-NOISE, COMF-VIB
- Automated machinery spaces / integrated systems — AUT-UMS, AUT-CCS, AUT-PORT
- Dynamic positioning — **DYNAPOS** (AM / AT / AM-AT / AM-AT R / AM-AT RS / SAM)
- Environmental protection — CLEANSHIP and related (EAL lubricants)
- Redundant propulsion — **AVM-DPS** (Part F, Ch.2); related **HEADING CONTROL-DS** / **HEADING CONTROL-IS** (Part F, Ch.11)
- Shaft-line monitoring — MON-SHAFT (Part F, Ch.5)
- Electric propulsion / power supply (Part F, Ch.14) — relevant to fully electric or hybrid pod/azimuth thruster installations; cross-check against Chapter 7
- Elastic shaft alignment & hydroelasticity (Part F, Ch.15) — relevant where a thruster’s vertical/propeller shaft alignment scheme claims an elastic-alignment notation; cross-check against Chapter 9

Reference correction: Dynamic positioning is an *additional class notation* (**DYNAPOS**) defined in **NR467 Part F**. There is no “NR216 DP rule”: **NR216** is the *Rules on Materials and Welding* (see below). Earlier drafts of this catalog mis-cited NR216 for DP — read DP references as **NR467 Part F (DYNAPOS)**.

20.1.2 Related BV Rule Notes (as applicable)

- **NR216** — Rules on Materials and Welding for the classification of marine units
- **NR266** — Requirements for Survey of Materials and Equipment
- **NR320** — Certification scheme of materials and equipment for marine units
- **NR527** — Ships operating in polar waters / icebreakers (Polar Class)
- **NR500** — Classification and certification of *yachts*
- **NR566** — Hull arrangement, stability and systems for *ships < 500 GT*
- **NR483** — Classification of *naval ships*
- **NR445** — Classification of *offshore units* (MODU / drillships)

20.2 International Standards

20.2.1 ISO Standards

- **ISO 6336:** Calculation of load capacity of spur and helical gears
- **ISO 22547:** Ships and marine technology — azimuth thrusters
- **ISO 484:** Shipbuilding — ship screw propellers (manufacturing tolerances)
- **ISO 4413:** Hydraulic fluid power — general rules for systems
- **ISO 20283 / ISO 6954:** Mechanical vibration — measurement & evaluation (supports COMF-VIB)

20.2.2 IEC Standards

- **IEC 60092 Series:** Electrical installations in ships
 - IEC 60092-101: Definitions and general requirements
 - IEC 60092-201: System design — general
 - IEC 60092-301: Equipment - Generators and motors
 - IEC 60092-352: Choice and installation of cables
 - IEC 60092-504: Control and instrumentation
- **IEC 60034 Series:** Rotating electrical machines (ratings, cooling, temperature rise)
- **IEC 61508:** Functional safety (for DP / thruster control systems)

20.2.3 IACS Unified Requirements & Codes

- **IACS UR I1–I3:** Polar Class — ships and machinery requirements (ice loads on propeller/shaft/gear)
- **IACS UR M:** Machinery requirements (shafting, gears, TVC principles)
- **IACS UR E22 / E26 / E27:** Programmable / cyber-resilient control systems
- **IMO Polar Code:** Ships operating in polar waters
- **Finnish-Swedish Ice Class Rules (TRAFICOM):** Baltic ice classes basis

20.2.4 SOLAS Convention

- **Chapter II-1, Regulation 29:** Steering gear
- **Chapter II-1, Reg. 8-1 & II-2, Reg. 21/22:** Safe Return to Port / systems availability after a casualty (passenger ships)
- **Chapter II-2:** Fire protection; hazardous-area boundaries
- **Chapter V, Regulation 28:** Maneuverability

20.2.5 Ship-Type / Service Rule Sets & Codes

- **IEC 60079 series:** Explosion protection — equipment in hazardous areas (tankers, gas carriers, bow-thruster rooms)
- **IGC Code:** Gas carriers — hazardous-zone requirements
- **IMO MODU Code / offshore-unit rules:** Mobile offshore drilling units and offshore service craft
- **HSC Code:** High-speed craft (may modify/replace NR467 machinery requirements)
- **Naval ship rules** (e.g. BV NR483): Naval and patrol vessels — signature/silent operation
- **NR467 Part D:** Service notations (tug, escort tug, supply, dredging, passenger, tanker, etc.)

20.2.6 IMO Resolutions

- **IMO Res.A.468(XII):** Code on Noise Levels
- **IMO Res.MSC.337(91):** Code on Noise Levels on Board Ships (mandatory)
- **IMO MSC/Circ.645 & MSC.1/Circ.1580:** Guidelines for vessels/units with DP systems
- **IMO MSC.1/Circ.1369:** Interim explanatory notes for SRtP assessment

20.3 Online Resources

20.3.1 Bureau Veritas Marine & Offshore

- **Rules Explorer:** <https://rulesexplorer.bureauveritas.com/>
- **NR467 Rules:** <https://marine-offshore.bureauveritas.com/nr467-rules-classification-steel-ships>
- **All Rules & Guidance Notes:** <https://marine-offshore.bureauveritas.com/rules-classification-rule-notes-and-guidance-notes>

Chapter 21

Contact Information & Document Control

21.1 For Technical Queries

Bureau Veritas Marine & Offshore Division

- Regional Technical Support Offices
- Email: Contact through official BV channels
- Rules Explorer Support: Available through BV website

21.2 For Urgent Classification Matters

- Contact your assigned Plan Approval Manager
- Regional Marine & Offshore Director

21.3 Document Revision History

Table 21.1: Revision History

Version	Date	Changes	Author
1.0	2025	Initial comprehensive catalog based on NR467 Sections 7, 14, 15 and NR216	Jules (BV AI Assistant)
1.1	2026	Added Voith-Schneider (cycloidal) and other propulsor types (rim-driven, pump-jet, gill/jet, steering grid); prime-mover chapter (diesel-engine vs. electric-motor drive incl. full-train TVC); ice class & winterisation chapter; additional BV notations chapter (COMF, AUT, CLEANSHIP, RP, service notations); expanded checklists, quick-reference tables and standards. Preamble/compile fixes.	Plan Approval Reference (expanded ed.)
1.2	2026	Added Ship-Type & Service-Notation chapter (ship-type → thruster expectation matrix; Safe Return to Port for passenger ships; hazardous-area/Ex for tankers & gas carriers; offshore/MODU & DP-intensive vessels; tugs & escort tugs; thruster-compartment requirements). Added ship-type/service rule sets & codes to references (IEC 60079, IGC, MODU, HSC, naval, SRtP).	Plan Approval Reference (expanded ed.)
1.3	2026	Added MON-SHAFT shaft-line condition-monitoring notation (Section 9.3) with submissions table and cross-references in the notation matrix/quick-guide; added hydraulic-system rule-basis note (Sec.14/Sec.15/piping, ISO 4413, fail-safe pitch). Added per-ship-type submission cover sheets (one-page tick-off) for 15 ship types plus a generic template.	Plan Approval Reference (expanded ed.)
1.4	2026	Readability/accessibility: switched to scalable Latin Modern fonts (crisp, selectable, searchable text) with microtype; enabled navigable PDF bookmarks (open, numbered) and FitH view; added “Navigating this PDF” guide; slightly opened line spacing.	Plan Approval Reference (expanded ed.)
1.5	2026	Rule-reference correction (verified against NR467 Jan. 2026):	Plan Approval Reference (ex

21.4 Important Disclaimers

! CRITICAL NOTICE FOR SURVEYORS:

1. **Verification Required:** This catalog is a reference guide compiled from Bureau Veritas rules. Always verify against the latest official BV rules and guidance notes.
2. **Rule Updates:** BV rules are updated periodically. Ensure you are working with the current version applicable to the vessel's build date and classification notation.
3. **Complex Cases:** For unusual thruster configurations, hybrid systems, or novel technologies, consult with BV technical specialists before approval.
4. **Project-Specific Requirements:** Some projects may have additional requirements beyond standard rules (e.g., owner specifications, flag state requirements, special notations).
5. **Overlapping Requirements:** When thrusters serve multiple functions (propulsion + steering, or DP + steering), ALL applicable requirements must be met.
6. **FMEA Critical:** For DP systems, the FMEA is the cornerstone document. Inadequate FMEA is grounds for rejection.
7. **Steering Gear Compliance:** If thrusters provide steering, full SOLAS steering gear requirements apply.
8. **Material Traceability:** All critical components must have traceable material certificates.
9. **Software Validation:** Control system software, especially for DP and steering functions, requires validation documentation.
10. **Cybersecurity:** Modern thruster control systems must address cybersecurity per latest BV guidance and IMO requirements.

! PLEASE CAREFULLY REVIEW THIS DOCUMENT

It may contain errors or omissions. Always verify against official BV rules.

Bureau Veritas

Thruster Requirements Comprehensive Surveyor Catalog

Document Version 1.7
2026

For Bureau Veritas Plan Approval Surveyors

Source Links:

<https://marine-offshore.bureauveritas.com/nr467-rules-classification-steel-ships>
<https://marine-offshore.bureauveritas.com/rules-classification-rule-notes-and-guidance-notes>
<https://rulesexplorer.bureauveritas.com/>