

---

## Checkpoint 2

p7zip

Arnav Nidumolu, Atharva Kale, Pascal von Fintel, Patrick  
Negus

2023-04-06

## Checkpoint 2

### Contents:

- [Checkpoint 2](#)
  - [Contents:](#)
  - [Static Analysis](#)
  - [Dynamic Analysis](#)

## **Static Analysis**

## Dynamic Analysis

```
Starting evaluation of codeql/cpp-queries/Security/CWE/CWE-704/WcharCharConversion.q1.
[42/47 eval 8ms] Evaluation done; writing results to codeql/cpp-queries/Security/CWE/CWE-676/DangerousUseOfCin.bqrs.
Starting evaluation of codeql/cpp-queries/Security/CWE/CWE-732/OpenCallMissingModeArgument.q1.
[43/47 eval 63ms] Evaluation done; writing results to codeql/cpp-queries/Security/CWE/CWE-704/WcharCharConversion.bqrs.
Starting evaluation of codeql/cpp-queries/Security/CWE/CWE-732/UnsafeDacLSecurityDescriptor.q1.
[44/47 eval 28ms] Evaluation done; writing results to codeql/cpp-queries/Security/CWE/CWE-732/OpenCallMissingModeArgument.bqrs.
Starting evaluation of codeql/cpp-queries/Summary/LinesOfCode.q1.
[45/47 eval 13ms] Evaluation done; writing results to codeql/cpp-queries/Security/CWE/CWE-732/UnsafeDacLSecurityDescriptor.bqrs.
Starting evaluation of codeql/cpp-queries/Summary/LinesOfUserCode.q1.
[46/47 eval 4ms] Evaluation done; writing results to codeql/cpp-queries/Summary/LinesOfCode.bqrs.
[47/47 eval 2.1s] Evaluation done; writing results to codeql/cpp-queries/Summary/LinesOfUserCode.bqrs.
Shutting down query evaluator.
Interpreting results.
Analysis produced the following diagnostic data:
```

Diagnostic	Summary
Successfully extracted files	44 results

```
Analysis produced the following metric data:
```

Metric	Value
Total lines of user written C/C++ code in the database	4129
Total lines of C/C++ code in the database	400756

```
→ codeql-playground git:(main) ✗ cat analysis.csv
→ codeql-playground git:(main) ✗
```

**american fuzzy lop ++4.07a {main-afl-} (...Bundles/Alone2/\_o/bin/7zz) [fast]**

process timing		overall results
run time	: 2 days, 13 hrs, 15 min, 48 sec	cycles done : 149
last new find	: 0 days, 0 hrs, 12 min, 9 sec	corpus count : 9166
last saved crash	: none seen yet	saved crashes : 0
last saved hang	: 0 days, 0 hrs, 13 min, 43 sec	saved hangs : 79
cycle progress	map coverage	findings in depth
now processing	: 7353.33 (80.2%)	map density : 0.91% / 5.65%
runs timed out	: 0 (0.00%)	count coverage : 5.25 bits/tuple
stage progress		
now trying	: splice 1	favorable items : 773 (8.43%)
stage execs	: 42/43 (97.67%)	new edges on : 1488 (16.23%)
total execs	: 117M	total crashes : 0 (0 saved)
exec speed	: 598.4/sec	total tmouts : 298 (0 saved)
fuzzing strategy yields	item geometry	
bit flips	: disabled (default, enable with -D)	levels : 33
byte flips	: disabled (default, enable with -D)	pending : 140
arithmetics	: disabled (default, enable with -D)	pend fav : 0
known ints	: disabled (default, enable with -D)	own finds : 8281
dictionary	: n/a	imported : 198
havoc/splice	: 5532/44.1M, 2749/73.6M	stability : <b>81.95%</b>
py/custom/rq	: unused, unused, unused, unused	
trim/eff	: disabled, disabled	

[cpu000:116%]

american fuzzy lop ++4.07a {variant-afl-tsan} (.../Alone2/\_o/bin/7zz) [fast]

process timing		overall results	
run time : 2 days, 13 hrs, 11 min, 34 sec		cycles done : <b>1</b>	
last new find : 0 days, 0 hrs, 16 min, 36 sec		corpus count : 7029	
last saved crash : none seen yet		saved crashes : 0	
last saved hang : 0 days, 0 hrs, 17 min, 57 sec		saved hangs : 91	
cycle progress		map coverage	
now processing : 1058.242 (15.1%)		map density : 6.77% / 24.98%	
runs timed out : 1 (0.01%)		count coverage : 5.52 bits/tuple	
stage progress		findings in depth	
now trying : splice 14		favored items : 672 (9.56%)	
stage execs : 9/12 (75.00%)		new edges on : 1251 (17.80%)	
total execs : 5.40M		total crashes : 0 (0 saved)	
exec speed : <b>37.03/sec (slow!)</b>		total tmouts : 191 (0 saved)	
fuzzing strategy yields		item geometry	
bit flips : disabled (default, enable with -D)		levels : 8	
byte flips : disabled (default, enable with -D)		pending : 2705	
arithmetics : disabled (default, enable with -D)		pend fav : 0	
known ints : disabled (default, enable with -D)		own finds : 1435	
dictionary : n/a		imported : 4907	
havoc/splice : 494/775k, 941/2.11M		stability : <b>69.15%</b>	
py/custom/rq : unused, unused, unused, unused			
trim/eff : 6.48%/2.46M, disabled			
		[cpu003: <b>150%</b> ]	

american fuzzy lop ++4.07a {variant-afl-msan} (.../Alone2/\_o/bin/7zz) [fast]

<b>process timing</b> run time : 2 days, 13 hrs, 14 min, 31 sec last new find : 0 days, 0 hrs, 2 min, 53 sec last saved crash : 0 days, 1 hrs, 13 min, 31 sec last saved hang : 0 days, 0 hrs, 36 min, 4 sec		<b>overall results</b> cycles done : 1 corpus count : 7427 saved crashes : 978 saved hangs : 94
<b>cycle progress</b> now processing : 4889*0 (65.8%) runs timed out : 26 (0.35%)	<b>map coverage</b> map density : 1.05% / 5.58% count coverage : 5.37 bits/tuple	
<b>stage progress</b> now trying : trim 8/8 stage execs : 27/90 (30.00%) total execs : 4.77M exec speed : 30.83/sec (slow!)	<b>findings in depth</b> favored items : 722 (9.72%) new edges on : 1327 (17.87%) total crashes : 220k (978 saved) total tmouts : 206 (0 saved)	
<b>fuzzing strategy yields</b> bit flips : disabled (default, enable with -D) byte flips : disabled (default, enable with -D) arithmetics : disabled (default, enable with -D) known ints : disabled (default, enable with -D) dictionary : n/a havoc/splice : 465/343k, 1270/1.46M py/custom/rq : unused, unused, unused, unused trim/eff : 6.55%/2.91M, disabled		<b>item geometry</b> levels : 5 pending : 2456 pend fav : 1 own finds : 1268 imported : 5472 stability : 74.96%
[cpu002:100%]		

[illegible]

## Static Analysis

We ran the codebase through the static analysis tool `cppcheck`, which tagged 1569 warnings and errors. One of the common errors flagged by `cppcheck` was `shiftTooManyBits`

Unfortunately, when looking at the actual source code, almost all of these errors come from an innocuous function:

```
#define GetUi64(p) (GetUi32(p) | ((UInt64)GetUi32(((const Byte *) (p)) + 4) << 32))

#define GetUi32(p) ( \
    ((const Byte *) (p))[0] | \
    ((UInt32)((const Byte *) (p))[1] << 8) | \
    ((UInt32)((const Byte *) (p))[2] << 16) | \
    ((UInt32)((const Byte *) (p))[3] << 24))
```

The rest, on closer inspection, are also falsely flagged as errors, such as this one:

[2594](#) shiftTooManyBits

[758](#) error

Shifting 32-bit value by 63 bits is undefined behaviour

```
2594     if (node.FileSize ≥ ((UInt64)1 << 63))
2595     |     return S_FALSE;
```

A more promising error seems to be a possible null pointer exception:

[390r-debugging-setup\p7zip\CPP\7zip\Archive\Zip\ZipHandlerOut.cpp](#)

[41](#) nullPointerRedundantCheck

[476](#) warning

Either the condition &#039;password&#039; is redundant or there is possible null pointer dereference: s++.

[41](#) nullPointerArithmeticRedundantCheck

[682](#) warning

Either the condition &#039;password&#039; is redundant or there is pointer arithmetic with NULL pointer.

```
37     static bool IsSimpleAsciiString(const wchar_t *s)
38     {
39         for (;;)
40         {
41             wchar_t c = *s++;
42             if (c == 0)
43                 return true;
44             if (c < 0x20 || c > 0x7F)
45                 return false;
46         }
47     }
```

This function is only called once, in the same file at line 415:



```

392     CMyComPtr<ICryptoGetTextPassword2> getTextPassword;
393     {
394         CMyComPtr<IArchiveUpdateCallback> udateCallBack2(callback);
395         udateCallBack2.QueryInterface(IID_ICryptoGetTextPassword2, &getTextPassword);
396     }
397     CCompressionMethodMode options;
398     (CBaseProps &)options = _props;
399     options._dataSizeReduce = largestSize;
400     options._dataSizeReduceDefined = largestSizeDefined;
401
402     options.PasswordIsDefined = false;
403     options.Password.Wipe_and_Empty();
404     if (getTextPassword)
405     {
406         CMyComBSTR_Wipe password;
407         Int32 passwordIsDefined;
408         RINOK(getTextPassword->CryptoGetTextPassword2(&passwordIsDefined, &password));
409         options.PasswordIsDefined = IntToBool(passwordIsDefined);
410         if (options.PasswordIsDefined)
411         {
412             if (!m_ForceAesMode)
413                 options.IsAesMode = thereAreAesUpdates;
414
415             if (!IsSimpleAsciiString(password))
416                 return E_INVALIDARG;

```

It looks like `password` gets populated in `CryptoGetTexPassword2`, looking at that function, and the subsequent call to `StringToBstr`, it unfortunately looks like the nullpointer is properly checked for.

```

97     STDMETHODIMP CUpdateCallback100Imp::CryptoGetTextPassword2(Int32 *passwordIsDefined, BSTR *password)
98     {
99         *password = NULL;
100         *passwordIsDefined = BoolToInt>PasswordIsDefined);
101         if (!PasswordIsDefined)
102             return S_OK;
103         return StringToBstr>Password, password);
104     }

```

```

77     inline HRESULT StringToBstr(LPCOLESTR src, BSTR *bstr)
78     {
79         *bstr = ::SysAllocString(src);
80         return (*bstr) ? S_OK : E_OUTOFMEMORY;
81     }

```