
O-RAN Work Group 10 (OAM for O-RAN)

Topology Exposure and Inventory Data Model Specification - Stage 3

Copyright © 2025 by the O-RAN ALLIANCE e.V.

The copying or incorporation into any other work of part or all of the material available in this specification in any form without the prior written permission of O-RAN ALLIANCE e.V. is prohibited, save that you may print or download extracts of the material of this specification for your personal use, or copy the material of this specification for the purpose of sending to individual third parties for their information provided that you acknowledge O-RAN ALLIANCE as the source of the material and that you inform the third party that these conditions apply to them and that they must comply with them.

O-RAN ALLIANCE e.V., Buschkauler Weg 27, 53347 Alfter, Germany

Register of Associations, Bonn VR 11238, VAT ID DE321720189

Contents

Foreword.....	3
Modal verbs terminology.....	3
Executive summary	3
1. Scope	4
2. References	4
2.1. Normative references	4
2.2. Informative references.....	4
3. Definition of terms, symbols and abbreviations.....	4
3.1. Terms.....	4
3.2. Symbols.....	4
3.3. Abbreviations	4
4. Solution Set (SS) definitions	5
4.1 YANG based Solution Set (SS) definitions.....	5
4.1.1 TE&IV Mapping from YANG to JSON schema	5
Annex A (normative): YANG definitions for common types and extensions.....	7
A.1 Generals.....	7
A.2 Common Modules	7
A.2.1 module o-ran-smo-teiv-common-yang-types.....	7
A.2.2 module o-ran-smo-teiv-common-yang-extensions	9
Annex B (normative): YANG definitions for O-RAN TE&IV RAN Domain.....	12
B.1 General	12
B.2 module o-ran-smo-teiv-ran.....	12
Annex C (normative): YANG definitions for O-RAN TE&IV Physical Domain.....	16
C.1 General	16
C.2 module o-ran-smo-teiv-physical.....	16
Annex D (normative): YANG definitions for O-RAN TE&IV Physical-RAN Domain.....	18
D.1 General	18
D.2 module o-ran-smo-teiv-rel-physical-ran.....	18
Annex E (informative): YANG based User Defined Data Input Schema	21
E.1 General	21
E.2 Example Module (Decorators and Classifiers)	21
E.3 Example Module (Classifiers).....	21
E.4 Example Module (Decorators)	22
Annex (informative): Change History	23

Foreword

This Technical Specification (TS) has been produced by WG10 of the O-RAN ALLIANCE.

The content of the present document is subject to continuing work within O-RAN and may change following formal O-RAN approval. Should the O-RAN ALLIANCE modify the contents of the present document, it will be re-released by O-RAN with an identifying change of version date and an increase in version number as follows:

version xx.yy.zz

where:

- xx: the first digit-group is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc. (the initial approved document will have xx=01). Always 2 digits with leading zero if needed.
- yy: the second digit-group is incremented when editorial only changes have been incorporated in the document. Always 2 digits with leading zero if needed.
- zz: the third digit-group included only in working versions of the document indicating incremental changes during the editing process. External versions never include the third digit-group. Always 2 digits with leading zero if needed.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the O-RAN Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in O-RAN deliverables except when used in direct citation.

Executive summary

The present document specifies the TE&IV Data Models suited to realize the TE&IV Information Models as specified in [1].

1. Scope

This document specifies the TE&IV Data Models used to support TE&IV services within the SMO.

2. References

2.1. Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies. In the case of a reference to a 3GPP document, a non-specific reference implicitly refers to the latest version of that document in Release 18.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, O-RAN cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] O-RAN.WG10.TS.TE&IV-CIMI.0: "Topology Exposure & Inventory Common Information Models and Interface Specification - Stage 2" ("TE&IV CIMI")
- [2] O-RAN.WG10.TS.TE&IV-API.0: "Topology Exposure & Inventory Application Protocols Specification - Stage 3" ("TE&IV API")
- [3] IETF RFC 7951: "JSON Encoding of Data Modeled with YANG"

2.2. Informative references

"Not Applicable"

3. Definition of terms, symbols and abbreviations

3.1. Terms

Void

3.2. Symbols

Void

3.3. Abbreviations

Void

4. Solution Set (SS) definitions

4.1 YANG based Solution Set (SS) definitions

The present document defines the following TE&IV Solution Set definitions for O-RAN:

- YANG based ORAN TEIV Common YANG Types and Extensions Solution Set (Annex A).
- YANG based ORAN TE&IV RAN Domain Solution Set (Annex B).
- YANG based ORAN TE&IV Physical Domain Solution Set (Annex C).
- YANG based ORAN TE&IV REL-Physical-RAN Domain Solution Set (Annex D).
- YANG based User Defined Data Schema (Annex E).

4.1.1 TE&IV Mapping from YANG to JSON schema

4.1.1.1 Introduction

As specified in Clause 5.3 of the TE&IV API Specification [2], responses with message content shall be in JSON format.

This clause defines the JSON mappings for the YANG schema specified in clause 4.1. Building on the principles outlined in RFC 7951 [3], the mappings specified here are extended to accommodate the YANG extensions in the O-RAN TE&IV YANG based Solution Set.

4.1.1.2 The “biDirectionalTopologyRelationship” Data Node

The biDirectionalTopologyRelationship data node describes a bi-directional relationship in the TE&IV model. It is a relationship comprising of an aSide and a bSide.

aSide and bSide are YANG extensions representing each end of the relationship. The order of aSide and bSide is important and must not be changed once defined. See TE&IV Common Information Models and Interface [1] Clause 4.2.1.1.4.1. Both aSide and bSide take a Topology Entity type as an argument. This entity type is represented by an instance identifier.

A biDirectionalTopologyRelationship instance is encoded as an object containing an array of nested objects, where each nested object represents child data nodes as its properties, as shown below.

A YANG example for the biDirectionalTopologyRelationship definition would be

```
or-teiv-yext:biDirectionalTopologyRelationship NFDEPLOYMENT_SERVES_ODUFUNCTION {  
  
  ...  
  key id;  
  
  leaf-list served-oduFunction {  
    description "O-DU Function served by this NF Deployment.";   
    or-teiv-yext:aSide or-teiv-cloud:NFDeployment;  
    type instance-identifier;  
  }  
  
  leaf-list serving-nFDeployment {  
    description "NF Deployment that serves this O-DU Function.";   
    or-teiv-yext:bSide or-teiv-ran:ODUFunction;  
    type instance-identifier;  
  }  
}
```

the following is an example of a valid JSON-encoded instance:

```
{  
  "o-ran-smo-teiv-rel-ran-cloud: NFDEPLOYMENT_SERVES_ODUFUNCTION": [  

```

```
{
  "id": "urn:<instance identifier of NFDeployment_serves_ODUFunction>",
  "serving-nfDeployment": "urn:<instance identifier of NFDeployment>",
  "served-oduFunction": "urn:<instance identifier of ODUFunction>",
  "sourceIds": [
    "urn:<instance source identifier of NFDeployment>",
    "urn:<instance source identifier of ODUFunction>"
  ]
}
```

Annex A (normative): YANG definitions for common types and extensions

A.1 Generals

This annex contains the YANG definitions for the common types and extensions to the YANG language that topology and inventory model will frequently use, in accordance with information model definitions specified in TE&IV CIMI [1].

A.2 Common Modules

A.2.1 module o-ran-smo-teiv-common-yang-types

```
<CODE BEGINS>
module o-ran-smo-teiv-common-yang-types {
  yang-version 1.1;
  namespace "urn:o-ran-smo-teiv-common-yang-types";
  prefix or-teiv-types;

  import o-ran-smo-teiv-common-yang-extensions { prefix or-teiv-yext; }

  import _3gpp-common-yang-types { prefix types3gpp; }

  organization "O-RAN Alliance";

  contact
    "www.o-ran.org";

  description
    "Topology and Inventory common types model.
    This model contains re-usable data types that topology and inventory models
    will frequently use as part of types and relationships.

    Copyright 2025 the O-RAN Alliance.

    THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS'
    AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
    IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
    ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE
    LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
    CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
    SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
    INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
    CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
    ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
    POSSIBILITY OF SUCH DAMAGE.

    Redistribution and use in source and binary forms, with or without
    modification, are permitted provided that the following conditions are met:

    * Redistributions of source code must retain the above copyright notice,
    this list of conditions and the above disclaimer.
    * Redistributions in binary form must reproduce the above copyright notice,
    this list of conditions and the above disclaimer in the documentation
    and/or other materials provided with the distribution.
    * Neither the Members of the O-RAN Alliance nor the names of its
    contributors may be used to endorse or promote products derived from
    this software without specific prior written permission.";

  revision "2025-06-30" {
    description "Added support for TE&IV User defined data";
    or-teiv-yext:label 1.2.0;
    reference "O-RAN.WG10.TE&IV-DM.0-R005-v03.00";
  }
}
```

```

revision "2025-02-24" {
    description "Renamed Adapter Entity to Origin Entity. Added Geo-Information";
    or-teiv-yext:label 1.1.0;
    reference "O-RAN.WG10.TE&IV-DM.0-R004-v02.00";
}

revision "2024-10-10" {
    description "Initial revision.";
    or-teiv-yext:label 1.0.0;
    reference "O-RAN.WG10.TE&IV-DM.0-R004-v01.00.00";
}

grouping Top_Grp_Type {
    description "Grouping containing the key attribute common to all types. All types MUST use this grouping.";

    leaf id {
        type string;
        description "Unique identifier of topology entities. Represents the Entity Instance Identifier.";
    }
}

grouping Origin_Entity_Mapping_Grp {
    description "Grouping to identify sourceIds on a topology object";

    leaf-list sourceIds {
        type sourceId;
        min-elements 1;
        ordered-by user;
        description
            "An ordered list of identities that represent the set of native
            source identifiers for participating entities.
            This must be attached to Topology Entity instance, outside of the
            declared Topology Entity's attributes. This is exposed to the
            consumers and can only be set by the responsible adapter. This
            cannot be instantiated, and it MUST NOT be augmented or deviated
            in any way, unless stated otherwise.";
    }
}

grouping Origin_Relationship_Mapping_Grp {
    description "Grouping to identify sourceIds on a topology relationship.";

    leaf-list sourceIds {
        type sourceId;
        min-elements 2;
        ordered-by user;
        description
            "An ordered list of identities that represent the set of native
            source identifiers for participating entities in the relationship.
            This must be attached to the Topology Relation instance, outside of the
            declared Topology Relationship's attributes. This is exposed to the
            consumers and can only be set by the responsible adapter. This
            cannot be instantiated, and it MUST NOT be augmented or deviated in
            any way, unless stated otherwise.";
    }
}

typedef sourceId {
    type string;
    description "An identity that represents a native identifier of a topology entity.";
}

grouping GeoInformation {
    description "A physical location with address and coordinates.";

    leaf address {
        type string;
        description "Address of the physical location.";
    }

    container coordinate {
        uses types3gpp:GeoCoordinateGrp;
        description "Geographical coordinate containing Latitude, Longitude and Altitude. Reference:
        3GPP TS 28.623";
    }
}

```

```

container decorators {
  description
    "This container serves as extension point for applications wishing
    to define their own decorators. This is done via augmentations. They
    can only be defined in name value pair.
    This is a consumer data and can be attached to Topology Entity or
    Topology Relation instance, outside of the declared Topology Entity
    or Topology Relationship's attributes. This cannot be instantiated,
    and it MUST NOT be augmented or deviated in any way, unless stated
    otherwise.";
}
leaf-list classifiers {
  type identityref { base classifier; }
  description
    "Consumer defined tags to topology entities and relationships.
    This is a consumer data and can be attached to Topology Entity or
    Topology Relation instance, outside of the declared Topology Entity
    or Topology Relationship's attributes. This cannot be instantiated,
    and it MUST NOT be augmented or deviated in any way, unless stated
    otherwise.";
}

identity classifier {
  description "The classifier is used as a base to provide all classifiers
  with identity. ";
}
}
<CODE ENDS>

```

A.2.2 module o-ran-smo-teiv-common-yang-extensions

```

<CODE BEGINS>
module o-ran-smo-teiv-common-yang-extensions {
  yang-version 1.1;
  namespace "urn:o-ran-smo-teiv-common-yang-extensions";
  prefix or-teiv-yext;

  organization "O-RAN Alliance";

  contact
    "www.o-ran.org";

  description
    "Topology and Inventory YANG extensions model.
    This model contains extensions to the YANG language that topology and
    inventory models will use to define and annotate types and relationships.

    Copyright 2025 the O-RAN Alliance.

    THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS'
    AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
    IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
    ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE
    LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
    CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
    SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
    INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
    CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
    ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
    POSSIBILITY OF SUCH DAMAGE.

    Redistribution and use in source and binary forms, with or without
    modification, are permitted provided that the following conditions are met:

    * Redistributions of source code must retain the above copyright notice,
    this list of conditions and the above disclaimer.
    * Redistributions in binary form must reproduce the above copyright notice,
    this list of conditions and the above disclaimer in the documentation
    and/or other materials provided with the distribution.
    * Neither the Members of the O-RAN Alliance nor the names of its
    contributors may be used to endorse or promote products derived from
    this software without specific prior written permission.";

  revision "2025-02-14" {
    description "Updates for bi-directional relationship.";
  }
}

```

```

    or-teiv-yext:label 1.1.0;
reference "O-RAN.WG10.TE&IV-DM.0-R004-v02.00";
}

```

```

revision "2024-10-10" {
    description "Initial revision.";
    or-teiv-yext:label 1.0.0;
    reference "O-RAN.WG10.TE&IV-DM.0-R004-v01.00";
}

```

```

extension biDirectionalTopologyRelationship {
    argument relationshipName;
    description
        "Defines a bi-directional relationship in the topology.
        A bi-directional-association (BDA) is a relationship comprising of
        an aSide and a bSide. The aSide is considered the originating
        side of the relationship; the bSide is considered the terminating
        side of the relationship. The order of aSide and bSide is of
        importance and MUST NOT be changed once defined."
}

```

Both aSide and bSide are defined on a type, and are given a role. A type may have multiple originating and/or terminating sides of a relationship, all distinguished by role name.

The statement MUST only be a substatement of the 'module' statement. Multiple 'biDirectionalTopologyRelationship' statements are allowed per parent statement.

Substatements to the 'biDirectionalTopologyRelationship' define the aSide and the bSide, respectively, and optionally properties of the relationship. Data nodes of types 'leaf' and 'leaf-list' are used for this purpose. One of the data nodes MUST be annotated with the 'aSide' extension; another data node MUST be annotated with the 'bSide' extension. Other data nodes define properties of the relationship.

The argument is the name of the relationship. The relationship name is scoped to the namespace of the declaring module and MUST be unique within the scope.";

```

}

```

```

extension aSide {
    argument aSideType;
    description
        "Defines the aSide of a relationship."
}

```

The statement MUST only be a substatement of a 'leaf' or 'leaf-list' statement, which itself must be a substatement of the 'biDirectionalTopologyRelationship' statement.

The data type of the parent 'leaf' or 'leaf-list' MUST be 'instance-identifier'. Constraints MAY be used as part of the parent 'leaf' or 'leaf-list' to enforce cardinality.

The identifier of the parent 'leaf' or 'leaf-list' is used as name of the role of the aSide of the relationship. The name of the role is scoped to the type on which the aSide is defined and MUST be unique within the scope.

While the parent 'leaf' or 'leaf-list' does not result in a property of the relationship, it is RECOMMENDED to avoid using the name of an existing type property as role name to avoid potential ambiguities between properties of a type, and roles of a relationship on the type.

The argument is the name of the type on which the aSide resides. If the type is declared in another module, the type must be prefixed, and a corresponding 'import' statement be used to declare the prefix.";

```

}

```

```

extension bSide {
    argument bSideType;
    description
        "Defines the bSide of a relationship."
}

```

The statement MUST only be a substatement of a 'leaf' or 'leaf-list' statement, which itself must be a substatement of the

'biDirectionalTopologyRelationship' statement.

The data type of the parent 'leaf' or 'leaf-list' MUST be 'instance-identifier'. Constraints MAY be used as part of the parent 'leaf' or 'leaf-list' to enforce cardinality.

The identifier of the parent 'leaf' or 'leaf-list' is used as name of the role of the bSide of the relationship. The name of the role is scoped to the type on which the bSide is defined and MUST be unique within the scope. While the parent 'leaf' or 'leaf-list' does not result in a property of the relationship, it is RECOMMENDED to avoid using the name of an existing type property as role name to avoid potential ambiguities between properties of a type, and roles of a relationship on the type.

The argument is the name of the type on which the bSide resides. If the type is declared in another module, the type must be prefixed, and a corresponding 'import' statement be used to declare the prefix.";

}

```
extension domain {
  argument domainName;
  description "Keyword used to carry domain information.";
}
```

```
extension label {
  argument semversion;
  description
    "The label can be used to give modules and submodules a semantic
    version, in addition to their revision.
```

The format of the label is 'x.y.z' - expressed as pattern, it is [0-9]+\.[0-9]+\.[0-9]+

The statement MUST only be a substatement of the revision statement. Zero or one revision label statements per parent statement are allowed.

Revision labels MUST be unique amongst all revisions of a module or submodule.";

}

<CODE ENDS>

Annex B (normative): YANG definitions for O-RAN TE&IV RAN Domain

B.1 General

This annex contains the YANG definitions for the TE&IV RAN domain, in accordance with ORAN.SMO.TEIV.RAN information model definitions specified in TE&IV CIMI [1].

B.2 module o-ran-smo-teiv-ran

```
<CODE BEGINS>
module o-ran-smo-teiv-ran {
  yang-version 1.1;
  namespace "urn:o-ran:smo-teiv-ran";
  prefix or-teiv-ran;

  import o-ran-smo-teiv-common-yang-types {prefix or-teiv-types; }

  import o-ran-smo-teiv-common-yang-extensions {prefix or-teiv-yext; }

  import _3gpp-common-yang-types { prefix types3gpp; }

  organization "O-RAN Alliance";

  contact
    "www.o-ran.org";

  description
    "RAN Logical topology model.
    This model contains the topology entities and relations in the
    RAN Logical domain, which represents the functional capability
    of the deployed RAN that are relevant to rApps use cases.

    Copyright 2025 the O-RAN Alliance.

    THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS'
    AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
    IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
    ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE
    LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
    CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
    SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
    INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
    CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
    ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
    POSSIBILITY OF SUCH DAMAGE.

    Redistribution and use in source and binary forms, with or without
    modification, are permitted provided that the following conditions are met:

    * Redistributions of source code must retain the above copyright notice,
    this list of conditions and the above disclaimer.
    * Redistributions in binary form must reproduce the above copyright notice,
    this list of conditions and the above disclaimer in the documentation
    and/or other materials provided with the distribution.
    * Neither the Members of the O-RAN Alliance nor the names of its
    contributors may be used to endorse or promote products derived from
    this software without specific prior written permission."

  revision "2025-02-14" {
    description "Revision to rename adapter group to origin group.";
    or-teiv-yext:label 1.1.0;
    reference "O-RAN.WG10.TE&IV-DM.0-R004-v02.00";
  }

  revision "2024-10-10" {
```

```
description "Initial revision.";
or-teiv-yext:label 1.0.0;
reference "O-RAN.WG10.TE&IV-DM.0-R004-v01.00";
}
```

```
or-teiv-yext:domain RAN;
```

```
list ODUFfunction {
  uses or-teiv-types:Top_Grp_Type;
  uses or-teiv-types:Origin_Entity_Mapping_Grp;
  key id;
  description "O-RAN Distributed Unit (O-DU)."
```

The O-DU is an O-RAN NF in the O-RAN Architecture. An O-DU, combined with one or more O-RU(s) connected to it, supports and is fully compatible with the functions of a gNB-DU as defined by 3GPP TS 38.401.

The O-DU terminates the E2 and the F1 interface, and the Open Fronthaul interface (also known as LLS interface) as well as the RLC, MAC, and High-PHY functions of the radio interface towards the UE.

Note: O-DU is a concrete class that extends the ORANNetworkFunction abstract class. In Topology, you can create, read, update, and delete the O-DU object.

The management characteristics of the O-DU O-RAN NF is represented by the IOC GNBDUFunction as specified in 3GPP NR NRM model, as per 3GPP TS 28.541";

```
container attributes {
  description "Container for O-RAN Distributed Unit (O-DU) attributes";
  leaf gNBIDid {
    type int64;
    description "Unique identifier for the DU within a gNodeB";
  }

  leaf gNBID {
    type int64;
    description "Identity of gNodeB within a PLMN";
  }

  leaf gNBIDLength {
    type int32;
    description "Length of gNBID bit string representation";
  }
}
```

```
list OCUCPFunction {
  uses or-teiv-types:Top_Grp_Type;
  uses or-teiv-types:Origin_Entity_Mapping_Grp;
  key id;
```

```
description "O-RAN Central Unit - Control Plane (O-CU-CP)"
```

The O-CU-CP terminates the NG-c, X2-c, Xn-c, F1-c, and E1 interfaces as well as the RRC and PDCP (for SRB) protocols towards the UE as defined by 3GPP TS 38.401. The O-CU-CP terminates E2 interface to Near-RT RIC and is managed via O1 interface by the SMO.

Note: O-CU-CP is a concrete class that extends the ORANNetworkFunction abstract class. In Topology, you can create, read, update, and delete the O-CU-CP object.

The management characteristics of the O-CU-CP O-RAN NF is represented by the IOC GNBCUCPFunction as specified in 3GPP NR NRM model, as per 3GPP TS 28.541";

```
container attributes {
  description "Container for O-RAN Central Unit - Control Plane (O-CU-CP) attributes";
  leaf gNBCUName {
    type string;
    description "Name of gNodeB-CU";
  }

  leaf gNBID {
    type int64;
    description "Identity of gNodeB within a PLMN";
  }

  leaf gNBIDLength {
    type int32;
    description "Length of gNBID bit string representation";
  }

  container plmnId {
    description "PLMN identifier to be used as part of global RAN node identity";
    uses types3gpp:PLMNId;
  }
}
```

```

    }
}

list OCUUPFunction {
    uses or-teiv-types:Top_Grp_Type;
    uses or-teiv-types:Origin_Entity_Mapping_Grp;
    key id;

    description "O-RAN Central Unit - User Plane (O-CU-UP)"
        The O-CU-UP terminates the NG-u, X2-u, Xn-u, F1-u, and E1 interfaces as well as the PDCP and SDAP
        protocols towards the UE as defined by 3GPP TS 38.401. The O-CU-UP terminates E2 interface to Near-RT RIC
        and is managed via O1 interface by the SMO.
        Note: O-CU-UP is a concrete class that extends the ORANNetworkFunction abstract class. In Topology,
        you can create, read, update, and delete the O-CU-UP object.
        The management characteristics of the O-CU-UP O-RAN NF is represented by the IOC GNBCUUPFunction as
        specified in 3GPP NR NRM model, as per 3GPP TS 28.541";

    container attributes {
        description "Container for O-RAN Central Unit - User Plane (O-CU-UP) attributes";
        leaf gNBId {
            type int64;
            description "Identity of gNodeB within a PLMN";
        }

        leaf gNBIdLength {
            type int32;
            description "Length of gNBId bit string representation";
        }

        list pLMNIdList {
            key "mcc mnc";
            description "List of unique identities for PLMN";
            uses types3gpp:PLMNId;
        }
    }
}

list NearRTRICFunction {
    uses or-teiv-types:Top_Grp_Type;
    uses or-teiv-types:Origin_Entity_Mapping_Grp;
    key id;

    description "Near-Real-Time RAN Intelligent Controller (Near-RT RIC)"
        Near-RT RIC is an O-RAN NF that enables near real-time control and optimization of services and
        resources of E2 Nodes via fine-grained data collection and actions over the E2 interface with control
        loops in the order of 10 ms-1s.";

    container attributes {
        description "Container for Near-Real-Time RAN Intelligent Controller (Near-RT RIC) attributes";
        container pLMNId {
            description "PLMN identifier to be used as part of global RAN node identity";
            uses types3gpp:PLMNId;
        }

        leaf nearRtRicId {
            type int32;
            description "Identifier of Near-RT RIC";
        }
    }
}

list ORUFunction {
    uses or-teiv-types:Top_Grp_Type;
    uses or-teiv-types:Origin_Entity_Mapping_Grp;
    key id;

    description "O-RAN Radio Unit (O-RU)"
        The O-RU terminates the Open Fronthaul interface (also known as LLS interface) as well as Low-PHY
        functions of the radio interface towards the UE. This is deployed as a PNF.
        The O-RU terminates the Open Fronthaul M-Plane interface towards the O-DU and SMO.";

    container attributes {
        description "Container for O-RAN Radio Unit (O-RU) attributes";
        leaf oruId {
            type string;

```

```
        description "Identity of the O-RU as discovered from the source domain based on M-Plane
architecture model";
    }
}
}
<CODE ENDS>
```

Annex C (normative): YANG definitions for O-RAN TE&IV Physical Domain

C.1 General

This annex contains the YANG definitions for the TE&IV Physical domain, in accordance with ORAN.SMO.TEIV.Physical information model definitions specified in TE&IV CIMI [1].

C.2 module o-ran-smo-teiv-physical

```
<CODE BEGINS>
module o-ran-smo-teiv-physical {
  yang-version 1.1;
  namespace "urn:o-ran-smo-teiv-physical";
  prefix or-teiv-physical;

  import o-ran-smo-teiv-common-yang-types {prefix or-teiv-types; }

  import o-ran-smo-teiv-common-yang-extensions {prefix or-teiv-yext; }

  organization "O-RAN Alliance";

  contact
    "www.o-ran.org";

  description
    "Physical domain topology model.
    This model contains the topology entities and relations in the
    Physical domain.

    Copyright 2025 the O-RAN Alliance.

    THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS'
    AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
    IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
    ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE
    LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
    CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
    SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
    INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
    CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
    ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
    POSSIBILITY OF SUCH DAMAGE.

    Redistribution and use in source and binary forms, with or without
    modification, are permitted provided that the following conditions are met:

    * Redistributions of source code must retain the above copyright notice,
    this list of conditions and the above disclaimer.
    * Redistributions in binary form must reproduce the above copyright notice,
    this list of conditions and the above disclaimer in the documentation
    and/or other materials provided with the distribution.
    * Neither the Members of the O-RAN Alliance nor the names of its
    contributors may be used to endorse or promote products derived from
    this software without specific prior written permission."

  revision "2025-06-30" {
    description "Updated revision to add container attribute for site.";
    or-teiv-yext:label 1.1.0;
    reference "O-RAN.WG10.TE&IV-DM.0-R005-v03.00";
  }

  revision "2025-02-10" {
    description "Initial revision.";
    or-teiv-yext:label 1.0.0;
    reference "O-RAN.WG10.TE&IV-DM.0-R004-v02.00";
  }
}
```

```

or-teiv-yext:domain PHYSICAL;

list PhysicalAppliance {
  uses or-teiv-types:Top_Grp_Type;
  uses or-teiv-types:Origin_Entity_Mapping_Grp;
  key id;

  description "Represents the Physical Appliance in the Physical domain";

  container attributes {
    description "Container for Physical Appliance attributes";
    leaf vendorName {
      type string;
      description "Name of the physical appliance vendor";
    }

    leaf modelName {
      type string;
      description "Name of the physical appliance model";
    }
  }
}

list Site {
  uses or-teiv-types:Top_Grp_Type;
  uses or-teiv-types:Origin_Entity_Mapping_Grp;
  key id;
  description "Represents the Site in the Physical domain";
  container attributes {
    description "Container for Site attributes";
    container siteLocation {
      description "Representation of physical site location";
      uses or-teiv-types:GeoInformation;
    }
    leaf siteName {
      type string;
      description "Human readable name of the physical site as identified by the mobile network
operator";
    }
  }
}

or-teiv-yext:biDirectionalTopologyRelationship PHYSICALAPPLIANCE_INSTALLEDAT_SITE { // 1..n to 1..m
  uses or-teiv-types:Top_Grp_Type;
  uses or-teiv-types:Origin_Relationship_Mapping_Grp;
  key id;
  description "The aSide of this relationship is an instance of the PhysicalAppliance type.
The bSide of this relationship is an instance of the Site type.";

  leaf-list installing-site {
    type instance-identifier;
    description "Site installing PhysicalAppliance.";
    or-teiv-yext:aSide PhysicalAppliance;
  }

  leaf-list installed-physicalAppliance {
    type instance-identifier;
    description "PhysicalAppliance installed at Site.";
    or-teiv-yext:bSide Site;
  }
}
}
<CODE ENDS>

```

Annex D (normative): YANG definitions for O-RAN TE&IV Physical-RAN Domain

D.1 General

This annex contains the YANG definitions for the TE&IV REL-Physical-RAN domain, in accordance with ORAN.SMO.TEIV.REL-Physical-RAN information model definitions specified in TE&IV CIMI [1].

D.2 module o-ran-smo-teiv-rel-physical-ran

```
<CODE BEGINS>
module o-ran-smo-teiv-rel-physical-ran {
  yang-version 1.1;
  namespace "urn:o-ran-smo-teiv-rel-physical-ran";
  prefix or-teiv-rel-phyran;

  import o-ran-smo-teiv-common-yang-types {prefix or-teiv-types; }

  import o-ran-smo-teiv-common-yang-extensions {prefix or-teiv-yext; }

  organization "O-RAN Alliance";

  contact
    "www.o-ran.org";

  description
    "Physical to RAN Logical topology domain model.

    This model contains the topology relationship between the
    physical domain and the RAN domain.

    Copyright 2025 the O-RAN Alliance.

    THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS'
    AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
    IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
    ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE
    LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
    CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
    SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
    INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
    CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
    ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
    POSSIBILITY OF SUCH DAMAGE.

    Redistribution and use in source and binary forms, with or without
    modification, are permitted provided that the following conditions are met:

    * Redistributions of source code must retain the above copyright notice,
    this list of conditions and the above disclaimer.
    * Redistributions in binary form must reproduce the above copyright notice,
    this list of conditions and the above disclaimer in the documentation
    and/or other materials provided with the distribution.
    * Neither the Members of the O-RAN Alliance nor the names of its
    contributors may be used to endorse or promote products derived from
    this software without specific prior written permission.";

  revision "2025-02-10" {
    description "Initial revision.";
    or-teiv-yext:label 1.0.0;
    reference "O-RAN.WG10.TE&IV-DM.0-R004-v02.00";
  }

  or-teiv-yext:domain REL_PHYSICAL_RAN;

  or-teiv-yext:biDirectionalTopologyRelationship PHYSICALAPPLIANCE_SERVES_ODUFUNCTION { // 1..n to 1..m
    uses or-teiv-types:Top_Grp_Type;
  }
}
```

```

uses or-teiv-types:Origin_Relationship_Mapping_Grp;
key id;
description "The aSide of this relationship is an instance of the PhysicalAppliance type.
The bSide of this relationship is an instance of the ODUFfunction type.";

leaf-list served-oduFunction {
    type instance-identifier;
    description "ODUFfunction served by PhysicalAppliance.";
    or-teiv-yext:aSide or-teiv-physical:PhysicalAppliance;
}

leaf-list serving-physicalAppliance {
    type instance-identifier;
    description "PhysicalAppliance serving ODUFfunction.";
    or-teiv-yext:bSide or-teiv-ran:ODUFfunction;
}
}

or-teiv-yext:biDirectionalTopologyRelationship PHYSICALAPPLIANCE_SERVES_OCUCPFUNCTION { // 1..n to 1..m

    uses or-teiv-types:Top_Grp_Type;
    uses or-teiv-types:Origin_Relationship_Mapping_Grp;
    key id;
    description "The aSide of this relationship is an instance of the PhysicalAppliance type.
    The bSide of this relationship is an instance of the OCUCPFfunction type.";

    leaf-list served-ocucpfFunction {
        type instance-identifier;
        description "OCUCPFfunction served by PhysicalAppliance.";
        or-teiv-yext:aSide or-teiv-physical:PhysicalAppliance;
    }

    leaf-list serving-physicalAppliance {
        type instance-identifier;
        description "PhysicalAppliance serving OCUCPFfunction.";
        or-teiv-yext:bSide or-teiv-ran:OCUCPFfunction;
    }
}

or-teiv-yext:biDirectionalTopologyRelationship PHYSICALAPPLIANCE_SERVES_OCUUPFUNCTION { // 1..n to 1..m

    uses or-teiv-types:Top_Grp_Type;
    uses or-teiv-types:Origin_Relationship_Mapping_Grp;
    key id;
    description "The aSide of this relationship is an instance of the PhysicalAppliance type.
    The bSide of this relationship is an instance of the OCUUPFunction type.";

    leaf-list served-ocuupFunction {
        type instance-identifier;
        description "OCUUPFunction served by PhysicalAppliance.";
        or-teiv-yext:aSide or-teiv-physical:PhysicalAppliance;
    }

    leaf-list serving-physicalAppliance {
        type instance-identifier;
        description "PhysicalAppliance serving OCUUPFunction.";
        or-teiv-yext:bSide or-teiv-ran:OCUUPFunction;
    }
}

or-teiv-yext:biDirectionalTopologyRelationship PHYSICALAPPLIANCE_SERVES_NEARRTRICFUNCTION { // 1..n to
1..m

    uses or-teiv-types:Top_Grp_Type;
    uses or-teiv-types:Origin_Relationship_Mapping_Grp;
    key id;
    description "The aSide of this relationship is an instance of the PhysicalAppliance type.
    The bSide of this relationship is an instance of the NearRTRICFunction type.";

    leaf-list served-nearRTRICFunction {
        type instance-identifier;
        description "NearRTRICFunction served by PhysicalAppliance.";
        or-teiv-yext:aSide or-teiv-physical:PhysicalAppliance;
    }

    leaf-list serving-physicalAppliance {

```

```
    type instance-identifier;  
    description "PhysicalAppliance serving NearRTRICFunction.";   
    or-teiv-yext:bSide or-teiv-ran:NearRTRICFunction;  
  }  
}  
<CODE ENDS>
```

Annex E (informative): YANG based User Defined Data Input Schema

E.1 General

This annex contains the YANG schema input files for the User Defined Data specified in TE&IV CIMI [1]. Before classifying the entities or the relationships in the topology network, the modules defined in the clauses below must be created and validated by using its own endpoint as shown in TE&IV API [2]. The user must provide a unique module name, to avoid collision of multiple users access that are defining classifiers and decorators. The schema cannot be modified later on but only deleted and recreated, if needed. Once a schema is successfully created and validated, the user can add the classifiers to the entities or relationships. The following clauses provide example templates for the schema input files.

E.2 Example Module (Decorators and Classifiers)

```
<CODE BEGINS>
module module-rapp-module {

    yang-version 1.1;
    namespace "urn:module-rapp-model";
    prefix module;

    import o-ran-smo-teiv-common-yang-types { prefix module; }
    import o-ran-smo-teiv-common-yang-extensions {prefix or-teiv-yext; }

    revision "2024-06-10" {
        description
            "Initial revision.";
        or-teiv-yext:label 0.3.0;
    }

    augment /module:decorators {
        leaf decorator1 {
            type string;
        }
        leaf decorator2 {
            type boolean;
        }
        leaf decorator3 {
            type uint32;
        }
    }

    identity classifier1 {
        base module:classifiers;
    }

    identity classifier2 {
        base module:classifiers;
    }

    identity classifier3 {
        base module:classifiers;
    }
}
<CODE ENDS>
```

E.3 Example Module (Classifiers)

```
<CODE BEGINS>
module classifier-module-example {

    yang-version 1.1;
```

```
namespace "urn:classifier-module-example";
prefix module;

import o-ran-smo-teiv-common-yang-types { prefix module; }
import o-ran-smo-teiv-common-yang-extensions {prefix or-teiv-yext; }

revision "2025-05-10" {
    description
        "Initial revision.";
    or-teiv-yext:label 1.0.0;
}

identity classifier1 {
    base module:classifiers;
}

identity classifier2 {
    base module:classifiers;
}

identity classifier3 {
    base module:classifiers;
}
}
<CODE ENDS>
```

E.4 Example Module (Decorators)

```
<CODE BEGINS>
module module-rapp-module {

    yang-version 1.1;
    namespace "urn:module-rapp-model";
    prefix module;

    import o-ran-smo-teiv-common-yang-types { prefix module; }
    import o-ran-smo-teiv-common-yang-extensions {prefix or-teiv-yext; }

    revision "2025-05-10" {
        description
            "Initial revision.";
        or-teiv-yext:label 0.3.0;
    }

    augment /module:decorators {
        leaf decorator1 {
            type string;
        }
        leaf decorator2 {
            type boolean;
        }
        leaf decorator3 {
            type uint32;
        }
    }
}
<CODE ENDS>
```

Annex (informative): Change History

Date	Revision	Description
2024.10.01	00.00.01	Initial proposed skeleton for the TE&IV Data Model Specification
2024.11.21	01.00	Implemented the following CRs for the November 2024 train: ERI-2024.08.14-WG10-CR-0128-Initial Content for the TE&IV Data Model Specification-v01, ERI-2024.10.09-WG10-CR-0130-TE&IV_RAN_Model-v02, ERI-2024.11.07-WG10-CR-0136-TE&IV_DM_ReferenceUpdate-v01
2025.02.07	02.00	Implemented the following CRs for the March 2025 train: ERI-2024.12.10-WG10-CR-0139-TE&IV Mapping from YANG to JSON schema-v02, ERI.AO-2025.02.10-WG10-CR-0152-Update to TE&IV YANG Schema to JSON output-v01, ERI-2025.02.25-WG10-CR-0154-Update to existing TE&IV yang modules, ERI-2025.02.25-WG10-CR-0155-Introducing new yang extensions, ERI.AO-2025.02.25-WG10-CR-0156-Yang module for the Rel-Physical-RAN namespace, ERI.AO-2025.02.25-WG10-CR-0157-Yang module for the Physical namespace
2025.07.01	03.00	Implemented the following CRs for the July 2025 train: ERI-2025.05.20-WG10-CR-0176-YANG-Definitions-for-Classifiers-and-Decorators-v02, ERI-2025.05.26-WG10-CR-0177-Updating-3GPP-reference-v01, ERI-2025.06.25-WG10-CR-0188-Data Model editorials-v02. Updated the specification for formatting corrections and editorial updates based on ODR and TS template v04