



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

CENTRAL RESERVE PROCUREMENT DIRECTORATE MINISTRY OF HOME AFFAIRS, GOVERNMENT OF INDIA

OFFICE OF THE DIRECTOR GENERAL (PROCUREMENT) | LODHI ROAD, NEW DELHI — 110 003

TECHNICAL SPECIFICATIONS AND PERFORMANCE REQUIREMENTS

Tender Reference: CRPF/PPE/2026/001 | Procurement of Protective Equipment and Associated Technical Supplies

Rev.	Date	Description of Change	Prepared By	Approved By
1.0	15 Sep 2026	Initial issue — fictional training document	Procurement Cell, CRPD	DG (Procurement), CRPD
—	—	(Reserved for future revision)	—	—

FICTIONAL PROCUREMENT TRAINING DOCUMENT — All specifications, values, product names, reference numbers and test results contained herein are entirely fictitious and have been created exclusively to test an automated tender-evaluation system. NOT AN OFFICIAL GOVERNMENT DOCUMENT.

1. INTRODUCTION

- This document constitutes the Technical Specifications and Performance Requirements (hereinafter "Technical Specification" or "TS") for the procurement of Protective Equipment and Associated Technical Supplies under Tender Reference CRPF/PPE/2026/001 issued by the Central Reserve Procurement Directorate (CRPD), Ministry of Home Affairs (MHA), Government of India.
- These Technical Specifications form Schedule-II of the Tender Document and shall be read in conjunction with Schedule-I (Notice Inviting Tender), Schedule-III (Eligibility Criteria), Schedule-IV (Price Schedule), and all Annexures and Addenda issued thereunder.
- All specifications prescribed herein represent **minimum acceptable performance thresholds**. Bidders are encouraged to offer equipment meeting or exceeding the stated minima. Equipment not meeting even one mandatory parameter shall be treated as technically non-compliant and shall be rejected without further evaluation.
- This Technical Specification document is issued under Document No. **CRPD/TECH/2026/PPE/A3**, Revision 1.0, dated 15 September 2026.

2. SCOPE OF TECHNICAL SPECIFICATIONS

- These Technical Specifications apply to all six (6) line items in the Schedule of Requirements. Item-specific sub-specifications are provided in Clause 4 onward. Where a parameter is listed without a specific item qualifier, it applies to all items unless explicitly stated otherwise.

Item No.	Item Description	Fictional Spec. Code	Quantity
Item 1	Anti-Riot Helmet	FPS-2026-H01	2,500 Nos.
Item 2	Ballistic Body Armour Vest — Level IIIA	FPS-2026-B02	1,800 Nos.
Item 3	Fire-Retardant Overalls	FPS-2026-F03	5,000 Sets
Item 4	Protective Knee and Elbow Guard Set	FPS-2026-G04	3,200 Sets
Item 5	Lightweight Polycarbonate Shield	FPS-2026-S05	800 Nos.
Item 6	Technical Documentation and Training Dataset Package	FPS-2026-TD06	1 Lot

3. PRODUCT / SERVICE DESCRIPTION



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

3.1 Anti-Riot Helmet (Spec. FPS-2026-H01)

A full-face protective helmet designed for law-enforcement anti-riot and crowd-control operations. The helmet shall provide protection to the skull, face and neck region against blunt impacts, stone-pelting, low-velocity projectiles and chemical splash. The visor shall be optically clear, distortion-free polycarbonate. The shell shall be constructed from high-impact thermoplastic or composite material. Integrated chin-strap and padded suspension harness shall provide adjustable fit for head circumferences in the range 54–62 cm. The helmet shall conform to IS 4151:2015 (Protective Helmets) or equivalent.

3.2 Ballistic Body Armour Vest — Level IIIA (Spec. FPS-2026-B02)

A soft armour vest providing ballistic protection at National Institute of Justice (NIJ) Standard 0101.07 Level IIIA or equivalent BIS/DRDO standard. The vest shall protect against 9 mm FMJ RN (Full Metal Jacketed Round Nose) ammunition at up to 436 m/s and .44 Magnum SJHP at up to 436 m/s. The vest shall be ambidextrous, featuring front and rear armour panels with MOLLE-compatible carrier in olive/khaki colour. Stab resistance shall be rated ≥ KR1 per HOSDB UK standard.

3.3 Fire-Retardant Overalls (Spec. FPS-2026-F03)

One-piece coverall manufactured from inherently flame-retardant (IFR) fabric providing protection against thermal exposure, molten metal splatter and electric arc. Fabric shall conform to IS 11871:2018 (Protective Clothing — Flame Retardant). The garment shall incorporate antistatic threads throughout. Seams shall be double-stitched with FR thread. Reflective tape (retro-reflective, silver, 50 mm wide) on shoulders and lower legs. Compliant with EN 469:2020 (heat and flame) or equivalent.

3.4 Protective Knee and Elbow Guard Set (Spec. FPS-2026-G04)

Ergonomic hard-shell knee and elbow guards with high-density EVA foam backing for impact absorption. Shell material: injection-moulded ABS or HDPE thermoplastic, minimum thickness 4 mm. Guard set shall be adjustable via dual Velcro straps. Shall conform to EN 13594:2015 (Protective Gloves for Motorcycle Riders — adapted) or equivalent impact-attenuation standard. Supplied in matched sets of 4 (2 knee + 2 elbow).

3.5 Lightweight Polycarbonate Shield (Spec. FPS-2026-S05)

Anti-riot transparent shield, dimensions 600 mm (W) × 900 mm (H) × minimum 5 mm (T), constructed from clear optical-grade polycarbonate. Shall provide protection against blunt impacts (BS 7971-4:2000 Level 2 or equivalent) and resist penetration by sharp objects. Arm-strap handle with foam grip. Edge protection: black ABS extrusion. Light transmittance ≥ 85%. Mass ≤ 2.8 kg per shield.

3.6 Technical Documentation and Training Dataset Package (Spec. FPS-2026-TD06)

A structured digital and printed documentation package comprising: (a) User Manuals for each item in English and Hindi (editable PDF and printed), (b) Maintenance and Inspection Schedules, (c) Training slide decks in PPTX format, and (d) a structured Tender Evaluation Test Dataset in JSON and CSV formats for automated system testing (fictional data only). Supplied on encrypted USB drives (AES-256) plus 5 hard copies per manual.

4. TECHNICAL PARAMETERS AND MINIMUM REQUIRED SPECIFICATIONS

The following table lists all measurable technical parameters with minimum acceptable thresholds. The column **Bidder Offered Value** shall be completed by the bidder for each parameter and submitted as part of the Technical Bid. The column **Compliance** shall be marked **YES / NO / N/A** by the bidder. Any field left blank shall be treated as non-compliant.

Sr. No.	Item Ref.	Parameter	Minimum Requirement (with Unit)	Bidder Offered Value	Comply (Y/N/N/A)
		— ITEM 1: ANTI-RIOT HELMET (FPS-2026-H01) —			
1	Item 1	Shell Material — Impact Resistance			
2	Item 1	Visor Material and Optical Quality	Polycarbonate; minimum thickness 4.0 mm; optical distortion ≤ Class 1 per EN 166:2002; luminous transmittance ≥ 85% (clear visor)	[To be filled by Bidder]	YES / NO



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

Sr. No.	Item Ref.	Parameter	Minimum Requirement (with Unit)	Bidder Offered Value	Comply (Y/N/NA)
3	Item 1	Head Coverage / Protection Zone	Full-face protection; coverage area must conform to IS 4151:2015 Fig. 1 Zone A + B; neck flap extending minimum 80 mm below collar line	[To be filled by Bidder]	YES / NO
4	Item 1	Mass (Complete Assembly)	Maximum 1.6 kg including visor, chin strap and suspension harness; tested without padding removed	[To be filled by Bidder]	YES / NO
5	Item 1	Adjustable Head Circumference Range	54 cm (minimum) to 62 cm (maximum) using internal suspension harness; stepless adjustment or minimum 3 discrete positions	[To be filled by Bidder]	YES / NO
6	Item 1	Retention System — Chin Strap Strength	Chin strap assembly must withstand minimum tensile load of 200 N for 30 seconds without detachment per IS 4151:2015 Cl. 7.5	[To be filled by Bidder]	YES / NO
7	Item 1	Chemical Splash Resistance (Visor)	Visor must resist penetration / fogging by CS tear gas, OC spray and dilute sulphuric acid (10% v/v) for ≥ 30 seconds; no degradation of optical clarity beyond Class 2 after exposure	[To be filled by Bidder]	YES / NO
		— ITEM 2: BALLISTIC BODY ARMOUR VEST (FPS-2026-B02) —			
8	Item 2	Ballistic Protection Level			
9	Item 2	Stab / Spike Resistance	Minimum KR1 rating per HOSDB Body Armour Standard for UK Police (2017); blade energy 24 J, spike energy 36 J with zero penetration through strike face	[To be filled by Bidder]	YES / NO
10	Item 2	Area of Protection — Front Panel	Minimum 0.072 m ² (720 cm ²) of continuous ballistic material; measured per NIJ 0101.07 Annex A; shall cover sternum to lower abdomen (approx. T2 to L2 vertebral levels)	[To be filled by Bidder]	YES / NO
11	Item 2	Mass — Complete Vest (size Medium)	Maximum 3.6 kg for complete vest assembly (front + rear panel + carrier) in size Medium (chest 96–101 cm)	[To be filled by Bidder]	YES / NO
12	Item 2	Carrier Fabric — Tensile Strength	Outer carrier woven fabric: tensile strength ≥ 1,200 N/50 mm warp and weft per IS 1969 / EN ISO 13934-1; MOLLE webbing load-rated minimum 80 kg per loop	[To be filled by Bidder]	YES / NO
13	Item 2	Ballistic Panel Moisture Resistance	After immersion in water (23°C) for 2 hours, ballistic performance shall not degrade; conditioning per NIJ 0101.07 Annex B wet-conditioning protocol; BFD to remain ≤ 44 mm	[To be filled by Bidder]	YES / NO
		— ITEM 3: FIRE-RETARDANT OVERALLS (FPS-2026-F03) —			



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

Sr. No.	Item Ref.	Parameter	Minimum Requirement (with Unit)	Bidder Offered Value	Comply (Y/N/NA)
14	Item 3	Fabric — Flame Propagation / LOI	Inherently flame-retardant (IFR) fabric; Limiting Oxygen Index (LOI) $\geq 28\%$; flame propagation: char length ≤ 150 mm per IS 11871:2018 Cl. 6.2; no dripping, no molten drops after flame removal	[To be filled by Bidder]	YES / NO
15	Item 3	Fabric Weight (gsm)	Minimum $260 \text{ g/m}^2 \pm 5\%$; woven construction; tested per IS 1964 / EN ISO 3801 after 5 washes at 60°C	[To be filled by Bidder]	YES / NO
16	Item 3	Tensile Strength — Warp and Weft	Minimum 800 N (warp) and 700 N (weft) per strip method EN ISO 13934-1 on unwashed and post-5-wash samples; retention after washing $\geq 85\%$ of original value	[To be filled by Bidder]	YES / NO
17	Item 3	Antistatic Property	Surface resistivity $\leq 10^9 \Omega$ per EN 1149-1:2006 or IS 13935; antistatic thread integrated in fabric weave; not achievable by surface treatment alone	[To be filled by Bidder]	YES / NO
18	Item 3	Arc Flash Rating (ATPV / EBT)	Minimum ATPV (Arc Thermal Performance Value) of 8.0 cal/cm^2 per ASTM F1959/F1959M; Arc Rating Class: ARC 1 (minimum) per EN ISO 11612:2015	[To be filled by Bidder]	YES / NO
		— ITEM 4: KNEE AND ELBOW GUARD SET (FPS-2026-G04) —			
19	Item 4	Shell Impact Attenuation	Peak transmitted force $\leq 10 \text{ kN}$ from 5 J pendulum impact per EN 13594:2015 Annex A; tested at $23^\circ\text{C} \pm 2^\circ\text{C}$ ambient; no fracture or crack visible on shell post-test	[To be filled by Bidder]	YES / NO
20	Item 4	Shell Minimum Thickness	Injection-moulded ABS or HDPE shell; minimum wall thickness 4.0 mm at any point on the guard face; verified by calliper measurement at 9 points per IS 3 / EN standard	[To be filled by Bidder]	YES / NO
21	Item 4	Foam Backing — Energy Absorption	High-density EVA or memory foam backing; density $\geq 60 \text{ kg/m}^3$ per ASTM D3574 Test A; compression set $\leq 15\%$ after 22 h at 70°C per ASTM D3574 Test D	[To be filled by Bidder]	YES / NO
		— ITEM 5: LIGHTWEIGHT POLYCARBONATE SHIELD (FPS-2026-S05) —			
22	Item 5	Material and Thickness			
23	Item 5	Dimensions (Width $\times$ Height)	600 mm (W) $\times$ 900 mm (H) ± 5 mm tolerance on each dimension; corners radiused minimum 15 mm; edges finished with protective ABS extrusion strip, minimum $10 \text{ mm} \times 2 \text{ mm}$ cross-section	[To be filled by Bidder]	YES / NO



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

Sr. No.	Item Ref.	Parameter	Minimum Requirement (with Unit)	Bidder Offered Value	Comply (Y/N/NA)
24	Item 5	Impact Resistance	Must withstand Level 2 impact per BS 7971-4:2000 (shield and devices for riot control equipment); no spall, no crack, no perforation; tested at 0°C and +40°C	[To be filled by Bidder]	YES / NO
25	Item 5	Light Transmittance	Luminous transmittance $\geq 85\%$ (clear, uncoated face) per EN ISO 13666:2019; anti-scratch hard coating on both faces; pencil hardness $\geq 2H$ per ASTM D3363	[To be filled by Bidder]	YES / NO
26	Item 5	Mass per Shield (complete)	Maximum 2.8 kg including arm strap handle assembly; arm strap: nylon webbing, load-rated ≥ 150 kg; foam grip: polyurethane, Shore A 30–45	[To be filled by Bidder]	YES / NO
— GENERAL / CROSS-CUTTING REQUIREMENTS (Items 1–5) —					
27	All Items	Colour / Finish	Olive Green (RAL 6003) or Khaki Brown (RAL 7008) as per MHA colour standard MHA-COL-2023; high-visibility yellow reflective trim acceptable only on FR overalls; no civilian commercial markings visible on exterior	[To be filled by Bidder]	YES / NO
28	All Items	Shelf Life / Operational Life	Ballistic panels: minimum 5-year operational warranty from date of acceptance; all other items: minimum 3-year operational life under field conditions (temperature -10°C to $+55^{\circ}\text{C}$, humidity 10%–95% RH, non-condensing)	[To be filled by Bidder]	YES / NO
29	All Items	Markings — Mandatory Product Labelling	Each unit: permanently marked with (a) Manufacturer name, (b) Fictional Spec. Code, (c) Month/Year of manufacture, (d) Batch/Lot No., (e) Size (where applicable), (f) BIS Licence No. or equivalent certification mark; label must be tamper-evident and not removable without destruction	[To be filled by Bidder]	YES / NO
30	All Items	Country of Origin / Make in India Content	Local content $\geq 50\%$ by value (Class-I Local Supplier) preferred; minimum local content 20% (Class-II) mandatory; bidder to submit self-declaration of local content percentage in Proforma MII-01 per MII Order 2017 (amended 2024)	[To be filled by Bidder]	YES / NO

* Values in the 'Bidder Offered Value' column must be specific numerics with units; entries of 'As per spec.' or 'Compliant' without a numeric value are not acceptable.

* Bidder must provide test reports / data sheets corroborating every numeric value offered.

* All standard references (IS, EN, NIJ, ASTM, BS) refer to the edition current as of 15 Sep 2026 unless a specific year is stated.

* All figures in this table are FICTIONAL — created for training purposes only.

5. QUALITY REQUIREMENTS



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

5.1 Quality Management System

The manufacturer shall hold a valid ISO 9001:2015 Quality Management System certificate from an IAF-MLA accredited Certification Body, covering the design and manufacture of protective equipment. The certificate must be valid as of the bid submission date. A certificate expiring within 6 months of 22 Oct 2026 shall require a renewal in progress (evidence of audit scheduled).

5.2 Incoming Material Inspection (IMI)

Manufacturer shall maintain documented incoming inspection records for all raw materials: ballistic fabrics, thermoplastics, polycarbonate sheet, FR fabrics and foam. IMI records for the 12 months preceding bid submission shall be made available to CRPD inspectors during factory visits and Pre-Delivery Inspection (PDI). Records must identify material lot no., supplier, test parameters, results and accept/reject disposition.

5.3 In-Process Quality Control

Manufacturer shall perform in-process checks at minimum the following stages: (a) Post-cutting / pre-assembly dimensional check, (b) Post-ballistic-stitching seam strength pull test (sample rate $\geq 5\%$ per batch), (c) Post-shell-moulding surface finish and thickness check, (d) Pre-despatch fire-retardancy spot check. Records of all in-process checks with date, operator ID and result shall be retained for 7 years and submitted to CRPD on request.

5.4 Acceptable Quality Level (AQL)

Acceptance sampling for visual and dimensional inspection at goods receipt shall be conducted per IS 2500 Part-1 (equivalent to ISO 2859-1) using Normal Inspection Level II. AQL for critical defects (ballistic/structural): 0.65. AQL for major defects (functional/dimensional): 1.5. AQL for minor defects (cosmetic): 4.0. Lot sizes and sample sizes as per IS 2500 tables.

5.5 Non-Conformance Handling

All non-conforming items identified during PDI or Goods Received Inspection (GRI) shall be segregated, tagged and reported to CRPD Quality Assurance Cell within 24 hours. Supplier must submit a Corrective Action Report (CAR) within 7 working days. Three or more CARs on a single consignment shall entitle CRPD to invoke penalty clauses in the General Terms and Conditions.

6. CERTIFICATION REQUIREMENTS

Sl.	Item	Required Certification / Standard	Issuing / Testing Body	Valid Through	Class.
1	Item 1	BIS Licence — IS 4151:2015 (Protective Helmets for Police)	Bureau of Indian Standards (BIS) or NABL-accredited lab	22 Oct 2026	MANDATORY
2	Item 1	Optical clarity EN 166:2002 test report (visor)	NABL-accredited optical test lab (fictional: OPTLAB/NCR/2026)	22 Oct 2026	MANDATORY
3	Item 2	Ballistic Test Certificate — NIJ 0101.07 Level IIIA or DRDO/TBRL equivalent	DRDO / TBRL (fictional cert.: TBRL/BAL/2024/PPE/0312)	Within 36 months of 22 Oct 2026	MANDATORY
4	Item 2	Stab Resistance Certificate — HOSDB KR1 or equivalent	Accredited body per HOSDB standard	22 Oct 2026	MANDATORY
5	Item 3	IS 11871:2018 Flame Retardancy Test Report (fabric lot certificate)	NABL-accredited textile testing lab; lot-specific certificate	Per supply lot	MANDATORY
6	Item 3	Arc Flash ATPV Test — ASTM F1959; min. 8.0 cal/cm ²	NABL / A2LA accredited arc-flash test facility	22 Oct 2026	MANDATORY
7	Item 3	Antistatic EN 1149-1:2006 certificate	NABL-accredited lab / ERTL	Per fabric lot	MANDATORY
8	Item 4	Impact Attenuation Test Report — EN 13594:2015 Annex A	NABL-accredited mechanical testing lab	22 Oct 2026	MANDATORY
9	Item 5	Impact Resistance — BS 7971-4:2000 Level 2 Test Report	Accredited test lab (fictional: MATLAB/2026/PCB/0042)	22 Oct 2026	MANDATORY



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

Sl.	Item	Required Certification / Standard	Issuing / Testing Body	Valid Through	Class.
10	All	ISO 9001:2015 QMS Certificate (manufacturer)	IAF-MLA accredited Certification Body	22 Oct 2026	MANDATORY
11	Items 1-5	Make in India content declaration — Proforma MII-01	Bidder (self-declaration with ICAI CA certification if $\geq$ Class-I)	At bid submission	MANDATORY
12	Item 2	EN 1621-1:2012 Motorcycle Rider Protective Gear — Protector test (optional — attracts additional evaluation marks)	European Notified Body or NABL-accredited equivalent	22 Oct 2026	OPTIONAL

7. TESTING REQUIREMENTS

7.1 Pre-Bid Type Test Reports

Bidder shall submit, along with the Technical Bid, Type Test Reports from a NABL-accredited (or equivalent internationally accredited) testing laboratory for each parameter listed in Clause 4 that has a stated test standard. Reports shall not be older than **36 months** from the bid submission closing date (i.e., issued on or after **22 October 2023**). Reports must reference the specific test standard, test date, lot/batch number and result.

7.2 Acceptance Testing at Goods Receipt

On delivery of each consignment, CRPD Quality Assurance Cell (QAC) shall draw samples per IS 2500 Part-1 AQL procedure (see Clause 5.4). Selected samples shall be tested at a CRPD-nominated NABL-accredited testing laboratory. Cost of acceptance testing shall be borne by the supplier for the first consignment. Subsequent consignments: cost shared 50:50.

7.3 Third-Party Inspection (TPI)

CRPD reserves the right to appoint a Third-Party Inspection Agency (TPIA) — to be nominated from CRPD's approved panel — for Pre-Despatch Inspection (PDI) at the supplier's premises. Cost of TPI shall be borne by the supplier. TPIA inspection report shall be mandatory for release of payment against each consignment.

7.4 Environmental Conditioning Tests

For ballistic panels (Item 2), the following conditioning tests apply before ballistic re-test for type approval: (a) High Temperature: $70^{\circ}\text{C} \pm 3^{\circ}\text{C}$ for 4 hours; (b) Low Temperature: $-30^{\circ}\text{C} \pm 3^{\circ}\text{C}$ for 4 hours; (c) Water Immersion: 23°C for 2 hours. After each conditioning, panels must still meet the NIJ 0101.07 Level IIIA BFD ≤ 44 mm criterion.

7.5 Accelerated Ageing — FR Fabric (Item 3)

Flame retardancy performance must be maintained after accelerated wash ageing: 50 cycles at 60°C per EN ISO 6330 (domestic washing). Post-wash, LOI must remain $\geq 26\%$ and char length ≤ 200 mm. Residual FR performance certificate must accompany each supply lot.

8. INSPECTION REQUIREMENTS

Stage	Inspection Type	Conducted By	Location	Trigger
I	Pre-Production Meeting (PPM)	CRPD QAC + Supplier Quality Representative	Supplier's Works OR Video Conference	Within 14 days of supply order award
II	In-Process Inspection (IPI)	CRPD QAC inspector or nominated TPIA	Manufacturer's production floor	At 25% and 75% production completion stages
III	Pre-Despatch Inspection (PDI)	CRPD QAC + TPIA (mandatory)	Supplier's despatch bay	Before any consignment is dispatched; PDI clearance mandatory
IV	Goods Received Inspection (GRI)	CRPD Stores Officer + QAC sample inspector	Central Stores, CRPD Depot, Gurgaon	Within 48 hours of receipt at destination



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

Stage	Inspection Type	Conducted By	Location	Trigger
V	Final Acceptance Testing (FAT)	NABL-accredited lab nominated by CRPD QAC	NABL lab premises	On GRI samples; result within 21 working days of sampling

9. PACKAGING AND DELIVERY REQUIREMENTS

9.1 Individual Unit Packaging

Each unit shall be individually packed in a polyethylene bag (minimum 100-micron thickness, heat-sealed) and placed in a rigid corrugated fibreboard (CFB) inner carton. Each carton shall be clearly labelled with item description, size, batch number, quantity, month/year of manufacture and supply order reference.

9.2 Master Carton / Outer Case

Inner cartons shall be packed in double-walled CFB master cartons (burst factor ≥ 5) or wooden crates (for shields and ballistic vests). Master cartons shall not exceed 30 kg gross mass. Ballistic panels shall be stored and transported in moisture-barrier packaging with silica gel desiccant sachets (minimum 20 g per panel).

9.3 Delivery Address and Incoterm

Delivery: DDP (Delivered Duty Paid) to Central Stores, CRPD Depot, Sector-14, Gurgaon, Haryana — 122 001 (Fictional). Supplier is responsible for all freight, insurance, customs (if any) and last-mile delivery costs. Risk transfers to CRPD only after successful completion of Stage IV GRI.

9.4 Delivery Schedule

Complete delivery of all 6 line items within **90 calendar days** from the date of issuance of the Supply Order. Partial deliveries are permitted subject to advance written approval from CRPD. Minimum 40% of each item quantity must be delivered by Day 45. Delay beyond Day 90 shall attract Liquidated Damages (LD) of 0.5% per week of contract value, maximum 10%.

9.5 Transit Insurance

Supplier shall arrange transit insurance (All-Risk Policy) for each consignment for 110% of the supply order value. Insurance policy copy shall be submitted to CRPD prior to despatch of each consignment.

10. TECHNICAL COMPLIANCE SHALL BE DEMONSTRATED THROUGH DOCUMENTARY EVIDENCE

10.1 Every parameter stated in Clause 4 of this Technical Specification must be substantiated by documentary evidence submitted with the Technical Bid. Assertion without supporting evidence shall be treated as non-compliant. The required documents for each parameter category are tabulated below:

Evidence Type	Parameters Covered	Acceptable Source	Max Age
Type Test Report (TTR)	All numeric performance parameters in Clause 4 (Sr. 1–30)	NABL / A2LA / DAkkS accredited lab; specific standard cited	36 months
Product Data Sheet (PDS)	Material properties: gsm, thickness, density, optical transmittance	Manufacturer's published technical data sheet (not marketing brochure)	Current edition
Lot / Batch Test Certificate (BTC)	FR fabric lot parameters; ballistic panel lot ID and test result	Manufacturer's in-house lab (NABL accredited) or third-party lab	12 months
BIS Licence Certificate	IS 4151 (helmets); applicable BIS standards for other items	Bureau of Indian Standards (BIS), India	Valid as of 22 Oct 2026
Ballistic Test Certificate	NIJ Level IIIA ballistic performance; BFD; stab resistance	DRDO/TBRL or NIJ-compliant accredited ballistic test facility	36 months
Self-Declaration (Bidder)	MII local content %, country of origin, product markings conformance	Bidder's authorised signatory; CA-certified for Class-I MII claim	At bid submission



FICTIONAL PROCUREMENT TRAINING CASE | NOT FOR OFFICIAL USE | FICTIONAL PROCUREMENT TRAINING DOCUMENT — NOT AN OFFICIAL GOVERNMENT DOCUMENT

Evidence Type	Parameters Covered	Acceptable Source	Max Age
Compliance Statement (Clause-by-Clause)	All clauses in Sections 3–9; bidder must address each sub-clause	Bidder — Proforma TECH-CMP-01 (attached as Annexure-TC)	At bid submission

10.2 Bidders are advised that CRPD may, at its discretion, conduct independent verification tests on samples drawn from bid samples submitted (Clause 10.3) at a NABL-accredited laboratory of its choice. Results of such tests shall be final and binding.

10.3 **Bid Samples:** Bidder shall submit physical samples of Items 1, 2, 3 and 5 (one unit each, in size Medium / standard size) along with the Technical Bid — delivered to CRPD Procurement Cell, New Delhi (Fictional address) by the bid submission closing date. Samples will not be returned. No payment for samples.

Place: New Delhi Date: 15 September 2026 Document No.: CRPD/TECH/2026/PPE/A3 Tender Ref.: CRPF/PPE/2026/001 Revision 1.0	Authorized Signatory Deputy Director General (Procurement) Central Reserve Procurement Directorate Ministry of Home Affairs, Govt. of India (Office Seal)
--	---

This Technical Specification document (Doc No. CRPD/TECH/2026/PPE/A3, Revision 1.0) forms Schedule-II of the Tender Document for Tender Ref. CRPF/PPE/2026/001. It supersedes all previous drafts and informal communications regarding technical requirements for this procurement. —
FICTIONAL PROCUREMENT TRAINING DOCUMENT ONLY —