LUMENSTAR LIGHTING TECHNOLOGIES PVT LTD
PRODUCT TECHNICAL SPECIFICATION FILE & COMPLIANCE DOSSIER

PRODUCT: 9W Self-Ballasted LED Lamp for General Lighting
MODEL DESIGNATION: LMN-LED-09W-B22
MANUFACTURER: LumenStar Lighting Technologies Pvt Ltd
FACILITY ADDRESS: Industrial Sector 62, Phase 3, Noida, Uttar Pradesh 201301

ELECTRICAL & POWER CHARACTERISTICS:
- Rated Wattage: 9W (Tolerance: 9.0 W nominal, 230 V AC)
- Rated Voltage: 230 V AC (Operating Range: 100 - 300 V AC, 50 Hz)
- Power Factor: 0.92 (Nominal active PF)
- Total Harmonic Distortion (THD): 24.5% (Mains input current distortion)
- Driver Efficiency: 88.5% Constant-Current isolated IC topology

OPTICAL & PHOTOMETRIC PERFORMANCE:
- Luminous Efficacy: 78 lm/W (Total initial luminous flux: 702 lumens)
- Color Rendering Index (CRI): 82 Ra
- Correlated Color Temperature (CCT): 6500 K (Cool Daylight)
- Beam Angle: 220 Degrees Omni-directional

MECHANICAL & SAFETY CHARACTERISTICS:
- Lamp Cap Fitment: B22d Standard Bayonet Cap (conforming to IS 16102)
- Torsion Resistance: 3.2 Nm axial torque withstand without cap loosening
- Insulation Resistance: 5.2 M-Ohm tested at 500 V DC between live and accessible parts
- Electric Shock Protection: IP20 Enclosure with ultrasonic polycarbonate welding
- Marking: English product label artwork; bilingual Hindi carton marking pending

END OF TECHNICAL SPECIFICATION SHEET