

Physical Activity Recognition of Elderly People and People with Parkinson's (PwP) during Standard Mobility Tests using Wearable Sensors

Fatemeh Tahavori,
Emma Stack, Veena Agarwal,
Malcolm Burnett and Ann Ashburn
The Faculty of Health Sciences, University of
Southampton, Southampton, SO17 1BJ, UK.
Email: f.tahavori@soton.ac.uk

Seyed Amir Hoseinitabatabaei
The Institute for Communication
Systems, University of Surrey,
Guildford, GU2 7XH, UK.

William Harwin
The Department of Biomedical
Engineering, University of Reading,
Reading, RG6 6AY, UK.

Abstract—Physical activity recognition plays a vital role in the application of wearable sensors in healthcare. This paper explores the capability of machine learning algorithms to recognise activities of healthy elderly adults and people with Parkinson's (PwP) using wearable sensor data. We examined the potential of triaxial accelerometer alone and with gyroscope for activity recognition. We employed a comprehensive study of several features and classifiers for recognising different activities. The random forest algorithm identified physical activities among elderly people and PwP with an accuracy of 92.29% when both accelerometer and gyroscope sensors used at the same time.

Index Terms—Activity recognition, Parkinson's, wearable sensors

I. INTRODUCTION

Physical activity recognition using machine learning algorithms trained on data from wearable sensors has a crucial role in several applications such as fall detection. If we can monitor people using unobtrusive sensors, we may soon be able to review and check their activities over a long period of time. We also may be able to understand more about changes in their health state such as deteriorating mobility and balance. Movement parameters obtained from wearable sensors might also reveal subtle changes which are harder to identify clinically in the early stage of neurodegenerative diseases such as stroke or Parkinson's and thus assist in diagnosis.

The aim of this study was to examine whether machine learning algorithms trained on data of tri-axial accelerometer alone or with Gyroscope could identify human physical activities. In this study, we developed our algorithms using a cohort of healthy older adults participants and Parkinson's (PwP) performing validated clinical tests. We chose this cohort of people because they have very different movement patterns while performing physical activities in comparison to young participants.

II. RELATED WORKS

In this section, we reviewed prior work of activity recognition using wearable sensors; and explain the difference

between our method and the current works in the literature. Among a large body of work on activity recognition these studies [1], [2], [3] and [4] concentrated on activity recognition for PwP. Most of the studies evaluated their systems using data from young and healthy participants. But, our algorithms have been developed using a cohort of older participants and a disease-specific, PwP.

III. METHODS

In this study, we explored the use of wearable sensors for automatic identification of activities performed by participants in the laboratory. The flowchart in Figure 1 presents an overview of proposed activity recognition study, which includes four main levels: data collection, pre-processing, activity recognition and evaluation.

A. Data collection

10 healthy elderly volunteers (mean age 75 years) and two PwP (mean age 76 years) participated in our study. They performed six various mobility tests in the laboratory including Tandem walk¹, stand to sit, sit to stand, standing, backwards walking test and 3m walk. Each activity was performed three times. We collected participants movement by a video camera and a wearable sensor (includes an accelerometer and a gyroscope, set to capture three axes at 50 Hz) attached to participant's lumbar spine as shown in Figure 2. This sensor's position is near to the centre of mass of the body thus can considerably indicate various human activities.

B. Pre-processing

We segmented the recorded video and sensor data using ELAN annotation software² according to activities. Each activity was then further segmented to sliding windows of 2s (100 samples) as most studies used 2-3 s window size in order to drive their features. We obtained several features, time

¹During Tandem walk participants were asked to walk 10 steps while at each step the toes of one foot touching the heel of the other foot [5].

²<https://tla.mpi.nl/tools/tla-tools/elan/>




Fig. 1. Physical activity recognition framework.



Fig. 2. An example of an elderly participant wearing a wearable sensor while performing physical activities in the laboratory.

and frequency-domains from each window generating a feature vector. These features are summarised in Table I. This feature vector was then used to train the classifiers.

For instance, mean and Root Mean Square (RMS) value of acceleration could be used as simple statistical features. The RMS value can be used to classify walking from standing activities as shown in Figure 3(a). However, backward walking test and Tandem walk may have very similar features that cannot be separated easily using these statistical features, see Figure 3(b).

To investigate the importance of each sensor (accelerometer and gyroscope), we extracted features from the accelerometer and gyroscope data and utilised them to identify activities in two cases: individually and concurrently. Various feature selections methods were tested to eliminate redundant features such as correlation based feature selection, forward and backwards features selection methods and a wrapper feature selection method based on random forest algorithm. We utilised the WEKA toolkit [26]³ for implementing these feature selection methods. By using feature selection methods, we were able to identify specific features which were unique to each activity performed in this study, these features were

³<http://www.cs.waikato.ac.nz/ml/weka/>




Fig. 3. Normalised histograms of (a) 3m walk and standing activities and (b) Backward walking and Tandem walk, presenting RMS feature can be used for recognising standing and walking activities in (a).

less correlated between activities and therefore less likely to confuse recognition of one activity from another.

C. Activity recognition

We examined several machine learning algorithms and feature sets to identify the most reliable activity recognition technique. These machine learning algorithms include Naive Bayes [27], LogitBoost [28], random forest [29] and Support Vector Machine (SVM) [30]. For training and testing of these machine learning algorithms, a 10-fold cross-validation was utilised. The precision, recall and accuracy were used to find the algorithm that performs the best for activity recognition.

TABLE I

EXTRACTED FEATURES FROM THE DATA FOR PHYSICAL ACTIVITY RECOGNITION. THE THREE AXES OF THE ACCELEROMETER AND/OR GYROSCOPE WERE CONSIDERED INDEPENDENTLY AS A FEATURE. FOR POWER SPECTRAL DENSITY, LOCATIONS AND POWER LEVELS OF HIGHEST SIX PEAKS WERE EXTRACTED AS FEATURES. TOTAL POWER IN FIVE PREDEFINED FREQUENCY BANDS (0.5-20) WERE UTILISED AS SPECTRAL POWER FEATURES.

Feature	Method 1	Method 2	Studies
Mean (μ)	μ_{Acc}	μ_{Acc} & μ_{Gyro}	[6]
Autocorrelation (r)	r_{Acc}		[7]
Power spectral density (P)	P_{Acc}	P_{Gyro}	[8]
Spectral power (s)		s_{Acc}	[9], [10]
Entropy (En)	En_{Acc}	En_{Acc} & En_{Gyro}	[11], [12]
SumPowerDetCoeff ($SPDC$)	$SPDC_{Acc}$		[13], [14]
InterQuartile range (IQ)		IQ_{Gyro}	[14], [6], [15], [16]
Spectral variance (Sv)		Sv_{Gyro}	[17]
Main frequency (Mf)	Mf_{Acc}	Mf_{Acc} & Mf_{Gyro}	[18]
Intensity (Int)	Int_{Acc}	Int_{Acc}	[19]
Zero-crossing rate (Zcr)	Zcr_{Acc}	Zcr_{Acc}	[20], [6]
Skewness (Sk)		Sk_{Gyro}	[10], [21], [22]
Correlation coefficient (CC)	CC_{Acc}	CC_{Acc} & CC_{Gyro}	[23], [24], [25]

TABLE II

THE PERFORMANCES OF THE ACTIVITY RECOGNITION USING DIFFERENT CLASSIFICATION METHODS.

Naive Bayes	Accelerometer	Accelerometer & Gyroscope
Precision	0.98	1.00
Recall	0.98	0.97
Average accuracy	78.39	81.24
LogitBoost	Accelerometer	Accelerometer & Gyroscope
Precision	0.98	0.99
Recall	0.90	0.99
Average accuracy	87.63	89.69
Random forest	Accelerometer	Accelerometer & Gyroscope
Precision	0.99	0.99
Recall	1.00	0.99
Average accuracy	89.91	92.29
SVM	Accelerometer	Accelerometer & Gyroscope
Precision	0.91	0.95
Recall	1.00	1.00
Average accuracy	82.17	84.17

IV. RESULTS

As shown in Table II, random forest algorithm best identified the physical activity of elderly people and PwP during standard mobility tests with an accuracy of 89.84% using accelerometer data and 92.29% using both accelerometer and gyroscope data. The LogitBoost gives the best results after random forest with an accuracy of 87.63% (using accelerometer) and 89.69% (using accelerometer and gyroscope) respectively. The Naive Bayes algorithm shows the lowest accuracy with 78.39% using the accelerometer and 81.24% using both accelerometer and gyroscope data which is consistent with the result reported by Safi et. al [31]. As can be seen in Table II, using both accelerometer and gyroscope data in the feature vector can improve the accuracy of classification algorithms.

When we used both accelerometer and gyroscope data, the most informative feature sets were obtained equally from both acceleration and angular velocity. For acceleration data, the features derived along the vertical axis were the most informative features. However, for angular velocity, features were mostly along the horizontal posterior-anterior direction.

The confusion matrix (presenting the true activity class vs. the predicted class) of the random forest classifier is illustrated

in Tables III and IV. The backwards walking test was confused with the Tandem walk test as it included a component of walking. If we are going to monitor people for a long period of time at their home, it is very rare that people perform Tandem walk activity.

V. CONCLUSION

We evaluated machine learning algorithms for identifying activities of elderly people and PwP based on data obtained using low-cost wearable sensors. We assessed the power of accelerometer alone or in conjunction with gyroscope for physical activity identification. Results show that the use of both sensors concurrently can improve the accuracy. The performance of activity recognition methods using decision tree algorithm showed the best accuracy. We would like to test the proposed system when people perform activities at home for a longer period of time and on a larger study.

ACKNOWLEDGMENT

This work was performed under the SPHERE (Sensor Platform for Healthcare in a Residential Environment) interdisciplinary research collaboration funded by the Engineering and Physical Sciences Research Council (EPSRC) UK: Grant EP/KO31910/1. The authors thank the participants for participating in this study; the branches of Parkinson's UK who allowed them to invite their members to take part in the study.

REFERENCES

- [1] J. Cancela, M. Pastorino, M. T. Arredondo, K. S. Nikita, F. Villagra, and M. A. Pastor, "Feasibility study of a wearable system based on a wireless body area network for gait assessment in Parkinson's disease patients," *Sensors*, vol. 14, no. 3, pp. 4618–4633, 2014.
- [2] F. B. Horak and M. Mancini, "Objective biomarkers of balance and gait for Parkinson's disease using body-worn sensors," *Movement Disorders*, vol. 28, no. 11, pp. 1544–1551, 2013.
- [3] S. T. Moore, H. G. MacDougall, and W. G. Ondo, "Ambulatory monitoring of freezing of gait in Parkinson's disease," *Journal of neuroscience methods*, vol. 167, no. 2, pp. 340–348, 2008.
- [4] A. Salarian, H. Russmann, F. J. Vingerhoets, P. R. Burkhard, and K. Aminian, "Ambulatory monitoring of physical activities in patients with Parkinson's disease," *IEEE Transactions on Biomedical Engineering*, vol. 54, no. 12, pp. 2296–2299, 2007.
- [5] H. Kremer et al., "Unified huntington's disease rating scale: reliability and consistency," *Movement disorders*, vol. 11, pp. 136–142, 1996.

TABLE III
CONFUSION MATRIX OF RANDOM FOREST FOR PHYSICAL ACTIVITY RECOGNITION USING ACCELEROMETER DATA.

Random forest	Standing	3m Walk	Tandem walk	Backwards	Sit to stand	Stand to sit
Standing	1.00	0.00	0.00	0.00	0.00	0.00
3m Walk	0.00	0.67	0.28	0.04	0.00	0.00
Tandem walk	0.02	0.03	0.90	0.05	0.01	0.00
Backwards	0.05	0.00	0.56	0.38	0.02	0.00
Sit to stand	0.00	0.03	0.13	0.00	0.70	0.13
Stand to sit	0.00	0.03	0.23	0.00	0.03	0.70

TABLE IV
CONFUSION MATRIX OF RANDOM FOREST FOR PHYSICAL ACTIVITY RECOGNITION USING ACCELEROMETER AND GYROSCOPE DATA.

Random forest	Standing	3m Walk	Tandem walk	Backwards	Sit to stand	Stand to sit
Standing	0.99	0.00	0.00	0.00	0.00	0.00
3m Walk	0.00	0.84	0.15	0.01	0.00	0.00
Tandem walk	0.00	0.02	0.94	0.04	0.01	0.00
Backwards	0.05	0.00	0.52	0.41	0.02	0.00
Sit to stand	0.00	0.03	0.17	0.00	0.80	0.00
Stand to sit	0.00	0.00	0.17	0.07	0.00	0.77

- [6] J. Yang, "Toward physical activity diary: motion recognition using simple acceleration features with mobile phones," in *Proceedings of the 1st international workshop on Interactive multimedia for consumer electronics*. ACM, 2009, pp. 1–10.
- [7] K. Ellis, J. Kerr, S. Godbole, G. Lanckriet, D. Wing, and S. Marshall, "A random forest classifier for the prediction of energy expenditure and type of physical activity from wrist and hip accelerometers," *Physiological measurement*, vol. 35, no. 11, p. 2191, 2014.
- [8] J. Pärkkä, *Analysis of personal health monitoring data for physical activity recognition and assessment of energy expenditure, mental load and stress*. VTT, 2011.
- [9] A. Mannini, S. S. Intille, M. Rosenberger, A. M. Sabatini, and W. Haskell, "Activity recognition using a single accelerometer placed at the wrist or ankle," *Medicine and science in sports and exercise*, vol. 45, no. 11, p. 2193, 2013.
- [10] M. Ermes, J. Pärkkä, J. Mäntylä, and I. Korhonen, "Detection of daily activities and sports with wearable sensors in controlled and uncontrolled conditions," *IEEE transactions on information technology in biomedicine*, vol. 12, no. 1, pp. 20–26, 2008.
- [11] Y. Tochigi, N. A. Segal, T. Vaseenon, and T. D. Brown, "Entropy analysis of tri-axial leg acceleration signal waveforms for measurement of decrease of physiological variability in human gait," *Journal of Orthopaedic Research*, vol. 30, no. 6, pp. 897–904, 2012.
- [12] J. P. Kaipust, J. M. Huisinga, M. Filipi, and N. Stergiou, "Gait variability measures reveal differences between multiple sclerosis patients and healthy controls," *Motor Control*, vol. 16, no. 2, pp. 229–244, 2012.
- [13] M. Sekine, T. Tamura, T. Fujimoto, and Y. Fukui, "Classification of walking pattern using acceleration waveform in elderly people," in *Engineering in Medicine and Biology Society, Proceedings of the 22nd Annual International Conference of the IEEE*, vol. 2. IEEE, 2000, pp. 1356–1359.
- [14] K. Kunze, P. Lukowicz, H. Junker, and G. Tröster, "Where am I: Recognizing on-body positions of wearable sensors," in *International Symposium on Location and Context-Awareness*. Springer, 2005, pp. 264–275.
- [15] J.-Y. Yang, J.-S. Wang, and Y.-P. Chen, "Using acceleration measurements for activity recognition: An effective learning algorithm for constructing neural classifiers," *Pattern recognition letters*, vol. 29, no. 16, pp. 2213–2220, 2008.
- [16] F. Miao, Y. He, J. Liu, Y. Li, and I. Ayoola, "Identifying typical physical activity on smartphone with varying positions and orientations," *Biomedical engineering online*, vol. 14, no. 1, p. 1, 2015.
- [17] S. A. Hoseinitabatabaei, A. Gluhak, and R. Tafazolli, "Towards a position and orientation independent approach for pervasive observation of user direction with mobile phones," *Pervasive and Mobile Computing*, vol. 17, pp. 23–42, 2015.
- [18] D. Kelly and B. Caulfield, "An investigation into non-invasive physical activity recognition using smartphones," in *Annual International Conference of the IEEE Engineering in Medicine and Biology Society*. IEEE, 2012, pp. 3340–3343.
- [19] N. Györfi, Á. Fábrián, and G. Hományi, "An activity recognition system for mobile phones," *Mobile Networks and Applications*, vol. 14, no. 1, pp. 82–91, 2009.
- [20] U. Maurer, A. Smailagic, D. P. Siewiorek, and M. Deisher, "Activity recognition and monitoring using multiple sensors on different body positions," in *International Workshop on Wearable and Implantable Body Sensor Networks (BSN'06)*. IEEE, 2006, pp. 4–116.
- [21] S. A. Hoseinitabatabaei, A. Gluhak, R. Tafazolli, and W. Headley, "Design, realization, and evaluation of uDirect-An approach for pervasive observation of user facing direction on mobile phones," *IEEE Transactions on Mobile Computing*, vol. 13, no. 9, pp. 1981–1994, 2014.
- [22] K. Altun and B. Barshan, "Human activity recognition using inertial/magnetic sensor units," in *International Workshop on Human Behavior Understanding*. Springer, 2010, pp. 38–51.
- [23] L. Gao, A. Bourke, and J. Nelson, "Evaluation of accelerometer based multi-sensor versus single-sensor activity recognition systems," *Medical engineering & physics*, vol. 36, no. 6, pp. 779–785, 2014.
- [24] M. Arif, M. Bilal, A. Kattan, and S. I. Ahamed, "Better physical activity classification using smartphone acceleration sensor," *Journal of medical systems*, vol. 38, no. 9, pp. 1–10, 2014.
- [25] L. Atallah, B. Lo, R. King, and G.-Z. Yang, "Sensor positioning for activity recognition using wearable accelerometers," *IEEE transactions on biomedical circuits and systems*, vol. 5, no. 4, pp. 320–329, 2011.
- [26] I. H. Witten, E. Frank, M. A. Hall, and C. J. Pal, *Data Mining: Practical machine learning tools and techniques*. Morgan Kaufmann, 2016.
- [27] O. Cakmakci, J. Coutaz, K. Van Laerhoven, and H.-W. Gellersen, "Context awareness in systems with limited resources," *context*, vol. 2, no. 1, p. 2ln, 2002.
- [28] A. Bayat, M. Pomplun, and D. A. Tran, "A study on human activity recognition using accelerometer data from smartphones," *Procedia Computer Science*, vol. 34, pp. 450–457, 2014.
- [29] L. Bedogni, M. D. Felice, and L. Bononi, "By train or by car? detecting the user's motion type through smartphone sensors data," in *2012 IFIP Wireless Days*, Nov 2012, pp. 1–6.
- [30] A. Krause, M. Ihmig, E. Rankin, D. Leong, S. Gupta, D. Siewiorek, A. Smailagic, M. Deisher, and U. Sengupta, "Trading off prediction accuracy and power consumption for context-aware wearable computing," in *Ninth IEEE International Symposium on Wearable Computers (ISWC'05)*, Oct 2005, pp. 20–26.
- [31] K. Safi, F. Attal, S. Mohammed, M. Khalil, and Y. Amirat, "Physical activity recognition using inertial wearable sensors—a review of supervised classification algorithms," in *Advances in Biomedical Engineering (ICABME), 2015 International Conference on*. IEEE, 2015, pp. 313–316.