



# PERFORMANCE ANALYSIS OF DISTRIBUTED GPU-ACCELERATED TASK-BASED WORKFLOWS



Marcos Nogueira Lobo de Carvalho<sup>1,2,3</sup>;

Anna Queralt<sup>1</sup>; Oscar Romero<sup>1</sup>; Alkis Simitsis<sup>2</sup>;

Home Institution: Universitat Politècnica de Catalunya (UPC)<sup>1</sup>

Host Institution: Athena Research Center (ARC)<sup>2</sup>|University of Athens (UoA)<sup>3</sup>

Contact: marcos.nogueira@upc.edu




## Motivation

**Research Question:** What are the main factors to consider to run distributed GPU-accelerated task-based workflows efficiently?


**Contributions:**

- A systematic performance analysis of thread-level parallelism:
  - Our results reveal that the gains provided by GPUs are highly affected by the parallel fraction processing within tasks
- A systematic performance analysis of task-level parallelism:
  - Our results reveal that depending on the amount of tasks, scheduling policy and storage architecture used, data (de-)serialization can be significantly high, dominating the total execution time
- Feature extraction considering algorithm, data set, resource and distributed execution framework:
  - We demonstrate that these features are highly correlated with the performance in terms of execution time and, therefore, can be considered as key features to characterize the execution of such workflows

## Multi-level Parallelism



(a) Massively parallel algorithm (e.g. Matmul)



(b) Slightly parallel algorithm (e.g. K-means)

Figure 1: Monitored metrics in each class of algorithms

## Execution Setup


Total worker nodes	8	CPU-GPU bus	PCIe 3.0
Total CPU cores	128	Total GPU devices	32
RAM memory per node	128 GB	GPU memory per device	12 GB
CPU model	Intel Xeon E5-2630	GPU model	NVIDIA K80

Table 1: Cluster settings

Algorithm	Task	Computational Complexity	Data Set
Matmul	<i>matmul_func</i>	$O(N^3)$	8 GB
	<i>add_func</i>	$O(N)$	(32000 x 32000)
K-means	<i>partial_sum</i>	$O(MNK^2)$	10 GB (12500000 x 100)

Table 2: Algorithm tasks and data sets (M and N are the number of rows and columns in a block, respectively, and K is the number of clusters)


## End-to-end Analysis



(a) Matmul

(b) K-means

## Performance Analysis of Task User Code Processing



(a) Matmul: task *matmul\_func*

(b) Matmul: task *add\_func*

(c) K-means: 10 clusters

(d) K-means: 100 clusters