Time left 0:18:23 Hide

In the 8086 microprocessor, what is the purpose of the following assembler directive?

```
ASSUME CS:Code_segment_1, DS:Data_segment_1
```

a. It initializes the code and data segments to zero.

b. It reserves memory for the code and data segments.

c. It tells the compiler that the instructions of the program are stored in the segment **CODE_segment_1** and data are stored in the segment **Data_segement_1**.

d. It loads the `CS` and `DS` registers with the addresses of `Code_segment_1` and `Data_segment_1`.

Next page

Search

QUIZ # 1

Back

Time left 0:19:48 Hide

Question 1

Not yet answered

Marked out of 2.00

Flag question

Which of the following statements correctly describes the **HLDA (Hold Acknowledge)** signal in the 8086 microprocessor?

a. It is an acknowledge signal by the processor to the bus master requesting the control of the bus through HOLD. The acknowledge is asserted high, when the processor accepts HOLD.

b. It is an input signal used by the bus master to request control of the system bus.

c. It is an output signal that resets the processor after a HOLD request.

d. It is an input signal that indicates the completion of a memory read operation.

Next page

Quiz navig

1 2 3

Finish attempt

33°C مشمس

Search

ENG US

QUIZ # 1

Back

Question 2

Not yet answered

Marked out of 2.00

Flag question

The **8086** is called a **16-bit microprocessor** because:

a. It can process **16 bits of data at a time** using its 16-bit ALU and internal registers.

b. It can address only 16 KB of memory.

c. It has a 16-bit instruction queue.

d. It has a 16-bit address bus.

Time left 0:19:12

Hide

Previous page

Next page

Search

ENG
US

QUIZ # 1

Back

Time left 0:17:38 Hide

Question 4

Not yet answered

Marked out of 2.00

Flag question

How many **bytes of memory** are reserved for the following variable declaration?

```
ARRAY DQ -5, 0AAACBh, 10b, 30
```

- a. 8
- b. 40
- c. 5
- d. 16

Previous page

Next page

33°C مشمس Search

QUIZ # 1

Back

Time left 0:16:34 Hide

Question 5

Not yet answered

Marked out of 2.00

Flag question

If the offset address of **X** in the extra segment is equal to **1BCh**, and **ES=9AFBh**, then the physical memory address of X is:

- a. 9B0DCh
- b. 9B17Ch
- c. 9AFBCh
- d. 9B14Ch

Previous page

Finish attempt ...

33°C
مشمس
Search
ENG
US