INT 10H			
			Description
02	BH: page # DH- y coordinate (Row#) DL- x coordinate (Col#)		screen. BIOS
06	BH: Screen attribute for cleared CL: x coordinate UL CH: y coordinate UL DL: x coordinate LR DH: y coordinate LR		Clear or scro l up If AL contains zero, this function clea the rectangular portion of the screen specified by CL/CH (the upper left hand corner) and DL/DH (the lower right hand corner). If AL contains any other value, this service will scroll that rectangular window up the number of lines specified in AL.
07	BH: Screen attribute for cleared CL: x coordinate UL CH: y coordinate UL DL: x coordinate LR DH: y coordinate LR		Clear or scroll up. If AL contains zero, this function clea the rectangular portion of the screen specified by CL/CH (the upper left hand corner) and DL/DH (the lower right hand corner). If AL contains any other value, this service will scroll that rectangular window down the number of lines specified in AL.
09	CX: # of times to replicate Character		and on **the** .

INT 21H			
			Description
01		AL: char read	Reads a single character from the keyboard with echo (displays typed character on screen). if there is no character in the keyboard buffer, the function waits until any key is pressed.
02	DL: character to display		Writes a single character to the display.
09	DS:DX- pointer to string (terminated with "$").		Display String: This function displays the characters from location DS:DX up to (but not including) a terminating "$" character.
0A	DS:DX- pointer to input buffer.		Buffered Keyboard Input: This function reads a line of text from the keyboard and stores it into the input buffer pointed at by DS:DX. The first byte of the buffer must contain a count between one and 255 that contains the maximum number of allowable characters the input buffer. This routi stores the actual number of characters read the second byte The actual nput characters begin at the third byte of the buffer

ليث، عمرو

Assignment #1: Write an assembly code to do the following:

1. Clear the screen and change the background color to light gray and the foreground color to blue.
2. Display a message "enter a number between 0 and 9' in the screen.
3. Accept an input from the keyboard then clear the screen and test the number

- If the number is divisible by 3 then draw the following shape at the center

```
*
  *
    *
      *
        *
```

- Otherwise, draw the following shape (diagonal shape)

```
#
  #
    #
      #
        #
```

Solution:

```
ORG 100H
MOV AH,6
MOV AL,0
MOV BH,71H
MOV CX,0
MOV DX,184FH
INT 10H

MOV AH,9
MOV DX,OFFSET STR1
INT 21H

MOV AH,1
INT 21H

AND AL,0FH
MOV BL,3
MOV AH,0
DIV BL
CMP AH,0
JE L1
MOV SI,'#'
L1:

MOV AH,7
MOV AL,0
MOV BH,71H
MOV CX,0
MOV DX,184FH
INT 10H

MOV AH,2
MOV DX,0A26H
MOV BH,0
INT 10H

MOV CX,5
MOV AH,2
L2:MOV DX,SI
INT 21H
MOV DL,0AH
INT 21H
LOOP L2
HLT
STR1 DB 'ENTER A NUMBER BETWEEN 0 AND 9:$'
STR2 DB '*'
```

ليث، عمرو