

Lecture Template

ADA Compliant

July 7, 2026

Architecture and Compliance

Lists/Tables/Figures

Math/Verbatim

Custom Frames and Blocks

Toggle Visibility Logic

UF Brand Center

Summary

Technical Requirements

Reference: [Dr. Jason Nowell](#).

Critical Workflow Components:

- **Engine:** Use LuaLaTeX for its superior handling of OpenType math fonts, which is critical for MathML generation in order to populate math tags.
- **Kernel:** Use the Phase 3 Beta kernel (released Nov 1st, 2025, or later).
- **Preamble:** Use preamble and accessibility packages provided in this presentation and reference. For slides use (highly experimental) document class [ltx-talk](#).
- **Validation:**
 - **Structural:** Use [veraPDF](#) (Industry Standard). Also recommend checker [PAC 2026](#) with detailed report and built-in screen reader.
 - **Semantic:** Verify with screen readers (NVDA, JAWS, or VoiceOver).
- **Best Practices:** Prioritize structural simplicity to ensure tag-tree integrity.

Architecture and Compliance

Lists/Tables/Figures

Math/Verbatim

Custom Frames and Blocks

Toggle Visibility Logic

UF Brand Center

Summary

Lists

Ordered and unordered lists are automatically tagged for screen reader navigation. Lists in this template have been defaulted to have 10pt separation. Here is an example of a list with custom overlays:

- First item.

Lists

Ordered and unordered lists are automatically tagged for screen reader navigation. Lists in this template have been defaulted to have 10pt separation. Here is an example of a list with custom overlays:

- First item.
- Second item.

Lists

Ordered and unordered lists are automatically tagged for screen reader navigation. Lists in this template have been defaulted to have 10pt separation. Here is an example of a list with custom overlays:

- First item.
- Second item.
- Third item.

Lists

Ordered and unordered lists are automatically tagged for screen reader navigation. Lists in this template have been defaulted to have 10pt separation. Here is an example of a list with custom overlays:

- First item.
- Second item.
- Third item.
- Fourth item (while also displaying third).

Table

Tables require explicit header row identification for data association in screen readers. Use `\tagpdfsetup{table/header-rows={1}}`.

Known Limitation: If you encounter issues with regular captions, use the `makebox` workaround shown.

```
\makebox[0pt][c]{Table 1: Calculated Standard Errors}
```

Method	Sample Size (n)	Standard Error
Simple Random	100	0.050
Stratified	100	0.032
Cluster	100	0.075

Table 1: Calculated Standard Errors

Figures

- **Alt Text:** Mandatory for all non-artifact images.
- **Color Space:** Avoid CMYK (.eps). Use RGB (.png/.jpg) to ensure compliance with digital accessibility standards.

```
\includegraphics[width=0.5\textwidth,alt={University of Florida logo:  
a blue rectangle containing the letters UF in orange and the words  
UNIVERSITY of FLORIDA below.}]{Logo_RGB_Raster.png}
```



Figure 1: Official UF Signature Logo

Architecture and Compliance

Lists/Tables/Figures

Math/Verbatim

Custom Frames and Blocks

Toggle Visibility Logic

UF Brand Center

Summary

Automatic MathML Support

An example of a slide containing math.

- **Sampling distribution:**

Let $T(Y_1, Y_2, \dots, Y_n)$ be some *statistic*, i.e., some function of the data. Then, we call the probability distribution of $T(Y_1, Y_2, \dots, Y_n)$ the *sampling distribution*.

Automatic MathML Support

An example of a slide containing math.

- **Sampling distribution:**

Let $T(Y_1, Y_2, \dots, Y_n)$ be some *statistic*, i.e., some function of the data. Then, we call the probability distribution of $T(Y_1, Y_2, \dots, Y_n)$ the *sampling distribution*.

- **Standard error:**

The *standard error* of an estimator $\hat{\theta}$ is the standard deviation of the sampling distribution:

$$SE(\hat{\theta}) = \sqrt{E[(\hat{\theta} - \theta)^2]}$$

Automatic MathML Support

An example of a slide containing math.

Block

This is a block, like a theorem. Background colors can cause issues, even if color scheme is appropriate.

Unlike beamer where we used:

```
\begin{frame}[fragile]
```

With ltx-talk, simply use

```
\begin{frame*}...
```

Note that this command cannot be nested within another command.

Architecture and Compliance

Lists/Tables/Figures

Math/Verbatim

Custom Frames and Blocks

Toggle Visibility Logic

UF Brand Center

Summary

Custom Blocks

Theory: Optional Title

This is a theorem

Custom Blocks

Example: Optional Title

This is an example.

Custom Blocks

Remark: Optional Title

This is a remark.

Custom Blocks

Definition: Optional Title

This is a definition.

Custom Blocks

Mandatory Title

This is a generic block. If no title is provided it will just say “Block”.

Example

This is an example that takes up the whole slide. A block is not sufficient. We create an example frame using:

```
\exampleon  
\begin{frame}  
...  
\end{frame}  
\exampleoff
```

Similarly we can completely remove the top banner using:

```
\banneroff  
\begin{frame}  
...  
\end{frame}  
\banneron
```

Architecture and Compliance

Lists/Tables/Figures

Math/Verbatim

Custom Frames and Blocks

Toggle Visibility Logic

UF Brand Center

Summary

Toggle Visibility Logic

Current Mode: **Solutions Visible**

In preamble comment out one:

`\showsolutionstrue`

`\showolutionsfalse`

$$\begin{aligned} V(\hat{\mu}) &= V\left(\frac{1}{n} \sum_{i=1}^n Y_i\right) \\ &= \frac{1}{n^2} \sum_{i=1}^n V(Y_i) = \frac{\sigma^2}{n} \\ \Rightarrow \text{SE}(\hat{\mu}) &= \frac{\sigma}{\sqrt{n}} \end{aligned}$$

Preamble Command Used

`\sol[space_when_false]{content when true}`

allows for a single-source workflow, generating an “Instructor” and “Student” version easily.

Overlay in align*

Use of `\onslide` within `align*` to present specific lines.

$$x = x$$

Overlay in align*

Use of `\onslide` within `align*` to present specific lines.

$$x = x$$

$$y = y$$

Temporal Overlays

With the use of `\temporal`, can create faded overlays whereby a before, current, and after options can be chosen.

```
\NewDocumentCommand\fade{D<>{all}}{%  
  \temporal<#1>{\color{black!70}}{\color{black}}{\color{black!10}}  
}
```

1. First item.
2. Second item.
3. Third item.
4. Fourth item (while also displaying third).

Note: Unlike standard overlays, temporal overlays for lists retain visible bullets. The use of `\temporal` inside a list, the new kernel's tagging engine (tagpdf) forces the item bullet to be a protected "Label"

Temporal Overlays

With the use of `\temporal`, can create faded overlays whereby a before, current, and after options can be chosen.

```
\NewDocumentCommand\fade{D<>{all}}{%  
  \temporal<#1>{\color{black!70}}{\color{black}}{\color{black!10}}  
}
```

1. First item.
2. Second item.
3. Third item.
4. Fourth item (while also displaying third).

Note: Unlike standard overlays, temporal overlays for lists retain visible bullets. The use of `\temporal` inside a list, the new kernel's tagging engine (tagpdf) forces the item bullet to be a protected "Label"

Temporal Overlays

With the use of `\temporal`, can create faded overlays whereby a before, current, and after options can be chosen.

```
\NewDocumentCommand\fade{D<>{all}}{%  
  \temporal<#1>{\color{black!70}}{\color{black}}{\color{black!10}}  
}
```

1. First item.
2. Second item.
3. Third item.
4. Fourth item (while also displaying third).

Note: Unlike standard overlays, temporal overlays for lists retain visible bullets. The use of `\temporal` inside a list, the new kernel's tagging engine (tagpdf) forces the item bullet to be a protected "Label"

Temporal Overlays

With the use of `\temporal`, can create faded overlays whereby a before, current, and after options can be chosen.

```
\NewDocumentCommand\fade{D<>{all}}{%  
  \temporal<#1>{\color{black!70}}{\color{black}}{\color{black!10}}  
}
```

1. First item.
2. Second item.
3. Third item.
4. Fourth item (while also displaying third).

Note: Unlike standard overlays, temporal overlays for lists retain visible bullets. The use of `\temporal` inside a list, the new kernel's tagging engine (tagpdf) forces the item bullet to be a protected "Label"

Temporal Overlays

With the use of `\temporal`, can create faded overlays whereby a before, current, and after options can be chosen.

```
\NewDocumentCommand\fade{D<>{all}}{%  
  \temporal<#1>{\color{black!70}}{\color{black}}{\color{black!10}}  
}
```

1. First item.
2. Second item.
3. Third item.
4. Fourth item (while also displaying third).

Note: Unlike standard overlays, temporal overlays for lists retain visible bullets. The use of `\temporal` inside a list, the new kernel's tagging engine (tagpdf) forces the item bullet to be a protected "Label"

Temporal Overlays

With the use of `\temporal`, can create faded overlays whereby a before, current, and after options can be chosen.

```
\NewDocumentCommand\fade{D<>{all}}{%  
  \temporal<#1>{\color{black!70}}{\color{black}}{\color{black!10}}  
}
```

1. First item.
2. Second item.
3. Third item.
4. Fourth item (while also displaying third).

Note: Unlike standard overlays, temporal overlays for lists retain visible bullets. The use of `\temporal` inside a list, the new kernel's tagging engine (tagpdf) forces the item bullet to be a protected "Label"

Temporal Overlays

With the use of `\temporal`, can create faded overlays whereby a before, current, and after options can be chosen.

```
\NewDocumentCommand\fade{D<>{all}}{%  
  \temporal<#1>{\color{black!70}}{\color{black}}{\color{black!10}}  
}
```

1. First item.
2. Second item.
3. Third item.
4. Fourth item (while also displaying third).

Note: Unlike standard overlays, temporal overlays for lists retain visible bullets. The use of `\temporal` inside a list, the new kernel's tagging engine (tagpdf) forces the item bullet to be a protected "Label"

Overlay Suppression and Other Info

To generate a static version for student notes, use:

```
\documentclass[mode=handout]{ltx-talk}
```

More information on overlay functions and environments in Section 9 of ltx-talk documentation.

Architecture and Compliance

Lists/Tables/Figures

Math/Verbatim

Custom Frames and Blocks

Toggle Visibility Logic

UF Brand Center

Summary

Colors and Typography

UF Brand Center has resources on appropriate use of:

- COLORS, including [AA-Compliant Color Formulas for Screen Applications](#)
- TYPOGRAPHY, including [Extended Character Language Support and Accessibility](#)

Architecture and Compliance

Lists/Tables/Figures

Math/Verbatim

Custom Frames and Blocks

Toggle Visibility Logic

UF Brand Center

Summary

Key takeaways

- **Mandatory Engine:** LuaLaTeX.

Key takeaways

- **Mandatory Engine:** LuaLaTeX.
- **Kernel Release:** kernel dated 2025.11.01 or later.

Key takeaways

- **Mandatory Engine:** LuaLaTeX.
- **Kernel Release:** kernel dated 2025.11.01 or later.
- **Preamble:** Appropriate calls are used in preamble. For presentations use `ltx-talk`.

Key takeaways

- **Mandatory Engine:** LuaLaTeX.
- **Kernel Release:** kernel dated 2025.11.01 or later.
- **Preamble:** Appropriate calls are used in preamble. For presentations use `ltx-talk`.
- **Best Practices:** Still highly experimental, keep it simple.

Key takeaways

- **Mandatory Engine:** LuaLaTeX.
- **Kernel Release:** kernel dated 2025.11.01 or later.
- **Preamble:** Appropriate calls are used in preamble. For presentations use `ltx-talk`.
- **Best Practices:** Still highly experimental, keep it simple.
- **Future:** Development is ongoing.