

Generated by Scopus AI, Sat May 09 2026

Audio-based depression detection

Audio-Based Depression Detection Using MODMA and DAIC-WOZ Datasets: Techniques, Performance, and Challenges

Quick Reference

Key Findings Table

Aspect	MODMA Dataset	DAIC-WOZ Dataset	Cross-Dataset Insights
Modalities	Audio, EEG, Multilingual	Audio, Text, Visual, English	Multimodal fusion improves accuracy
Sample Size	Moderate, Multilingual	Small, English, Semi-clinical	Both limited for large-scale generalization
Feature Extraction	MFCC, Mel-spectrogram, Hybrid, EEG	MFCC, Mel-spectrogram, Spectral, Handcrafted	Fusion and advanced features outperform MFCC
Best Model Types	CNN, BiLSTM, Hybrid, Swarm-optimized	CNN, Transformer, Hybrid, Swarm-optimized	Hybrid CNN-Transformer, Swarm-optimized best
Reported Accuracy (Audio-only)	Up to 94% (CNN, MFCC, augmentation)	Up to 99% (Hybrid CNN-Transformer, AST-MFCC)	Multimodal: up to 99.5% (ensemble, fusion)
Generalizability	Good with multilingual data, still limited	Poor cross-lingual, subject leakage issues	Transfer learning, domain adaptation needed
Main Challenges	Standardization, cultural generalizability	Subject leakage, heterogeneity, small samples	Dataset diversity, robust biomarkers
Noise Robustness	Improved with psychoacoustic features	Improved with DOCC, augmentation, fusion	Feature selection, augmentation critical
Clinical Applicability	High with EEG fusion, needs validation	Moderate, limited by dataset and protocol	Multimodal, interpretable models promising

Direct Answer

Audio-based depression detection using the MODMA and DAIC-WOZ datasets leverages advanced feature extraction (MFCC, Mel-spectrogram, psychoacoustic features), deep learning (CNN, BiLSTM, Transformer,

hybrid models), and multimodal fusion to achieve high accuracy (often >90%). Hybrid CNN-Transformer architectures, especially when optimized with swarm intelligence algorithms, outperform traditional models. However, challenges such as dataset heterogeneity, subject leakage, and poor cross-lingual generalization persist, necessitating more diverse, standardized, and clinically oriented research methodologies for robust, scalable depression detection tools [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#).

Study Scope

- **Time Period:** 2018–2024 (focus on recent advances)
- **Disciplines:** Computational psychiatry, affective computing, speech processing, machine learning, deep learning, multimodal AI
- **Methods:** Empirical benchmarking, meta-analysis, cross-dataset evaluation, feature engineering, model optimization, multimodal fusion

Assumptions & Limitations

- Both datasets are representative but limited in size and diversity.
- Reported accuracies may be inflated due to subject leakage or overfitting, especially in DAIC-WOZ.
- Cross-lingual and cross-cultural generalizability remains a major challenge.
- Clinical applicability is constrained by lack of longitudinal and real-world deployment studies.

Suggested Further Research

- Develop larger, more diverse, and multilingual datasets.
- Standardize diagnostic protocols and recording conditions.
- Integrate longitudinal and ecological momentary assessment data.
- Advance interpretable, culturally adaptive, and clinically validated multimodal models.
- Explore large language models and psychological knowledge integration for robust, scalable screening.

1. Introduction

Background and Motivation

Depression is a leading cause of disability worldwide, yet its diagnosis remains subjective and resource-intensive. Objective, scalable, and non-invasive methods for depression detection are urgently needed. Audio-based analysis offers a promising avenue, as speech carries rich paralinguistic cues reflective of affective and cognitive states. Automated depression detection from speech can enable early screening, continuous monitoring, and remote assessment, addressing gaps in traditional mental health care [1](#) [7](#) [8](#).

Overview of MODMA and DAIC-WOZ Datasets

The MODMA and DAIC-WOZ datasets are two of the most widely used resources for audio-based depression detection research. MODMA provides multilingual, multimodal data (audio, EEG, text), supporting robust cross-lingual studies. DAIC-WOZ, a benchmark in the field, offers semi-clinical interviews with synchronized audio, text, and visual data, but is limited by sample size and methodological issues such as subject leakage. Both datasets underpin state-of-the-art research and serve as testbeds for novel algorithms [1](#) [9](#) [10](#).

2. Dataset Characteristics and Suitability

Key Features and Modalities

- **MODMA:** Multilingual (Chinese, English), includes audio, EEG (128-channel), and text. Enables multimodal and cross-lingual studies. High classification accuracy (up to 99.68% with EEG, ~86% with audio MFCC+BiLSTM) [9](#) [11](#).
- **DAIC-WOZ:** English, semi-clinical interviews, audio, text, and visual data. Widely used for benchmarking, but suffers from subject leakage and small sample size. Audio-based models achieve moderate to high accuracy (up to 91% with CNN autoencoders) [1](#) [10](#) [12](#).
- **Multimodal Fusion:** Combining modalities (audio, text, visual, EEG) consistently improves detection accuracy, with ensemble and late fusion methods achieving >90% accuracy [13](#) [14](#).

Methodological Issues and Subject Leakage

- **Subject Leakage:** DAIC-WOZ is prone to subject leakage due to domain gaps and class imbalance, inflating performance metrics and limiting generalizability [15](#).
- **Mitigation Strategies:** Data-Free Domain Incremental Learning (DIL-MDD), adaptive threshold learning, and privacy-preserving methods reduce leakage. Standardized preprocessing and multimodal adaptive attention further enhance robustness [15](#) [16](#) [17](#).
- **Reproducibility:** Rigorous data partitioning and incremental learning frameworks are essential for reliable evaluation [2](#).

Multilingual and Cross-Dataset Generalizability

- **MODMA's Multilingual Data:** Supports robust cross-lingual transfer. MFCC-40 + BiLSTM achieves up to 86% accuracy across languages. Transfer learning improves accuracy by >20% on new languages [11](#) [18](#).
- **Cross-Dataset Studies:** Robust acoustic biomarkers can be identified and transferred, but heterogeneity in recording conditions and diagnostic tools remains a barrier [19](#).
- **Multimodal/Multilingual Fusion:** Models like M3L and BCMA-MBF leverage cross-modal attention for improved generalizability [20](#) [21](#).

Limitations and Opportunities for Improvement

- **Sample Size:** Both datasets are relatively small, limiting statistical power and generalizability [2](#) [8](#).

- **Recording Variability:** Naturalistic conditions introduce noise and heterogeneity, challenging model robustness [6](#).
- **Cultural Generalizability:** Limited diversity restricts applicability across populations [19](#).
- **Future Directions:** Larger, more diverse, and standardized datasets; integration of longitudinal and ecological data; improved diagnostic consistency [2](#) [6](#) [8](#) [19](#).

Synthesis:

MODMA and DAIC-WOZ are foundational for audio-based depression detection, but their limitations—especially in sample size, subject leakage, and cross-lingual generalizability—necessitate methodological rigor and ongoing dataset development for robust, scalable solutions [2](#) [8](#) [20](#) [22](#).

3. Audio Feature Extraction Techniques

Traditional and Deep Learning-Based Feature Extraction

- **MFCC:** The most common feature, effective for both datasets. Logistic regression with MFCC achieves 88.24% (MODMA), CNN autoencoders with MFCC reach 91% (DAIC-WOZ) [3](#) [12](#).
- **Spectrograms:** Used with CNNs for improved performance, often exceeding 90% accuracy [23](#) [24](#).
- **Hybrid Handcrafted Features:** Combining textural, statistical, and wavelet features yields up to 94.63% accuracy (MODMA) [25](#).
- **Topological Data Analysis (TDA):** Betti curves from audio signals improve robustness to individual variance [26](#).

Advanced and Hybrid Feature Extraction Methods

- **Beyond MFCC:** Mel-spectrogram, psychoacoustic voice quality features (F0, formants, harmonic-to-noise ratios), and DOCCs enhance noise robustness and accuracy [27](#) [28](#) [29](#).
- **Feature Fusion:** Combining MFCC, Mel-spectrogram, and short-term energy (MS-MFCC-SE) in hybrid CNN-BiGRU models achieves F1 scores of 0.94 (MODMA) and 0.67 (DAIC-WOZ) [27](#).
- **Autoencoders:** Deep learning autoencoders with SVM classifiers reach up to 97% accuracy (DAIC-WOZ) [30](#).

Feature Selection and Fusion Strategies

- **Fisher Score, PCA:** Feature selection improves accuracy; dynamic ensemble selection with Fisher score-selected features outperforms individual classifiers [31](#).
- **Feature-Level Fusion:** Early fusion of multimodal features (audio, text, video) with CNNs and attention mechanisms yields higher accuracy and F1 scores than unimodal or late fusion models [32](#) [33](#) [34](#).
- **Complementarity:** Fusion leverages strengths of different modalities, improving robustness and reliability [14](#) [35](#).

Noise Robustness and Data Augmentation

- **Psychoacoustic Features:** Improve robustness under noise and short utterances [28](#).
- **Data Augmentation:** Counterfactual augmentation, synthetic data generation, and hierarchical augmentation strategies mitigate overfitting and enhance generalization, especially in small-sample settings [36](#) [37](#).
- **Speaker-Invariant Modeling:** Reduces bias and improves accuracy by minimizing speaker-specific information [38](#).

Synthesis:

Advanced feature extraction and fusion—especially when combining MFCC, Mel-spectrogram, psychoacoustic features, and deep learning representations—significantly enhance depression detection accuracy and robustness, particularly when paired with effective feature selection and augmentation strategies [3](#) [27](#) [28](#) [34](#).

4. Machine Learning and Deep Learning Models

Traditional Machine Learning and Baseline Models

- **SVM, Random Forest, XGBoost:** Achieve 78–84% accuracy on DAIC-WOZ; ensemble methods and deep learning models outperform traditional ML [4](#) [13](#) [39](#).
- **Ensemble Models:** Combining classifiers on multimodal features (E-DAIC) achieves up to 99.54% accuracy [13](#).

Deep Learning Architectures: CNNs, RNNs, and Transformers

- **CNNs:** Effective for local feature extraction from spectrograms and MFCCs; high accuracy on both datasets [23](#) [40](#).
- **RNNs (LSTM, BiLSTM):** Capture temporal dependencies; BiLSTM with MFCC-40 achieves up to 86% (MODMA) [11](#).
- **Transformers:** Superior for long-term dependencies and multimodal fusion. Hybrid CNN-Transformer models achieve up to 99.4% accuracy (DAIC-WOZ) [41](#).
- **Hybrid Models:** CNNs for local, Transformers for global features; parallel and multi-scale architectures further boost performance [42](#) [43](#).

Swarm Intelligence and Optimization Algorithms

- **Firefly, Dragonfly, Moth Flame, PSO, WOA:** Used for feature selection and model optimization, improving macro F1 scores (up to 0.86) and generalization across datasets [5](#) [44](#) [45](#).
- **Training Efficiency:** Swarm intelligence reduces feature set size, enhances accuracy, and optimizes model parameters [5](#) [44](#).

Multimodal and Fusion Models

- **Audio-Text-Visual Fusion:** Multimodal models with adaptive attention and cross-modal transformers outperform unimodal models, achieving F1 scores up to 0.98 and accuracy up to 99.5% [13](#) [14](#) [46](#) [47](#).
- **Attention Mechanisms:** Bidirectional cross-modal attention and multi-level fusion improve robustness and generalization, especially in cross-lingual contexts [21](#) [48](#) [49](#).

Performance Trade-offs and Generalizability

- **Sensitivity vs. False Positives:** Naive transformer models are more sensitive but have higher false positive rates; hybrid AST-MFCC models better control false positives [50](#).
- **Cross-Dataset Performance:** Models trained on DAIC-WOZ often underperform on other datasets, highlighting the need for robust, scalable approaches [22](#) [51](#).

Synthesis:

Hybrid deep learning models—especially those combining CNNs, Transformers, and swarm intelligence optimization—consistently outperform traditional ML and unimodal approaches. Multimodal fusion and attention mechanisms are key to achieving high accuracy and robustness, but generalizability and clinical translation remain challenging [5](#) [41](#) [50](#) [52](#).

5. Challenges and Research Gaps

Dataset Heterogeneity and Cross-Lingual Generalization

- **Heterogeneity:** Differences in recording conditions, diagnostic tools, and sample composition create domain gaps, reducing model robustness and cross-lingual transferability [19](#) [22](#).
- **Generalization:** Models often learn disorder-general cues rather than depression-specific markers, limiting specificity across languages and cultures [53](#).
- **Transfer Learning:** Methods like DCAN and GNN-SDA align feature distributions, improving cross-lingual performance by up to 21.9% [18](#) [54](#).

Feature Robustness and Interpretability

- **Biomarker Identification:** Robust, interpretable, and dataset-independent acoustic biomarkers are difficult to identify due to naturalistic variability and speaker differences [11](#) [19](#) [55](#) [56](#).
- **Noise and Variability:** Psychoacoustic features and advanced augmentation improve robustness, but further work is needed for interpretability and clinical acceptance [28](#) [29](#).

Multimodal Fusion and Clinical Applicability

- **Fusion Benefits:** Multimodal fusion (audio, text, visual, EEG) with adaptive attention mechanisms improves accuracy and adaptability [13](#) [57](#) [58](#).
- **Barriers:** Data alignment, interpretability, and lack of clinical validation hinder deployment [57](#) [59](#).
- **LLMs:** Large language models offer new opportunities for contextual inference and cross-modal alignment but require domain-specific fine-tuning [10](#) [57](#) [58](#).

Opportunities for Future Research

- **Dataset Development:** Larger, more diverse, and multilingual datasets; standardized protocols; longitudinal and ecological data [7](#) [8](#) [57](#).
- **Model Innovation:** Culturally adaptable, interpretable, and scalable multimodal models; integration of psychological knowledge and LLMs [7](#) [8](#) [57](#) [58](#).
- **Clinical Integration:** Focus on real-world deployment, continuous monitoring, and integration with healthcare systems.

Synthesis:

Persistent challenges—including dataset heterogeneity, subject leakage, and poor cross-lingual generalizability—underscore the need for methodological rigor, dataset innovation, and advanced model adaptation to realize clinically scalable and culturally adaptable depression detection tools [19](#) [22](#) [29](#) [60](#).

6. Conclusion

Summary of Findings

- **Dataset Suitability:** MODMA and DAIC-WOZ are foundational but limited by size, heterogeneity, and generalizability issues [1](#) [3](#) [4](#) [6](#).
- **Feature Extraction:** Advanced and hybrid feature extraction (MFCC, Mel-spectrogram, psychoacoustic, deep learning) and fusion strategies significantly enhance accuracy and robustness [3](#) [27](#) [28](#) [34](#).
- **Modeling Approaches:** Hybrid CNN-Transformer and swarm intelligence–optimized models outperform traditional ML; multimodal fusion and attention mechanisms are critical for state-of-the-art performance [5](#) [41](#) [50](#) [52](#).
- **Challenges:** Subject leakage, dataset heterogeneity, and poor cross-lingual generalizability remain major barriers to clinical translation [19](#) [22](#) [29](#) [60](#).

Implications for Research and Practice

- **Research:** Focus on dataset diversity, methodological rigor, and interpretable, multimodal models. Leverage transfer learning, domain adaptation, and LLMs for robust, scalable solutions [7](#) [8](#) [57](#).
- **Practice:** Multimodal, adaptive, and interpretable models hold promise for clinical deployment, but require validation in diverse, real-world settings. Integration with healthcare systems and continuous monitoring are key for impact.

Suggested Further Research

- **Unified Multimodal Frameworks:** Develop frameworks that dynamically integrate audio, text, visual, and physiological data with culturally adaptive transfer learning, leveraging large language models and psychological knowledge.

- **Dataset Expansion:** Create large, diverse, and multilingual datasets with standardized protocols and longitudinal follow-up.
- **Clinical Validation:** Conduct real-world, longitudinal studies to validate model effectiveness and scalability in clinical and community settings.
- **Interpretability and Fairness:** Advance interpretable AI and fairness-aware models to ensure equitable and transparent depression detection across populations.

In summary, audio-based depression detection using MODMA and DAIC-WOZ datasets has achieved remarkable progress through advanced feature extraction, hybrid deep learning, and multimodal fusion. However, addressing dataset limitations, methodological rigor, and clinical translation remains essential for realizing the full potential of these technologies in global mental health care [1](#) [3](#) [4](#) [6](#) [7](#) [8](#) [57](#).

References

1. The Detection of Depression Using Multimodal Models Based on Text and Voice Quality Features Solieman, H., Pustozarov, E.A. Proceedings of the 2021 IEEE Conference of Russian Young Researchers in Electrical and Electronic Engineering, ElConRus 2021, 2021 <https://www.scopus.com/pages/publications/85104715442?origin=scopusAI>
2. Common Pitfalls and Recommendations for Use of Machine Learning in Depression Severity Estimation: DAIC-WOZ Study Danylenko, I., Unold, O. Applied Sciences (Switzerland), 2026 <https://www.scopus.com/pages/publications/105027291365?origin=scopusAI>
3. The Significance of Time Duration and Feature Extraction of Voice Signal Dataset for Depression Classification Tongnopparat, P., Kiatrungrit, K., Treebupachatsakul, T., Poomrittigul, S. 16th Biomedical Engineering International Conference, BMEiCON 2024, 2024 <https://www.scopus.com/pages/publications/105000365814?origin=scopusAI>
4. Depression Detection through Audio Analysis using Machine Learning Models Ensuring Sustainable Development of Mankind Yadav, P., Jain, P., Jain, T. CEUR Workshop Proceedings, 2023 <https://www.scopus.com/pages/publications/85183921499?origin=scopusAI>
5. Efficacy of swarm-based neural networks in automated depression detection Atta, A., ElSayad, D., Ezzat, D., (...), ElGamal, M. Scientific Reports, 2025 <https://www.scopus.com/pages/publications/105010644143?origin=scopusAI>
6. Depression detection from speech data using deep learning-based optimized temporal-frequency-channel attention with interpretable acoustic-prosodic mapping Rezaee, K. Journal of Affective Disorders, 2026 <https://www.scopus.com/pages/publications/105027818735?origin=scopusAI>
7. Automated Depression Detection From Text and Audio: A Systematic Review Li, Y., Kumbale, S., Chen, Y., (...), Guan, C. IEEE Journal of Biomedical and Health Informatics, 2025 <https://www.scopus.com/pages/publications/105005454512?origin=scopusAI>
8. Public Datasets for Multimodal Machine Learning-Driven Depression Detection: A Comprehensive Survey Dou, Y., Li, S., Zhu, H., Peng, S. Proceedings - 2025 IEEE International Conference on Medical Artificial Intelligence, MedAI 2025, 2025 <https://www.scopus.com/pages/publications/105034152058?origin=scopusAI>
9. Automated Depression Diagnosis in MDD (Major Depressive Disorder) Patients Using EEG Signal Singh, S., Sheoran, P., Duhan, M. Lecture Notes in Networks and Systems, 2023 <https://www.scopus.com/pages/publications/85152557532?origin=scopusAI>

10. Exploring the Capabilities of a Language Model-Only Approach for Depression Detection in Text Data Sadeghi, M., Egger, B., Agahi, R., (...), Eskofier, B.M. BHI 2023 - IEEE-EMBS International Conference on Biomedical and Health Informatics, Proceedings, 2023
<https://www.scopus.com/pages/publications/85179513471?origin=scopusAI>
11. MFCC-Based Multilingual Speech Processing for Depression Classification Pratiwi, M., Hayati, N., Kristianto, A.Y. 2025 International Conference on Applied Artificial Intelligence, Data Engineering and Sciences, ICAIDES 2025, 2025 <https://www.scopus.com/pages/publications/105036378301?origin=scopusAI>
12. Depression Classification Algorithm Based on Voice Signals Using MFCC and CNN Autoencoders Hong, J., Lee, J., Cho, D., Jung, J. Proceedings - 2024 International Conference on Machine Learning and Applications, ICMLA 2024, 2024 <https://www.scopus.com/pages/publications/105001031282?origin=scopusAI>
13. Ensemble-Based Multimodal Analysis for Depression Detection Jadhav, G.D., Babar, S.D., Mahalle, P.N. Engineered Science, 2025 <https://www.scopus.com/pages/publications/105015555719?origin=scopusAI>
14. Multimodal mental state analysis Rai, B.K., Jain, I., Tiwari, B., Saxena, A. Health Services and Outcomes Research Methodology, 2025 <https://www.scopus.com/pages/publications/85190500448?origin=scopusAI>
15. Leaving None Behind: Data-Free Domain Incremental Learning for Major Depressive Disorder Detection Chen, T., Guo, Y., Hao, S., Hong, R. IEEE Transactions on Affective Computing, 2025
<https://www.scopus.com/pages/publications/85206482514?origin=scopusAI>
16. TwoM: A model for joint time–frequency representation and spatial filtering for EEG-based depression recognition Wu, Z., Luo, G., Zhang, H., (...), Xu, D. Biomedical Signal Processing and Control, 2026
<https://www.scopus.com/pages/publications/105019741459?origin=scopusAI>
17. Deep Learning-Driven Behavioral Modeling in IoST for Mental Health Monitoring and Intervention Li, J., Akbar, M.A., Shah, S.H., (...), Yang, J. IEEE Transactions on Computational Social Systems, 2026
<https://www.scopus.com/pages/publications/105001539211?origin=scopusAI>
18. A cross-linguistic depression detection method based on speech data Qin, S., Zhang, Y., Ma, Y., (...), Zhao, X. Journal of Affective Disorders, 2025 <https://www.scopus.com/pages/publications/105009336154?origin=scopusAI>
19. Identifying robust and dataset-independent acoustic biomarkers of depression through multi-model feature consensus analysis Yousufi, M., Maskeliunas, R. Computer Speech and Language, 2026
<https://www.scopus.com/pages/publications/105030933113?origin=scopusAI>
20. M3L: A Multi-Modal and Multi-Lingual Depression Detection Framework You, J., Wang, S., Gong, X., Wan, X. Proceedings of the Annual Conference of the International Speech Communication Association, INTERSPEECH, 2025 <https://www.scopus.com/pages/publications/105020032412?origin=scopusAI>
21. BCMA-MBF: Research on depression prediction based on bidirectional cross-modal attention with multi-task linear fusion Wang, X., He, R., Wen, S., (...), Wang, J. Journal of Affective Disorders, 2026
<https://www.scopus.com/pages/publications/105019261052?origin=scopusAI>
22. Cross-Cultural Identification of Acoustic Voice Features for Depression: A Cross-Sectional Study of Vietnamese and Japanese Datasets Le, P.T.V., Nakamura, M., Higuchi, M., (...), Tokuno, S. Bioengineering, 2026 <https://www.scopus.com/pages/publications/105028720090?origin=scopusAI>
23. Leveraging Deep Learning based Feature Extraction Techniques for Improved Audio-Based Depression Detection Joshi, D., Kaur, M. 2024 1st International Conference on Sustainability and Technological Advancements in Engineering Domain, SUSTAINED 2024, 2024
<https://www.scopus.com/pages/publications/105013623326?origin=scopusAI>
24. A deep learning model for depression detection based on MFCC and CNN generated spectrogram features Das, A.K., Naskar, R. Biomedical Signal Processing and Control, 2024
<https://www.scopus.com/pages/publications/85180984859?origin=scopusAI>

25. Multilevel hybrid handcrafted feature extraction based depression recognition method using speech Taşcı, B. *Journal of Affective Disorders*, 2024 <https://www.scopus.com/pages/publications/85200851897?origin=scopusAI>
26. Topological Data Analysis to Engineer Features from Audio Signals for Depression Detection Tlachac, M.L., Sargent, A., Toto, E., (...), Rundensteiner, E. *Proceedings - 19th IEEE International Conference on Machine Learning and Applications, ICMLA 2020*, 2020 <https://www.scopus.com/pages/publications/85102503133?origin=scopusAI>
27. A Comparative Study of AI Models for Depression Assessment using Voice Features Jeon, E., Moon, S., Lee, S., (...), Kim, J.E. *Proceedings - 2023 IEEE International Conference on Bioinformatics and Biomedicine, BIBM 2023*, 2023 <https://www.scopus.com/pages/publications/85184902449?origin=scopusAI>
28. Effectiveness of voice quality features in detecting depression Afshan, A., Guo, J., Park, S.J., (...), Alwan, A. *Proceedings of the Annual Conference of the International Speech Communication Association, INTERSPEECH*, 2018 <https://www.scopus.com/pages/publications/85054966529?origin=scopusAI>
29. Noise and reverberation effects on depression detection from speech Mitra, V., Tsiartas, A., Shriberg, E. *ICASSP, IEEE International Conference on Acoustics, Speech and Signal Processing - Proceedings*, 2016 <https://www.scopus.com/pages/publications/84973375237?origin=scopusAI>
30. Deep Learning Technique to Diagnose Depression in Audio Misra, G., Kumar, D. *ACM International Conference Proceeding Series*, 2023 <https://www.scopus.com/pages/publications/85175721252?origin=scopusAI>
31. Improving Depression Prediction Accuracy Using Fisher Score-Based Feature Selection and Dynamic Ensemble Selection Approach Based on Acoustic Features of Speech Janardhan, N., Kumares, N. *Traitement du Signal*, 2022 <https://www.scopus.com/pages/publications/85128182660?origin=scopusAI>
32. Multimodal measurement of depression using deep learning models Yang, L., Pei, E., Jiang, D., (...), Sahli, H. *AVEC 2017 - Proceedings of the 7th Annual Workshop on Audio/Visual Emotion Challenge, co-located with MM 2017*, 2017 <https://www.scopus.com/pages/publications/85035339678?origin=scopusAI>
33. Depression detection methods based on multimodal fusion of voice and text Xu, Z., Gao, Y., Wang, F., (...), Shu, J. *Scientific Reports*, 2025 <https://www.scopus.com/pages/publications/105009551994?origin=scopusAI>
34. Multimodal Data Fusion for Depression Detection Approach Nykoniuk, M., Basystiuk, O., Shakhovska, N., Melnykova, N. *Computation*, 2025 <https://www.scopus.com/pages/publications/85216033696?origin=scopusAI>
35. Depression Detection via Dual Audio Streams and Transformer Fusion Ben-Ismael, B., Fathallah, W., Salah, B.B., (...), Sakli, H. *Procedia Computer Science*, 2025 <https://www.scopus.com/pages/publications/105024072598?origin=scopusAI>
36. Vector Quantization-Based Counterfactual Augmentation for Speech-Based Depression Detection Under Data Scarcity Zuo, L., Mak, M.-W. *IEEE Journal of Biomedical and Health Informatics*, 2025 <https://www.scopus.com/pages/publications/105004199092?origin=scopusAI>
37. Depression Detection in Speech Using Generative Models Elghandour, L.A., Eltoweiry, A., Salem, M.A.-M., Sharaf, N. *Proceedings - 2025 IEEE 12th International Conference on Intelligent Computing and Information Systems, ICICIS 2025*, 2025 <https://www.scopus.com/pages/publications/105031785439?origin=scopusAI>
38. Avoiding dominance of speaker features in speech-based depression detection Zuo, L., Mak, M.-W. *Pattern Recognition Letters*, 2023 <https://www.scopus.com/pages/publications/85167785104?origin=scopusAI>
39. Depression Detection from Speech Using a Voting Ensemble Approach Bhatt, N., Jain, A., Jain, M., Bhatt, S. *2024 IEEE 8th International Conference on Information and Communication Technology, CICT 2024*, 2024 <https://www.scopus.com/pages/publications/105000696473?origin=scopusAI>

40. A Novel Deep Learning Model Leveraging State-of-the-Art Audio Transformations for Robust Speech Depression Detection Lakkaraju, A. International Conference on Electrical, Computer, and Energy Technologies, ICECET 2025, 2025 <https://www.scopus.com/pages/publications/105037173890?origin=scopusAI>
41. Hyb-PcnDTr: a Hybrid Parallel CNN-Assisted Dense Transformer for Automatic Speech-Based Depression Detection Jaishankar, U., Nirmal, J.H. Proceedings of 2025 2nd International Conference on Cognitive Robotics and Intelligent Systems, ICC - ROBINS 2025, 2025 <https://www.scopus.com/pages/publications/105013466889?origin=scopusAI>
42. LightDepressionNet: A Lightweight Depression Diagnostic System Based on CNN-Transformer Liu, X., Zhou, L., Zhang, W., (...), Chen, C. 2025 15th International Conference on Biomedical Engineering and Technology, ICBET 2025, 2025 <https://www.scopus.com/pages/publications/105037468627?origin=scopusAI>
43. Automatic Depression Level Assessment Based on Mel Spectrum and Deep Learning Technology Zhang, T., Chen, Y., Yue, J., Li, M. 2025 6th International Conference on Electronic Communication and Artificial Intelligence, ICECAI 2025, 2025 <https://www.scopus.com/pages/publications/105018801997?origin=scopusAI>
44. Hybrid Approach Using LSTM Neural Networks and Whale Optimization Algorithm For Enhancing Depression Diagnosis Atta, A., Sayad, D.E., Ezzat, D., (...), Gamal, M.E. 2024 International Conference on Future Telecommunications and Artificial Intelligence, IC-FTAI 2024 - Proceedings, 2024 <https://www.scopus.com/pages/publications/105003910589?origin=scopusAI>
45. Novel Cuckoo Search-Based Metaheuristic Approach for Deep Learning Prediction of Depression Jawad, K., Mahto, R., Das, A., (...), Kumar, P. Applied Sciences (Switzerland), 2023 <https://www.scopus.com/pages/publications/85159336364?origin=scopusAI>
46. A Self-Supervised Audio-Text Transformer for Depression Detection Using Speech & Linguistic Cues Kovvuru, P.K., Sunitha, G., Naresh, B., (...), Rao, P.V. Proceedings of the 4th IEEE International Conference on Interdisciplinary Approaches in Technology and Management for Social Innovation, IATMSI 2026, 2026 <https://www.scopus.com/pages/publications/105036945075?origin=scopusAI>
47. DPD (DePression Detection) Net: a deep neural network for multimodal depression detection He, M., Bakker, E.M., Lew, M.S. Health Information Science and Systems, 2024 <https://www.scopus.com/pages/publications/85209804542?origin=scopusAI>
48. A multimodal fusion model with multi-level attention mechanism for depression detection Fang, M., Peng, S., Liang, Y., (...), Liu, S. Biomedical Signal Processing and Control, 2023 <https://www.scopus.com/pages/publications/85145258750?origin=scopusAI>
49. An Enhanced Cross-Attention Based Multimodal Model for Depression Detection Kou, Y., Ge, F., Chen, D., (...), Liu, H. Computational Intelligence, 2025 <https://www.scopus.com/pages/publications/85215321757?origin=scopusAI>
50. Towards AST-LLDs for the Analysis of Depression in Speech Signals Nagappan, S., Lim, C.H., Dharmaratne, A.T. 2023 Asia Pacific Signal and Information Processing Association Annual Summit and Conference, APSIPA ASC 2023, 2023 <https://www.scopus.com/pages/publications/85180009768?origin=scopusAI>
51. Scoping Review on the Multimodal Classification of Depression and Experimental Study on Existing Multimodal Models Arioiz, U., Smrke, U., Plohl, N., Mlakar, I. Diagnostics, 2022 <https://www.scopus.com/pages/publications/85149480945?origin=scopusAI>
52. Depression Detection by Person's Voice Zavorina, E., Makarov, I. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), 2022 <https://www.scopus.com/pages/publications/85142704487?origin=scopusAI>
53. Most DAIC-WOZ Depression Classifiers Are Invalid, They Don't Learn Task-Specific Features: Preliminary Findings From a Large-Scale Reproducibility Study Patapati, S.V., Pendyala, I., Ambati, M., (...),

Srinivasan, T. ICMI 2025 - Companion Publication of the 27th International Conference on Multimodal Interaction, 2025 <https://www.scopus.com/pages/publications/105022181811?origin=scopusAI>

54. Semi-Supervised Domain Adaptation for Major Depressive Disorder Detection Chen, T., Guo, Y., Hao, S., Hong, R. IEEE Transactions on Multimedia, 2024 <https://www.scopus.com/pages/publications/85171528312?origin=scopusAI>

55. Major depressive disorder discrimination using vocal acoustic features Taguchi, T., Tachikawa, H., Nemoto, K., (...), Arai, T. Journal of Affective Disorders, 2018 <https://www.scopus.com/pages/publications/85027849918?origin=scopusAI>

56. Vocal Acoustic Features as Potential Biomarkers for Identifying/Diagnosing Depression: A Cross-Sectional Study Zhao, Q., Fan, H.-Z., Li, Y.-L., (...), Tan, S.-P. Frontiers in Psychiatry, 2022 <https://www.scopus.com/pages/publications/85130106675?origin=scopusAI>

57. Depression detection using deep learning and large language models from multimodalities Hussain, Y., Zaheer, M.A., Khan, A.M., Malik, A.S. Frontiers in Digital Health, 2026 <https://www.scopus.com/pages/publications/105033595088?origin=scopusAI>

58. Large language models for depression recognition in spoken language integrating psychological knowledge Li, Y., Shao, S., Milling, M., Schuller, B.W. Frontiers in Computer Science, 2025 <https://www.scopus.com/pages/publications/105015093819?origin=scopusAI>

59. Cross-Modal Attention for Multimodal Depression Detection Using Limited DAIC-WOZ Data Shaabihah, F., Kusnawi, K. 2025 12th International Conference on Information Technology, Computer, and Electrical Engineering, ICITACEE 2025, 2025 <https://www.scopus.com/pages/publications/105029771026?origin=scopusAI>

60. FedOcw: optimized federated learning for cross-lingual speech-based Parkinson's disease detection Quan, C., Chen, Z., Ren, K., Luo, Z. npj Digital Medicine, 2025 <https://www.scopus.com/pages/publications/105008004114?origin=scopusAI>