

# Translit

usage: translit.py [-h] [-l] [-s SEARCH] [-i INPUT] [-t TRANSFORM] [-c CUSTOM] [-r RULES]

Transliterate strings

Options:

-h, --help	Show this help message and exit
-l, --list	List all supported transformations.
-s SEARCH, --search SEARCH	Search supported transformations.
-i INPUT, --input INPUT	String to be transformed.
-t TRANSFORM, --transform TRANSFORM	Transformation to be applied to input.
-c CUSTOM, --custom CUSTOM	Custom transformation rules to be applied to input.
-r RULES, --rules RULES	Read transformation rules from LDML file.

## Transformations provided with ICU

Specifying an input string and an ICU transformation:

```
./translit -i=<input_string> -t=<transform>
```

Examples:

```
$ ./translit -i="Ψάπφω" -t='Greek-Latin'  
Psápphō  
$ ./translit -i="የኢትዮጵያ ኦርቶዶክስ ተዋሕዶ ቤተ ክርስቲያን" -t="Ethiopic-Latin/ALALOC"  
ya'iteyoṗeyā oretodokes tawāḥedo bēta keresetiyān  
$ ./translit -i="የኢትዮጵያ ኦርቶዶክስ ተዋሕዶ ቤተ ክርስቲያን" -t="Ethiopic-Latin/Aethiopica"  
yä'itəyopəya orətodokəs tāwāḥədo betä kərəsətiyan  
$ ./translit -i="የኢትዮጵያ ኦርቶዶክስ ተዋሕዶ ቤተ ክርስቲያን" -t="Ethiopic-Latin/Beta_Metsehaf"  
ya'itəyopəyā orətodokəs tawāḥədo beta kərəsətiyān
```

# Custom rules

```
$ ./translit -i="የኢትዮጵያ ኦርቶዶክስ ተዋሕዶ ቤተ ክርስቲያን" -c=":: any-hex;"
\u12E8\u12A2\u1275\u12EE\u1335\u12EB\u0020\u12A6\u122D\u1276\u12F6\u12AD\u1235\u0020\u12
x ./translit -i="Thu᠋᠋ᠵᠠᠩ" -c=":: lower ; :: NFD ; :: any-hex;"
\u0074\u0068\u0075\u0254\u014B\u006A\u0061\u0308\u014B
$ ./translit -i="\u0074\u0068\u0075\u0254\u014B\u006A\u0061\u0308\u014B" -c=":: any-hex,
thu᠋᠋ᠵᠠᠩ
$ ./translit -i="Thu᠋᠋ᠵᠠᠩ" -c=":: Lower; :: NFD; :: [:Mn:] Remove;"
thu᠋᠋ᠵᠠᠩ
```

## Reading rules form LDML file