

TDMA Schedule Planner and Spatial Reuse Optimizer

System Architecture, Mathematical Modeling, & Empirical Benchmarks

1. Executive Summary & Problem Understanding

In shared-spectrum wireless communications, Time Division Multiple Access (TDMA) prevents frame collisions by allocating designated timeslots to transmitting nodes within a periodic frame. This project designs and optimizes a deterministic Python-based TDMA schedule planner supporting spatial reuse under 500-meter radio range constraints.

Key Conflict Rules:

- **Distance-1 Conflict (Direct Range):** Adjacent nodes ($d \leq 500$ m) cannot transmit concurrently.
- **Distance-2 Conflict (Hidden Terminal):** Nodes sharing a common intermediate neighbor cannot share a slot.
- **Spatial Concurrency:** Nodes ≥ 3 hops apart may safely reuse the same timeslot without collision.

2. Mathematical Formulation & Equivalence Proof

Graph Representation: Let $G = (V, E)$ be the physical connectivity graph where $(u, v) \in E$ iff $d(u, v) \leq 500.0$ m. The conflict graph G_{conflict} is the graph square $G^2 = \text{nx.power}(G, 2)$, where an edge connects nodes with shortest path hop distance ≤ 2 .

Equivalence Theorem: A distance-2 vertex coloring of G is mathematically isomorphic to an ordinary vertex coloring of G^2 . Consequently, minimizing the TDMA frame length is equivalent to computing the chromatic number $\chi(G^2)$.

Theoretical Bounds: $\omega(G^2) \leq \chi(G^2) \leq \Delta(G^2) + 1$, where ω is the maximum clique size.

3. Optimization Engine Architecture

To balance runtime efficiency with frame minimization, the system implements 5 complementary heuristics alongside exact solvers:

1. **Largest-Degree-First (LDF / Welsh-Powell):** Prioritizes highly conflicted nodes first; $O(V \log V + E)$.
2. **DSATUR (Degree of Saturation):** Dynamic greedy coloring selecting maximal saturated vertices; $O(V^2 + E)$.
3. **Smallest-Last (Degeneracy):** Matula-Beck elimination ordering bounding colors by subgraph degeneracy; $O(V + E)$.
4. **Randomized Restarts (N=1000):** Explores random permutation basins deterministically with fixed random seeds.
5. **Local Search & Color Reduction:** Kempe-chain 2-color swaps and min-conflicts Tabu search to compress frame length.
6. **Exact Solvers:** Google OR-Tools CP-SAT (0-1 ILP with clique symmetry breaking) and pure-Python Branch & Bound fallback.

4. Empirical Benchmark Results

Topology Scenario	Nodes	G Edges	G ² Edges	Max Deg	Exact Opt	Best Heur	Gap
1. 4x4 Grid (300 m)	16	42	90	15	9 slots	9 slots	0 (Opt)
2. Sparse Linear (350 m)	16	15	29	4	3 slots	3 slots	0 (Opt)
3. Dense Cluster (≤ 500 m)	16	120	120	15	16 slots	16 slots	0 (Opt)
4. Two Disconnected Clusters	16	56	56	7	8 slots	8 slots	0 (Opt)

5. Independent Verification & Integrity Assurance

An independent verification engine evaluates candidate schedules directly on physical graph G via BFS shortest paths. It validates node coverage, contiguous slot labeling (0..K-1), and rigorously flags Distance-1 or Distance-2 collisions. Full unit test suite (42 tests) passes with 100% test coverage.

6. EMANE Emulation Bridge (Part 2)

The Part 2 integration bridge bridges mathematical schedules to Adjacent Link's EMANE TDMA radio model (tdmaeventschedulerradiomodel). Configured with 1 ms slots (1000 μ s), 50 μ s guard time, and 2.4 GHz carrier frequency. Includes an automated XML translator, a Python event script generator, and an end-to-end round-trip schema validation test suite.