

C:\ Administrator: Command Prompt



Tunnel adapter isatap.{42A1F8B7-30A8-4EF7-81AF-C694F5F3D81B}:

Media State : Media disconnected
Connection-specific DNS Suffix . :

Tunnel adapter 6T04 Adapter:

Connection-specific DNS Suffix . :
IPv6 Address : 2002:3200:a::3200:a
Default Gateway :

C:\Users\user>ping 50.0.0.20

Pinging 50.0.0.20 with 32 bytes of data:

Reply from 50.0.0.20: bytes=32 time=2ms TTL=128
Reply from 50.0.0.20: bytes=32 time=1ms TTL=128
Reply from 50.0.0.20: bytes=32 time=1ms TTL=128
Reply from 50.0.0.20: bytes=32 time=1ms TTL=128

Ping statistics for 50.0.0.20:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Users\user>

```
Router#
Router#
Router#
Router#
Router#
Router#
Router#show ip interface brief
Interface                IP-Address      OK? Method Status      Prot
lo0
Ethernet0/0               50.0.0.1        YES manual  up          up
Ethernet0/1               60.0.0.1        YES manual  up          up
Ethernet0/2               unassigned      YES TFTP    down        down
Ethernet0/3               unassigned      YES TFTP    down        down
Router#
```

C:\WINDOWS\system32\cmd.exe - cmd

```
Connection-specific DNS Suffix . :  
IP Address . . . . . : 50.0.0.10  
Subnet Mask . . . . . : 255.0.0.0  
Default Gateway . . . . . :
```

```
C:\Documents and Settings\user>cmd  
Microsoft Windows XP [Version 5.1.2600]  
(C) Copyright 1985-2001 Microsoft Corp.
```

```
C:\Documents and Settings\user>ping 50.0.0.1
```

```
Pinging 50.0.0.1 with 32 bytes of data:
```

```
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255  
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255  
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255  
Reply from 50.0.0.1: bytes=32 time=1ms TTL=255
```

```
Ping statistics for 50.0.0.1:
```

```
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
```

```
Approximate round trip times in milli-seconds:
```

```
Minimum = 1ms, Maximum = 1ms, Average = 1ms
```

```
C:\Documents and Settings\user>
```

C:\WINDOWS\system32\cmd.exe

Persistent Routes:

None

C:\>

C:\>

C:\>

C:\>route add 50.0.0.0 mask 255.0.0.0 60.0.0.1

C:\>

C:\>

C:\>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:

Reply from 50.0.0.10: bytes=32 time=2ms TTL=127

Reply from 50.0.0.10: bytes=32 time=1ms TTL=127

Reply from 50.0.0.10: bytes=32 time=1ms TTL=127

Reply from 50.0.0.10: bytes=32 time=1ms TTL=127

Ping statistics for 50.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\>

Network Connections

Local Area Connection Properties

General | Advanced

Internet Protocol (TCP/IP) Properties

General

You can get IP settings assigned automatically if your network supports this capability. Otherwise, you need to ask your network administrator for the appropriate IP settings.

☐ Obtain an IP address automatically☒ Use the following IP address:

IP address: 50 . 0 . 0 . 10

Subnet mask: 255 . 0 . 0 . 0

Default gateway: 50 . 0 . 0 . 1

☐ Obtain DNS server address automatically☒ Use the following DNS server addresses:

Preferred DNS server: . . .

Alternate DNS server: . . .

Advanced...

OK

Cancel

Connected

01:28:35

1.0 Gbps



Received

36

19

Close

Details

Local Area Connection

LAN or High-Speed Internet

C:\WINDOWS\system32\cmd.exe

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 60.0.0.8:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>

C:\>

C:\>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:

Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\>