KGP-PGW [QR] API Specification v.1.2.1

Version 1.2.1
8 April 2026

1. Version History

Document Name: KGP-PGW [QR] API Specification v.1.2.1

Version: 1.2.1

Effective Date: 8 April 2026

Version	Revision Date	Summary of Changes	Changed by
1.0	11 June 2025	**Initial Version** • Updated the Error Code: In the case of unsuccessful transactions, only HTTP Code 417 will be displayed.	Onnalin T.
1.1	12 August 2025	**Charge** • App switch other bank additional field in billpayment: bank_code	Thanat. tu
1.2	5 January 2026	**Charge** • ref_1, ref_2 change to mandatory for App switch • ref_1, ref_2, ref_3 change length from 128 to 20	Thanat. tu
1.2.1	8 April 2026	Change the template of specification and fix minor typo.	Nuttawan R.

Content

1. Version History **2**
2. Create QR **5**
2.1. Request Parameters 5
Header **5**
Body **5**
2.2. Example Request 6
Header **6**
Body **6**
2.3. Response parameters 7
Header **7**
Body **7**
2.4. Example Response 8
Header **8**
Body **8**
3. Get QR Image **9**
3.1. Response parameters 9
Header **9**
Body **9**
3.2. Example Response 9
Header **9**
4. Cancel QR **9**
4.1. Request Parameters 10
Header **10**
4.2. Response parameters 10
Header **10**
Body **10**
4.3. Example Response 10
Header **10**
Body **10**
5. Charge Inquiry **11**
5.1. Request Parameters 11
Header **11**
5.2. Example Request 11
Header **11**
5.3. Response parameters 11
Header **11**
Body **11**
5.4. Example Response 13
Header **13**
Body **13**
6. Notify Payment **14**
6.1. Request Parameters 14
Body **14**
6.2. Example Request 15

Body **15**
6.3. Response parameters 16
Header **16**
Body **16**
6.4. Example Response 16
Header **16**
Body **17**
7. Refund Transaction **17**
7.1. Request Parameters 17
Header **17**
Body **17**
7.2. Example Request 18
Header **18**
Body **18**
7.3. Response parameters 18
Header **18**
Body **18**
7.4. Example Response 19
Header **19**
Body **19**
8. Refund Notification **19**
8.1. Request Parameters 19
Header **19**
Body **20**
8.2. Response parameters 20
Header **20**
Body **20**
9. Refund Inquiry **21**
9.1. Request Parameters 21
Header **21**
9.2. Response parameters 21
Header **21**
Body **21**
10. Appendix **22**
10.1. Error HTTP Status Code 22
11. Checksum **24**

2. Create QR

Create QR API for generating order confirmations using QR codes.

Service Name	Create QR
API Endpoint (Test Domain)	https://openapi-uat.kgppayments.com
API Endpoint (Production Domain)	https://openapi.kgppayments.com
URL	`/api/v2/qr`
HTTP Method	**POST**

2.1. Request Parameters

Header

Field	Type	Description
content-type	string(255)	(mandatory) Media type of resource JSON **format**: `application/json`
x-api-key	string(64)	(mandatory) Merchant api **secret key**
x-request-id	string(36)	(mandatory) A client creates some random ID, unique per request and passes it to the server. (UUIDv4)

Body

Field	Type	Description
created_datetime	timestamp(25)	(mandatory) UTC datetime of request creation in ISO 8601 format. **Date time format:** `YYYY-MM-DDThh:mm:ssZ`
amount	number(15, 2)	(mandatory) Payment transaction amount **Format:** `000000000000000.00`
currency	string(3)	(mandatory) 3 Letter ISO Currency code in upper case (Only **THB** are accepted.) JSON **format**: `{ "currency": "THB" }`
description	string(256)	(mandatory) Product description
source_type	enum(ThaiQR)	(mandatory) Source type JSON **format**: `{ "source_of_fund": "ThaiQR" }`
order_id	string(100)	(optional) Order ID ***Note:*** *This field should not be included in the API request*
reference_order	string(50)	(mandatory) Unique Order reference number generated by Merchant

metadata	object	object[]	(optional) Additional request object
	item	string(100)	(optional) Product item
	qty	integer	(optional) Product item quantity
	amount	number(15, 2)	(optional) Product amount
ref_1		string(128)	(optional) Reference 1 ***Not allow*** *special character*
ref_2		string(128)	(optional) Reference 2 ***Not allow*** *special character*
ref_3		string(128)	(optional) Reference 3 ***Not allow*** *special character*
qr_expire_time		integer	QR expiration time in seconds If specified, the value must be between 60 seconds and 86,400 seconds (1 day)

2.2. Example Request

Header

```
curl --location '' \
--header 'content-type: application/json' \
--header 'x-api-key: skey_test_1GzaL0tZIZVQPJk1CZYGpIA4qRL3uo4y6' \
--header 'x-request-id: 46c91461-a7e6-4bfa-9665-69d4a88e340b'
```

Body

```
{
    "created_datetime": "2025-05-20T14:20:21+07:00",
    "amount": 999.99,
    "currency": "THB",
    "description": "KGP Product",
    "source_type": "ThaiQR",
    "reference_order": "20250520144614",
    "ref_1": "referenceid1",
    "ref_2": "referenceid2",
    "qr_expire_time": "600"
}
```

2.3. Response parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource `JSON` **format**: `application/json`

Body

Field	Type	Description
qr_id	string(100)	(mandatory) QR ID
object	string(10)	(mandatory) Object Type (Source of funds) `JSON` **format**: `{ "object": "qr" }`
order_id	string(100)	(mandatory) Order ID
created_datetime	string(25)	(mandatory) UTC datetime of request creation in ISO 8601 format. **Date time format:** `YYYY-MM-DDThh:mm:ssZ`
qr_expire_time	integer	(mandatory) QR expiration time in seconds ***Note:*** *The value must match the one specified in the request message*
expired_datetime	timestamp(25)	(optional) QR expired time ISO 8601 format. **Date time format:** `YYYY-MM-DDThh:mm:ssZ`
status	enum("success", "fail")	(mandatory) This API processes the creation of a QR code and returns the status of the QR creation process
reference_order	string(50)	(mandatory) Reference number generated by merchant site ***Note:*** *The value must match the one specified in the request message.*
description	string(256)	(mandatory) Product description ***Note:*** *The value must match the one specified in the request message.*
ref_1	string(128)	(optional) Reference 1 ***Note:*** *The value must match the one specified in the request message.*
ref_2	string(128)	(optional) Reference 2 ***Note:*** *The value must match the one specified in the request message.*
ref_3	string(128)	(optional) Reference 3

		Note: *The value must match the one specified in the request message.*
account_name	string(255)	(mandatory) Account name
paint_text	string(255)	(mandatory) QR Code date
image_with_base64	string(255)	(mandatory) QR image base 64
image_url	string(255)	(mandatory) QR image url
failure_code	string(10)	(optional) Failure code
failure_message	string(256)	(optional) Failure description
qr_reference2	string(20)	(optional) Reference2 of QR Code

2.4. Example Response

Header

```
curl --location '' \
--header 'content-type: application/json' \
```

Body


```
{
    "qr_id": "qr_prod_81584b6131b2a83347cba1e41da6bce3b96f",
    "object": "qr",
    "order_id", "order_prod_8158b9a940c706484db49f5637ed9a83caf2",
    "created_datetime": "2025-05-20T14:20:21+07:00",
    "qr_expire_time": "600",
    "expired_datetime": "2025-01-08T16:47:41+07:00",
    "stauts": "success",
    "reference_order": "20250520144614",
    "description": "KGP Product",
    "ref_1": "referenceid1",
    "ref_2": "referenceid2",
    "account_name": "KASIKORN GLOBAL PAYMENT",
    "paint_text": "00020010020020006A16662222212001110002 9992",
    "image_with_base64": "IVB0Rw0KGghAAAAANSjIAAAJHHDgy1sJAAAAAA",
    "image_url": "https://openapi-
uat.kgppayments.com/api/v1/qr/qr_prod_81584b6131b2a83347cba1e41da6bce3b96f/image",
    "qr_reference2": "250623210552VKE9UEYT",
}
```

3. Get QR Image

API for creating QR Image

Service Name	Get QR Image
API Endpoint (Test Domain)	https://openapi-uat.kgppayments.com
API Endpoint (Production Domain)	https://openapi.kgppayments.com
URL	`/qr/v1/image/{qr_id}?x-api-key={pkey}`
HTTP Method	**GET**

3.1. Response parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource

Body

Field	Type	Description
Binary Image	Image file .PNG	(mandatory) QR Code Image file

3.2. Example Response

Header

```
curl --location '' \
--header 'content-type: application/json' \
```

4. Cancel QR

The Cancel QR Transaction API is used to cancel product orders using QR code.

Service Name	Cancel QR
API Endpoint (Test Domain)	https://openapi-uat.kgppayments.com
API Endpoint (Production Domain)	https://openapi.kgppayments.com
URL	`/api/v2/qr/cancel/{qr_id}`
HTTP Method	**POST**

4.1. Request Parameters

Header

Field	Type	Description
content-type	string(255)	(mandatory) Media type of resource `JSON` **format**: `application/json`
x-api-key	string(64)	(mandatory) Merchant api **secret key**
x-request-id	string(36)	(mandatory) A client creates some random ID, unique per request and passes it to the server. (UUIDv4)

4.2. Response parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource `JSON` **format**: `application/json`

Body

Field	Type	Description
qr_id	string(100)	(mandatory) QR ID
status	enum("success")	(mandatory) Whether the qr is cancel (success) • success: The cancellation of the QR code was successful.
failure_code	string(10)	(optional) Failure code
failure_message	string(256)	(optional) Failure description

4.3. Example Response

Header

```
curl --location '' \
--header 'content-type: application/json' \
```

Body

```
{
    "qr_id": "qr_prod_81584b6131b2a83347cba1e41da6bce3b96f",
    "stauts": "success",
}
```

5. Charge Inquiry

The Inquiry Transaction API is used to retrieve payment transaction information.

Service Name	Charge Inquiry
API Endpoint (Test Domain)	https://openapi-uat.kgppayments.com
API Endpoint (Production Domain)	https://openapi.kgppayments.com
URL	`/api/v2/charge/{charge_id | order_id | reference_order}`
HTTP Method	**GET**

5.1. Request Parameters

Header

Field	Type	Description
content-type	string(255)	(mandatory) Media type of resource `JSON` **format**: `application/json`
x-api-key	string(64)	(mandatory) Merchant api **secret key**
x-request-id	string(36)	(mandatory) A client creates some random ID, unique per request and passes it to the server. (UUIDv4)

5.2. Example Request

Header

```
curl --location '' \
--header 'content-type: application/json' \
--header 'x-api-key: skey_test_1GzaL0tZIZVQPJk1CZYGpIA4qRL3uo4y6' \
--header 'x-request-id: 46c91461-a7e6-4bfa-9665-69d4a88e340b'
```

5.3. Response parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource

Body

Field	Type	Description
charge_id	string(100)	(mandatory) Charge ID
object	string(10)	(mandatory) The objective of request (Constant value: charge) `JSON` **format**: `{ "object": "charge" }`

order_id		string(100)	(optional) Order ID
amount		number(15, 2)	(mandatory) Payment transaction amount **Format:** `000000000000000.00`
currency		string(3)	(mandatory) 3 Letter ISO Currency code in upper case (Only **THB** are accepted.) `JSON` **format**: `{ "currency": "THB" }`
transaction_state		string(50)	(mandatory) Transaction state • Authorized • Settled • Voided • Refunded • Partial Refund `JSON` **format**: `{ "transaction_status": "` Autrorized" }
source	object	object	(mandatory) The source object that was charged
	source_id	string(50)	(mandatory) Source ID from the Create QR API
	object	string(10)	(mandatory) Object Type (Source of funds) `JSON` **format**: `{ "object": "qr" }`
	brand	string(10)	(mandatory) Payment Method brand • ThaiQR
created_datetime		timestamp(25)	(mandatory) UTC datetime of request creation in ISO 8601 format. **Date time format:** `YYYY-MM-DDThh:mm:ssZ`
status		enum("success", "fail")	(mandatory) Transaction status • **success:** Payment transaction completed successfully • **fail:** Payment transaction failed If the status **fail**, please refer to the failure code and failure message fields for the reason
failure_code		string(10)	(optional) Failure code returned when there is an error ***Appendix:*** *Error code*
failure_message		string(256)	(optional) Failure description returned when there is an error ***Appendix:*** *Error code*
description		string(256)	(mandatory) Product description form the Create QR API

reference_order	string(20)	(mandatory) Reference number generated by merchant site form the Create QR API
expired_datetime	timestamp(25)	(optional) Expiration time in ISO 8601 format. **Date time format:** YYYY-MM-DDThh:mm:ssZ
ref_1	string(128)	(optional) Reference 1 from the Create QR API
ref_2	string(128)	(optional) Reference 2 from the Create QR API
ref_3	string(128)	(optional) Reference 3 from the Create QR API
info_1	string(128)	(optional) Information 1 from the Create QR API
info_2	string(128)	(optional) Information 2 from the Create QR API
info_3	string(128)	(optional) Information 3 from the Create QR API
authorized_datetime	timestamp(25)	(optional) Authorized Date Time in ISO 8601 format. **Date time format:** YYYY-MM-DDThh:mm:ssZ
qr_reference2	string(20)	(optional) Reference2 of QR Return Reference2 of QR Code

5.4. Example Response

Header

```
curl --location '' \
--header 'content-type: application/json' \
```

Body

```
{
    "charge_id": "chrg_prod_odd_250901_08158da13b40cac7a4b5aa408b23257e9f8ce",
    "object": "charge",
    "order_id", "order_prod_odd_250901_08158da13b40cac7a4b5aa408b23257e9f8ce",
    "amount": 200.5,
    "currency": "THB",
    "transaction_state": "Authorized",
    "source": [{
        "source_id": " qr_prod_12343028bafc09c847e785ac38622d3d6ee5 ",
        "object": "qr",
        "brand": "ThaiQR"
    }],
    "created_datetime": "2025-05-20T14:20:21+07:00",
    "stauts": "success",
    "description": "KGP Product",
    "reference_order": "20180530175600",
```

```
    "expired_datetime": "2025-05-20T14:20:21+07:00",
    "ref_1": "referenceid1",
    "ref_2": "referenceid2",
    "authorized_datetime": "2025-05-20T14:20:21+07:00",
    "qr_refernce2": "250623210552VKE9UEYT"
}
```


6. Notify Payment

Notify payment via webhook callback

Service Name	Notify Payment
API Endpoint (Test Domain)	*Merchant provides the URL Endpoint*
API Endpoint (Production Domain)	*Merchant provides the URL Endpoint*
HTTP Method	**POST**

6.1. Request Parameters

Body

Field		Type	Description
charge_id		string(100)	(mandatory) Charge ID
object		string(10)	(mandatory) The objective of request (Constant value: charge) JSON **format**: { "object": "charge" }
amount		number(15, 2)	(mandatory) Payment transaction amount **Format:** 000000000000000.00
currency		string(3)	(mandatory) 3 Letter ISO Currency code in upper case (Only **THB** are accepted.) JSON **format**: { "currency": "THB" }
transaction_state		string(50)	(mandatory) Transaction state • Authorized JSON **format**: { "transaction_status": " Authorized" }
source	object	object	(mandatory) The source object
	source_id	string(100)	(mandatory) Source ID from the Create QR API
	object	string(10)	(mandatory) Object Type (Source of funds) JSON **format**: { "object": "qr" }
	brand	string(10)	(mandatory) Payment Method brand • ThaiQR

created_datetime	timestamp(25)	(mandatory) Creation date of the charge in ISO 8601 format. **Date time format:** `YYYY-MM-DDThh:mm:ssZ`
authorized_datetime	timestamp(25)	(mandatory) Authorized Date Time in ISO 8601 format. **Date time format:** `YYYY-MM-DDThh:mm:ssZ`
expired_datetime	timestamp(25)	(mandatory) Expiration Date Time in ISO 8601 format. **Date time format:** `YYYY-MM-DDThh:mm:ssZ`
status	enum("success")	(mandatory) Transaction status • **success:** Payment transaction completed successfully
description	string(256)	(mandatory) Product description form the Create QR API
order_id		(mandatory) Order ID from the Create QR API
reference_order	string(20)	(mandatory) Reference number generated by merchant site form the Create QR API
ref_1	string(128)	(optional) Reference 1 from the Create QR API
ref_2	string(128)	(optional) Reference 2 from the Create QR API
ref_3	string(128)	(optional) Reference 3 from the Create QR API
info_1	string(128)	(optional) Information 1 from the Create QR API
info_2	string(128)	(optional) Information 2 from the Create QR API
info_3	string(128)	(optional) Information 3 from the Create QR API
failure_code	string(10)	(optional) Failure code ***Appendix:*** *Error code*
failure_message	string(256)	(optional) Failure description ***Appendix:*** *Error code*
checksum	string(1024)	(mandatory) Checksum value generated by KGP-Payment Gateway
qr_reference2	string(20)	(optional) Reference2 of QR for the Create QR API

6.2. Example Request

Body

```
{
    "charge_id": "chrg_prod_odd_250901_08158da13b40cac7a4b5aa408b23257e9f8ce",
    "object": "charge",
    "amount": 200.5,
```

```
    "currency": "THB",
    "transaction_state": "Authorized",
    "source": [{
        "source_id": " qr_prod_8158cb811285b1a64351800aaf9aeee705bd ",
        "object": "qr",
        "brand": "ThaiQR"
    }],
    "created_datetime": "2025-05-20T14:20:21+07:00",
    "authorized_datetime": "2025-05-20T14:20:21+07:00",
    "expired_datetime": "2025-05-20T14:20:21+07:00",
    "stauts": "success",
    "description": "KGP Product",
    "order_id", "order_prod_odd_250901_08158da13b40cac7a4b5aa408b23257e9f8ce",
    "reference_order": "20250520144614",
    "ref_1": "referenceid1",
    "ref_2": "referenceid2",
    "checksum": "5f60d113a45fa44055ce2359c51bda57aaf4217281979db824bc2ecb771b736f",
    "qr_reference2": "250623210552VKE9UEYT"
}
```


6.3. Response parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource

Body

Field	Type	Description
failure_code	string(10)	(optional) Failure code returned when there is an error ***Appendix:*** *Error code*
failure_message	string(256)	(optional) Failure description returned when there is an error ***Appendix:*** *Error code*

6.4. Example Response

Header

```
curl --location '' \
--header 'content-type: application/json' \
```

Body

```
{
    "failure_code": "1012",
    "failure_message": "invalid Request",
}
```

7. Refund Transaction

Refund Transaction is a request for a refund to the transaction account online.

Service Name	Refund Transaction
API Endpoint (Test Domain)	https://openapi-uat.kgppayments.com
API Endpoint (Production Domain)	https://openapi.kgppayments.com
URL	`/api/v2/refund/{charge_id}`
HTTP Method	POST

7.1. Request Parameters

Header

Field	Type	Description
content-type	string(255)	(mandatory) Media type of resource `JSON` **format**: `application/json`
x-api-key	string(64)	(mandatory) Merchant api **secret key**
x-request-id	string(36)	(mandatory) A client creates some random ID, unique per request and passes it to the server. (UUIDv4)

Body

Field	Type	Description
refund_ref_id	string(100)	(optional) The unique refund transaction ID that generated by merchant.
refund_amount	number(15, 2)	(mandatory) The amount charged in currency unit. **Format:** `000000000000000.00`
refund_reason	string(255)	(mandatory) Reason for refund transaction.
refund_by	string(50)	(optional) The user who refunds transaction.
transaction_date	string(8)	(optional) Creation date of the charge.

7.2. Example Request

Header

```
curl --location '' \
--header 'content-type: application/json' \
```

Body

```
{
    "refund_ref_id": " 46c91461-a7e6-4bfa-9665-69d4a88e340b",
    "refund_amount": 200.5,
    "refund_reason": "Reject order",
    "refund_by": "Manee Meejai",
    "transaction_date": "27012026"
}
```

7.3. Response parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource

Body

Field	Type	Description
refund_id	string(100)	(mandatory) The unique id assigns by system to refers to the refund transaction
refund_ref_id	string(100)	(optional) The unique id that is generated by merchants. The value must match the one specified in the request message.
charge_id	string(100)	(mandatory) Original charge transaction id
status	string(10)	(mandatory) The refund status • pending • success
refund_amount_type	string(1)	(mandatory) Refund amount type • F: full refund • P: partial refund
refund_day_type	string(1)	(mandatory) Refund Day type • S: SameDay • N: NextDay

failure_code	string(10)	(optional) Failure code returned when there is an error ***Appendix:*** *Error code*
failure_message	string(256)	(optional) Failure description returned when there is an error ***Appendix:*** *Error code*

7.4. Example Response

Header

```
curl --location '' \
--header 'content-type: application/json' \
```

Body

```
{
    "refund_id": "refd_prod_odd_250901_08158da13b40cac7a4b5aa408b23257e9f8ce",
    "refund_ref_id": "46c91461-a7e6-4bfa-9665-69d4a88e340b",
    "charge_id": "chrg_prod_odd_250901_08158da13b40cac7a4b5aa408b23257e9f8ce",
    "status": "pending",
    "refund_amount_type": "F",
    "refund_day_type": "S"
}
```

8. Refund Notification

Refund Notification API for updating refund status to merchant

Service Name	Refund Notification
API Endpoint (Test Domain)	*Merchant provides the URL Endpoint*
API Endpoint (Production Domain)	*Merchant provides the URL Endpoint*
HTTP Method	**POST**

8.1. Request Parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource

Body

Field	Type	Description
refund_id	string(100)	(mandatory) The unique id assigns by system to refers to the refund transaction
refund_ref_id	string(100)	(optional) The unique id that is generated by merchants. The value must match the one specified in the request message.
charge_id	string(100)	(mandatory) Original charge transaction id
status	string(10)	(mandatory) The refund status • pending • success
refund_amount_type	string(1)	(mandatory) Refund amount type • F: full refund • P: partial refund
refund_day_type	string(1)	(mandatory) Refund Day type • S: SameDay • N: NextDay
failure_code	string(10)	(optional) Failure code returned when there is an error ***Appendix:*** *Error code*
failure_message	string(256)	(optional) Failure description returned when there is an error ***Appendix:*** *Error code*

8.2. Response parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource

Body

Field	Type	Description
failure_code	string(10)	(optional) Failure code returned when there is an error
failure_message	string(256)	(optional) Failure description returned when there is an error

9. Refund Inquiry

Inquiry refund transaction

Service Name	Refund Inquiry
API Endpoint (Test Domain)	https://openapi-uat.kgppayments.com
API Endpoint (Production Domain)	https://openapi.kgppayments.com
URL	`/api/v2/refund/{refund_id} or {refund_ref_id}`
HTTP Method	**GET**

9.1. Request Parameters

Header

Field	Type	Description
content-type	string(255)	(mandatory) Media type of resource `JSON` **format**: `application/json`
x-api-key	string(64)	(mandatory) Merchant api **secret key**
x-request-id	string(36)	(mandatory) A client creates some random ID, unique per request and passes it to the server. (UUIDv4)

9.2. Response parameters

Header

Field	Type	Description
content-type	string(255)	(-) Media type of resource

Body

Field	Type	Description
refund_id	string(100)	(mandatory) The unique id assigns by system to refers to the refund transaction
refund_ref_id	string(100)	(optional) The unique id that is generated by merchants.
charge_id	string(100)	(mandatory) Original charge transaction id
status	string(10)	(mandatory) The refund status • pending • success • fail If the status "fail", please refer to the Failure Code and Failure Message fields for the reason.

refund_amount_type	string(1)	(mandatory) Refund amount type • F: full refund • P: partial refund
refund_day_type	string(1)	(mandatory) Refund Day type • S: SameDay • N: NextDay
failure_code	string(10)	(optional) Failure code returned when there is an error ***Appendix:*** *Error code*
failure_message	string(256)	(optional) Failure description returned when there is an error ***Appendix:*** *Error code*

10. Appendix

10.1. Error HTTP Status Code

HTTP Code	Failure Code	Failure Message
417	1001	Over limit amount / Transaction
417	1002	Over limit amount / day
417	1003	Over limit amount / month
417	1004	Transaction amount is invalid
417	1005	cannot refund this transaction
417	1006	cannot void this transaction
417	1007	This transaction has already voided/refunded
417	1008	This transaction is not paid
417	1009	Merchant ID does not exist
417	1010	Unauthorized Function
417	1011	Unable to Process
417	1012	Invalid Request
417	1013	Transaction limit exceeded
417	1014	Bank account is not allow to process
417	1015	Bank is invalid
417	1016	Your payment transaction has failed or was cancelled. Please try again

417	1017	Your transaction is still being processed
417	1018	Missing or invalid : [Parameter]
417	1019	Duplicate entry : [Parameter]
417	1021	cannot cancel this transaction
417	1022	Charge ID does not exist or invalid
417	1023	Refund Ref ID does not exist or invalid
417	1025	Order ID does not exist or invalid
417	1026	Order ID is already used
417	1027	The service hours are now over. Please try again later
417	1028	Transaction does not exist
417	1029	Settlement details does not exist
417	1030	Reference number already exist
417	1031	Reference order already exist
417	2001	QR is cancelled
417	2002	QR already expired
417	2003	QR already paid
417	2004	QR ID is not found
417	2005	minimum expiry time is 1 minutes
417	2006	maximum expiry time is 24 hours
417	2007	Refund cannot be processed for this transaction at the moment
417	5001	Other Error (XX Error Code)
417	9000	Internal Server Error
417	9001	Internal Server Error
417	9999	Internal System Error

11. Checksum

The value is generated by concatenating all necessary values in received JSON request body and adding salt (salt is merchant secret key) then hashing/ encrypting the concatenate string with SHA-256.

The order of the concatenate string is as follows the table:

Field	Description
charge_id	Charge ID
amount	The amount charged in currency units Remark: convert to string format to 4 decimal places
currency	3 Letter ISO Currency code in upper case
status	Whether the transaction is success or fail
transaction_state	Charge transaction state
salt	The salt is merchant **secret key**

Full pattern: id (Charge ID) + amount (convert to string format to 4 decimal places) + currency + status + transaction_state + salt (salt is merchant secret key)

After concatenating the string, apply the SHA-256 algorithm to convert the string into a **checksum**.

Remark: Merchant needs to compare the generated checksum with the value in checksum attribute that received in JSON request body. If both values are the same, merchants can be confident that all receive payment data is secure and can be updated in merchant database