

Pump Shafts — Technical Datasheet

Precision pump shafts manufactured to OEM drawings for centrifugal, vertical turbine, marine, and process pumps.

Standard Capability

Outside Diameter	50 mm to 1500 mm
Length (Machining)	Up to 8000 mm (8 metres)
Length (Grinding)	Up to 6500 mm
Surface Finish	10 to 50 microns (Ra 0.2 – 1.6 µm)
Concentricity	Within 0.01 mm
Straightness	0.05 mm per metre
Weight Capacity	Up to 5 Tonnes per piece
Dynamic Balance	ISO 1940 Grade G2.5 / G6.3
Heat Treatment	Through hardening, induction hardening, nitriding
Coating	Hard chrome plating, HVOF available

Materials Processed

- SS316 / SS316L — Austenitic stainless for chemical and water applications
- Duplex (UNS S31803) — High strength with superior pitting resistance
- Super Duplex (UNS S32750) — Exceptional stress corrosion cracking resistance
- Nitronic 50 — High-strength stainless with excellent corrosion resistance
- EN8 / EN19 / EN24 — High-tensile alloy steels for non-corrosive environments

Documentation Provided

- EN 10204 Type 3.1 Material Test Certificate (MTC)
- Dimensional inspection report
- NDT report (DPT / UT)
- Dynamic balancing certificate (where applicable)

Contact

For drawing-based quotations, email sales@pakoshaft.com or call +91 97670 43447.

