

Introduction to Java Swing

- Java Swing is used to build GUI for Java applications.
- There are two types of swing controls :
 - Containers (Eg: **JFrame**, **JPanel**)
 - Components (individual components that are placed inside containers)
 - Eg:- **JLabel**, **TextField**, **JButton**, **JCheckBox**, **JRadioButton**, **JComboBox**, **JList**, **JPasswordField**, **JTextArea**, **JTable** etc.
- There are separate classes for each swing control. Those classes are defined in the package **javax.swing**
- When Users of Java applications directly interact with GUI using mouse or keyboard, Events will be generated.
- Corresponding to each generated event , there is an **Event Class** and an **Event Listener** interface. Those classes and interfaces are defined in the package **java.awt.event** or in **javax.swing.event**

How to build a GUI using **JButton** & **JLabel**?

- **Import the packages –**
 - **javax.swing** - it contains the classes for the component controls and the container **JFrame**
 - **java.awt.event** - it contains the event classes and event listeners for event handling
- Create a **GUI class** that implements **ActionListener** interface
- Inside the class, declare a **JButton object** and **JLabel object**
- Define **Constructor of the class** that does the following:
 - **create a JFrame**, set its size, set the layout to null
 - create and initialize **JButton & JLabel objects** (set the boundaries x, y, width and height within the frame)
 - **Add button and label into frame** in a proper layout
 - **Call addActionListener()** method of Button object to **register for receiving the eventobject generated** when the user click on the button control
 - make the **Visible property of JFrame to true** (show the frame)
- Define the **public void actionPerformed(ActionEvent e)** method of the **ActionListener** interface to handle the events generated from the Button object
- Create **mian() function** and instantiate an object of GUI class (i. e. **create an object of the GUI Class**)

Demonstrating the above steps with an exercise that displays a message in the label box while clicking on the Button

```
1 // Introducing JButton and JLabel
2 import javax.swing.*;
3 import java.awt.event.*;
4 class GUISample1 implements ActionListener
5 {
6     JButton btnMsg;
7     JLabel lblMsg;
8     GUISample1()
9     {
10         JFrame frm = new JFrame("Button & Label Interface");
11         btnMsg = new JButton("Click Me");
12         lblMsg = new JLabel(".....");
13         frm.setSize(300,300);
14         frm.setLayout(null);
15         frm.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
16         btnMsg.setBounds(50, 100, 100, 50);
17         lblMsg.setBounds(50, 160, 100, 50);
18         frm.add(btnMsg);
19         frm.add(lblMsg);
20         btnMsg.addActionListener(this);
21         frm.setVisible(true);
22     }
23     public void actionPerformed(ActionEvent ae)
24     {
25         if(btnMsg.getText().equals("Click Me"))
26         {
27             lblMsg.setText("Clicked !!!");
28             btnMsg.setText("Clear Me");
29         }
30         else
31         {
32             lblMsg.setText(".....");
33             btnMsg.setText("Click Me");
34         }
35     }
36     public static void main(String args[])
37     {
38         new GUISample1();
39     }
40 }
```

Methods of JButton class

1	JButton(String str)	Constructor to create JButton object
2	setBounds(x, y, width, height)	To set the position and size of the button in the frame
3	setText(string)	To change the text message on the button
4	getText()	To get the text message on the button
5	addActionListener(listener_object)	To register for the action event

Methods of JLabel class

1	JLabel(String str)	Constructor to create label object
2	getText()	To read the string message on the label object
3	setText(string)	to set the string message on a label object
4	setBounds(x, y, width, height)	


Methods of JFrame class

1	JFrame(String)	constructor to create a JFrame object with title
2	setSize(width, height)	set the size of the frame window
3	setLayout()	decide which Layout Manager to use or manual layout
4	add(component_object)	to add component object into a frame
5	setVisible(true)	to show the frame on screen
6	setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE)	To close the application when we close the frame

How to build a GUI using **JRadioButton**, **JCheckBox** , **JTextArea**

- **Import the packages –**
 - **javax.swing** - it contains the classes for the component controls and the container **JFrame**
 - **java.awt.event** - it contains the event classes and event listeners for event handling
- Create a **GUI class** that implements **ActionListener** and **ItemListener** interfaces
- Inside the class, declare necessary **JRadioButton** objects, **JCheckBox** objects and **JTextArea** objects
- Define **Constructor of the class** that does the following:
 - **create a JFrame**, set its size, set the layout to null
 - create and **initialise JRadioButton** objects, **JCheckBox** objects and **JTextArea** objects(set the boundaries **x**, **y**, **width** and **height** within the frame)
 - **Add the created componet objects into the frame** in a proper layout
 - Call **addActionListener()** method of Button object to **register for receiving the eventobject generated** when the user click on the buttoncontrol (Only if you are added a **JButton** in your frame)
 - Call **addItemListener()** method of RadioButton and CheckBox to receive their change events
 - make the **Visible property of JFrame to true** (show the frame)
- Define the **public void actionPerformed(ActionEvent e)** of the **ActionListener** interface to handle the events generated from the Button object
- Define the **public void itemStateChanged(ItemEvent e)** of the **ItemListener** interface to handle the events generated from the **RadioButton** and **CheckBox** object
- Create **mian()** function and instantiate an object of GUI class (i. e. **create an object of the GUI Class**)

*Sample Program:- Demonstrating the above steps with an exercise that displays a the state of a **RadioButton** group for choosing gender and two **CheckBoxes** to select the qualifications. A **Button** for clearing the data is also included . User Interface will be as shown below:*



```
1 // Introducing JRadioButton and JCheckBox and JTextArea
2 import javax.swing.*;
3 import java.awt.event.*;
4 class GUISample2 implements ActionListener, ItemListener
5 {
6     JButton btnClear;
7     JRadioButton rdMale, rdFemale;
8     JCheckBox chkDegree, chkDiploma;
9     JTextArea txtAreaData;
10    ButtonGroup bg;
11
12    GUISample2()
13    {
14        JFrame frm = new JFrame("Radio Button, CheckBox and TextArea");
15        frm.setSize(500,500);
16        frm.setLayout(null);
17        frm.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
18
19        btnClear = new JButton("Clear");
20        btnClear.setBounds(160, 170, 100, 50);
21
22        rdMale = new JRadioButton("Male");
23        rdMale.setBounds(50,50,100,50);
24
25        rdFemale = new JRadioButton("Female");
26        rdFemale.setBounds(160,50,100,50);
27
28        bg=new ButtonGroup();
29        bg.add(rdMale);
30        bg.add(rdFemale);
31
32        chkDegree = new JCheckBox("Degree");
33        chkDegree.setBounds(50,110, 100,50);
34
35        chkDiploma = new JCheckBox("Diploma");
36        chkDiploma.setBounds(160,110, 100,50);
37
38        txtAreaData = new JTextArea("");
39        txtAreaData.setBounds(270, 50, 150, 120);
40    }
```

```
41         frm.add(rdMale);
42         frm.add(rdFemale);
43         frm.add(chkDegree);
44         frm.add(chkDiploma);
45         frm.add(btnClear);
46         frm.add(txtAreaData);
47         btnClear.addActionListener(this);
48         rdMale.addItemListener(this);
49         rdFemale.addItemListener(this);
50         chkDegree.addItemListener(this);
51         chkDiploma.addItemListener(this);
52         frm.setVisible(true);
53     }
```

```
54     public void actionPerformed(ActionEvent ae)
55     {
56         if (ae.getSource() == btnClear)
57         {
58             chkDegree.setSelected(false);
59             chkDiploma.setSelected(false);
60             rdMale.setSelected(false);
61             rdFemale.setSelected(false);
62             txtAreaData.setText("");
63         }
64     }
65     public void itemStateChanged(ItemEvent ie)
66     {
67         String data = "";
68         if(rdMale.isSelected())
69             data = data + "Gender = Male\n";
70         else if (rdFemale.isSelected())
71             data = data + "Gender = Female\n";
72
73         if (chkDegree.isSelected())
74             data = data + "Diploma\n";
75         if (chkDiploma.isSelected())
76             data = data + "Degree\n";
77         txtAreaData.setText(data);
78     }
79
80     public static void main(String args[])
81     {
82         new GUISample2();
83     }
84 }
```

Methods of JRadioButton class

1	JRadioButton(String str)	Constructor to create RadioButton object
2	getText()	To read the text message on RadioButton
3	setText(string)	to set the string message on RadioButton object
4	setBounds(x, y, width, height)	
5	isSelected()	Returns true if the radiobutton is selected
6	addItemListener()	To register for listening the ItemChange Event generated when the user interacts with JRadioButton
7	setSelected(boolean)	To select and deselect the button through program

Methods of JCheckBox class

1	JCheckBox(String str)	Constructor to create CheckBox object
2	getText()	To read the string message on the object
3	setText(string)	to set the string message on the object
4	setBounds(x, y, width, height)	
5	isSelected()	Returns true if the checkBox is ticked
6	addItemListener()	To register for listening the ItemChange Event generated when the user interacts with JCheckBox
7	setSelected(boolean)	To select and deselect the CheckBox through program


Methods of JTextArea class

1. **JTextArea(String str)** – Constructor to create JTextArea object
2. **getText()** – To read the string message on the object
3. **setText(string)** – to set the string message on the object
4. **setBounds(x, y, width, height)**

How to build a GUI using JComboBox?

- **Import the packages –**
 - **javax.swing** - it contains the classes for the component controls and the container JFrame
 - **java.awt.event** - it contains the event classes and event listeners for event handling
- **Define a GUI class that implements ItemListener interface**
- **Inside the class, declare a JComboBox object and JLabel object**
- **Define Constructor of the class that does the following:**
 - **create a JFrame, set its size, set the layout to null**
 - **create and initialize JComboBox & JLabel objects (set the boundaries x, y, width and height within the frame)**
 - **Add ComboBox and label into frame in a proper layout**
 - **Call addItemListener() method of ComboBox object to register for receiving the eventobject generated when the user selecting an item from Combo Box**
 - **make the Visible property of JFrame to true (show the frame)**
- **Define the public void itemStateChanged(ItemEvent e) of the ItemListener interface to handle the events generated from the Button object**
- **Create main() function and instantiate an object of GUI class (i. e. create an object of the GUI Class)**

Sample Program: Demonstrating the above steps with an exercise that displays the capital of selected country




```
1 // Introducing JComboBox
2 import javax.swing.*;
3 import java.awt.event.*;
4 class GUISample3 implements ItemListener
5 {
6     JComboBox cbCountry;
7     JLabel lblCapital;
8     String country[]={"Afghanistan", "Brazil", "Canada", "Denmark",
9                       "Finland", "Germany", "Holland"};
10    String capital[]={"Kabul", "Brasilia", "Ottawa", "Copenhagen",
11                     "Helsinki", "Berlin", "Amsterdam"};
12    GUISample3()
13    {
14        JFrame frm = new JFrame("Country Vs. Capital");
15        frm.setSize(200,200);
16        frm.setLayout(null);
17        frm.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
18
19        cbCountry = new JComboBox(country);
20        cbCountry.setBounds(50, 50, 100, 50);
21
22        lblCapital = new JLabel("Capital");
23        lblCapital.setBounds(50, 110,100,50);
24
25        frm.add(cbCountry);
26        frm.add(lblCapital);
27        cbCountry.addItemListener(this);
28        frm.setVisible(true);
29    }
30    public void itemStateChanged(ItemEvent ie)
31    {
32        int index=cbCountry.getSelectedIndex();
33        lblCapital.setText(capital[index]);
34    }
35    public static void main(String args[])
36    {
37        new GUISample3();
38    }
39 }
```

Methods of JComboBox class

1. **JComboBox(String Array)** - Constructor to create JComboBox with a list of objects from which we can select one
2. **setBounds(x, y, width, height)** - To set the position and size of the button in frame
3. **setSelectedIndex(int)** - to select an item from the combo box list through program
4. **getSelectedIndex()** - to get the index of selected item
5. **getSelectedItem()** - to get the item selected from the combo box
6. **addItemListener(listener_object)** – to register for the action event

EventClass, ActionListener used in the program


- The event class used in this program – **ItemEvent**
- The event listener used is - **ItemListener**
- The method to implement - **itemStateChanged(ItemEvent)**

How to build a GUI using JTextField?

** Here we discuss the simple two operand calculator which includes three TextField objects (two numbers and the result)*

- Import the packages –
 - javax.swing - it contains the classes for the component controls and the container JFrame
 - java.awt.event - it contains the event classes and event listeners for event handling
- Define a GUI class that implements ActionListener interface
- Inside the class, declare a three JTextField objects and necessary JLabel objects & Three Buttons
- Define Constructor of the class that does the following:
 - create a JFrame, set its size, set the layout to null
 - create and initialise JTextField , JLabel and JButton objects (set the boundaries x, y, width and height within the frame)
 - Add all components into frame in a proper layout
 - Call addActionListener() method of Button objects to register for button events
 - make the Visible property of JFrame to true (show the frame)
- Define the public void actionPerformed((ActionEvent e) of the ActionListener interface to handle the events generated from the List object
- Create main() function and instantiate an object of GUI class (i. e. create an object of the GUI Class)

Demonstrating the above steps with an exercise that implements simple calculator



```
1 // Simple Calculator using Java Swing Controls
2 import javax.swing.*;
3 import java.awt.event.*;
4
5 class Calculator implements ActionListener
6 {
7     JLabel lblNum1, lblNum2, lblResult;
8     JTextField txtNum1, txtNum2, txtResult;
9     JButton btnAdd, btnSub, btnClear;
10
11     Calculator()
12     {
13         JFrame jfrm = new JFrame("Math Calculator");
14         lblNum1 = new JLabel("Number 1:");
15         lblNum2 = new JLabel("Number 2:");
16         lblResult = new JLabel("Result :");
17         txtNum1 = new JTextField("0");
18         txtNum2 = new JTextField("0");
19         txtResult = new JTextField("0");
20         txtResult.setEditable(false);
21         btnAdd = new JButton("Add");
22         btnSub = new JButton("Subtract");
23         btnClear = new JButton("Clear");
24
25         jfrm.setSize(500, 500);
26         jfrm.setLayout(null);
27         jfrm.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
28
29         lblNum1.setBounds(100, 50, 100, 50); // (x, y, width, height)
30         lblNum2.setBounds(100, 120, 100, 50);
31         lblResult.setBounds(100, 190, 100, 50);
32         txtNum1.setBounds(250, 50, 100, 50); // (x, y, width, height)
33         txtNum2.setBounds(250, 120, 100, 50);
34         txtResult.setBounds(250, 190, 100, 50);
35         btnAdd.setBounds(100, 250, 75, 50);
36         btnSub.setBounds(180, 250, 150, 50);
37         btnClear.setBounds(335, 250, 75, 50);
```

```
38
39         jfrm.add(lblNum1);
40         jfrm.add(txtNum1);
41         jfrm.add(lblNum2);
42         jfrm.add(txtNum2);
43         jfrm.add(lblResult);
44         jfrm.add(txtResult);
45         jfrm.add(btnAdd);
46         jfrm.add(btnSub);
47         jfrm.add(btnClear);
48
49         btnAdd.addActionListener(this);
50         btnSub.addActionListener(this);
51         btnClear.addActionListener(this);
52         jfrm.setVisible(true);
53     }
54
```

```
55     public void actionPerformed(ActionEvent ae)
56     {
57         float n1, n2, r;
58         n1 = Float.parseFloat(txtNum1.getText());
59         n2 = Float.parseFloat(txtNum2.getText());
60         String cmd = ae.getActionCommand();
61         if (cmd.equals("Add"))
62         {
63             r = n1 + n2;
64             txtResult.setText(Float.toString(r));
65         }
66         else if(cmd.equals("Subtract"))
67         {
68             r = n1 - n2;
69             txtResult.setText(Float.toString(r));
70         }
71         else
72         {
73             txtNum1.setText("0");
74             txtNum2.setText("0");
75             txtResult.setText("0");
76         }
77     }
78 }
79 class MainCalculator
80 {
81     public static void main(String args[])
82     {
83         new Calculator();
84     }
85 }
```

Methods of JTextField class

1. **JTextField(String)** - Constructor to create Text field (Editable field) with a list of objects from which we can select one
2. **getText()** - To get the string from text field
3. **setText(string)** - To set a string in the text field
4. **setBounds(x, y, width, height)** - To set the position and size of the button in frame
5. **cut() , paste(), copy()** - to cut, copy and paste the selected text
6. **getSelectedText()** - to get the index of selected item
7. **addActionListener(listener_object)** - to register for the action event
8. **setEditable(boolean)** - if editable is false, user cannot edit the text
9. **setEnabled(boolean)** - if enabled is false, user cannot use the control


EventClass, EventListener used in the program

- The event class used in this program – **ActionEvent**
- The event listener used is - **ActionListener**
- The method implemented – **actionPerformed(ActionEvent)**

How to build a GUI using JList?

- Import the packages –
 - **javax.swing** - it contains the classes for the component controls and the container **JFrame**
 - **java.awt.event** - it contains the event classes and event listeners for event handling
- Define a GUI class that implements **ListSelectionListener** interface
- Inside the class, declare a **JList** object and **JLabel** object
- Define Constructor of the class that does the following:
 - create a **JFrame**, set its size, set the layout to null
 - create and initialise **JList** & **JLabel** objects (set the boundaries x, y, width and height within the frame)
 - Add **ListBox** and label into frame in a proper layout
 - Call **addListSelectionListener()** method of **ComboBox** object to register for receiving the eventobject generated when the user selecting an item from **List Box**
 - make the **Visible** property of **Jframe** to true (show the frame)
- Define the public void **valueChanged(ListSelectionEvent e)** of the **ListSelectionListener** interface to handle the events generated from the **List** object
- Create **mian()** function and instantiate an object of GUI class (i. e. create an object of the GUI Class)

Demonstrating the above steps with an exercise that displays the the selected text on the label control



```
1 // Demo of JList Swing control
2 import javax.swing.*;
3 import javax.swing.event.*;
4 import java.awt.event.*;
5 class ListDemo implements ListSelectionListener
6 {
7     JList lstMonths;
8     JLabel lblMessage;
9     String months[]={"Jan", "Feb","Mar", "Apr"};
10    ListDemo()
11    {
12
13        JFrame frm=new JFrame("List Demo");
14        frm.setLayout(null);
15        frm.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
16        frm.setSize(300,300);
17
18        lstMonths= new JList<String> (months);
19        lstMonths.setBounds(50,50,100,100);
20        lblMessage = new JLabel(".....");
21        lblMessage.setBounds(50,175, 100,50);
22
23        frm.add(lstMonths);
24        frm.add(lblMessage);
25        lstMonths.addListSelectionListener(this);
26
27        frm.setVisible(true);
28    }
29    public void valueChanged(ListSelectionEvent le)
30    {
31        int index=lstMonths.getSelectedIndex();
32        lblMessage.setText(months[index]);
33    }
34    public static void main(String args[])
35    {
36        new ListDemo();
37    }
38 }
```

Methods of JList class

1. **JList(String Array) - Constructor to create List box with a list of objects from which we can select one**
2. **setBounds(x, y, width, height) - To set the position and size of the button in frame**
3. **setSelectedIndex(int) - to select an item from the combo box list through program**
4. **getSelectedIndex() - to get the index of selected item**
5. **addListSelectionListener(listener_object) – to register for the action event**

EventClass, EventListener used in the program

- The event class used in this program – ListSelectionEvent
- The event listener used is - ListSelectionListener
- The method implemented - valueChanged(ListSelectionEvent)

Handling Mouse Events

To handle mouse events that occurs upon a swing control , We have to do the following tasks in our GUI class

1. Implement MouseListener interface in your GUI class (In this program, GUI class is extended from JFrame and implemented MouseListener)
2. As usual, design your user interface by creating and adding the components in a container frame.
3. Register for MouseEvents using the method addMouseListener()
4. Define the five abstract methods of MouseListener interface. Those methods are:
 - a) mouseClicked(MouseEvent)
 - b) mousePressed(MouseEvent)
 - c) mouseEntered(MouseEvent)
 - d) mouseExited(MouseEvent)
 - e) mouseReleased(MouseEvent)
- 5) Finally create an instance (object) of your GUI class in the main() method to display the user interface so that you can interact with it.

Sample program is given below:

```
1 import javax.swing.*;
2 import java.awt.event.*;
3 class DemoMouseEvents extends JFrame implements MouseListener
4 {
5     JTextField txtMsg;
6     JLabel lblMsg;
7     DemoMouseEvents()
8     {
9         setSize(300,300);
10        setLayout(null);
11        setDefaultCloseOperation(EXIT_ON_CLOSE);
12
13        txtMsg=new JTextField();
14        txtMsg.setBounds(75, 75,150,50);
15
16        lblMsg=new JLabel("*****");
17        lblMsg.setBounds(75,130,150,50);
18
19        add(txtMsg);
20        add(lblMsg);
21
22        txtMsg.addMouseListener(this);
23        setVisible(true);
24    }
25
26    public void mouseClicked(MouseEvent e)
27    {
28        lblMsg.setText("MouseClicked on text field !!!");
29    }
30    public void mousePressed(MouseEvent e)
31    {
32        lblMsg.setText("Mouse Pressed on text field !!!");
33    }
34    public void mouseEntered(MouseEvent e)
35    {
36        lblMsg.setText("Mouse Entered on text field !!!");
37    }
38    public void mouseExited(MouseEvent e)
39    {
40        lblMsg.setText("MouseExited on text field !!!");
41    }
42    public void mouseReleased(MouseEvent e)
43    {
44        lblMsg.setText("MouseReleased on text field !!!");
45    }
46
47    public static void main(String args[])
48    {
49        new DemoMouseEvents();
50    }
51 }
```

Handling Key Events

1. To handle Key board events that occurs upon a swing control , we have to do the following tasks in our GUI class

2. Implement KeyListener interface in your GUI class (In this program, GUI class is extended from JFrame and implemented KeyListener)
3. As usual, design your user interface by creating and adding the components in a container frame.
4. Register for KeyEvents using the method addKeyListener()
5. Define the three abstract methods of KeyListener interface. Those methods are:
 - a) keyPressed(KeyEvent)
 - b) keyReleased(KeyEvent)
 - c) keyTyped(KeyEvent)
6. Finally create an instance (object) of your GUI class in main() method to display the user interface so that you can interact with it.

Sample program is given below (Displays number of characters you typed in a JTextField control):

```
1 import javax.swing.*;
2 import java.awt.event.*;
3 class DemoKeyEvents extends JFrame implements KeyListener
4 {
5     JTextField txtMsg;
6     JLabel lblMsg;
7     DemoKeyEvents()
8     {
9         setSize(300,300);
10        setLayout(null);
11        setDefaultCloseOperation(EXIT_ON_CLOSE);
12
13        txtMsg=new JTextField();
14        txtMsg.setBounds(75, 75,150,50);
15
16        lblMsg=new JLabel("*****");
17        lblMsg.setBounds(75,130,150,50);
18
19        add(txtMsg);
20        add(lblMsg);
21
22        txtMsg.addKeyListener(this);
23        setVisible(true);
24    }
25
26    public void keyPressed(KeyEvent e)
27    {
28        // Empty definition
29    }
30    public void keyReleased(KeyEvent e)
31    {
32        String txt = txtMsg.getText();
33        lblMsg.setText("Character Count:"+ txt.length());
34    }
35    public void keyTyped(KeyEvent e)
36    {
37        //Empty definition
38    }
39
40    public static void main(String args[])
41    {
42        new DemoKeyEvents();
43    }
44 }
```