

CUSTOMER TABLE

```
CREATE TABLE CUSTOMER_29(CUSTOMER_ID INT PRIMARY KEY,CUSTOMER_NAME VARCHAR(30),
CONTACT_NO INT, ADDRESS VARCHAR(100),
CITY VARCHAR(30),POSTAL_CODE INT,COUNTRY VARCHAR(30));

INSERT INTO CUSTOMER_29 VALUES(1, 'ROSE MARY', '1234567890', '12 Main St', 'New York', '10001', 'USA');
INSERT INTO CUSTOMER_29 VALUES(2, 'NISHA S', '2345678901', '45 Oak St', 'Los Angeles', '90001', 'USA');
INSERT INTO CUSTOMER_29 VALUES(3, 'JOVAKKI ROSE', '3456789012', '78 Pine St', 'Chicago', '60007', 'USA');
INSERT INTO CUSTOMER_29 VALUES(4, 'ADITHYAN A', '4567890123', '23 Elm St', 'London', '60090', 'UK');
INSERT INTO CUSTOMER_29 VALUES(5, 'PIOUS JACOB', '5678901234', '56 Maple St', 'Toronto', '62094', 'Canada');
SELECT * FROM CUSTOMER_29;
```

	CUSTOMER_ID	CUSTOMER_NAME	CONTACT_NO	ADDRESS	CITY	POSTAL_CODE	COUNTRY
1	1	ROSE MARY	1234567890	12 Main St	New York	10001	USA
2	2	NISHA S	2345678901	45 Oak St	Los Angeles	90001	USA
3	3	JOVAKKI ROSE	3456789012	78 Pine St	Chicago	60007	USA
4	4	ADITHYAN A	4567890123	23 Elm St	London	60090	UK
5	5	PIOUS JACOB	5678901234	56 Maple St	Toronto	62094	Canada

EMPLOYEES TABLE

```
CREATE TABLE EMPLOYEES(EMPLOYEE_ID INT PRIMARY KEY, LAST_NAME VARCHAR(30),
FIRST_NAME VARCHAR(30), BIRTH_DATE DATE, PHOTO VARCHAR(200));

INSERT INTO EMPLOYEES VALUES(1, 'AYINA', 'SARA', TO_DATE('2004-05-17', 'YYYY-MM-DD'), 'photo1.jpg');
INSERT INTO EMPLOYEES VALUES(3, 'KARTHIK', 'KRISHNAN', TO_DATE('2005-05-10', 'YYYY-MM-DD'), 'photo1.jpg');
INSERT INTO EMPLOYEES VALUES(2, 'ATHULYA', 'ANIL', TO_DATE('2006-07-20', 'YYYY-MM-DD'), 'photo2.jpg');
INSERT INTO EMPLOYEES VALUES(4, 'ZARA', 'RIYAN', TO_DATE('1990-03-15', 'YYYY-MM-DD'), 'photo3.jpg');
INSERT INTO EMPLOYEES VALUES(5, 'LINDA', 'MATHEW', TO_DATE('2008-11-30', 'YYYY-MM-DD'), 'photo4.jpg');
SELECT * FROM EMPLOYEES;
```

	EMPLOYEE_ID	LAST_NAME	FIRST_NAME	BIRTH_DATE	PHOTO
1	1	AYINA	SARA	17-05-04	photo1.jpg
2	2	ATHULYA	ANIL	20-07-06	photo2.jpg
3	3	KARTHIK	KRISHNAN	10-05-05	photo1.jpg
4	4	ZARA	RIYAN	15-03-90	photo3.jpg
5	5	LINDA	MATHEW	30-11-08	photo4.jpg

ORDER TABLE

```
CREATE TABLE ORDERS(ORDER_ID INT PRIMARY KEY,CUSTOMER_ID INT,EMPLOYEE_ID INT,
ORDER_DATE DATE,SHIPPER_ID INT,
FOREIGN KEY(CUSTOMER_ID) REFERENCES CUSTOMER_29(CUSTOMER_ID),
FOREIGN KEY(EMPLOYEE_ID) REFERENCES EMPLOYEES(EMPLOYEE_ID));
```

```

INSERT INTO ORDERS VALUES(101, 1, 1, TO_DATE('10-01-2023','DD-MM-YYYY'), 1);
INSERT INTO ORDERS VALUES(102, 2, 2, TO_DATE('15-02-2023','DD-MM-YYYY'), 2);
INSERT INTO ORDERS VALUES(103, 1, 3, TO_DATE('05-03-2023','DD-MM-YYYY'), 1);
INSERT INTO ORDERS VALUES(104, 3, 4, TO_DATE('25-01-2023','DD-MM-YYYY'), 3);
INSERT INTO ORDERS VALUES(105, 1, 5, TO_DATE('01-04-2023','DD-MM-YYYY'), 2);
SELECT * FROM ORDERS;

```

	ORDER_ID	CUSTOMER_ID	EMPLOYEE_ID	ORDER_DATE	SHIPPER_ID
1	101	1	1	10-01-23	1
2	102	2	2	15-02-23	2
3	103	1	3	05-03-23	1
4	104	3	4	25-01-23	3
5	105	1	5	01-04-23	2

1.

```

SELECT * FROM CUSTOMER_29 ORDER BY CUSTOMER_NAME;

```

	CUSTOMER_ID	CUSTOMER_NAME	CONTACT_NO	ADDRESS	CITY	POSTAL_CODE	COUNTRY
1	4	ADITHYAN A	4567890123	23 Elm St	London	60090	UK
2	3	JOVAKKI ROSE	3456789012	78 Pine St	Chicago	60007	USA
3	2	NISHA S	2345678901	45 Oak St	Los Angeles	90001	USA
4	5	PIOUS JACOB	5678901234	56 Maple St	Toronto	62094	Canada
5	1	ROSE MARY	1234567890	12 Main St	New York	10001	USA

2.

```

SELECT * FROM ORDERS ORDER BY ORDER_DATE

```

	ORDER_ID	CUSTOMER_ID	EMPLOYEE_ID	ORDER_DATE	SHIPPER_ID
1	101	1	1	10-01-23	1
2	104	3	4	25-01-23	3
3	102	2	2	15-02-23	2
4	103	1	3	05-03-23	1
5	105	1	5	01-04-23	2

3.

```

SELECT * FROM EMPLOYEES WHERE BIRTH_DATE > TO_DATE('01-01-1980','DD-MM-YYYY') ORDER BY BIRTH_DATE DESC;

```

	EMPLOYEE_ID	LAST_NAME	FIRST_NAME	BIRTH_DATE	PHOTO
1	5	LINDA	MATHEW	30-11-08	photo4.jpg
2	2	ATHULYA	ANIL	20-07-06	photo2.jpg
3	3	KARTHIK	KRISHNAN	10-05-05	photo1.jpg
4	1	AYINA	SARA	17-05-04	photo1.jpg
5	4	ZARA	RIYAN	15-03-90	photo3.jpg

4.

```
SELECT * FROM ORDERS WHERE CUSTOMER_ID IN(SELECT CUSTOMER_ID FROM CUSTOMER_29 WHERE COUNTRY='USA')
ORDER BY ORDER_DATE DESC;
```

	ORDER_ID	CUSTOMER_ID	EMPLOYEE_ID	ORDER_DATE	SHIPPER_ID
1	105	1	5	01-04-23	2
2	103	1	3	05-03-23	1
3	102	2	2	15-02-23	2
4	104	3	4	25-01-23	3
5	101	1	1	10-01-23	1

5.

```
SELECT CUSTOMER_ID, COUNT(*) AS TOTAL_ORDERS FROM ORDERS GROUP BY CUSTOMER_ID;
```

	CUSTOMER_ID	TOTAL_ORDERS
1	1	3
2	2	1
3	3	1

6.

```
SELECT CITY, COUNT(*) AS TOTALCUSTOMERS FROM CUSTOMER_29 GROUP BY CITY;
```

	CITY	TOTALCUSTOMERS
1	London	1
2	New York	1
3	Los Angeles	1
4	Toronto	1
5	Chicago	1

7.

```
SELECT CUSTOMER_ID, COUNT(*) AS TOTALORDERS FROM ORDERS GROUP BY CUSTOMER_ID HAVING COUNT(*) > 2;
```

	CUSTOMER_ID	TOTALORDERS
1	1	3

8.

```
SELECT CITY, COUNT(*) AS TOTALCUSTOMERS FROM CUSTOMER_29 GROUP BY CITY HAVING COUNT(*) > 3;
```

	CITY	TOTALCUSTOMERS
--	------	----------------