

ASSIGNMENT #03

Web Application Pentesting

Using OWASP Juice Shop

Cybersecurity Assessment Report

Course: Certified Cyber Security Analyst

Student: Athulya Binu

Testing Environment: Local Security Lab

Application: OWASP Juice Shop

August 2026

Contents

1	Introduction	5
2	Scope of Testing	6
2.1	Target Application	6
2.2	Testing Areas	6
2.3	Out of Scope	6
3	Testing Methodology	7
3.1	Phase 1 – Reconnaissance	7
3.2	Phase 2 – HTTP Traffic Interception	7
3.3	Phase 3 – Request Analysis	7
3.4	Phase 4 – Vulnerability Testing	7
3.5	Phase 5 – Validation	7
3.6	Phase 6 – Evidence Collection	8
3.7	Phase 7 – Reporting	8
4	Tools Used	9
4.1	Burp Suite	9
4.2	Web Browser	9
4.3	Kali Linux	9
5	Part A – Setup	10
5.1	Setup Verification	10
5.2	Mandatory Vulnerability Categories	12
6	Finding F-01 – Admin Section	13
6.1	Description	13
6.2	Security Issue	13
6.3	Testing Procedure	13
6.4	Observed Result	13
6.5	Evidence	14
6.6	Security Impact	14
6.7	Recommendation	14
7	Finding F-02 – Confidential Document	16
7.1	Description	16
7.2	Security Issue	16
7.3	Testing Procedure	16
7.4	Impact	17
7.5	Evidence	17
7.6	Security Recommendation	18
8	Finding F-03 – DOM XSS	19
8.1	Description	19
8.2	Affected Functionality	19
8.3	Payload	19
8.4	Testing Procedure	19

8.5	Observed Result	20
8.6	Impact	20
8.7	Evidence	21
8.8	Security Recommendation	21
9	Finding F-04 – Improper Error Handling	22
9.1	Description	22
9.2	Security Issue	22
9.3	Testing Procedure	22
9.4	Observed Result	23
9.5	Impact	23
9.6	Evidence	23
9.7	Security Recommendation	24
10	Finding F-05 – Exposed Credentials	25
10.1	Description	25
10.2	Exposed Information	25
10.3	Testing Procedure	25
10.4	Security Impact	26
10.5	Evidence	26
10.6	Recommendation	26
11	Finding F-06 – Bjoern’s Cat Photo	28
11.1	Description	28
11.2	Security Issue	28
11.3	Testing Procedure	28
11.4	Observed Behavior	29
11.5	Impact	29
11.6	Recommendation	29
11.7	Evidence	30
11.8	Conclusion	30
12	Finding F-07 – Forged Review	31
12.1	Description	31
12.2	Security Issue	31
12.3	Testing Procedure	31
12.4	Observed Behavior	31
12.5	Impact	32
12.6	Evidence	32
12.7	Recommendation	33
12.8	Conclusion	33
13	Finding F-08 – Administrator Authentication Bypass	34
13.1	Description	34
13.2	Security Issue	34
13.3	Testing Procedure	34
13.4	Impact	35
13.5	Recommendation	35
13.6	Evidence	35

14 Finding F-09 – Bender Login	37
14.1 Description	37
14.2 Security Issue	37
14.3 Testing Procedure	37
14.4 Observed Result	38
14.5 Impact	38
14.6 Evidence	38
14.7 Recommendation	39
14.8 Conclusion	40
15 Finding F-10 – Jim Login	41
15.1 Description	41
15.2 Impact	41
15.3 Testing Procedure	41
15.4 Evidence	42
15.5 Recommendation	42
15.6 Conclusion	43
16 Finding F-11 – View Basket	44
16.1 Description	44
16.2 Impact	44
16.3 Testing Procedure	44
16.4 Evidence	44
16.5 Recommendation	45
16.6 Conclusion	46
17 Finding F-12 – Exposed Metrics	47
17.1 Description	47
17.2 Impact	47
17.3 Testing Procedure	47
17.4 Evidence	47
17.5 Recommendation	48
17.6 Conclusion	48
18 Finding F-13 – Greedy Chatbot Manipulation	49
18.1 Description	49
18.2 Testing Environment	49
18.3 LLM Integration Verification	49
18.4 Testing Procedure	50
18.5 Observed Behavior	50
18.6 Security Impact	51
18.7 Root Cause	51
18.8 Recommendation	51
18.9 Evidence	52
18.10 Conclusion	52
19 Overall Security Analysis	54
19.1 Access Control	54
19.2 Authentication	54

19.3 Client-Side Security	54
19.4 Sensitive Data Exposure	54
19.5 Information Disclosure and Input Validation	55
19.6 AI and LLM Security	55
20 Risk Classification	56
21 Remediation Recommendations	57
21.1 Access Control	57
21.2 Prevent Unauthorized Object Access	57
21.3 Secure Authentication	57
21.4 Protect Sensitive Information	58
21.5 Prevent Cross-Site Scripting	58
21.6 Secure Error Handling	58
21.7 Protect Metrics Endpoints	58
21.8 Secure AI and LLM Integration	59
22 Evidence Collection	60
22.1 Recommended Screenshot Placement	60
23 Limitations	61
24 Ethical Considerations	62
25 Conclusion	63
26 Final Summary	64

1. Introduction

OWASP Juice Shop is an intentionally vulnerable web application designed for learning modern web application security.

The application contains vulnerabilities that represent many of the risks commonly found in real-world web applications.

The main objectives of this assessment were:

- Understand the basic architecture of a web application.
- Analyze HTTP requests and responses.
- Identify weaknesses in authentication and authorization.
- Test application input handling.
- Identify client-side security vulnerabilities.
- Validate vulnerabilities using Burp Suite.
- Capture reproducible evidence.
- Document findings in a professional penetration-testing format.

Testing Restriction: All security testing was restricted to the authorized OWASP Juice Shop lab environment. No real-world or unauthorized systems were targeted.

2. Scope of Testing

2.1 Target Application

Target	OWASP Juice Shop
Target URL	<code>http://localhost:3000</code>
Environment	Local Security Lab
Primary Tool	Burp Suite
Operating System	Kali Linux

2.2 Testing Areas

The following application components were examined:

- Authentication
- Authorization
- User accounts
- Shopping basket functionality
- Product functionality
- Review functionality
- Administrative functionality
- Application error handling
- Metrics endpoints
- Client-side JavaScript
- Confidential document access
- User-controlled input

2.3 Out of Scope

The following were outside the scope of the assessment:

- Real-world websites
- Third-party applications
- Unrelated networks
- Production systems
- Systems without explicit authorization

3. Testing Methodology

The assessment followed a structured web application penetration-testing process.

3.1 Phase 1 – Reconnaissance

The application was accessed through the browser and its available functionality was explored.

The objective was to understand the application's structure and identify potential areas requiring further testing.

3.2 Phase 2 – HTTP Traffic Interception

Burp Suite was configured as a proxy between the browser and the Juice Shop application. This allowed HTTP requests and responses to be inspected.

3.3 Phase 3 – Request Analysis

Requests were analyzed for:

- HTTP methods
- Endpoints
- Parameters
- Cookies
- Authentication information
- User identifiers
- Server responses

3.4 Phase 4 – Vulnerability Testing

The application was tested for weaknesses involving:

- Authentication
- Authorization
- Input validation
- Client-side execution
- Information disclosure
- Data integrity

3.5 Phase 5 – Validation

Potential vulnerabilities were reproduced to confirm that the identified behavior represented a genuine security weakness.

3.6 Phase 6 – Evidence Collection

Screenshots, HTTP requests, responses, and browser results were collected as evidence.

3.7 Phase 7 – Reporting

The confirmed findings were categorized according to their security area, impact, reproducibility, and recommended remediation.

4. Tools Used

4.1 Burp Suite

Burp Suite was used as the primary web application penetration-testing tool.

It was used for:

- HTTP request interception
- Request modification
- Repeater-based testing
- Response analysis
- Parameter manipulation
- Authorization testing

4.2 Web Browser

The browser was used to:

- Access Juice Shop
- Interact with application functionality
- Test client-side behavior
- Verify successful exploitation
- Capture screenshots

4.3 Kali Linux

Kali Linux provided the security testing environment and tools required for the assessment.

5. Part A – Setup

The vulnerable application was installed and executed in a controlled local environment.

The application was accessed using:

```
http://localhost:3000
```

The application successfully loaded in the browser.

Evidence: Setup Verification




Figure 1: OWASP Juice Shop running successfully




Figure 2: Application accessed through the browser

5.1 Setup Verification

The following conditions were verified:

- Juice Shop was running successfully.
- The application was accessible through the browser.
- HTTP requests were generated successfully.
- Burp Suite intercepted application traffic.
- Testing could be performed against the local target.

The assessment identified **13 valid and unique findings** across multiple security categories. Each finding was reproduced in the authorized OWASP Juice Shop laboratory environment and supported by appropriate evidence.

ID	Finding	Category	Status
F-01	Admin Section	Server-side / Broken Access Control	Confirmed
F-02	Confidential Document	Server-side / Sensitive Data Exposure	Confirmed
F-03	DOM-Based XSS	Client-side / Cross-Site Scripting	Confirmed
F-04	Improper Error Handling	Server-side / Information Disclosure	Confirmed
F-05	Exposed Credentials	Client-side / Sensitive Data Exposure	Confirmed
F-06	Bjoern's Cat Photo	Server-side / Improper Input Validation	Confirmed
F-07	Forged Review	Server-side / Broken Access Control	Confirmed
F-08	Administrator Login	Server-side / Authentication	Confirmed
F-09	Bender Login	Server-side / Authentication	Confirmed
F-10	Jim Login	Server-side / Authentication	Confirmed
F-11	View Basket	Server-side / Broken Access Control	Confirmed
F-12	Exposed Metrics	Server-side / Information Disclosure	Confirmed
F-13	Greedy Chatbot Manipulation	AI/LLM / Prompt Injection	Confirmed

Assessment Result: A total of **13 valid and unique findings** were identified during the assessment. The findings include both server-side and client-side security weaknesses, satisfying the mandatory requirements of the assignment.

5.2 Mandatory Vulnerability Categories

Requirement	Validated Finding
Server-side vulnerability	F-01 – Admin Section and other confirmed server-side findings
Client-side vulnerability	F-03 – DOM-Based XSS
Additional confirmed findings	F-02, F-04–F-13

6. Finding F-01 – Admin Section

F-01 – Unauthorized Access to Admin Section

Category: Server-side

Security Area: Broken Access Control

6.1 Description

The OWASP Juice Shop application provides an administration panel that contains privileged functionality and administrative user information.

During testing, after authenticating to the application, the administration interface was accessed by navigating directly to the administration route:

```
http://localhost:3000/#/administration
```

The administration panel was successfully loaded and displayed privileged information, including a list of application users.

This demonstrates the importance of enforcing authorization controls for administrative functionality on the server side.

6.2 Security Issue

The administration page provides access to privileged functionality and user information. A secure application should verify that the authenticated account has the appropriate administrative privileges before allowing access to the administration functionality and its underlying API resources.

6.3 Testing Procedure

1. Opened the OWASP Juice Shop application at `http://localhost:3000`.
2. Logged in using the administrator account.
3. After successful authentication, navigated to the administration route:

```
http://localhost:3000/#/administration
```

4. The administration panel was successfully loaded.
5. Inspected the displayed administrative information.
6. Verified that the panel displayed a list of application users.

6.4 Observed Result

The administration interface was successfully displayed after navigating directly to the administration route.

The panel provided access to privileged administrative functionality and displayed information relating to application users.

Administrative interfaces can expose sensitive user and application information and may provide functionality capable of modifying application data. If appropriate server-side authorization controls are not enforced, an unauthorized account could potentially access privileged resources.

6.5 Evidence

Evidence: Admin Section




Figure 1: Successful administrator authentication




Figure 2: Administration panel displaying application user information

6.6 Security Impact

The successful access to the administration panel demonstrates that administrative functionality and user information are available through the application's administration route.

In a production application, administrative functionality should only be accessible to users whose accounts have the required privileges.

6.7 Recommendation

The application should enforce authorization on the server side for all administrative functionality and related API endpoints.

Recommended controls include:

- Verify the authenticated user's role before processing administrative requests.
- Enforce authorization checks on every administrative API endpoint.
- Do not rely solely on frontend route protection.
- Apply the principle of least privilege.

- Prevent non-administrative users from accessing administrative user information.

Key Recommendation: Administrative access should be protected by server-side role-based authorization checks rather than relying only on the frontend administration route.

7. Finding F-02 – Confidential Document

F-02 – Unauthorized Access to Confidential Document

Category: Server-side

Security Area: Access Control / Information Disclosure

7.1 Description

A confidential document named `acquisitions.md` was accessible through the application's publicly reachable FTP resource directory.

During testing, the FTP resource page was accessed through:

```
http://localhost:3000/ftp
```

The page displayed multiple files, including the `acquisitions.md` Markdown document. The document could be opened directly and its contents were successfully viewed.

Sensitive internal documents should be protected by appropriate authentication and authorization controls.

7.2 Security Issue

The finding demonstrates insufficient access control over a sensitive document exposed through the application's FTP resource.

The application allowed the document to be accessed by following the publicly available file listing and selecting `acquisitions.md`.

7.3 Testing Procedure

1. Started the OWASP Juice Shop application in the local Kali Linux testing environment.
2. Opened the Juice Shop application in the browser.
3. Navigated to the FTP resource directory using:

```
http://localhost:3000/ftp
```

4. Observed the list of available files and documents.
5. Identified the file:

```
acquisitions.md
```

6. Selected `acquisitions.md` from the FTP file listing.
7. The document opened successfully in the browser.
8. Verified that the document contained confidential application information.

7.4 Impact

Unauthorized access to confidential documents may result in disclosure of sensitive information and provide attackers with additional information about the application's internal structure.

In a real-world application, exposed internal documents could assist attackers during reconnaissance and potentially reveal information that should only be available to authorized personnel.

7.5 Evidence

Evidence: Confidential Document Access




Figure 1: FTP resource directory displaying *acquisitions.md*




Figure 2: Confidential *acquisitions.md* document successfully accessed




Figure 3: Successful OWASP Juice Shop notification confirming the confidential document access *acquisitions.md*

7.6 Security Recommendation

The application should implement appropriate access controls for sensitive documents and file directories.

Recommended controls include:

- Prevent confidential documents from being publicly accessible.
- Require authentication and authorization for sensitive files.
- Restrict unnecessary directory listing.
- Store confidential documents outside publicly accessible web directories.
- Apply server-side authorization checks to protected resources.
- Regularly audit publicly accessible files and directories.

Key Recommendation: The `acquisitions.md` document should not be accessible through a publicly reachable resource directory. Access to confidential documents must be restricted to authorized users.

8. Finding F-03 – DOM XSS

F-03 – DOM-Based Cross-Site Scripting (XSS)

Category: Client-side

Security Area: Cross-Site Scripting (XSS)

8.1 Description

A DOM-based Cross-Site Scripting (DOM XSS) vulnerability was identified in the product search functionality of the OWASP Juice Shop application.

During testing, the product search parameter `q` was observed in the application URL. The original search value was replaced with an attacker-controlled JavaScript payload.

When the modified input was processed by the client-side application, JavaScript execution occurred in the browser and an alert box was displayed.

This demonstrates that attacker-controlled input supplied through the search functionality was processed unsafely by client-side JavaScript.

8.2 Affected Functionality

The vulnerable functionality was the product search feature.

A normal product search was initially performed using:

```
apple
```

The application generated a URL containing the search parameter:

```
http://localhost:3000/#/search?q=apple
```

The value of the `q` parameter was then modified during testing.

8.3 Payload

The following test payload was used to demonstrate JavaScript execution:

```
<iframe src="javascript:alert('xss')">
```

The payload was used only within the authorized OWASP Juice Shop laboratory environment.

8.4 Testing Procedure

1. Opened the OWASP Juice Shop application in the browser.
2. Navigated to the product search functionality.
3. Searched for a product using the search term `apple`.

4. Observed that the search term was reflected in the URL through the `q` query parameter.

```
http://localhost:3000/#/search?q=apple
```

5. Removed the original value `apple` from the `q` parameter.
6. Replaced the search value with the following DOM XSS test payload:

```
<iframe src="javascript:alert('xss')">
```

7. Submitted the modified URL and allowed the application to process the supplied input.
8. The browser processed the injected content as executable JavaScript.
9. A JavaScript alert box displaying the test message was successfully generated.
10. The successful JavaScript execution confirmed the presence of the DOM-based Cross-Site Scripting vulnerability.
11. The OWASP Juice Shop notification was subsequently observed, confirming successful completion of the corresponding challenge.

8.5 Observed Result

The injected payload was successfully processed by the client-side application.

The browser displayed a JavaScript alert box containing the test message. This demonstrated that attacker-controlled input could result in JavaScript execution within the browser context.

The OWASP Juice Shop challenge-completion notification provided additional confirmation of the successful validation.

8.6 Impact

DOM XSS can allow attacker-controlled JavaScript to execute in a victim's browser context.

Depending on the application's functionality and security controls, successful exploitation may allow:

- Manipulation of webpage content.
- Execution of attacker-controlled JavaScript.
- Phishing or fraudulent interface modification.
- Unauthorized actions performed in the victim's browser context.
- Access to information available to client-side JavaScript.

8.7 Evidence

Evidence: DOM-Based XSS




Figure 1: JavaScript alert demonstrating successful execution of the DOM XSS payload




Figure 2: OWASP Juice Shop notification confirming successful DOM XSS challenge completion

8.8 Security Recommendation

The application should ensure that user-controlled search parameters cannot be interpreted as executable code by the browser.

Recommended controls include:

- Treat all URL parameters as untrusted input.
- Properly validate and encode user-controlled input.
- Avoid unsafe DOM manipulation methods.
- Use safe DOM APIs for displaying search results.
- Implement an appropriate Content Security Policy (CSP).
- Ensure that user input is never interpreted as executable JavaScript.
- Apply output encoding appropriate to the HTML or JavaScript context.

Key Recommendation:

The product search functionality should safely process the `q` parameter and ensure that attacker-controlled input is treated strictly as data rather than executable JavaScript.

Assignment Requirement:

This finding satisfies the mandatory **client-side vulnerability** requirement of the assessment.

9. Finding F-04 – Improper Error Handling

F-04 – Improper Error Handling

Category: Server-side

Security Area: Information Disclosure

9.1 Description

The OWASP Juice Shop application was observed exposing technical error information when a modified request was submitted to a server-side endpoint.

During testing, an existing application request was intercepted using Burp Suite. The request was sent to Burp Suite Repeater, where the request information was modified and resent to the application.

The resulting server response demonstrated improper error handling and exposed technical information about the application's internal processing.

9.2 Security Issue

The application did not handle the modified request securely. Instead of returning a generic error response, technical information was returned in the server response.

Detailed error information can provide useful information about the application's internal implementation and may assist further security testing.

9.3 Testing Procedure

1. Opened the OWASP Juice Shop application in the browser.
2. Configured Burp Suite to intercept the application's HTTP traffic.
3. Identified a relevant application request from the intercepted HTTP traffic.
4. Sent the request to Burp Suite Repeater for controlled testing.
5. Modified the relevant request information in Repeater.
6. Sent the modified request to the application server.
7. Observed the resulting server response in Burp Suite Repeater.
8. The application returned an error containing technical information related to the request processing.
9. The behavior was verified as the intended OWASP Juice Shop error-handling challenge.
10. A successful OWASP Juice Shop notification was displayed, confirming successful completion of the challenge.

9.4 Observed Result

The modified request resulted in an error response containing technical information about the application's internal processing.

The successful OWASP Juice Shop notification subsequently confirmed that the error-handling challenge had been successfully completed.

9.5 Impact

Improper error handling can disclose technical information that may help an attacker understand the application's backend behavior.

Potentially disclosed information may include:

- Database-related errors.
- Backend implementation details.
- Application processing information.
- Internal error messages.
- Information about endpoints or parameters.
- Technical details useful for further vulnerability analysis.

Such information can increase the effectiveness of subsequent attacks when combined with other vulnerabilities.

9.6 Evidence

Evidence: Improper Error Handling




Figure 1: Burp Suite Repeater showing the modified request and resulting server response




Figure 2: OWASP Juice Shop notification confirming successful completion of the error-handling challenge

9.7 Security Recommendation

The application should implement secure error-handling mechanisms.

Recommended controls include:

- Return generic error messages to users.
- Avoid exposing detailed backend or database errors.
- Prevent stack traces and debugging information from being returned to clients.
- Store detailed technical errors securely in server-side logs.
- Validate incoming request parameters before processing them.
- Implement centralized error handling.
- Disable verbose error messages in production environments.

Key Recommendation:

Detailed technical error information should be available only to authorized administrators through secure server-side logs. The client should receive a controlled and generic error response.

10. Finding F-05 – Exposed Credentials

F-05 – Exposed Credentials

Category: Client-side

Security Area: Sensitive Data Exposure / Authentication

10.1 Description

During the assessment, valid credentials for a testing account were identified within the application's client-side JavaScript resource `main.js`.

The credentials were discovered by inspecting the application source using the browser Developer Tools. The `main.js` file contained hardcoded values for a testing username and password.

Because `main.js` is delivered to and accessible by the client, an attacker can inspect the JavaScript source and recover the exposed authentication credentials.

10.2 Exposed Information

The following credential variables were identified in `main.js`:

```
testingUsername = "testing@juice-sh.op";  
testingPassword = "IamUsedForTesting";
```

Security Note: The credentials above were identified directly within the client-accessible `main.js` resource. This demonstrates that authentication secrets were exposed to the client.

10.3 Testing Procedure

1. Opened the OWASP Juice Shop application in the authorized local security-testing environment.
2. Opened the browser Developer Tools using **Shift + Ctrl + I**.
3. Navigated to the **Sources** section.
4. Located the application's `main.js` JavaScript file.
5. Inspected the contents of `main.js`.
6. Identified the hardcoded `testingUsername` and `testingPassword` values.
7. Recorded the exposed credentials as evidence.
8. Navigated to the Juice Shop login page.
9. Entered the discovered username and password.
10. Submitted the login form.

11. Verified that authentication was successful.
12. Confirmed the successful completion of the corresponding Juice Shop challenge.

10.4 Security Impact

Exposing valid authentication credentials in a client-side JavaScript file allows users who can access the application to retrieve those credentials. An attacker could subsequently use the credentials to authenticate as the associated account.

Potential consequences include:

- Unauthorized account access.
- User impersonation.
- Exposure of account information.
- Unauthorized actions performed through the compromised account.
- Increased security risk if privileged credentials are exposed.

10.5 Evidence

Evidence: Exposed Credentials




Figure 1: main.js source showing the exposed testing username and password




Figure 2: Successful authentication using the exposed credentials

10.6 Recommendation

The application should never store valid authentication credentials inside client-side JavaScript files such as main.js.

Recommended controls include:

- Remove hardcoded credentials from `main.js`.
- Never expose passwords through client-side JavaScript.
- Store authentication secrets securely on the server side.
- Rotate credentials that have already been exposed.
- Review JavaScript bundles and static resources for additional hardcoded secrets.
- Apply the principle of least privilege to application accounts.

Key Recommendation: Authentication credentials must remain protected on the server side and must never be embedded in client-accessible JavaScript resources such as `main.js`.

11. Finding F-06 – Bjoern’s Cat Photo

F-06 – Bjoern’s Cat Photo / Improper Input Handling

Category: Server-side

Security Area: Improper Input Validation / Resource Handling

11.1 Description

During testing of the OWASP Juice Shop Photo Wall, a broken image associated with Bjoern’s cat was identified.

The image resource contained special characters within its filename. The filename and resource path were examined through the browser Developer Tools, where the image source and associated resource path were visible.

The resource could then be accessed directly, allowing the intended cat photograph to be retrieved successfully.

This demonstrates improper handling of special characters in resource identifiers and insufficient URL encoding or validation of image resource paths.

11.2 Security Issue

The application uses a filename containing special characters as part of an image resource path. Special characters in URLs and resource identifiers must be handled and encoded correctly.

Improper handling of such characters can result in broken resource references, unexpected URL interpretation, or unintended access to application resources.

11.3 Testing Procedure

The following procedure was followed during the assessment:

1. Opened the OWASP Juice Shop application.
2. Navigated to the **Photo Wall** functionality.
3. Examined the photographs displayed by the application.
4. Identified the broken image associated with Bjoern’s cat.
5. Opened the browser Developer Tools to inspect the image element and its source.
6. Identified the image resource path and filename containing special characters.
7. Examined the **src** attribute of the image element.
8. Accessed the identified image resource.
9. Successfully retrieved and viewed Bjoern’s cat photograph.
10. Verified the successful completion notification generated by the OWASP Juice Shop application.

11.4 Observed Behavior

The Photo Wall contained a broken image entry. Inspection of the corresponding HTML element revealed the image source and filename.

The relevant image element contained a resource similar to:

```

```

The presence of special characters such as # in the resource filename requires correct URL encoding when the resource is referenced by the browser.

The resource was successfully accessed and the intended cat photograph was retrieved.

11.5 Impact

Improper handling of filenames and resource identifiers can result in unexpected application behavior and unintended resource exposure. In a production application, similar weaknesses could potentially contribute to resource disclosure or other file and URL handling vulnerabilities.

11.6 Recommendation

The application should implement proper validation and encoding for resource filenames and identifiers.

Recommended controls include:

- Properly URL-encode filenames and resource identifiers.
- Validate filenames before using them as resource paths.
- Avoid directly using untrusted strings in resource URLs.
- Apply canonicalization before processing file paths.
- Restrict direct access to sensitive application resources.
- Use server-generated identifiers for uploaded files instead of relying on potentially unsafe filenames.
- Ensure that special characters are handled consistently by both the application and web server.

Key Recommendation:

Resource filenames should be validated, canonicalized, and safely encoded before being used in URLs or file-system operations. The application should avoid relying on raw filenames containing special characters when generating resource paths.

11.7 Evidence

Evidence: Bjoern's Cat Photo




Figure 1: OWASP Juice Shop Photo Wall and Developer Tools showing the Bjoern cat image resource.




Figure 2: Bjoern’s cat photograph successfully retrieved from the identified image resource.




Figure 3: Successful OWASP Juice Shop notification confirming completion of the Bjoern’s Cat Photo challenge.

11.8 Conclusion

The test successfully demonstrated that the Bjoern cat image resource could be identified through the Photo Wall and browser Developer Tools, retrieved using its resource path, and validated through the successful OWASP Juice Shop challenge notification.

12. Finding F-07 – Forged Review

F-07 – Forged Review

Category: Server-side

Security Area: Broken Access Control

12.1 Description

The application was found to allow a product review to be posted on behalf of another user or an existing review to be modified without proper authorization.

A review operation should be associated with the authenticated user, and the server should verify that the user has permission to create, modify, or delete the targeted review.

During testing, the review request was intercepted and examined using Burp Suite. User-related information in the request was modified, after which the request was forwarded to the server. The application accepted the modified request and the review operation was successfully performed for another user.

12.2 Security Issue

The vulnerability occurs because the server does not sufficiently validate whether the authenticated user is authorized to perform the requested review operation.

Client-side controls or user-supplied identifiers must not be trusted for authorization decisions. Authorization must be enforced server-side for every review operation.

12.3 Testing Procedure

1. Logged into the OWASP Juice Shop application using a normal user account.
2. Navigated to a product containing a review.
3. Performed a review operation to generate the corresponding HTTP request.
4. Intercepted the request using Burp Suite.
5. Examined the request parameters and user-related information.
6. Modified the relevant user/review information in the request.
7. Forwarded the modified request to the application server.
8. Observed the server response.
9. Verified that the review operation was successfully performed on behalf of another user or against another user's review.

12.4 Observed Behavior

The modified request was accepted by the application server.

The server did not adequately verify that the authenticated user was authorized to perform the requested review operation.

This allowed the review operation to be associated with another user's identity or existing review.

12.5 Impact

An attacker could potentially manipulate reviews belonging to other users or create fraudulent reviews on behalf of another account.

This can affect data integrity, user reputation, and the trustworthiness of product reviews.

Potential impacts include:

- Modification of another user's review.
- Creation of fraudulent reviews.
- Impersonation of another user within the review system.
- Loss of review data integrity.
- Manipulation of product ratings or reputation.

12.6 Evidence

The following evidence demonstrates the review request before and after the user-related information was modified.

Evidence: Forged Review




Figure 1: Original review request captured in Burp Suite.




Figure 2: Successful server response demonstrating the forged review.

12.7 Recommendation

The application should enforce authorization checks on the server for every review operation.

Recommended controls include:

- Associate reviews with the authenticated user's server-side identity.
- Do not trust user identifiers supplied by the client.
- Verify review ownership before allowing modification or deletion.
- Validate authorization for every review-related API request.
- Prevent users from changing the owner of an existing review through request manipulation.
- Return an appropriate authorization error when the user does not have permission to perform the requested operation.

Key Recommendation:

Authorization decisions must be performed on the server using the authenticated session identity. User-supplied identifiers should never be sufficient to authorize modification of another user's review.

12.8 Conclusion

The test demonstrated a Broken Access Control vulnerability in the review functionality. By manipulating the review request, the application accepted an operation that should have been restricted to the authorized owner.

This finding demonstrates the importance of enforcing object-level authorization on the server for all user-controlled resources.

13. Finding F-08 – Administrator Authentication Bypass

F-08 – SQL Injection Authentication Bypass

Category: Server-side

Security Area: Authentication

13.1 Description

The administrator authentication mechanism of the OWASP Juice Shop application was found to be vulnerable to SQL injection.

During the authorized laboratory testing, a SQL injection payload was supplied in the username field of the login form. The payload ' OR 1=1- manipulated the authentication query and resulted in successful authentication without providing the legitimate administrator password.

This demonstrates that user-supplied authentication input was not properly protected against SQL injection.

13.2 Security Issue

The login functionality was susceptible to SQL injection through the username parameter. The following payload was used during testing:

```
' OR 1=1-
```

The manipulated input altered the authentication logic and allowed the authentication process to be bypassed. Successful exploitation resulted in access to the administrator account and its associated privileged functionality.

13.3 Testing Procedure

1. Opened the OWASP Juice Shop login page.
2. Entered the SQL injection payload ' OR 1=1- in the username field.
3. Submitted the login form without providing the legitimate administrator password.
4. The application processed the manipulated authentication input.
5. Authentication was successfully bypassed.
6. The application granted access to the administrator account and its associated privileged functionality.

13.4 Impact

Successful exploitation of this vulnerability can allow an attacker to bypass the application's authentication mechanism and gain unauthorized access to privileged accounts. In a real-world application, this could result in unauthorized access to sensitive information, administrative functionality, user management operations, and other protected resources.

13.5 Recommendation

The following security controls should be implemented to prevent SQL injection-based authentication bypass:

- Use parameterized queries or prepared statements for all database operations.
- Never construct SQL queries by directly concatenating user-supplied input.
- Apply strict server-side input validation.
- Use an established and secure authentication framework.
- Store passwords using strong, modern password hashing algorithms.
- Implement multi-factor authentication for privileged administrator accounts.
- Apply rate limiting and monitoring to authentication endpoints.
- Perform regular security testing of authentication and database-related functionality.

Key Recommendation: Use parameterized database queries and secure authentication mechanisms to prevent user-controlled input from modifying authentication queries. Privileged administrator accounts should additionally be protected using strong authentication and multi-factor authentication.

13.6 Evidence

The following evidence demonstrates the complete administrator authentication process, from the login page and SQL injection payload to successful authentication and administrator access.

Evidence: Administrator Authentication Bypass




Figure 1: OWASP Juice Shop login page showing the SQL injection payload entered in the username field.




Figure 2: Successful authentication following the SQL injection attempt.




Figure 3: Successful administrator login and access to the privileged administrator account.

14. Finding F-09 – Bender Login

F-09 – Bender Account Authentication Bypass

Category: Server-side

Security Area: Authentication

14.1 Description

During the authorized OWASP Juice Shop laboratory assessment, the authentication mechanism for the Bender account was successfully tested.

The Bender account and its associated email address were identified through the administration functionality. The login request was then intercepted using Burp Suite and transferred to Burp Suite Repeater for controlled request analysis.

The authentication request was modified so that the user identity corresponded to the Bender account. The modified request was accepted by the application, resulting in successful authentication as Bender.

14.2 Security Issue

The finding demonstrates a weakness in the application's authentication mechanism. The authentication process allowed the account identity to be manipulated through a modified HTTP request.

Authentication decisions should be performed entirely on the server using securely validated credentials and the authenticated session identity. Client-supplied account information must not be trusted for authentication decisions.

14.3 Testing Procedure

1. Opened the OWASP Juice Shop application in the authorized laboratory environment.
2. Accessed the administration panel and inspected the displayed application-user information.
3. Identified the Bender account and its associated email address.
4. Opened the login page and initiated an authentication attempt.
5. Intercepted the authentication request using Burp Suite.
6. Sent the request to Burp Suite Repeater for controlled testing.
7. Modified the relevant account identity information in the authentication request.
8. Sent the modified request to the application server.
9. Observed the server response and resulting application state.
10. The application successfully authenticated the session as the Bender account.

11. The successful authentication confirmed the corresponding Bender Login challenge.

14.4 Observed Result

The modified authentication request was accepted by the application. Following the request, the application established an authenticated session associated with the Bender account.

The successful authentication demonstrated that the tested authentication mechanism did not sufficiently protect the account identity from request manipulation.

14.5 Impact

Weak authentication controls may allow an attacker to authenticate as another user without possessing the legitimate account credentials.

Potential consequences include:

- Unauthorized access to another user's account.
- User impersonation.
- Exposure of account-specific information.
- Unauthorized use of account functionality.
- Further attacks using the privileges of the compromised account.

14.6 Evidence

The following evidence demonstrates the authentication request manipulation and the resulting successful authentication as the Bender account.

Evidence: Bender Authentication Bypass




Figure 1: Modified authentication request in Burp Suite Repeater.




Figure 2: Successful authentication as the Bender account.

14.7 Recommendation

The application should implement secure server-side authentication and authorization controls to prevent authentication bypass through manipulated input.

Recommended controls include:

- Validate authentication credentials entirely on the server.
- Use parameterized queries and prepared statements for all database operations.
- Never construct authentication queries using direct concatenation of user-supplied input.
- Never trust client-supplied usernames, email addresses, or account identifiers as proof of identity.
- Bind the authenticated session to the identity verified by the server.
- Perform strict server-side input validation.
- Use secure password hashing and credential verification mechanisms.
- Enforce server-side authorization after successful authentication.
- Prevent modification of authentication identity fields from changing the authenticated account.
- Implement multi-factor authentication for sensitive accounts where appropriate.
- Apply rate limiting to authentication endpoints.

- Monitor and log suspicious authentication requests and repeated authentication failures.
- Ensure that sensitive account information is accessible only to appropriately authorized users.

Key Recommendation:

Authentication must be based on credentials securely verified by the server. User-supplied usernames, email addresses, or account identifiers must never be sufficient to authenticate a user as another account. Authentication and authorization decisions must be enforced independently on the server.

14.8 Conclusion

The Bender Login challenge was successfully validated within the authorized OWASP Juice Shop laboratory environment.

The test demonstrated that manipulation of the authentication request could result in successful authentication as the Bender account. This highlights the importance of secure server-side credential validation, parameterized database queries, and proper protection of authenticated account identity.

15. Finding F-10 – Jim Login

F-10 – Jim Login

Category: Server-side

Security Area: Authentication

15.1 Description

An authentication bypass affecting the Jim user account was identified during testing of the OWASP Juice Shop application.

The Jim user's email address was first identified through the administrative interface. The login functionality was then tested using Jim's email address with an invalid password. The authentication request was subsequently captured in Burp Suite Repeater and modified to test whether the server-side authentication logic could be bypassed.

The modified request was accepted by the application, resulting in successful authentication as the Jim user despite the use of an invalid password.

15.2 Impact

Successful exploitation of this weakness could allow an attacker to authenticate as another user without knowing the user's legitimate password.

Potential impacts include:

- Unauthorized access to the Jim user account.
- Exposure of information associated with the compromised account.
- Unauthorized actions performed in the context of the victim account.
- Potential account compromise if the affected account has additional privileges.

15.3 Testing Procedure

1. Accessed the administrative interface within the authorized OWASP Juice Shop laboratory environment.
2. Identified the email address associated with the Jim user.
3. Navigated to the application login page and submitted Jim's email address with an invalid password.
4. Captured the authentication request using Burp Suite.
5. Sent the request to Burp Suite Repeater and modified the authentication input to test for server-side authentication bypass.
6. Resubmitted the modified request.
7. Observed that the application authenticated the session as the Jim user despite the invalid password.

15.4 Evidence

The following evidence demonstrates the Jim authentication request captured and modified in Burp Suite, followed by the successful authentication result.

Evidence: Jim Login




Figure 1: Burp Suite Repeater showing the modified Jim authentication request.




Figure 2: Successful authentication confirming login as the Jim user.

15.5 Recommendation

The application should implement secure server-side authentication controls to prevent authentication bypass through manipulated login requests.

Recommended controls include:

- Validate the supplied password against the authenticated user's account entirely on the server.
- Never allow client-controlled input to determine the authenticated user's identity.
- Use parameterized queries and prepared statements for all authentication-related database operations.
- Apply strict server-side input validation to authentication parameters.
- Use secure password hashing and verification mechanisms.
- Implement rate limiting and account lockout protections for repeated authentication failures.
- Implement multi-factor authentication for sensitive accounts where appropriate.
- Log and monitor suspicious authentication requests and repeated failed login attempts.

Key Recommendation:

Authentication decisions must be based on credentials securely verified by the server. Manipulation of client-supplied authentication parameters must never allow a user to authenticate as another account without the correct password.

15.6 Conclusion

The Jim Login challenge was successfully validated within the authorized OWASP Juice Shop laboratory environment.

Testing demonstrated that manipulation of the authentication request could result in successful authentication as the Jim user despite the use of an invalid password. This confirms a server-side authentication bypass and demonstrates the need for robust credential verification and secure server-side authentication controls.

16. Finding F-11 – View Basket

F-11 – View Basket

Category: Server-side

Security Area: Broken Access Control

16.1 Description

A broken access control vulnerability was identified in the basket functionality of the application.

During testing, it was possible to access the basket belonging to another user by manipulating the basket-related request. The server returned the other user's basket information without properly verifying that the authenticated user was authorized to access that basket.

16.2 Impact

This vulnerability may allow an authenticated attacker to access another user's basket and potentially view sensitive information associated with that basket.

Potential impacts include:

- Unauthorized access to another user's basket.
- Exposure of basket contents and associated information.
- Violation of user data isolation.
- Potential access to additional resources if similar access control weaknesses exist elsewhere in the application.

16.3 Testing Procedure

1. Logged in to the application using an authorized test account.
2. Identified the request used to retrieve the user's basket.
3. Modified the basket identifier to reference another user's basket.
4. Sent the modified request to the server.
5. Observed that the server returned the other user's basket information.

16.4 Evidence

The following evidence demonstrates successful access to another user's basket through the application.

Evidence: Unauthorized Basket Access




Figure 1: Successful access to another user's basket, demonstrating broken access control.

16.5 Recommendation

The application should enforce server-side authorization checks for every basket access request.

Recommended controls include:

- Verify that the authenticated user owns the requested basket.
- Do not rely solely on client-supplied basket identifiers.
- Enforce object-level authorization on every basket request.
- Prevent users from accessing resources belonging to other users.
- Return an appropriate authorization error when access is denied.
- Test access controls using multiple user accounts before deployment.

Key Recommendation:

The server must verify that the authenticated user is authorized to access the requested basket. Client-supplied identifiers must never be treated as sufficient authorization.

16.6 Conclusion

The View Basket challenge was successfully validated within the authorized OWASP Juice Shop laboratory environment.

Testing demonstrated that one user could access another user's basket, confirming a server-side broken access control vulnerability. Proper object-level authorization and server-side ownership validation should be implemented to ensure that users can access only their own basket data.

17. Finding F-12 – Exposed Metrics

F-12 – Exposed Metrics

Category: Server-side

Security Area: Information Disclosure

17.1 Description

An application metrics endpoint was identified and accessed through the application. The endpoint returned monitoring-related metrics that were accessible without appropriate restriction.

The exposed metrics may provide information about application activity and internal behavior that should not be unnecessarily available to unauthorized users.

17.2 Impact

Exposed application metrics may assist attackers during reconnaissance by revealing:

- Application activity and request statistics.
- Internal application behavior.
- Service and endpoint usage patterns.
- Monitoring and operational information.

This information could help an attacker better understand the application and identify areas for further testing.

17.3 Testing Procedure

1. Accessed the application running in the authorized local laboratory environment.
2. Identified the application metrics endpoint.
3. Requested the metrics endpoint through the browser.
4. Observed that the endpoint displayed application metrics.
5. Verified the returned metrics content.

17.4 Evidence

The following evidence demonstrates the exposed metrics endpoint and the metrics information returned by the application.

Evidence: Exposed Metrics




Figure 1: Metrics content returned by the application.




Figure 2: Successful exposed metrics notification in the OWASP Juice Shop application.

17.5 Recommendation

The application should restrict access to metrics and monitoring endpoints and expose only the information required for legitimate monitoring purposes.

Recommended controls include:

- Require authentication and authorization for sensitive metrics endpoints.
- Restrict metrics endpoints to trusted monitoring systems where possible.
- Avoid exposing unnecessary internal application information.
- Review the information contained in exposed metrics regularly.
- Apply appropriate network-level access restrictions to monitoring interfaces.

Key Recommendation:

Metrics endpoints should not expose unnecessary application or operational information to unauthorized users. Access should be restricted according to the application's security requirements.

17.6 Conclusion

The Exposed Metrics challenge was successfully validated within the authorized OWASP Juice Shop laboratory environment.

Testing confirmed that the application's metrics endpoint was accessible and returned application monitoring information. Restricting access to the endpoint and minimizing the information exposed would reduce unnecessary information disclosure.

18. Finding F-13 – Greedy Chatbot Manipulation

F-13 – Greedy Chatbot Manipulation

Category: Server-side / AI Application

Security Area: Prompt Injection / AI Security

18.1 Description

The OWASP Juice Shop chatbot was tested for resistance to manipulation of its predefined coupon-generation policy.

The chatbot was configured to use a locally hosted Ollama large language model through an OpenAI-compatible API. During testing, adversarial user instructions were used to influence the chatbot's behavior and bypass its intended coupon-generation restrictions.

The chatbot eventually disclosed information related to a **10% discount coupon**, followed by a successful sale notification.

This demonstrates that the chatbot's behavior could be influenced by user-supplied instructions that conflicted with its intended policy.

18.2 Testing Environment

AI Model	qwen2.5:1.5b
LLM API	http://host.docker.internal:11434/v1
Application	OWASP Juice Shop
Target	http://localhost:3000
LLM Runtime	Ollama
Chat Endpoint	/rest/chat

18.3 LLM Integration Verification

Initial testing was performed using the **gemma3:1b** model. The model was not suitable for the chatbot integration because it did not provide the required tool-calling capability.

A tool-capable model, **qwen2.5:1.5b**, was subsequently installed and configured.

The selected model reported the following capabilities:

capabilities: ["completion", "tools"]

The Juice Shop chatbot was configured to communicate with Ollama through the following OpenAI-compatible API endpoint:

http://host.docker.internal:11434/v1

The resulting communication path was:

Juice Shop → /rest/chat → OpenAI-compatible API → Ollama → qwen2.5:1.5b

A request to the `/rest/chat` endpoint successfully returned a streamed Server-Sent Events (SSE) response containing model-generated content and a completion signal.

This confirmed successful end-to-end communication between the Juice Shop application, the OpenAI-compatible API, Ollama, and the selected tool-capable LLM.

LLM Integration Status: Confirmed

The `qwen2.5:1.5b` model was successfully integrated with OWASP Juice Shop through the OpenAI-compatible Ollama API. The successful `/rest/chat` response confirmed that the chatbot integration was operational and ready for security testing.

18.4 Testing Procedure

1. Configured the OWASP Juice Shop chatbot to communicate with the locally hosted Ollama service.
2. Verified that the `qwen2.5:1.5b` model supported the required tool-calling capability.
3. Verified that the Juice Shop application was running on `http://localhost:3000`.
4. Sent a normal request to the chatbot endpoint `/rest/chat` and confirmed that the chatbot returned a successful streamed response.
5. Interacted with the chatbot using adversarial instructions designed to influence its predefined coupon-generation policy.
6. Attempted multiple instruction variations to determine whether the chatbot would disclose or generate restricted discount information.
7. Observed that the chatbot eventually disclosed information related to a **10% discount coupon**.
8. Verified the resulting successful sale notification displayed by the application.

18.5 Observed Behavior

The chatbot initially maintained restrictions around coupon generation. However, after successive adversarial instructions, its response behavior changed.

The chatbot eventually disclosed information related to a **10% discount coupon**. The application subsequently displayed a successful sale notification.

This demonstrates that the chatbot's behavior could be influenced by user-supplied instructions that conflicted with its intended policy.

18.6 Security Impact

AI assistants that do not reliably enforce system-level policies may be manipulated into producing responses or performing actions that violate their intended business rules.

In a real-world application, this could potentially result in unauthorized discounts, disclosure of restricted coupon information, or other unintended business actions.

Security-sensitive business decisions should therefore not rely solely on the language model's ability to follow instructions.

18.7 Root Cause

The underlying issue is related to insufficient separation between:

- Trusted system instructions
- Application security policies
- User-supplied instructions
- Security-critical business logic

The chatbot was able to interpret adversarial user instructions in a way that influenced its intended coupon-generation behavior.

Security-critical business rules should not depend solely on the LLM's instruction-following behavior.

18.8 Recommendation

Security-critical business rules should be enforced by the application backend rather than relying exclusively on the chatbot.

Recommended controls include:

- Treat all chatbot user input as untrusted.
- Keep system instructions separate from user instructions.
- Validate AI-generated actions before execution.
- Enforce coupon and discount limits through server-side business logic.
- Do not allow the LLM to directly authorize discounts or security-sensitive coupon decisions.
- Apply allowlists for sensitive chatbot operations.
- Log and monitor suspicious prompt manipulation attempts.
- Perform security testing against prompt injection and instruction-conflict scenarios.

Key Recommendation:

The LLM should assist with conversation and recommendations, but the application backend must make the final authorization decision for security-sensitive operations such as coupon generation, discount application, and coupon redemption.

18.9 Evidence

The following evidence demonstrates successful chatbot manipulation resulting in the disclosure of a 10% discount coupon and the corresponding successful sale notification.

Evidence: Greedy Chatbot Manipulation




Figure 1: Successful chatbot manipulation resulting in the disclosure of a 10% discount coupon and a successful sale notification.

18.10 Conclusion

The Greedy Chatbot challenge was successfully validated within the authorized OWASP Juice Shop laboratory environment.

The chatbot was successfully integrated with the locally hosted `qwen2.5:1.5b` model

through Ollama and the OpenAI-compatible API. Testing subsequently demonstrated that adversarial instructions could influence the chatbot's intended coupon-generation behavior.

The chatbot disclosed information related to a **10% discount coupon**, followed by a successful sale notification. This confirms a prompt injection and AI policy enforcement weakness.

The application should therefore enforce all security-sensitive coupon and discount decisions through independent server-side business logic rather than relying solely on the LLM.

19. Overall Security Analysis

The assessment identified vulnerabilities across several important areas of web application and AI security. A total of **13 confirmed findings** were documented during the assessment.

19.1 Access Control

Several findings demonstrated weaknesses in server-side authorization and access control:

- F-01 – Admin Section
- F-02 – Confidential Document
- F-07 – Forged Review
- F-11 – View Basket

These findings demonstrate the importance of enforcing authorization checks on the server side for every protected resource and ensuring that users can access only resources for which they are authorized.

19.2 Authentication

Authentication-related weaknesses were identified in several login functions:

- F-08 – Administrator Login
- F-09 – Bender Login
- F-10 – Jim Login

The findings demonstrate the importance of secure server-side credential verification and preventing manipulation of authentication parameters from resulting in unauthorized account access.

19.3 Client-Side Security

The following finding demonstrated a client-side security weakness:

- F-03 – DOM-Based XSS

The finding demonstrates the risks associated with processing untrusted input through unsafe browser-side JavaScript and DOM operations.

19.4 Sensitive Data Exposure

Sensitive information exposure was identified through:

- F-02 – Confidential Document
- F-05 – Exposed Credentials

These findings demonstrate the importance of protecting sensitive information and preventing confidential data or credentials from being exposed to unauthorized users.

19.5 Information Disclosure and Input Validation

The assessment also identified information disclosure and input validation weaknesses:

- F-04 – Improper Error Handling
- F-06 – Bjoern's Cat Photo
- F-12 – Exposed Metrics

These findings demonstrate how improperly handled errors, exposed resources, and accessible application metrics can provide useful information to an attacker during reconnaissance.

19.6 AI and LLM Security

The assessment also included testing of the application's AI chatbot:

- F-13 – Greedy Chatbot Manipulation

The finding demonstrated that adversarial user instructions could influence chatbot behavior and result in disclosure of information related to a 10% discount coupon.

Security-sensitive business rules should therefore be enforced through independent server-side application logic rather than relying solely on LLM instruction following.

20. Risk Classification

The following qualitative risk ratings are used for this educational assessment.

ID	Finding	Suggested Risk
F-01	Admin Section	High
F-02	Confidential Document	Medium–High
F-03	DOM-Based XSS	High
F-04	Improper Error Handling	Medium
F-05	Exposed Credentials	High
F-06	Bjoern's Cat Photo	Low–Medium
F-07	Forged Review	Medium
F-08	Administrator Login	High
F-09	Bender Login	Medium
F-10	Jim Login	Medium
F-11	View Basket	High
F-12	Exposed Metrics	Low–Medium
F-13	Greedy Chatbot Manipulation	Medium

These ratings are qualitative ratings for the training environment. A production security assessment should use the application's actual business impact and an appropriate methodology such as CVSS.

21. Remediation Recommendations

21.1 Access Control

Implement server-side authorization checks for every protected resource.

The server should verify:

```
Authenticated User
    |
    v
Requested Resource
    |
    v
Required Permission
    |
    v
Allow / Deny
```

Authorization should never depend only on frontend restrictions or client-supplied identifiers.

21.2 Prevent Unauthorized Object Access

Applications should verify ownership or authorization before returning objects such as:

- Shopping baskets
- Reviews
- Documents
- User profiles
- Orders

21.3 Secure Authentication

Authentication should be performed entirely on the server.

Recommended controls include:

- Strong authentication mechanisms
- Secure password hashing and verification
- Parameterized database queries
- Rate limiting
- Login attempt monitoring
- Secure session management
- Multi-factor authentication for privileged accounts

21.4 Protect Sensitive Information

Sensitive documents, credentials, and account information should be accessible only to authorized users.

Recommended controls include:

- Apply strict access controls to confidential resources.
- Never expose credentials through client-side code.
- Avoid storing sensitive credentials in publicly accessible locations.
- Use secure secret management mechanisms.
- Review application responses for unnecessary sensitive data.

21.5 Prevent Cross-Site Scripting

Applications should:

- Validate user input where appropriate.
- Encode output according to its context.
- Avoid unsafe DOM APIs.
- Use safe DOM manipulation methods.
- Implement an appropriate Content Security Policy.

21.6 Secure Error Handling

Production applications should avoid displaying detailed technical errors to users.

A generic message should be displayed instead:

```
An unexpected error occurred.  
Please try again later.
```

Detailed technical information should be stored securely in server-side logs.

21.7 Protect Metrics Endpoints

Metrics endpoints should be:

- Authenticated where appropriate
- Authorized
- Restricted to trusted monitoring systems where possible
- Configured to expose only required information

21.8 Secure AI and LLM Integration

AI assistants should not be trusted as the sole enforcement mechanism for security-sensitive business rules.

Recommended controls include:

- Treat all user prompts as untrusted input.
- Separate system instructions from user instructions.
- Validate AI-generated actions before execution.
- Enforce coupon and discount rules through server-side logic.
- Prevent the LLM from directly authorizing sensitive operations.
- Log and monitor prompt manipulation attempts.
- Perform regular prompt-injection security testing.

22. Evidence Collection

Evidence was collected during the testing process using screenshots, HTTP request/response information, and application responses.

For each vulnerability, the report should contain:

1. Vulnerability title
2. Vulnerability category
3. Affected functionality
4. Description
5. Testing procedure
6. Payload or modified parameter where applicable
7. HTTP request/response where applicable
8. Screenshot showing successful validation
9. Security impact
10. Recommended remediation

22.1 Recommended Screenshot Placement

Finding	Recommended Evidence
F-01	Admin section screenshot
F-02	Confidential document screenshot
F-03	DOM XSS payload and successful alert screenshot
F-04	Burp request and error response
F-05	Exposed credential screenshot
F-06	Bjoern's cat photo retrieval screenshot
F-07	Original and modified review request
F-08	Administrator login/result
F-09	Bender login/result
F-10	Jim login/result
F-11	Unauthorized basket access/result
F-12	Metrics endpoint and returned metrics content
F-13	Chatbot manipulation and successful 10% coupon notification

23. Limitations

The assessment was conducted against an intentionally vulnerable training application.

Therefore:

- Findings are specific to the OWASP Juice Shop environment.
- Results should not automatically be applied to unrelated applications.
- Testing was restricted to the authorized laboratory environment.
- Some vulnerabilities are intentionally simplified for educational purposes.
- Risk ratings may differ in real-world applications.
- The AI chatbot testing was performed using a locally hosted LLM configuration.

24. Ethical Considerations

All testing was performed against an authorized OWASP Juice Shop instance in a controlled laboratory environment.

No unauthorized third-party systems or real-world websites were targeted.

The techniques demonstrated in this assignment are intended for:

- Authorized penetration testing
- Cybersecurity education
- Vulnerability research
- Defensive security improvement

Security testing should always be performed only with appropriate authorization and within a clearly defined scope.

25. Conclusion

The OWASP Juice Shop penetration-testing exercise provided practical experience in identifying, validating, and documenting common web application and AI security vulnerabilities.

A total of **13 confirmed findings** were identified during the assessment. These findings covered several security categories, including:

- Broken Access Control
- Authentication weaknesses
- DOM-Based Cross-Site Scripting
- Sensitive Data Exposure
- Information Disclosure
- Improper Input Validation
- Improper Error Handling
- AI/LLM Prompt Injection

The assessment demonstrated the importance of strong server-side authorization, secure authentication, protection of sensitive information, proper input validation, safe client-side processing, controlled error handling, protected monitoring endpoints, and secure AI integration.

The assessment also demonstrated that security-sensitive business logic should not depend solely on client-side controls or AI model instruction-following behavior.

The practical use of Burp Suite provided experience in analyzing HTTP communication and validating security weaknesses through controlled request manipulation within the authorized laboratory environment.

26. Final Summary

Assessment Item	Result
OWASP Juice Shop Setup	Completed
Local Testing Environment	Completed
Burp Suite Testing	Completed
Server-side Vulnerabilities	Identified
Client-side Vulnerability	Identified
AI/LLM Security Testing	Completed
Confirmed Findings	13
Evidence Collection	Screenshots / Re-requests / Responses

End of Security Assessment Report