



Chapter 18 : Concurrency Control

Database System Concepts, 7th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use



Outline

- Lock-Based Protocols
- Timestamp-Based Protocols
- Validation-Based Protocols
- Multiple Granularity
- Multiversion Schemes
- Insert and Delete Operations
- Concurrency in Index Structures



Lock-Based Protocols

- A lock is a mechanism to control concurrent access to a data item
- Data items can be locked in two modes :
 1. **exclusive** (*X*) *mode*. Data item can be both read as well as written. X-lock is requested using **lock-X** instruction.
 2. **shared** (*S*) *mode*. Data item can only be read. S-lock is requested using **lock-S** instruction.
- Lock requests are made to concurrency-control manager. Transaction can proceed only after request is granted.



Lock-Based Protocols (Cont.)

- **Lock-compatibility matrix**

	S	X
S	true	false
X	false	false

- A transaction may be granted a lock on an item if the requested lock is compatible with locks already held on the item by other transactions
- Any number of transactions can hold shared locks on an item,
- But if any transaction holds an exclusive on the item no other transaction may hold any lock on the item.



Lock-Based Protocols (Cont.)

- Example of a transaction performing locking:

T_2 : **lock-S**(A);

read (A);

unlock(A);

lock-S(B);

read (B);

unlock(B);

display(A+B)

- Locking as above is not sufficient to guarantee serializability



Transactions with Lock-Based Protocols

	T_1	T_2	concurrency-control manager
T_1 :	lock-X(B)		
	read(B);		grant-X(B, T_1)
	$B := B - 50$;		
	write(B);		
	unlock(B);		
	lock-X(A);		
	read(A);	lock-S(A)	
	$A := A + 50$;		grant-S(A, T_2)
	write(A);	read(A)	
	unlock(A).	unlock(A)	
		lock-S(B)	
			grant-S(B, T_2)
		read(B)	
		unlock(B)	
		display($A + B$)	
T_2 :			
	lock-S(A);		
	read(A);		
	unlock(A);		
	lock-S(B);		
	read(B);		
	unlock(B);		
	display($A + B$).		
		lock-X(A)	
			grant-X(A, T_1)
		read(A)	
		$A := A + 50$	
		write(A)	
		unlock(A)	

Figure 18.4 Schedule 1.



Schedule With Lock Grants

- Grants omitted in rest of chapter
 - Assume grant happens just before the next instruction following lock request
- This schedule is not serializable (why?)
- A **locking protocol** is a set of rules followed by all transactions while requesting and releasing locks.
- Locking protocols enforce serializability by restricting the set of possible schedules.

T_1	T_2	concurrency-control manager
lock-X(B)		grant-X(B, T_1)
read(B)		
$B := B - 50$		
write(B)		
unlock(B)		
	lock-S(A)	
		grant-S(A, T_2)
	read(A)	
	unlock(A)	
	lock-S(B)	
		grant-S(B, T_2)
	read(B)	
	unlock(B)	
	display($A + B$)	
lock-X(A)		grant-X(A, T_1)
read(A)		
$A := A + 50$		
write(A)		
unlock(A)		



Transactions with unlocking delayed

T_3 : lock-X(B);
 read(B);
 $B := B - 50$;
 write(B);
 lock-X(A);
 read(A);
 $A := A + 50$;
 write(A);
 unlock(B);
 unlock(A).

T_4 : lock-S(A);
 read(A);
 lock-S(B);
 read(B);
 display($A + B$);
 unlock(A);
 unlock(B).

T_1	T_2	concurrency-control manager
lock-X(B)		grant-X(B, T_1)
read(B) $B := B - 50$ write(B) unlock(B)		
	lock-S(A)	grant-S(A, T_2)
	read(A) unlock(A) lock-S(B)	
		grant-S(B, T_2)
	read(B) unlock(B) display($A + B$)	
lock-X(A)		grant-X(A, T_1)
read(A) $A := A + 50$ write(A) unlock(A)		



Deadlock

- Consider the partial schedule

T_3	T_4
lock-X(B) read(B) $B := B - 50$ write(B)	
	lock-S(A) read(A) lock-S(B)
lock-X(A)	

- Neither T_3 nor T_4 can make progress — executing **lock-S(B)** causes T_4 to wait for T_3 to release its lock on B , while executing **lock-X(A)** causes T_3 to wait for T_4 to release its lock on A .
- Such a situation is called a **deadlock**.
 - To handle a deadlock one of T_3 or T_4 must be rolled back and its locks released.




Deadlock (Cont.)

- The potential for deadlock exists in most locking protocols. Deadlocks are a necessary evil.
- **Starvation** is also possible if concurrency control manager is badly designed. For example:
 - A transaction may be waiting for an X-lock on an item, while a sequence of other transactions request and are granted an S-lock on the same item.
 - The same transaction is repeatedly rolled back due to deadlocks.
- Concurrency control manager can be designed to prevent starvation.



The Two-Phase Locking Protocol

- A protocol which ensures conflict-serializable schedules.
- Phase 1: **Growing Phase**
 - Transaction may obtain locks
 - Transaction may not release locks
- Phase 2: **Shrinking Phase**
 - Transaction may release locks
 - Transaction may not obtain locks
- The protocol assures serializability. It can be proved that the transactions can be serialized in the order of their **lock points** (i.e., the point where a transaction acquired its final lock).





Partial Schedule under Two-Phase Locking Protocol

T_5	T_6	T_7
lock-X(A) read(A) lock-S(B) read(B) write(A) unlock(A)	lock-X(A) read(A) write(A) unlock(A)	lock-S(A) read(A)



The Two-Phase Locking Protocol (Cont.)

- Two-phase locking *does not* ensure freedom from deadlocks
- Extensions to basic two-phase locking needed to ensure recoverability of freedom from cascading roll-back
 - **Strict two-phase locking:** a transaction must hold all its exclusive locks till it commits/aborts.
 - Ensures recoverability and avoids cascading roll-backs
 - **Rigorous two-phase locking:** a transaction must hold *all* locks till commit/abort.
 - Transactions can be serialized in the order in which they commit.
- Most databases implement rigorous two-phase locking, *but refer to it as simply two-phase locking*



Lock Conversions

- Two-phase locking protocol with lock conversions:
 - Growing Phase:
 - can acquire a lock-S on item
 - can acquire a lock-X on item
 - can **convert** a lock-S to a lock-X (**upgrade**)
 - Shrinking Phase:
 - can release a lock-S
 - can release a lock-X
 - can convert a lock-X to a lock-S (**downgrade**)
- This protocol ensures serializability



The Two-Phase Locking Protocol (Cont.)

Example to lock conversion

T_8 : read(a_1);
 read(a_2);
 ...
 read(a_n);
 write(a_1).

T_9 : read(a_1);
 read(a_2);
 display($a_1 + a_2$).

T_8	T_9
lock-S(a_1)	lock-S(a_1)
lock-S(a_2)	lock-S(a_2)
lock-S(a_3)	
lock-S(a_4)	
	unlock(a_1)
	unlock(a_2)
lock-S(a_n)	
upgrade(a_1)	



The Two-Phase Locking Protocol (Cont.)

- Two-phase locking is not a necessary condition for serializability
 - There are conflict serializable schedules that cannot be obtained if the two-phase locking protocol is used.
- In the absence of extra information (e.g., ordering of access to data), two-phase locking is necessary for conflict serializability *in the following sense*:
 - *Given a transaction T_i that does not follow two-phase locking, we can find a transaction T_j that uses two-phase locking, and a schedule for T_i and T_j that is not conflict serializable.*

T_1	T_2
lock-X(B)	
read(B)	
$B := B - 50$	
write(B)	
unlock(B)	
	lock-S(A)
	read(A)
	unlock(A)
	lock-S(B)
	read(B)
	unlock(B)
	display($A + B$)
lock-X(A)	
read(A)	
$A := A + 50$	
write(A)	
unlock(A)	



Locking Protocols

- Given a locking protocol (such as 2PL)
 - A schedule S is **legal** under a locking protocol if it can be generated by a set of transactions that follow the protocol
 - A protocol **ensures** serializability if all legal schedules under that protocol are serializable



Automatic Acquisition of Locks

- A transaction T_i issues the standard read/write instruction, without explicit locking calls.
- The operation **read**(D) is processed as:
 - if** T_i has a lock on D
 - then**
 - read(D)
 - else begin**
 - if necessary wait until no other transaction has a **lock-X** on D
 - grant T_i a **lock-S** on D ;
 - read(D)
 - end**



Automatic Acquisition of Locks (Cont.)

- The operation **write**(D) is processed as:
if T_i has a **lock-X** on D
 then
 write(D)
 else begin
 if necessary wait until no other trans. has any lock on D ,
 if T_i has a **lock-S** on D
 then
 upgrade lock on D to **lock-X**
 else
 grant T_i a **lock-X** on D
 write(D)
 end;
- All locks are released after commit or abort




Implementation of Locking

- A **lock manager** can be implemented as a separate process
- Transactions can send lock and unlock requests as messages
- The lock manager replies to a lock request by sending a lock grant messages (or a message asking the transaction to roll back, in case of a deadlock)
 - The requesting transaction waits until its request is answered
- The lock manager maintains an in-memory data-structure called a **lock table** to record granted locks and pending requests



Lock Table

- Dark rectangles indicate granted locks, light colored ones indicate waiting requests
- Lock table also records the type of lock granted or requested
- New request is added to the end of the queue of requests for the data item, and granted if it is compatible with all earlier locks
- Unlock requests result in the request being deleted, and later requests are checked to see if they can now be granted
- If transaction aborts, all waiting or granted requests of the transaction are deleted
 - lock manager may keep a list of locks held by each transaction, to implement this efficiently






Graph-Based Protocols

- Graph-based protocols are an alternative to two-phase locking
- Impose a partial ordering \circ on the set $\mathbf{D} = \{d_1, d_2, \dots, d_h\}$ of all data items.
 - If $d_i \circ d_j$ then any transaction accessing both d_i and d_j must access d_i before accessing d_j .
 - Implies that the set \mathbf{D} may now be viewed as a directed acyclic graph, called a *database graph*.
- The *tree-protocol* is a simple kind of graph protocol.



Tree Protocol

- Only exclusive locks are allowed.
- The first lock by T_i may be on any data item. Subsequently, a data Q can be locked by T_i only if the parent of Q is currently locked by T_i .
- Data items may be unlocked at any time.
- A data item that has been locked and unlocked by T_i cannot subsequently be relocked by T_i .





Serialized Schedule under Tree Protocol

T_{10} : lock-X(B); lock-X(E); lock-X(D); unlock(B); unlock(E); lock-X(G);
 unlock(D); unlock(G).
 T_{11} : lock-X(D); lock-X(H); unlock(D); unlock(H).
 T_{12} : lock-X(B); lock-X(E); unlock(E); unlock(B).
 T_{13} : lock-X(D); lock-X(H); unlock(D); unlock(H).

T_{10}	T_{11}	T_{12}	T_{13}
lock-X(B)	lock-X(D) lock-X(H) unlock(D)		
lock-X(E) lock-X(D) unlock(B) unlock(E)		lock-X(B) lock-X(E)	
	unlock(H)		
lock-X(G) unlock(D)			lock-X(D) lock-X(H) unlock(D) unlock(H)
		unlock(E) unlock(B)	
unlock(G)			



Graph-Based Protocols (Cont.)

- The tree protocol ensures conflict serializability as well as freedom from deadlock.
- Unlocking may occur earlier in the tree-locking protocol than in the two-phase locking protocol.
 - Shorter waiting times, and increase in concurrency
 - Protocol is deadlock-free, no rollbacks are required
- Drawbacks
 - Protocol does not guarantee recoverability or cascade freedom
 - Need to introduce commit dependencies to ensure recoverability
 - Transactions may have to lock data items that they do not access.
 - increased locking overhead, and additional waiting time
 - potential decrease in concurrency
- Schedules not possible under two-phase locking are possible under the tree protocol, and vice versa.



Deadlock Handling

- System is **deadlocked** if there is a set of transactions such that every transaction in the set is waiting for another transaction in the set.

T_3	T_4
lock-X(B) read(B) $B := B - 50$ write(B)	
	lock-S(A) read(A) lock-S(B)
lock-X(A)	



Deadlock Handling

- ***Deadlock Prevention***
- ***Deadlock Detection & Deadlock Recovery***
- ***Deadlock prevention*** protocols ensure that the system will *never* enter into a deadlock state. Some prevention strategies:
 - Require that each transaction locks all its data items before it begins execution (pre-declaration).
 - Hard to predict what data items need to be locked
 - Poor data-item utilization (most of the time data items are idle)
 - No circular waits in ordering the requests for locks.
 - Transaction roll-back whenever the waiting for the lock is required.
 - Impose partial ordering of all data items and require that a transaction can lock data items only in the order specified by the partial order (graph-based protocol).



More Deadlock Prevention Strategies

- **wait-die** scheme — non-preemptive
 - Older transaction may wait for younger one to release data item.
 - Younger transactions never wait for older ones; they are rolled back instead.
 - A transaction may die several times before acquiring a lock
- **wound-wait** scheme — preemptive
 - Older transaction *wounds* (forces rollback) of younger transaction instead of waiting for it.
 - Younger transactions may wait for older ones.
 - Fewer rollbacks than *wait-die* scheme.
- In both schemes, a rolled back transactions is restarted with its original timestamp.
 - Ensures that older transactions have precedence over newer ones, and starvation is thus avoided.



Deadlock prevention (Cont.)


■ Timeout-Based Schemes:

- A transaction waits for a lock only for a specified amount of time. After that, the wait times out and the transaction is rolled back.
- Ensures that deadlocks get resolved by timeout if they occur
- Simple to implement
- But may roll back transaction unnecessarily in absence of deadlock
 - Difficult to determine good value of the timeout interval.
- Starvation is also possible




Deadlock Detection

- **Wait-for graph**
 - *Vertices:* transactions
 - *Edge from $T_i \rightarrow T_j$:* if T_i is waiting for a lock held in conflicting mode by T_j
- The system is in a deadlock state if and only if the wait-for graph has a cycle.
- Invoke a deadlock-detection algorithm periodically to look for cycles.



Wait-for graph without a cycle



Wait-for graph with a cycle



Deadlock Recovery

- When deadlock is detected :
 - Some transaction will have to rolled back (made a **victim**) to break deadlock cycle.
 - Select that transaction as victim that will incur minimum cost
 - How long the transaction is completed & left-over
 - How many data items the transaction has used and how many required for completion?
 - How many transactions are involved in deadlock
 - Rollback -- determine how far to roll back transaction
 - **Total rollback**: Abort the transaction and then restart it.
 - **Partial rollback**: Roll back victim transaction only as far as necessary to release locks that another transaction in cycle is waiting for
- Starvation can happen (why?)
 - One solution: oldest transaction in the deadlock set is never chosen as victim




Multiple Granularity

- Allow data items to be of various sizes and define a hierarchy of data granularities, where the small granularities are nested within larger ones
- Can be represented graphically as a tree (but don't confuse with tree-locking protocol)
- When a transaction locks a node in the tree *explicitly*, it *implicitly* locks all the node's descendants in the same mode.
- **Granularity of locking** (level in tree where locking is done):
 - **Fine granularity** (lower in tree): high concurrency, high locking overhead
 - **Coarse granularity** (higher in tree): low locking overhead, low concurrency



Example of Granularity Hierarchy

- The levels, starting from the coarsest (top) level are
 - *database*
 - *area*
 - *file*
 - *record*
- The corresponding tree





Intention Lock Modes

- In addition to S and X lock modes, there are three additional lock modes with multiple granularity:
 - ***intention-shared*** (IS): indicates explicit locking at a lower level of the tree but only with shared locks.
 - ***intention-exclusive*** (IX): indicates explicit locking at a lower level with exclusive or shared locks
 - ***shared and intention-exclusive*** (SIX): the subtree rooted by that node is locked explicitly in shared mode and explicit locking is being done at a lower level with exclusive-mode locks.
- Intention locks allow a higher level node to be locked in S or X mode without having to check all descendent nodes.



Compatibility Matrix with Intention Lock Modes

- The compatibility matrix for all lock modes is:

	IS	IX	S	SIX	X
IS	true	true	true	true	false
IX	true	true	false	false	false
S	true	false	true	false	false
SIX	true	false	false	false	false
X	false	false	false	false	false



Multiple Granularity Locking Scheme

- Transaction T_i can lock a node Q , using the following rules:
 1. The lock compatibility matrix must be observed.
 2. The root of the tree must be locked first, and may be locked in any mode.
 3. A node Q can be locked by T_i in S or IS mode only if the parent of Q is currently locked by T_i in either IX or IS mode.
 4. A node Q can be locked by T_i in X, SIX, or IX mode only if the parent of Q is currently locked by T_i in either IX or SIX mode.
 5. T_i can lock a node only if it has not previously unlocked any node (that is, T_i is two-phase).
 6. T_i can unlock a node Q only if none of the children of Q are currently locked by T_i .
- Observe that locks are acquired in root-to-leaf order, whereas they are released in leaf-to-root order.
- **Lock granularity escalation:** in case there are too many locks at a particular level, switch to higher granularity S or X lock



Multiple Granularity Locking Scheme

- Illustration of a Protocol :
 1. Suppose that transaction T_1 reads record ra_2 in file F_a . Then, T_1 needs to lock the database, area A_1 , and F_a in IS mode (and in that order), and finally to lock ra_2 in S mode.
 2. Suppose that transaction T_2 modifies record ra_9 in file F_a . Then, T_2 needs to lock the database, area A_1 , and file F_a (and in that order) in IX mode, and finally to lock ra_9 in X mode.
 3. Suppose T_3 reads all records in file F_a . Then T_3 needs to lock the database and area A_1 (and in that order) in IS mode, and finally to lock F_a in S mode.
 4. Suppose that transaction T_4 reads the entire database. It can do so after locking the database in S mode.
- T_1 , T_3 and T_4 can access the database concurrently
- T_1 and T_2 can execute concurrently
- T_2 cannot execute concurrently with either T_3 or T_4 .



Timestamp Based Concurrency Control



Timestamp-Based Protocols

- Each transaction T_i is issued a timestamp $TS(T_i)$ when it enters the system.
 - Each transaction has a *unique* timestamp
 - Newer transactions have timestamps strictly greater than earlier ones
 - Timestamp could be based on a logical counter
- Timestamp-based protocols manage concurrent execution such that
time-stamp order = serializability order
- Several alternative protocols based on timestamps



Timestamp-Ordering Protocol

The **timestamp ordering (TSO) protocol**

- Maintains for each data Q two timestamp values:
 - **W-timestamp**(Q) is the largest time-stamp of any transaction that executed **write**(Q) successfully.
 - **R-timestamp**(Q) is the largest time-stamp of any transaction that executed **read**(Q) successfully.
- Imposes rules on read and write operations to ensure that
 - Any conflicting operations are executed in timestamp order
 - Out of order operations cause transaction rollback



Timestamp-Based Protocols (Cont.)

- Suppose a transaction T_i issues a **read**(Q)
 1. If $TS(T_i) < \mathbf{W}\text{-timestamp}(Q)$, then T_i needs to read a value of Q that was already overwritten.
 - Hence, the **read** operation is rejected, and T_i is rolled back.
 2. If $TS(T_i) \geq \mathbf{W}\text{-timestamp}(Q)$, then the **read** operation is executed, and
R-timestamp(Q) is set to **max**(R-timestamp(Q), $TS(T_i)$).



Timestamp-Based Protocols (Cont.)

- Suppose that transaction T_i issues **write**(Q).
 1. If $TS(T_i) < R\text{-timestamp}(Q)$, then the value of Q that T_i is producing was needed previously, and the system assumed that that value would never be produced.
 - Hence, the **write** operation is rejected, and T_i is rolled back.
 2. If $TS(T_i) < W\text{-timestamp}(Q)$, then T_i is attempting to write an obsolete value of Q .
 - Hence, this **write** operation is rejected, and T_i is rolled back.
 3. Otherwise, the **write** operation is executed, and $W\text{-timestamp}(Q)$ is set to $TS(T_i)$.



Example of Schedule Under TSO

- Is this schedule valid under TSO?

Assume that initially:

$$R\text{-TS}(A) = W\text{-TS}(A) = 0$$

$$R\text{-TS}(B) = W\text{-TS}(B) = 0$$

Assume $TS(T_{25}) = 25$ and

$$TS(T_{26}) = 26$$

T_{25}	T_{26}
read(B)	read(B) $B := B - 50$ write(B)
read(A)	read(A)
display($A + B$)	$A := A + 50$ write(A) display($A + B$)

- How about this one,
where initially
 $R\text{-TS}(Q) = W\text{-TS}(Q) = 0$

T_{27}	T_{28}
read(Q)	write(Q)
write(Q)	



Another Example Under TSO


A partial schedule for several data items for transactions with timestamps 1, 2, 3, 4, 5, with all R-TS and W-TS = 0 initially

T_1	T_2	T_3	T_4	T_5
				read (X)
read (Y)	read (Y)			
		write (Y) write (Z)		
				read (Z)
	read (Z) abort			
read (X)			read (W)	
		write (W) abort		
				write (Y) write (Z)



Correctness of Timestamp-Ordering Protocol

- The timestamp-ordering protocol guarantees serializability since all the arcs in the precedence graph are of the form:



Thus, there will be no cycles in the precedence graph

- Timestamp protocol ensures freedom from deadlock as no transaction ever waits.
- But the schedule may not be cascade-free, and may not even be recoverable.



Recoverability and Cascade Freedom

- Solution 1:
 - A transaction is structured such that its writes are all performed at the end of its processing
 - All writes of a transaction form an atomic action; no transaction may execute while a transaction is being written
 - A transaction that aborts is restarted with a new timestamp
- Solution 2:
 - Limited form of locking: wait for data to be committed before reading it
- Solution 3:
 - Use commit dependencies to ensure recoverability



Thomas' Write Rule

- Modified version of the timestamp-ordering protocol in which obsolete **write** operations may be ignored under certain circumstances.
- When T_i attempts to write data item Q , if $TS(T_i) < W\text{-timestamp}(Q)$, then T_i is attempting to write an obsolete value of $\{Q\}$.
 - Rather than rolling back T_i as the timestamp ordering protocol would have done, this **{write}** operation can be ignored.
- Otherwise this protocol is the same as the timestamp ordering protocol.
- Thomas' Write Rule allows greater potential concurrency.
 - Allows some view-serializable schedules that are not conflict-serializable.



Concurrency Control under Insertion & Deletion Operations



Insert & Delete Operations

- Delete: $li = \text{delete}(Q)$
 - $lj = \text{read}(Q)$. li and lj conflict. If li comes before lj , Tj will have a logical error. If lj comes before li , Tj can execute the read operation successfully.
 - $lj = \text{write}(Q)$. li and lj conflict. If li comes before lj , Tj will have a logical error. If lj comes before li , Tj can execute the write operation successfully.
 - $lj = \text{delete}(Q)$. li and lj conflict. If li comes before lj , Tj will have a logical error. If lj comes before li , Ti will have a logical error.
 - $lj = \text{insert}(Q)$. li and lj conflict. Suppose that data item Q did not exist prior to the execution of li and lj . Then, if li comes before lj , a logical error results for Ti . If lj comes before li , then no logical error results. Likewise, if Q existed prior to the execution of li and lj , then a logical error results if lj comes before li , but not otherwise.



Two-phase locking and TSO protocols for Insert/Delete Operations

- Delete Operation
- Under the two-phase locking protocol, an exclusive lock is required on a data item before that item can be deleted.
- Under the timestamp-ordering protocol, a test similar to that for a write must be performed. Suppose that transaction T_i issues $\text{delete}(Q)$.
 - If $\text{TS}(T_i) < \text{R-timestamp}(Q)$, then the value of Q that T_i was to delete has already been read by a transaction T_j with $\text{TS}(T_j) > \text{TS}(T_i)$. Hence, the delete operation is rejected, and T_i is rolled back.
 - If $\text{TS}(T_i) < \text{W-timestamp}(Q)$, then a transaction T_j with $\text{TS}(T_j) > \text{TS}(T_i)$ has written Q . Hence, this delete operation is rejected, and T_i is rolled back.
 - Otherwise, the delete is executed.
- Insertion Operation
 - Conflicts with delete, read and write operations
 - Under the two-phase locking protocol, if T_i performs an $\text{insert}(Q)$ operation, T_i is given an exclusive lock on the newly created data item Q .
 - Under the timestamp-ordering protocol, if T_i performs an $\text{insert}(Q)$ operation, the values $\text{R-timestamp}(Q)$ and $\text{W-timestamp}(Q)$ are set to $\text{TS}(T_i)$.



Validation-Based Protocol

- Idea: can we use commit time as serialization order?
- To do so:
 - Postpone writes to end of transaction
 - Keep track of data items read/written by transaction
 - **Validation** performed at commit time, detect any out-of-serialization order reads/writes
- Also called as **optimistic concurrency control** since transaction executes fully in the hope that all will go well during validation



Validation-Based Protocol

- Execution of transaction T_i is done in three phases.
 1. **Read and execution phase:** Transaction T_i (a) During this phase, the system executes transaction T_i . It reads the values of the various data items and stores them in variables local to T_i . It performs all write operations on temporary local variables, without updates of the actual database.
 2. **Validation phase:** The validation test (described below) is applied to transaction T_i . This determines whether T_i is allowed to proceed to the write phase without causing a violation of serializability. If a transaction fails the validation test, the system aborts the transaction.
 3. **Write phase:** If the validation test succeeds for transaction T_i , the temporary local variables that hold the results of any write operations performed by T_i are copied to the database. Read-only transactions omit this phase.
- The three phases of concurrently executing transactions can be interleaved, but each transaction must go through the three phases in that order.
 - We assume for simplicity that the validation and write phase occur together, atomically and serially
 - I.e., only one transaction executes validation/write at a time.



Validation-Based Protocol (Cont.)

- Each transaction T_i has 3 timestamps
 - **StartTS**(T_i) : the time when T_i started its execution
 - **ValidationTS**(T_i): the time when T_i entered its validation phase
 - **FinishTS**(T_i) : the time when T_i finished its write phase
- Validation tests use above timestamps and read/write sets to ensure that serializability order is determined by validation time
 - Thus, $TS(T_i) = \text{ValidationTS}(T_i)$
- Validation-based protocol has been found to give greater degree of concurrency than locking/TSO if probability of conflicts is low.



Validation Test for Transaction T_j

- If for all T_i with $TS(T_i) < TS(T_j)$ either one of the following condition holds:
 - **finishTS**(T_i) < **startTS**(T_j)
 - **startTS**(T_j) < **finishTS**(T_i) < **validationTS**(T_j) **and** the set of data items written by T_i does not intersect with the set of data items read by T_j .

then validation succeeds and T_j can be committed.

- Otherwise, validation fails and T_j is aborted.
- Justification:
 - First condition applies when execution is not concurrent
 - The writes of T_j do not affect reads of T_i since they occur after T_i has finished its reads.
 - If the second condition holds, execution is concurrent, T_j does not read any item written by T_i .



Schedule Produced by Validation

- Example of schedule produced using validation

T_{25}	T_{26}
read(B)	read(B) $B := B - 50$ read(A) $A := A + 50$
read(A) <validate> display($A + B$)	<validate> write(B) write(A)