

theory of Computation

Relation Machine will do computations on the basis of Theory

Definition: Theory of Computation is branch of computer science that deals with how efficiently problem can be solved on a model of computation using an algorithm.

Theoretical computations is built upon two foundational elements: (i) Principles (ii) Concepts

(i) Principles: The underlying rules, mathematical logic, formal laws and proofs. (e.g. set theory, formal languages)

(ii) Concepts: Abstract ideas and models (e.g. state transition, decidability) etc.

Every Computational machine is defined by four core characteristics: (i) Compatibility (ii) Limitations (iii) Complexity (iv) Performance.

(i) Compatibility: How different machine models equate to or convert into one another.

(ii) Limitations: What a specific machine model can or cannot compute/recognize.

(iii) Complexity: The amount of resources (time and space/memory) a machine consumes for an input size n .

(iv) Performance: How efficiently or conveniently a machine executes computation.

Application of TOC

(i) It plays an important role in compiler design.


(ii) In switching theory and design and analysis of digital circuits automata theory is applied.

(iii) Design and Analysis of Complex hardware and software system.

iv) To improve connectionsness of the programm automata theory is used.

v) To design finite state machines such as ~~more~~ moore and melay machines

Pillars of TOC:



Language

to make language we need →

- Symbols
- Alphabets
- Strings

Symbols: Digits, letters
0, 1 a-z

Def: Basic building block of a language or smallest unit of a language are called Symbols

Alphabets: Finite set of symbols are called Alphabets. It is denoted by $(\Sigma) \rightarrow$ sigma

For example: $\Sigma = \{a, b\}$, $\Sigma = \{0, 1\}$

Strings: Finite/Infinite sequence of symbols are called Strings. It is denoted by $(w) \rightarrow$ omega

Examples: $\Sigma = \{a, b\}$ and string length = 2, strings?

$\therefore w = \{aa, bb, ab, ba\}$ [finite sequence]

formula $\rightarrow$ ~~(Σ)~~ $\left[\begin{array}{c} \text{string length} \\ \Sigma \end{array} \right]$

length of string denoted as $|w|$

Ques: $w = \{a b a a b a\}$ sequence = 1.

$|w| = ?$ $\rightarrow$ length = 6

Language: Collection of all possible strings are called Language. For example: ~~[All C-programms]~~ are strings. And If it is valid then that is Language]

Power of Sigma (Σ) (alphabets)

Lecture-3
27.07.2026

$\Sigma^0(\Sigma)$ epsilon

formula
 $\Sigma^{\text{str-length}}$

$$\Sigma^1 = \{a, b\} / \{0, 1\}$$

$$\Sigma^2 = \{aa, bb, ab, ba\}$$

$$\Sigma^3 = \{ \dots \}$$

$$\Sigma^K = \{ \dots \}$$

mother of all strings

⇒ If sigma is an alphabet, we can express set of all strings of certain length from that alphabet by using exponential notation. It is denoted by Σ^K K is the set of strings length


$$\Sigma = \{a, b\}$$

$$L = \{w \mid w, \text{ where each string starts with } a\}$$

$$= \{a, aa, aaa, ab, \dots\}$$

↓ Infinite Lang.

Finite Representation
Finite Automata



Automata theory and Language

It deals with definition and properties of various mathematical models of computation.

Definition: Automata is a self operating system or machine that performs predefined sequences of operation automatically.

Mathematical Models: (i) Finite Automata (ii) Context free Grammar
(iii) Turing Machine.

Types of Automata:

- (i) Finite Automata (FA)
- (ii) Push down Automata (PDA)
- (iii) Linear Bound " (LBA)

Finite Automata: F.A. is an abstract computing device. It is a mathematical model of a system with discrete inputs, outputs, states and set of transitions from state to state that occurs on input symbols from alphabets.

representation: (i) Graphical { transition diagram or transition table }
(ii) tabular { transition table }
(iii) Mathematical { transition function or mapping function }

Formal Definition of FA

Lecture-4

03.08.2026

A finite Automata is a set of 5 tuples. They are;

$Q, q_0, F, \Sigma, \delta$, where,

Q = set of states, is a finite called states.


q_0 = initial state

F = Final state

Σ = Alphabet, is a finite set called alphabets.

δ = Transition function.

State transition diagram:



Q = set of states = $\{A, B, C\}$

q_0 = initial state = A

F = final state = B

$\Sigma = \{a, b\}$ = alphabets

δ = Transition function = $Q \times \Sigma \rightarrow Q$

$\textcircled{A} \Rightarrow$ trap state
Conditionally 2026

states	a	b
$\rightarrow A$	B	C
$*B$	B	B
C	C	C


Q. - 10 उत्तर।

(i) formal definition of FA. {उपर्युक्त पर लिखिए}

(ii) Figure उत्तर formal def लिखिए।

(iii) यदि (ii) उत्तर उत्तर value 3 लिखिए।

Example-1



Define Finite Automata (formal definition)?

Solⁿ: A finite Automata is a set of 5 Tuples. They are:

$Q, q_0, F, \Sigma, \delta$ where;

Q = set of states = $\{q_0, q_1, q_2\}$

q_0 = initial state = q_0

F = final state = q_1


$\Sigma = \{0, 1\}$ = alphabets

δ = Transition function $\rightarrow$

$= Q \times \Sigma = Q$

states	0	1
$\rightarrow q_0$	q_1	q_2
$*q_1$	q_1	q_1
q_2	q_2	q_2

Example-2



Answer: A finite Automata is a set of 5 tuples. They are:

$Q = \text{set of states} = \{q_0, q_1, q_2, q_3, q_4\}$

$q_0 = \text{initial state} = q_0$


$F = \text{final state} = \{q_2, q_4\}$

$\Sigma = \{a, b\} = \text{alphabets}$

$\delta = \text{transition function} \rightarrow$
 $= Q \times \Sigma = Q$

$Q \times \Sigma$	a	b
$\rightarrow q_0$	q_1	q_3
q_1	q_1	q_2
$*q_2$	q_2	q_2
q_3	q_4	q_3
$*q_4$	q_4	q_3

Classification of Finite Automata (FA)



Deterministic: Deterministic means that the outcome is 100% fixed by the initial conditions, so the exact same cause will always lead to the exact same effect with no randomness. Example:

⇒ Consider a ^{math}function $f(n) = n + 5$. It is deterministic because if $n = 3$ $f(n)$ will always equal to 8. It will never result 7 or 9.

⇒ Consider an array $[4, 2, 9, 1]$. After sorting the number using merge sort it will always result $[1, 2, 4, 9]$ and will always carry this.

Deterministic vs Non-Deterministic

<u>Concept</u>	<u>Deterministic</u>	<u>Non-Deterministic</u>
Path	Single, fixed linear path	Multiple potential path or possibilities
Behavior	Predictable (100% certainty)	Uncertain, random or multi-choice
Reproducibility	Perfect - running it twice still gives the exact same outcome	Outcome or steps may vary across runs.

Criteria of DFA

- i) প্রত্যেকটা states প্রাক অবস্থান symbol নিয়ম কাজ
সম্পন্ন কিনা ensure করতে হবে।
- ii) অবস্থান state প্রাক প্রাক্কান symbol মুক্তি প্রকরণ হে কাজ করা
- iii) Conditionally trap state থাকতে পারে।
- iv) initial state always একটা হবে কিন্তু final state এক/
আধিক হতে পারে।

DFA (Deterministic Finite Automata)

Lecture-5
06.08.2026

Formal

Def: A Deterministic Finite Automaton (DFA) is a set of
5 tuples: They are $Q, q_0, F, \Sigma, \delta$, where:

Q = set of states, it is a finite called states.

q_0 = initial state

F = final state

Σ = Alphabet, is a finite set called alphabets.

δ = Transition function = $Q \times \Sigma$
= Q

Construct Criteria of DFA: উল্লিখিত নীতি ৥

Examples of DFA

Category: where each string starts with 'a'.


Example-1: Construct a DFA which accepts set of all strings over $\Sigma = \{a, b\}$ where each string starts with 'a'.

* remaining symbol ka diagram - $\rightarrow$ $\rightarrow$ $\rightarrow$ sequence:

- ① Self loop ② Back state ③ Trap state.

Soln: $L = \{a, aa, aaa, ab, aba, \dots\}$


state transition:



Example-2: $\dots$, where each string starts with 'aa'.

Soln: $L = \{aa, aqa, aqb, aqbb, aqba, \dots\}$

state transition:



Example-3: each string start with "aab". -

Solⁿ: $L = \{ aab, aaba, aabba, aabb, \dots \}$

State transition:

