

# Debugging in Serial & Parallel

M. D. Jones, Ph.D.

Center for Computational Research  
University at Buffalo  
State University of New York

High Performance Computing I, 2014

## Software for Debugging

The most common method for debugging (by far) is the “instrumentation” method:

- One “instruments” the code with print statements to check values and follow the execution of the program
- Not exactly sophisticated - one can certainly debug code in this way, but wise use of software debugging tools can be more effective

## Part I

# Basic (Serial) Debugging

## Debugging Tools

Debugging tools are abundant, but we will focus merely on some of the most common attributes to give you a bag of tricks that can be used when dealing with common problems.

# Basic Capabilities

Common attributes:

- Divided into command-line or graphical user interfaces
- Usually have to recompile (“-g” is almost a standard option to enable debugging) your code to utilize most debugger features
- Invocation by name of debugger and executable (e.g. **gdb ./a.out [core]**)

# Command-line debugging example

Consider the following code example:

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int indx;
5
6  void initArray(int nelem_in_array, int *array);
7  void printArray(int nelem_in_array, int *array);
8  int squareArray(int nelem_in_array, int *array);
9
10 int main(void) {
11     const int nelem = 10;
12     int *array1, *array2, *del;
13
14     /* Allocate memory for each array */
15     array1 = (int *)malloc(nelem*sizeof(int));
16     array2 = (int *)malloc(nelem*sizeof(int));
17     del = (int *)malloc(nelem*sizeof(int));
18
19     /* Initialize array1 */
20     initArray(nelem, array1);
21
22     for (indx = 0; indx < nelem; indx++) {
23         array1[indx] = indx + 2;
24     }

```

# Running Within

Inside a debugger (be it using a command-line interface (CLI) or graphical front-end), you have some very handy abilities:

- Look at source code listing (very handy when isolating an IEEE exception)
- Line-by-line execution
- Insert stops or “breakpoints” at certain functional points (i.e., when critical values change)
- Ability to monitor variable values
- Look at “stack trace” (or “backtrace”) when code crashes

```

25  /* Print the elements of array1 */
26  printf("array1 = ");
27  printArray(nelem, array1);
28
29  /* Copy array1 to array2 */
30  array2 = array1;
31
32  /* Pass array2 to the function 'squareArray( )' */
33  squareArray(nelem, array2);
34
35  /* Compute difference between elements of array2 and array1 */
36  for (indx = 0; indx < nelem; indx++) {
37      del[indx] = array2[indx] - array1[indx];
38  }
39
40  /* Print the computed differences */
41  printf("The difference in the elements of array2 and array1 are: ");
42  printArray(nelem, del);
43
44  free(array1);
45  free(array2);
46  free(del);
47  return 0;
48 }

```

```

49 void initArray(const int nelem_in_array, int *array) {
50     for (indx = 0; indx < nelem_in_array; indx++) {
51         array[indx] = indx + 1;
52     }
53 }
54
55 int squareArray(const int nelem_in_array, int *array) {
56     int indx;
57     for (indx = 0; indx < nelem_in_array; indx++){
58         array[indx] *= array[indx];
59     }
60     return *array;
61 }
62
63 void printArray(const int nelem_in_array, int *array){
64     printf("\n( ");
65     for (indx = 0; indx < nelem_in_array; indx++){
66         printf("%d ", array[indx]);
67     }
68     printf("\n");
69 }

```

Ok, now let's compile and run this code:

```

1 [rush:~/d_debug]$ gcc -g -o array-ex array-ex.c
2 [rush:~/d_debug]$ ./array-ex
3 array1 =
4 ( 2 3 4 5 6 7 8 9 10 11 )
5 The difference in the elements of array2 and array1 are:
6 ( 0 0 0 0 0 0 0 0 0 0 )
7 *** glibc detected *** ./array-ex: double free or corruption (fasttop): 0x000000001cc7010 ***
8 ===== Backtrace: =====
9 /lib64/libc.so.6[0x3e1be760e6]
10 ./array-ex[0x400710]
11 /lib64/libc.so.6[0x3e1be760e6]
12 ./array-ex[0x4004d9]
13 ===== Memory map: =====
14 ...

```

Not exactly what we expect, is it? Array2 should contain the squares of the values in array1, and therefore the difference should be  $i^2 - i$  for  $i = [2, 11]$ .

Now let us run the code from within **gdb**. Our goal is to set a **breakpoint** where the squared arrays elements are computed, then step through the code:

```

1 [rush:~/d_debug]$ gdb -quiet array-ex
2 Reading symbols from /ifs/user/jonesm/d_debug/array-ex...done.
3 (gdb) l 34
4 29
5 30 /* Copy array1 to array2 */
6 31 array2 = array1;
7 32
8 33 /* Pass array2 to the function 'squareArray( )' */
9 34 squareArray(nelem, array2);
10 35
11 36 /* Compute difference between elements of array2 and array1 */
12 37 for (indx = 0; indx < nelem; indx++) {
13 38     del[indx] = array2[indx] - array1[indx];
14 (gdb) b 34
15 Breakpoint 1 at 0x400660: file array-ex.c, line 34.
16 (gdb) run
17 Starting program: /ifs/user/jonesm/d_debug/array-ex
18 array1 =
19 ( 2 3 4 5 6 7 8 9 10 11 )
20
21 Breakpoint 1, main () at array-ex.c:34
22 34 squareArray(nelem, array2);

```

```

23 (gdb) s
24 squareArray (nelem_in_array=10, array=0x601010) at array-ex.c:59
25 59 for (indx = 0; indx < nelem_in_array; indx++){
26 (gdb) p indx
27 $1 = 10
28 (gdb) s
29 60 array[indx] *= array[indx];
30 (gdb) p indx
31 $2 = 0
32 (gdb) display indx
33 1: indx = 0
34 (gdb) display array[indx]
35 2: array[indx] = 2
36 (gdb) s
37 59 for (indx = 0; indx < nelem_in_array; indx++){
38 2: array[indx] = 4
39 1: indx = 0
40 (gdb) s
41 60 array[indx] *= array[indx];
42 2: array[indx] = 3
43 1: indx = 1

```

Ok, that is instructive, but no closer to finding the bug.

So, what have we learned so far about the command-line debugger:

- Useful for peaking inside source code
- (break) Breakpoints
- (s) Stepping through execution
- (p) Print values at selected points (can also use handy printf syntax as in C)
- (display) Displaying values for monitoring while stepping through code
- (bt) Backtrace, or 'Stack Trace' - haven't used this yet, but certainly will

```

18 Breakpoint 1, main () at array-ex.c:37
19   37     for (indx = 0; indx < nelem; indx++) {
20 (gdb) disp indx
21 1: indx = 10
22 (gdb) disp array1[indx]
23 2: array1[indx] = 49
24 (gdb) disp array2[indx]
25 3: array2[indx] = 49
26 (gdb) s
27   38         del[indx] = array2[indx] - array1[indx];
28   39     array2[indx] = 4
29   40     array1[indx] = 4
30   41     1: indx = 0
31 (gdb) s
32   37     for (indx = 0; indx < nelem; indx++) {
33   38     3: array2[indx] = 4
34   39     2: array1[indx] = 4
35   40     1: indx = 0
36 (gdb) s
37   38         del[indx] = array2[indx] - array1[indx];
38   39     3: array2[indx] = 9
39   40     2: array1[indx] = 9
40   41     1: indx = 1

```

## Digging Out the Bug

What we have learned is enough - look more closely at the line where the differences between array1 and array2 are computed:

```

1 (gdb) l 38
2 33     /* Pass array2 to the function 'squareArray( )' */
3 34     squareArray(nelem, array2);
4 35
5 36     /* Compute difference between elements of array2 and array1 */
6 37     for (indx = 0; indx < nelem; indx++) {
7 38         del[indx] = array2[indx] - array1[indx];
8 39     }
9 40
10 41     /* Print the computed differences */
11 42     printf("The difference in the elements of array2 and array1 are: ");
12 (gdb) b 37
13 Breakpoint 1 at 0x400611: file array-ex.c, line 37.
14 (gdb) run
15 Starting program: /san/user/jonesm/u2/d_debug/array-ex
16 array1 =
17 ( 2 3 4 5 6 7 8 9 10 11 )

```

Now that isn't right - array1 was **not** supposed to change. Let us go back and look more closely at the call to squareArray ...

```

1 (gdb) l
2 32
3      /* Pass array2 to the function 'squareArray( )' */
4      squareArray(nelem, array2);
5      35
6      /* Compute difference between elements of array2 and array1 */
7      for (indx = 0; indx < nelem; indx++) {
8          del[indx] = array2[indx] - array1[indx];
9      }
10     40
11     /* Print the computed differences */
12 (gdb) b 34
13 Breakpoint 2 at 0x400605: file array-ex.c, line 34.
14 (gdb) run
15 The program being debugged has been started already.
16 Start it from the beginning? (y or n) y
17
18 Starting program: /ifs/user/jonesm/d_debug/array-ex
19 array1 =
20 ( 2  3  4  5  6  7  8  9 10 11 )
21
22 Breakpoint 2, main () at array-ex.c:34
23 34      squareArray(nelem, array2);
24 3: array2[indx] = 49
25 2: array1[indx] = 49
26 1: indx = 10
27 (gdb) disp array2
28 4: array2 = (int *) 0x501010
29 (gdb) disp array1
30 5: array1 = (int *) 0x501010

```

## The Fix Is In

Just as an afterthought, what we ought to have done in the first place was copy array1 into array2:

```

1  /* Copy array1 to array2 */
2  /* array2 = array1; */
3  for (indx=0; indx<nelem; indx++) {
4      array2[indx]=array1[indx];
5  }

```

which will finally produce the right output:

```

1 (gdb) run
2 Starting program: /home/jonesm/d_debug/ex1
3 array1 =
4 ( 2  3  4  5  6  7  8  9 10 11 )
5 The difference in the elements of array2 and array1 are:
6 ( 2  6 12 20 30 42 56 72 90 110 )
7
8 Program exited normally.
9 (gdb)

```

Yikes, array1 and array2 point to the same memory location! See, pointer errors like this don't happen too often in Fortran ... Now, of course, the bug is obvious - but aren't they all obvious **after** you find them?

## Array Indexing Errors

Array indexing errors are one of the most common errors in both sequential and parallel codes - and it is not entirely surprising:

- Different languages have different indexing defaults
- Multi-dimensional arrays are pretty easy to reference out-of-bounds
- Fortran in particular lets you use very complex indexing schemes (essentially arbitrary!)

## Example: Indexing Error

```

1  #include <stdio.h>
2  #define N 10
3  int main(int argc, char *argv[]) {
4      int arr[N];
5      int i, odd_sum, even_sum;
6
7      for(i=1; i<(N-1); ++i) {
8          if(i<=4) {
9              arr[i]=(i*i)%3;
10             } else {
11                 arr[i]=(i*i)%5;
12             }
13         }
14         odd_sum=0;
15         even_sum=0;
16         for(i=0; i<(N-1); ++i) {
17             if(i%2==0) {
18                 even_sum += arr[i];
19             } else {
20                 odd_sum += arr[i];
21             }
22         }
23         printf("odd_sum=%d, even_sum=%d\n", odd_sum, even_sum);
24     }

```

Now, try compiling with **gcc** and running the code:

```

1  [rush:~/d_debug]$ gcc -O -g -o ex2 ex2.c
2  [rush:~/d_debug]$ ./ex2
3  odd_sum=5, even_sum=671173703

```

Ok, that hardly seems reasonable (does it?) Now, let's run this example from within **gdb** and set a breakpoint to examine the accumulation of values to `even_sum`.

```

1  (gdb) l 16
2  11             arr[i]=(i*i)%5;
3  12         }
4  13     }
5  14     odd_sum=0;
6  15     even_sum=0;
7  16     for(i=0; i<(N-1); ++i) {
8  17         if(i%2==0) {
9  18             even_sum += arr[i];
10  19         } else {
11  20             odd_sum += arr[i];
12  (gdb) b 16
13  Breakpoint 1 at 0x40051e: file ex2.c, line 16.
14  (gdb) run
15  Starting program: /ifs/user/jonesm/d_debug/ex2
16
17  Breakpoint 1, main (argc=Variable "argc" is not available.
18  ) at ex2.c:16
19  16     for(i=0; i<(N-1); ++i) {
20  (gdb) p arr
21  $1 = {671173696, 1, 1, 0, 1, 0, 1, 4, 4, 0}

```

So we see that our original example code missed initializing the first element of the array, and the results were rather erratic (in fact they will likely be compiler and flag dependent).

Initialization is just one aspect of things going wrong with array indexing - let us examine another common problem ...

# The (Infamous) Seg Fault

This example I “borrowed” from Norman Matloff (UC Davis), who has a nice article (well worth the time to read): “Guide to Faster, Less Frustrating Debugging,” which you can find easily enough on the web:

<http://heather.cs.ucdavis.edu/~matloff/unix.html>

## Main code: findprimes.c

```

1  /*
2     prime-number finding program - will (after bugs are fixed) report a list of
3     all primes which are less than or equal to the user-supplied upper bound
4  */
5  #include <stdio.h>
6
7  #define MaxPrimes 50
8  int Prime[MaxPrimes], /* Prime[I] will be 1 if I is prime, 0 otherwise */
9     UpperBound; /* we will check up through UpperBound for primeness */
10 void CheckPrime(int K); /* prototype for CheckPrime function */
11 int main()
12 {
13     int N;
14
15     printf("enter upper bound\n");
16     scanf("%d", &UpperBound);
17
18     Prime[2] = 1;
19
20     for (N = 3; N <= UpperBound; N += 2)
21         CheckPrime(N);
22     if (Prime[N]) printf("%d is a prime\n", N);
23 }

```

## Function FindPrime:

```

24
25 void CheckPrime(int K) {
26     int J;
27
28     /* the plan: see if J divides K, for all values J which are
29     (a) themselves prime (no need to try J if it is nonprime), and
30     (b) less than or equal to sqrt(K) (if K has a divisor larger
31     than this square root, it must also have a smaller one,
32     so no need to check for larger ones) */
33
34     J = 2;
35     while (1) {
36         if (Prime[J] == 1)
37             if (K % J == 0) {
38                 Prime[K] = 0;
39                 return;
40             }
41         J++;
42     }
43
44     /* if we get here, then there were no divisors of K, so it is
45     prime */
46     Prime[K] = 1;
47 }

```

so now if we compile and run this code ...

```

1 [rush:~/d_debug]$ gcc -g -o findprimes_orig findprimes_orig.c
2 [rush:~/d_debug]$ ./findprimes_orig
3 enter upper bound
4 20
5 Segmentation fault (core dumped)
6 [rush:~/d_debug]$ ulimit -c
7 0

```

Ok, let's fire up **gdb** and see where this code crashed:

```

1 [rush:~/d_debug]$ gdb -quiet ./findprimes_orig
2 Reading symbols from /ifs/user/jonesm/d_debug/findprimes_orig...done.
3 (gdb) run
4 Starting program: /ifs/user/jonesm/d_debug/findprimes_orig
5 enter upper bound
6 20
7
8 Program received signal SIGSEGV, Segmentation fault.
9 0x0000003e1be56ed0 in _IO_vfscanf_internal () from /lib64/libc.so.6
10 Missing separate debuginfos, use: debuginfo-install glibc-2.12-1.107.el6.x86_64
11 (gdb) bt
12 #0 0x0000003e1be56ed0 in _IO_vfscanf_internal () from /lib64/libc.so.6
13 #1 0x0000003e1be646cd in __isoc99_scanf () from /lib64/libc.so.6
14 #2 0x0000000004005a0 in main () at findprimes_orig.c:16

```

Now, the `scanf` intrinsic is probably pretty safe from internal bugs, so the error is likely coming from our usage:

```

1 (gdb) list 16
2 11 int main()
3 12 {
4 13     int N;
5 14
6 15     printf("enter upper bound\n");
7 16     scanf("%d", UpperBound);
8 17
9 18     Prime[2] = 1;
10 19
11 20     for (N = 3; N <= UpperBound; N += 2)

```

Yeah, pretty dumb - `scanf` needs a pointer argument, i.e. `scanf ("%d", &UpperBound)`, and that takes care of the first bug ... but let's keep running from within **`gdb`**

```

1 [rush:~/d_debug]$ gcc -g -o findprimes findprimes.c
2 [rush:~/d_debug]$ gdb findprimes
3 (gdb) run
4 Starting program: /ifs/user/jonesm/d_debug/findprimes
5 enter upper bound
6 20
7
8 Program received signal SIGSEGV, Segmentation fault.
9 0x0000000000400586 in CheckPrime (K=3) at findprimes.c:37
10 37         if (Prime[J] == 1)
11 (gdb) bt
12 #0 0x0000000000400586 in CheckPrime (K=3) at findprimes.c:37
13 #1 0x0000000000400547 in main () at findprimes.c:21
14 (gdb) l 37
15 32         than this square root, it must also have a smaller one,
16 33         so no need to check for larger ones) */
17 34
18 35         J = 2;
19 36         while (1) {
20 37             if (Prime[J] == 1)
21 38                 if (K % J == 0) {
22 39                     Prime[K] = 0;
23 40                     return;
24 41                 }
25 (gdb)

```

very often we get seg faults on trying to reference an array “out-of-bounds,” so have a look at the value of `J`:

```

26 (gdb) l 37
27 32         than this square root, it must also have a smaller one,
28 33         so no need to check for larger ones) */
29 34
30 35         J = 2;
31 36         while (1) {
32 37             if (Prime[J] == 1)
33 38                 if (K % J == 0) {
34 39                     Prime[K] = 0;
35 40                     return;
36 41                 }
37 (gdb) p J
38 $1 = 376

```

Oops! That is just a tad outside the bounds (50). Kind of forgot to put a cap on the value of `J` ...

Fixing the last bug:

```

1 (gdb) list 40
2 35         J = 2;
3 36         /* while (1) { */
4 37         for (J=2; J*J <= K; J++) {
5 38             if (Prime[J] == 1)
6 39                 if (K % J == 0) {
7 40                     Prime[K] = 0;
8 41                     return;
9 42                 }
10 43             /* J++; */
11 44         }

```

Ok, now let us try to run the code:

```

1 [rush:~/d_debug]$ gcc -g -o findprimes findprimes.c
2 [rush:~/d_debug]$ ./findprimes
3 enter upper bound
4 20
5 [rush:~/d_debug]$

```

Oh, fantastic - no primes between 1 and 20? Not hardly ...



Ok, so now we will set a couple of breakpoints - one at the call to `FindPrime` and the second where a successful prime is to be output:

```

1  (gdb) l
2  16      scanf("%d",&UpperBound);
3  17
4  18      Prime[2] = 1;
5  19
6  20      for (N = 3; N <= UpperBound; N += 2)
7  21          CheckPrime(N);
8  22      if (Prime[N]) printf("%d is a prime\n",N);
9  23  }
10 24
11 25      void CheckPrime(int K) {
12 (gdb) b 20
13 Breakpoint 1 at 0x40052d: file findprimes.c, line 20.
14 (gdb) b 22
15 Breakpoint 2 at 0x400550: file findprimes.c, line 22.
16 (gdb) run
17 Starting program: /ifs/user/jonesm/d_debug/findprimes
18 enter upper bound
19 20
20 Breakpoint 1, main () at findprimes.c:20
21 20      for (N = 3; N <= UpperBound; N += 2)
22 (gdb) c
23 Continuing.
24
25 Breakpoint 2, main () at findprimes.c:22
26 22      if (Prime[N]) printf("%d is a prime\n",N);
27 (gdb) p N
28 $1 = 21
29 (gdb)

```

Another gotcha - misplaced (or no) braces. Fix that:

```

1  (gdb) l
2  16      scanf("%d",&UpperBound);
3  17
4  18      Prime[2] = 1;
5  19
6  20      for (N = 3; N <= UpperBound; N += 2) {
7  21          CheckPrime(N);
8  22          if (Prime[N]) printf("%d is a prime\n",N);
9  23      }
10 24  }
11 25
12 (gdb) run
13 Starting program: /ifs/user/jonesm/d_debug/findprimes
14 enter upper bound
15 20
16 3 is a prime
17 5 is a prime
18 7 is a prime
19 11 is a prime
20 13 is a prime
21 17 is a prime
22 19 is a prime
23
24 Program exited with code 025.
25 (gdb)

```

Ah, the sweet taste of success ... (even better, give the program a return code!)

## Debugging Life Itself

Well, ok, not exactly debugging life itself; rather the **game of life**. Mathematician John Horton Conway's **game of life**<sup>1</sup>, to be exact. This example will basically be similar to the prior examples, but now we will work in Fortran, and debug some integer arithmetic errors.

And the context will be slightly more interesting.

<sup>1</sup>see, for example, Martin Gardner's article in *Scientific American*, **223**, pp. 120-123 (1970).

# Game of Life

The **Game of Life** is one of the better known examples of **cellular automata** (CA), namely a discrete model with a finite number of states, often used in theoretical biology, game theory, etc. The rules are actually pretty simple, and can lead to some rather surprising self-organizing behavior. The universe in the game of life:

- Universe is an infinite 2D grid of cells, each of which is alive or dead
- Cells interact only with nearest neighbors (including on the diagonals, which makes for eight neighbors)

# Sample Code - Game of Life

```

1  program life
2  !
3  ! Conway game of life (debugging example)
4  !
5  implicit none
6  integer, parameter :: ni=1000, nj=1000, nsteps = 100
7  integer :: i, j, n, im, ip, jm, jp, nsum, isum
8  integer, dimension(0:ni,0:nj) :: old, new
9  real :: arand, nim2, njm2
10 !
11 ! initialize elements of "old" to 0 or 1
12 !
13 do j = 1, nj
14   do i = 1, ni
15     call random_number(arand)
16     old(i,j) = NINT(arand)
17   enddo
18 enddo
19 nim2 = ni - 2
20 njm2 = nj - 2

```

# Rules of Life

The rules in the game of life:

- Any live cell with fewer than two neighbours dies, as if by loneliness
- Any live cell with more than three neighbours dies, as if by overcrowding
- Any live cell with two or three neighbours lives, unchanged, to the next generation
- Any dead cell with exactly three neighbours comes to life

An initial pattern is evolved by simultaneously applying the above rules to the entire grid, and subsequently at each "tick" of the clock.

```

21 !
22 ! time iteration
23 !
24 time_iteration: do n = 1, nsteps
25   do j = 1, nj
26     do i = 1, ni
27       !
28       ! periodic boundaries,
29       !
30       im = 1 + (i+nim2) - ((i+nim2)/ni)*ni ! if i=1, ni
31       ip = 1 + i - (i/ni)*ni ! if i=ni, 1
32       jm = 1 + (j+njm2) - ((j+njm2)/nj)*nj ! if j=1, nj
33       jp = 1 + j - (j/nj)*nj ! if j=nj, 1
34       !
35       ! for each point, add surrounding values
36       !
37       nsum = old(im,jp) + old(i,jp) + old(ip,jp) &
38              + old(im,j) + old(i,j) + old(ip,j) &
39              + old(im,jm) + old(i,jm) + old(ip,jm)

```

## Initial Run ...

```

40      !
41      ! set new value based on number of "live" neighbors
42      !
43      select case (nsum)
44      case (3)
45          new(i,j) = 1
46      case (2)
47          new(i,j) = old(i,j)
48      case default
49          new(i,j) = 0
50      end select
51      enddo
52      enddo
53      !
54      ! copy new state into old state
55      !
56      old = new
57      print*, 'Tick ',n,' number of living: ',sum(new)
58      enddo time_iteration
59      !
60      ! write number of live points
61      !
62      print*, 'number of live points = ', sum(new)
63      end program life

```

```

1 [bono:~/d_debug]$ ifort -g -o life life.f90
2 [bono:~/d_debug]$ ./life
3 Tick      1  number of living:      342946
4 Tick      2  number of living:      334381
5 Tick      3  number of living:      291022
6 Tick      4  number of living:      263356
7 Tick      5  number of living:      290940
8 Tick      6  number of living:      322733
9 :
10 :
11 Tick      99  number of living:      0
12 Tick     100  number of living:      0
13 number of live points =      0

```

Hmm, everybody dies! What kind of life is that? ... well, not a correct one, in this context, at least. Undoubtedly the problem lies within the neighbor calculation, so let us take a closer look at the execution ...

```

1 (gdb) l 30
2      25      do j = 1, nj
3      26      do i = 1, ni
4      27      !
5      28      ! periodic boundaries
6      29      !
7      30      im = 1 + (i+nim2) - ((i+nim2)/ni)*ni ! if i=1, ni
8      31      ip = 1 + i - (i/ni)*ni ! if i=ni, 1
9      32      jm = 1 + (j+njm2) - ((j+njm2)/nj)*nj ! if j=1, nj
10     33      jp = 1 + j - (j/nj)*nj ! if j=nj, 1
11 (gdb) b 25
12 Breakpoint 1 at 0x402e23: file life.f90, line 25.
13 (gdb) run
14 Starting program: /ifs/user/jonesm/d_debug/life
15
16 Breakpoint 1, life () at life.f90:25
17 25      do j = 1, nj
18 Current language: auto; currently fortran
19 (gdb) s
20 26      do i = 1, ni
21 (gdb) s
22 30      im = 1 + (i+nim2) - ((i+nim2)/ni)*ni ! if i=1, ni
23 (gdb) s
24 31      ip = 1 + i - (i/ni)*ni ! if i=ni, 1
25 (gdb) print im
26 $1 = 1
27 (gdb) print (i+nim2)/1000
28 $2 = 0.999

```

Ok, so therein lay the problem - `nim2` and `njm2` should be integers, not real values ... fix that:

```

1 program life
2 !
3 ! Conway game of life (debugging example)
4 !
5 implicit none
6 integer, parameter :: ni=1000, nj=1000, nsteps = 100
7 integer :: i, j, n, im, ip, jm, jp, nsum, isum, nim2, njm2
8 integer, dimension(0:ni,0:nj) :: old, new
9 real :: arand

```

and things become a bit more reasonable:

```

1 [bono:~/d_debug]$ ifort -g -o life life.f90
2 [bono:~/d_debug]$ ./life
3 Tick      1  number of living:      272990
4 Tick      2  number of living:      253690
5 :
6 :
7 Tick      99  number of living:      95073
8 Tick     100  number of living:      94664
9 number of live points =      94664

```

## Diversion - Demo life

<http://www.radicaleye.com/lifepage>

[http://en.wikipedia.org/wiki/Conway's\\_Game\\_of\\_Life](http://en.wikipedia.org/wiki/Conway's_Game_of_Life)

Interesting repository of Conway's life and cellular automata references.

Systems administrators set the core file size limit to zero by default for a good reason - these files generally contain the entire memory image of an application process when it dies, and that can be very large. End-users are also notoriously bad about leaving these files laying around ...

Having said that, we can up the limit, and produce a core file that can later be used for analysis.

## Core Files

Core files can also be used to instantly analyze problems that caused a code failure bad enough to “dump” a core file. Often the computer system has been set up in such a way that the default is **not** to output core files, however:

```
1 [rush:~/d_debug]$ ulimit -a
2 core file size          (blocks, -c) 0
3 data seg size           (kbytes, -d) unlimited
4 scheduling priority      (-e) 0
5 file size               (blocks, -f) unlimited
6 pending signals         (-i) 2066355
7 max locked memory       (kbytes, -l) 33554432
8 max memory size         (kbytes, -m) unlimited
9 open files              (-n) 1024
10 pipe size              (512 bytes, -p) 8
11 POSIX message queues    (bytes, -q) 819200
12 real-time priority      (-r) 0
13 stack size              (kbytes, -s) unlimited
14 cpu time                (seconds, -t) 900
15 max user processes      (-u) 1024
16 virtual memory          (kbytes, -v) unlimited
17 file locks              (-x) unlimited
```

for **bash** syntax.

## Core File Example

Ok, so now we can use one of our previous examples, and generate a core file:

```
1 [rush:~/d_debug]$ ulimit -c unlimited
2 [rush:~/d_debug]$ gcc -g -o findprimes_orig findprimes_orig.c
3 [rush:~/d_debug]$ ./findprimes_orig
4 enter upper bound
5 20
6 Segmentation fault (core dumped)
7 [rush:~/d_debug]$ ls -l core*
8 -rw----- 1 jonesm ccrstaff 196608 Sep 16 13:22 core.38729
```

this example core file is not at all large (it is a simple code with very little stored data - generally the core file size will reflect the size of the application in terms of its memory use when it crashed). Analyzing it is very similar to when running this example “live” in gdb:

```

1 [rush:~/d_debug]$ gdb -quiet findprimes_orig core.38729
2 Reading symbols from /ifs/user/jonesm/d_debug/findprimes_orig...done.
3 [New Thread 38729]
4 ...
5 Core was generated by `./findprimes_orig'.
6 Program terminated with signal 11, Segmentation fault.
7 #0 0x0000003e1be56ed0 in _IO_vfscanf_internal () from /lib64/libc.so.6
8 Missing separate debuginfos, use: debuginfo-install glibc-2.12-1.107.el6.x86_64
9 (gdb) bt
10 #0 0x0000003e1be56ed0 in _IO_vfscanf_internal () from /lib64/libc.so.6
11 #1 0x0000003e1be646cd in __isoc99_scanf () from /lib64/libc.so.6
12 #2 0x00000000004005a0 in main () at findprimes_orig.c:16
13 (gdb) l 16
14 11 int main()
15 12 {
16 13     int N;
17 14
18 15     printf("enter upper bound\n");
19 16     scanf("%d", &UpperBound);
20 17
21 18     Prime[2] = 1;
22 19
23 20     for (N = 3; N <= UpperBound; N += 2)

```

## More Comannd-line Debugging Tools

We focused on **gdb**, but there are command-line debuggers that accompany just about every available compiler product:

**pgdbg** part of the PGI compiler suite, defaults to a GUI, but can be run as a command line interface (CLI) using the **-text** option

**idb** part of the Intel compiler suite, defaults to CLI (has a special option **-gdb** for using gdb command syntax)

## Summary on Core Files

So why would you want to use a core file rather than interactively debug?

- Your bug may take quite a while to manifest itself
- You have to debug inside a batch queuing system where interactive use is difficult or curtailed
- You want to capture a “picture” of the code state when it crashes

## Run-time Compiler Checks

Most compilers support **run-time** checks than can quickly catch common bugs. Here is a handy short-list (contributions welcome!):

- For Intel fortran, “**-check bounds -traceback -g**” will automate bounds checking, and enable extensive traceback analysis in case of a crash (leave out the **bounds** option to get a crash report on any IEEE exception, format mismatch, etc.)
- For PGI compilers, **-Mbounds -g** will do bounds checking
- For GNU compilers, **-fbounds-check -g** should also do bounds checking, but is only currently supported for Fortran and Java front-ends.

## Run-time Compiler Checks(cont'd)

### WARNING

It should be noted that run-time error checking can very much slow down a code's execution, so it is not something that you will want to use all of the time.

## Serial Debugging GUIs

There are, of course, a matching set of GUIs for the various debuggers. A short list:

**ddd** a graphical front-end for the venerable **gdb**


**pgdbg** GUI for the PGI debugger

**idb -gui** GUI for Intel compiler suite debugger

It is very much a matter of preference whether or not to use the GUI. I find the GUI to be constraining, but it does make navigation easier.

## DDD Example

Running one of our previous examples using **ddd** ...



## More Information on Debuggers

More information on the tools that we have used/mentioned (**man** pages are also a good place to start):

- **gdb** User Manual:

<http://www.gnu.org/software/gdb/documentation>

- **ddd** User Manual:

<https://www.gnu.org/software/ddd/manual/>

- **idb** Manual:

[http://www.intel.com/software/products/compilers/docs/linux/idb\\_manual\\_1.html](http://www.intel.com/software/products/compilers/docs/linux/idb_manual_1.html)

- **pgdbg** Guide (locally on CCR systems):

[file:///util/pgi/linux86-64/\[version\]/doc/index.htm](file:///util/pgi/linux86-64/[version]/doc/index.htm)

# Source Code Checking Tools

Now, in a completely different vein, there are tools designed to help identify errors pre-compilation, namely by running it through the source code itself.

**splint** is a tool for statically checking C programs:

<http://www.splint.org>

**f77check** is a tool that checks only (alas) FORTRAN 77 codes:

<http://www.dsm.fordham.edu/~ftnchek/>

I can't say that I have found these to be particularly helpful, though.

## Strace

**strace** is a powerful tool that will allow you to trace **all** system calls and signals made by a particular binary, whether or not you have source code. Can be attached to already running processes. A powerful low-level tool. You can learn a lot from it, but is often a tool of last resort for user applications in HPC due to the copious quantity of extraneous information it outputs.

## Memory Allocation Tools

Memory allocation problems are very common - there are some tools designed to help you catch such errors at run-time:

**efence** , or Electric Fence, tries to trap any out-of-bounds references (see **man efence**)

**valgrind** is a suite of tools for analyzing and profiling binaries (see **man valgrind**) - there is a user manual available at <http://valgrind.org/> (watch out for version dependencies):

<http://valgrind.org/docs/manual>

**valgrind** I have seen used with good success, but not particularly in the HPC arena.

## Strace Example

As an example of using **strace**, let's peek in on a running MPI process (part of a 32 task job on **U2**):

[illegible]

## Part II

### Advanced (Parallel) Debugging

## Process Checking

First on the agenda - parallel processing involves multiple processes/threads (or both), and the first rule is to make sure that they are ending up where you think that they should be (needless to say, all too often they do not).

- Use `MPI_Get_processor_name` to report back on where processes are running
- Use `ps` to monitor processes as they run (useful flags: `ps u -L`), even on remote nodes (rsh/ssh into them)

## Wither Goest the GUI?

Using a GUI-based debugger gets considerably more difficult when dealing with debugging an MPI-based parallel code (not so much on the OpenMP side), due to the fact that you are now dealing with multiple processes scattered across different machines.

The **TotalView** debugger is the premier product in this arena (it has both CLI and GUI support) - but it is **very** expensive, and not present in all environments. We will start out using our same toolbox as before, and see that we can accomplish much without spending a fortune. The methodologies will be equally applicable to the fancy commercial products.

## Process Checking Example

```

1 [rush:/projects/jonesm/d_nwchem/d_siosi6]$ squeue --user jonesm
2          JOBID PARTITION  NAME      USER ST      TIME  NODES NODELIST(REASON)
3          436728      debug  siosi6  jonesm R      0:23      2 d09n29s02,d16n02
4 [rush:/projects/jonesm/d_nwchem/d_siosi6]$ ssh d16n02
5 [d16n02:~]$ ps -u jonesm -o pid,ppid,lwp,nlwp,psr,pcpu,rss,time,comm
6  PID  PPID  LWP  NLWP  PSR  %CPU  RSS      TIME  COMMAND
7  9665  9633  9665   5    0  98.4 1722040 00:01:12 nwchem-openib-i
8  9666  9633  9666   4    4  98.6 1365672 00:01:12 nwchem-openib-i
9  9667  9633  9667   4    1  98.2 1370000 00:01:12 nwchem-openib-i
10 9668  9633  9668   4    5  98.7 1358960 00:01:13 nwchem-openib-i
11 9669  9633  9669   4    2  98.7 1352112 00:01:13 nwchem-openib-i
12 9670  9633  9670   4    6  98.7 1360200 00:01:13 nwchem-openib-i
13 9671  9633  9671   4    3  98.7 1359828 00:01:13 nwchem-openib-i
14 9672  9633  9672   4    7  98.7 1361228 00:01:13 nwchem-openib-i
15 9751  9749  9751   1    7   0.0  2136 00:00:00 sshd
16 9752  9751  9752   1    0   0.0  2040 00:00:00 bash
17 9828  9752  9828   1    5   0.0  1204 00:00:00 ps

```



or you can script it (I called this script `job_ps`):

```

1  #!/bin/sh
2  #
3  # Shell script to take a single argument (Slurm job id) and launch a
4  # ps command on each node in the job
5  #
6  QST=`which squeue`
7  if [ -z $QST ]; then
8      echo "ERROR: no squeue in PATH: PATH=$PATH"
9      exit
10 fi
11 #
12 case $# in
13 0) echo "single SLURM_JOBID required."; exit ;; # no args, exit
14 1) jobid=$1 ;;
15 *) echo "single SLURM_JOBID required."; exit ;; # too many args, exit
16 esac
17 #
18 # get node listing
19 #
20 nodelist=`$QST --job $jobid --format="%i %N" | tail -1 | awk '{print $2}'`
21 echo "nodelist = $nodelist"
22 if [[ "$nodelist" == "" ]]; then
23     echo "Job is not running yet, retry later."
24     exit
25 fi

```

```

26 nodelist=`nodeset -e $nodelist`
27 echo "expanded nodelist = $nodelist"
28 #
29 # define ps command
30 #MYPSPS="ps -aeLf | awk '{if (\$5 > 10) print \$1, \$2, \$3, \$4, \$5, \$9, \$10}'"
31 MYPSPS="ps -u jonesm -L -o pid,ppid,lwp,nlwp,psr,pcpu,rss,time,comm"
32 #MYPSPS="ps -u jonesm -Lf"
33 echo "MYPSPS = $MYPSPS"
34
35 for node in $nodelist ; do
36     echo "NODE = $node, my CPU/thread Usage:"
37     ssh $node $MYPSPS
38 done

```

```

1 [rush:/projects/jonesm/d_nwchem/d_siosie6]$ job_ps 436728
2 nodelist = d09n29s02,d16n02
3 expanded nodelist = d16n02 d09n29s02
4 MYPSPS = ps -u jonesm -o pid,ppid,lwp,nlwp,psr,pcpu,rss,time,comm
5 NODE = d16n02, my CPU/thread Usage:
6   PID  PPID   LWP  NLWP  PSR  %CPU   RSS    TIME COMMAND
7   9665  9633  9665    5   0  98.2 1748340 00:03:32 nwchem-openib-i
8   9666  9633  9666    4   4  98.7 1479024 00:03:33 nwchem-openib-i
9   9667  9633  9667    4   1  98.6 1479352 00:03:33 nwchem-openib-i
10  9668  9633  9668    4   5  98.6 1466844 00:03:33 nwchem-openib-i
11  9669  9633  9669    4   2  98.9 1461372 00:03:33 nwchem-openib-i
12  9670  9633  9670    4   6  99.1 1474016 00:03:34 nwchem-openib-i
13  9671  9633  9671    4   3  98.8 1470640 00:03:33 nwchem-openib-i
14  9672  9633  9672    4   7  98.6 1474296 00:03:33 nwchem-openib-i
15  9921  9919  9921    1   4   0.0   2132 00:00:00 sshd
16  9922  9921  9922    1   5   2.0   1204 00:00:00 ps
17 NODE = d09n29s02, my CPU/thread Usage:
18   PID  PPID   LWP  NLWP  PSR  %CPU   RSS    TIME COMMAND
19  27963 27959 27963    1   4   0.0   1396 00:00:00 slurm_script
20  28145 27963 28145    5   3   0.0   7024 00:00:00 srun
21  28149 28145 28149    1   5   0.0     800 00:00:00 srun
22  28182 28167 28182    5   0  97.5 1750904 00:03:32 nwchem-openib-i
23  28183 28167 28183    4   4  98.0 1477128 00:03:33 nwchem-openib-i
24  28184 28167 28184    4   1  98.5 1472524 00:03:34 nwchem-openib-i
25  28185 28167 28185    4   5  98.3 1456200 00:03:34 nwchem-openib-i
26  28186 28167 28186    4   2  98.4 1488400 00:03:34 nwchem-openib-i
27  28187 28167 28187    4   6  98.1 1459120 00:03:33 nwchem-openib-i
28  28188 28167 28188    4   3  98.6 1470960 00:03:35 nwchem-openib-i
29  28189 28167 28189    4   7  98.4 1465752 00:03:34 nwchem-openib-i
30  28372 28370 28372    1   3   0.0   2148 00:00:00 sshd
31  28373 28372 28373    1   4   1.0   1204 00:00:00 ps

```

```

1 [rush:/projects/jonesm/d_nwchem/d_siosie6]$ job_ps 436749
2 nodelist = d09n29s02,d16n02
3 expanded nodelist = d16n02 d09n29s02
4 MYPSPS = ps -u jonesm -Lf
5 NODE = d16n02, my CPU/thread Usage:
6   UID   PID  PPID   LWP  NLWP  PSR  %CPU   RSS    TIME CMD
7   jonesm 14416 11382 11416 98    5 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
8   jonesm 14416 11382 11441 0     5 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
9   jonesm 14416 11382 11442 0     5 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
10  jonesm 14416 11382 11454 0     5 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
11  jonesm 14416 11382 11465 0     5 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
12  jonesm 14417 11382 11417 99    4 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
13  jonesm 14417 11382 11445 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
14  jonesm 14417 11382 11446 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
15  jonesm 14417 11382 11460 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
16  jonesm 14418 11382 11418 99    4 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
17  jonesm 14418 11382 11439 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
18  jonesm 14418 11382 11440 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
19  jonesm 14418 11382 11455 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
20  jonesm 14419 11382 11419 99    4 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
21  jonesm 14419 11382 11449 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
22  jonesm 14419 11382 11450 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
23  jonesm 14419 11382 11458 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
24  jonesm 14420 11382 11420 98    4 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
25  jonesm 14420 11382 11451 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
26  jonesm 14420 11382 11452 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
27  jonesm 14420 11382 11457 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
28  jonesm 14421 11382 11421 99    4 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
29  jonesm 14421 11382 11447 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
30  jonesm 14421 11382 11448 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
31  jonesm 14421 11382 11459 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
32  jonesm 14422 11382 11422 99    4 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
33  jonesm 14422 11382 11437 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
34  jonesm 14422 11382 11438 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
35  jonesm 14422 11382 11453 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
36  jonesm 14423 11382 11423 99    4 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
37  jonesm 14423 11382 11443 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
38  jonesm 14423 11382 11444 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
39  jonesm 14423 11382 11456 0     4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
40  jonesm 14489 11487 11489 0     1 17:02 ? 00:00:00 sshd: jonesm@notty
41  jonesm 11490 11489 11490 2     1 17:02 ? 00:00:00 ps -u jonesm -Lf
42 $

```

```

43 NODE = d09n29s02, my CPU/thread Usage:
44 UID PID PPID LWP C NLWP STIME TTY TIME CMD
45 jonesm 29706 29702 29706 0 1 17:01 ? 00:00:00 /bin/bash /var/spool/slurmd/job436749/slurm_script
46 jonesm 29883 29706 29883 0 1 17:01 ? 00:00:00 srun --mpi=pmi2 -n 16 -K /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
47 jonesm 29883 29706 29889 0 5 17:01 ? 00:00:00 srun --mpi=pmi2 -n 16 -K /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
48 jonesm 29883 29706 29891 0 5 17:01 ? 00:00:00 srun --mpi=pmi2 -n 16 -K /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
49 jonesm 29883 29706 29892 0 5 17:01 ? 00:00:00 srun --mpi=pmi2 -n 16 -K /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
50 jonesm 29883 29706 29895 0 5 17:01 ? 00:00:00 srun --mpi=pmi2 -n 16 -K /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
51 jonesm 29888 29883 29888 0 1 17:01 ? 00:00:00 srun --mpi=pmi2 -n 16 -K /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp
52 jonesm 29921 29905 29921 96 5 17:01 ? 00:00:59 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
53 jonesm 29921 29905 29958 0 5 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
54 jonesm 29921 29905 29959 0 5 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
55 jonesm 29921 29905 29967 0 5 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
56 jonesm 29921 29905 29984 0 5 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
57 jonesm 29922 29905 29922 97 4 17:01 ? 00:01:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
58 jonesm 29922 29905 29960 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
59 jonesm 29922 29905 29961 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
60 jonesm 29922 29905 29972 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
61 jonesm 29923 29905 29923 97 4 17:01 ? 00:01:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
62 jonesm 29923 29905 29954 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
63 jonesm 29923 29905 29955 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
64 jonesm 29923 29905 29966 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
65 jonesm 29924 29905 29924 97 4 17:01 ? 00:01:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
66 jonesm 29924 29905 29956 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
67 jonesm 29924 29905 29957 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
68 jonesm 29924 29905 29968 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
69 jonesm 29925 29905 29925 97 4 17:01 ? 00:01:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
70 jonesm 29925 29905 29964 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
71 jonesm 29925 29905 29965 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
72 jonesm 29925 29905 29973 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
73 jonesm 29926 29905 29926 97 4 17:01 ? 00:01:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
74 jonesm 29926 29905 29950 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
75 jonesm 29926 29905 29951 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
76 jonesm 29926 29905 29953 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
77 jonesm 29927 29905 29927 97 4 17:01 ? 00:01:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
78 jonesm 29927 29905 29962 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
79 jonesm 29927 29905 29963 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
80 jonesm 29927 29905 29971 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
81 jonesm 29928 29905 29928 97 4 17:01 ? 00:01:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
82 jonesm 29928 29905 29969 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
83 jonesm 29928 29905 29970 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
84 jonesm 29928 29905 29974 0 4 17:01 ? 00:00:00 /util/nwchem/nwchem-6.1.1/bin/nwchem-openib-imp siosif6-incore.nw
85 jonesm 30009 30007 30009 0 1 17:02 ? 00:00:00 sshd: jonesm@rcty
86 jonesm 30010 30009 30010 2 1 17:02 ? 00:00:00 ps -u jonesm -Lf

```

## Attaching GDB to Running Processes

The simplest way to use a CLI-based debugger in parallel is to “attach” it to already running processes, namely:

- Find the parallel processes using the `ps` command (may have to `ssh` into remote nodes if that is where they are running)
- Invoke `gdb` on each process ID:

```

1 [rush:~]$ ps -u jonesm
2   PID TTY          TIME CMD
3   1772 ?        00:00:00 sshd
4   1773 pts/30    00:00:00 bash
5  25814 ?        00:00:01 sshd
6  25815 pts/167  00:00:00 bash
7  34507 pts/169  00:00:00 mpirun
8  34512 pts/169  00:00:00 mpiexec.hydra
9  34513 pts/169  00:00:00 pmi_proxy
10 34517 pts/169  00:00:04 pp.gdb
11 34518 pts/169  00:00:04 pp.gdb
12 [rush:~/d_hw/d_pp]$ gdb -quiet pp.gdb -p 34517
13 Reading symbols from /ifs/user/jonesm/d_hw/d_pp/pp.gdb...done.
14 Attaching to program: /ifs/user/jonesm/d_hw/d_pp/pp.gdb, process 34517
15 ...
16 (gdb)

```

## Using Serial Debuggers in Parallel?

Yes, you can certainly run debuggers designed for use in sequential codes in parallel. They are even quite effective. You may just have to jump through a few extra hoops to do so ...

Of course, unless you put an explicit waiting point inside your code, the processes are probably happily running along when you attach to them, and you will likely want to exert some control over that.

First, using our above example, I was running two mpi tasks on the CCR cluster front end. After attaching gdb to each process, they paused, and we can easily release them using *continue*

```
1 [rush:~/d_hw/d_pp]$ gdb -quiet pp.gdb -p 34517
2 Reading symbols from /ifs/user/jonesm/d_hw/d_pp/pp.gdb...done.
3 Attaching to program: /ifs/user/jonesm/d_hw/d_pp/pp.gdb, process 34517
4 ...
5 (gdb) c
6 Continuing.
```

and on the second process:

```
1 [rush:~/d_hw/d_pp]$ gdb -quiet pp.gdb -p 34518
2 Reading symbols from /ifs/user/jonesm/d_hw/d_pp/pp.gdb...done.
3 Attaching to program: /ifs/user/jonesm/d_hw/d_pp/pp.gdb, process 34518
4 ...
5 (gdb) c
6 Continuing.
```

and we used the (c) continue command to let the execution pick up again where we (temporarily) interrupted it.

## Using a “Waiting Point”

You can insert a “waiting point” into your code to ensure that execution waits until you get a chance to attach a debugger:

```
1 integer :: gdbWait=0
2 ...
3 ...
4 CALL MPI_COMM_RANK(MPI_COMM_WORLD,myid,ierr)
5 CALL MPI_COMM_SIZE(MPI_COMM_WORLD,Nprocs,ierr)
6 ! dummy pause point for gdb instertion
7 do while (gdbWait /=1)
8 end do
```

and then you will find the waiting at that point when you attach *gdb*, and you can release it at your leisure (after setting breakpoints, etc.):

```
1 [rush:~/d_hw/d_pp]$ gdb -quiet pp.gdbwait -p 80444
2 Reading symbols from /ifs/user/jonesm/d_hw/d_pp/pp.gdbwait...done.
3 Attaching to program: /ifs/user/jonesm/d_hw/d_pp/pp.gdbwait, process 80444
4 ...
5 0x0000000000400df2 in pp () at pp.f90:42
6 42 do while (gdbWait /=1)
7 (gdb) set gdbWait=1
8 (gdb) c
9 Continuing.
```

```
1 [rush:~/d_hw/d_pp]$ gdb -quiet pp.gdbwait -p 80445
2 Reading symbols from /ifs/user/jonesm/d_hw/d_pp/pp.gdbwait...done.
3 Attaching to program: /ifs/user/jonesm/d_hw/d_pp/pp.gdbwait, process 80445
4 ...
5 pp () at pp.f90:42
6 42 do while (gdbWait /=1)
7 (gdb) set gdbWait=1
8 (gdb) c
9 Continuing.
```

## Using GDB Within MPI Task Launcher

Last, but not least, you can usually launch `gdb` through your MPI task launcher. For example, using the Intel MPI task launcher, `mpirun/mpiexec` (note that this generally pauses at `MPI_Init`):

```

1 [rush:~/d_hw/d_pp]$ mpirun -np 2 -gdb ./pp.gdb
2 mpigdb: np = 2
3 mpigdb: attaching to 22615 ./pp.gdb f07n05
4 mpigdb: attaching to 22616 ./pp.gdb f07n05
5 [0,1] (mpigdb) list 40
6 [0,1] 35 if (ierr /= 0) then
7 [0,1] 36 print*, 'Unable to intialize MPI.'
8 [0,1] 37 STOP
9 [0,1] 38 end if
10 [0,1] 39 CALL MPI_COMM_RANK(MPI_COMM_WORLD,myid,ierr)
11 [0,1] 40 CALL MPI_COMM_SIZE(MPI_COMM_WORLD,Nprocs,ierr)
12 [0,1] 41 ! dummy pause point for gdb insertion
13 [0,1] 42 !do while (gdbWait /=1)
14 [0,1] 43 !end do
15 [0,1] 44 if (Nprocs /= 2) then
16 [0,1] (mpigdb) c
17 [0,1] Continuing.
18 Hello from proc 0 of 2 f07n05
19 Number Averaged for Sigmas: 2
20 Hello from proc 1 of 2 f07n05

```

## Using Serial Debuggers in Parallel

So you can certainly use serial debuggers in parallel - in fact it is a pretty handy thing to do. Just keep in mind:

- Don't forget to compile with debugging turned on
- You can always attach to a running code (and you can instrument the code with that purpose in mind)
- Beware that not all task launchers are equally friendly towards built-in support for serial debuggers

## More Using GDB With MPI Task Launcher

```

1 [0,1] (mpigdb) list 84
2 [0,1] 79 do i=my_low,my_high,2
3 [0,1] 80 partial_sum_p = partial_sum_p + 1.0_dp/(2.0_dp*i-1.0_dp)
4 [0,1] 81 partial_sum_m = partial_sum_m - 1.0_dp/(2.0_dp*i+1.0_dp)
5 [0,1] 82 end do
6 [0,1] 83 partial_sum = partial_sum_p + partial_sum_m
7 [0,1] 84 CALL MPI_REDUCE(partial_sum,sum,1,MPI_DOUBLE_PRECISION,MPI_SUM,0, &
8 [0,1] 85 MPI_COMM_WORLD,ierr)
9 [0,1] 86 t1 = MPI_Wtime()
10 [0,1] 87 time_delta = time_delta + (t1-t0)
11 [0,1] 88 end do
12 [0,1] (mpigdb) b 83
13 [0,1] Breakpoint 1 at 0x401161: file pi-mpi.f90, line 83.
14 [0,1] (mpigdb) run
15 [0,1] Continuing.
16 Greetings from proc 0 of 2 f07n05
17 Nterms Nperproc Nreps error time/rep
18 Greetings from proc 1 of 2 f07n05
19 [0,1]
20 [0,1] Breakpoint 1, pimpi () at pi-mpi.f90:83
21 [0,1] 83 partial_sum = partial_sum_p + partial_sum_m
22 [0,1] (mpigdb) p my_low
23 [0] $1 = 1
24 [1] $1 = 65
25 [0,1] (mpigdb) p my_high
26 [0] $2 = 64
27 [1] $2 = 128

```

## The TotalView Debugger

The “premier” parallel debugger, TotalView:

- Sophisticated commercial product (think many \$\$ ...)
- Designed especially for HPC, multi-process, multi-thread
- Has both GUI and CLI
- Supports C/C++, Fortran 77/90/95, mixtures thereof
- The “official” debugger of DOE’s **Advanced Simulation and Computing** (ASC) program

## Using TotalView at CCR

Pretty simple to start using TotalView on the CCR systems:

- 1 Generally you want to load the latest version:

```
1 [dl6n03:~]$ module avail totalview
```

- 2 Make sure that your `X DISPLAY` environment is working if you are going to use the GUI.
- 3 The current CCR license supports 2 concurrent users up to 8 processors (precludes usage on nodes with more than 8 cores until/unless this license is upgraded).

## The DDT Debugger

Allinea's commercial parallel debugger, DDT:

- Sophisticated commercial product (think many \$\$ ...)
- Designed especially for HPC, multi-process, multi-thread
- Has both GUI and CLI
- Supports C/C++, Fortran 77/90/95, mixtures thereof
- CCR has a 32-token license for DDT (including CUDA and MAP profiler support)
- To find the latest installed version,  
`module avail ddt`

## Current Recommendations

CCR has licenses for Allinea's DDT and TotalView (although the current TotalView license is very small and outdated and will be either upgraded or dropped in favor of DDT). Both are quite expensive, but stay tuned for further developments. Note that the open-source **eclipse** project also has a parallel tools platform that can be used in combination with C/C++ and Fortran:

<http://www.eclipse.org/ptp>