



JUBILANT INDUSTRIES LIMITED

TECHNICAL DATA SHEET

JIVANJOR AQUABOND

FOR INFORMATION ONLY

JJ Aquabond is a synthetic resin based adhesive in the form of milky white viscous liquid. It is one pack ready to use adhesive for all wood working application. It is water based adhesive, non-flammable and non-toxic in nature.

TYPICAL PROPERTIES

• Appearance	Milky White Emulsion
• Solid Content %	47-50
• Viscosity at 25°C in Poise (By B.F.RVT Spl no-7,RPM-20)	250-350
• pH	2-4
• Flow	Continuous
• Spread ability	Smooth & easy
• Bond strength W/W kg\inch sq	300 min

APPLICATION METHOD

- Substrate surface to be bonded should be free from oil, grease, dust, dirt or any foreign particle and should be dry and properly leveled.
- Surface can be roughen by sand paper for best results if required.
- Stir the content of container before use.
- Apply uniform coat of JJ Aquabond first on non-porous surface, and then on more porous surface e.g. apply first on mica and then on plywood.

- Bring both the surfaces in contact before complete drying of adhesive and make proper alignment, start pressing from one side by wet cloth to avoid air entrapment, even spreading and better bonding
- Pressure can be applied by using nails, weight, tapes etc.
- Excess adhesive oozing out from edges can be cleaned with the help of wet cloth.
- Bonded surface are to be kept under pressure for 24 hrs to get optimum results.
- If required pressure can be released after 6-8 hrs and the bonded assembly can be put to use.
- For extremely porous surfaces like particle board and MDF, it is recommended that, a thin coat of JJ Aquabond is applied and allowed to completely dry. After drying, light sanding is done to get leveled and smooth surface then this surface is bonded as per standard method to get best results.

COVERAGE

- Approx 45-50 sq ft/per kg on ply to mica

USPs/ADVANTAGES

- Non-flammable and non-toxic as it is water based.
- Water resistant in normal case.
- No fire and health Hazards as it is solvent free.
- Free from objectionable smell.
- Handling strength in 6-8 hrs i.e. very quick setting time, better productivity.
- Superior flow ability and spreadability: better coverage.
- More application options; can be applied by brush, roller, spreader, fingertip or any applicator.
- Can be cleaned easily by wet cloth.
- Excellent bond strength.
- Clear transparent film after drying.
- Heat resistance in normal case.

AREA OF USAGE

Furniture Industries

- Bonding wood to wood; bonding laminate, plywood, veneer, all types of boards to each other.
- Any wood joineries application with moderate water exposer.

Non- Furniture Industries

- Wood joineries in Bus Body building.
- Wooden boxes and cabinets for TV and radio.
- Wooden Frames for wall clock.

PRECAUTIONS

- Container cap should be kept closed when not in use.
- Stir well before use.
- Skin formation if any, should be removed from the surface before use.
- Uniform pressure is must for bubble free application.

SHELF LIFE

- Best to be use before 12 months from date of manufacturing.

STORAGE CONDITION

- Store in cool & dark place; away from direct sunlight.