

HR / Workforce Analytics System

Monitor staffing, period attrition, attendance and payroll without double-counting monthly headcount.

BUSINESS BRIEF | CLIENT REQUIREMENTS | DATA MODEL | STEP-BY-STEP BUILD

What the project does

Monitor staffing, period attrition, attendance and payroll without double-counting monthly headcount. It turns the specified source tables into an interactive, filterable view of these business outcomes.

Synthetic demo checkpoints

Reference figures below describe the included synthetic dataset only; they are not client results.

REFERENCE KPI	DEMO VALUE
Headcount	290
Hires	125
Leavers	84
Period Attrition	0.32
Absence Rate	3.5%

REQUIREMENTS NOTE | This guide translates the repository specification into an implementation brief. Confirm it with the actual client; it is not a signed discovery or acceptance document.

01 / Business problem and client requirements

Agree the outcome and KPI definitions before loading customer data.

Business problem

Monitor staffing, period attrition, attendance and payroll without double-counting monthly headcount.

Without consistent definitions, business totals can be difficult to compare or trace back to a responsible team, customer, product, or period. The dashboard is designed to let managers review the specified KPIs, apply business filters, and inspect supporting detail. This is the intended use inferred from the project specification, not a claim about a named client's current process.

Requirements interpreted from the project specification

- Provide a Power BI report that supports the stated goal: Monitor staffing, period attrition, attendance and payroll without double-counting monthly headcount.
- Show the 3 project pages, their KPI cards, charts, filters, and detail tables listed in the page blueprint.
- Calculate the named measures using their documented formulas and preserve the project rules.
- Use the reporting scope: Jan-Sep 2026 department/month snapshots; headcount uses latest selected month.
- Allow analysis by: Calendar.Month, Departments.Department, Departments.Location
- Deliver editable PBIP report and semantic-model source, a data contract, private-source templates, and a reconciliation path.

Project boundaries

ClosingHeadcount = OpeningHeadcount + Hires - Leavers. Next month opening equals prior closing. All departments must have the same month coverage. AbsentHours <= ScheduledHours. Aggregate, synthetic HR data only; access controls for real employee information must be designed before deployment.

Client discovery questions

Confirm source systems and data owners; reporting currency and timezone; period and as-of date; refresh frequency; exact business definitions; privacy and access requirements; who signs off; and whether publishing to Power BI Service is in scope.

02 / Data contract and model

Keep the input tables at their documented grain; the grain determines what a summed KPI means.

TABLE	GRAIN / KEY	FIELDS (SOURCE TYPE)
Departments	one department / DepartmentID	DepartmentID (string), Department (string), Location (string)
Workforce	one department per month-end / SnapshotID	SnapshotID (string), DepartmentID (string), Date (dateTime), OpeningHeadcount (int64), ClosingHeadcount (int64), Hires (int64), Leavers (int64), ScheduledHours (int64), AbsentHours (int64), OvertimeHours (int64), Payroll (decimal)
Metrics	one metadata row / Label	Label (string)
Calendar	one calendar date / Date	Date (dateTime), Year (int64), Month (string), Quarter (string)

Relationships in the PBIP model

FROM (MANY)	TO (ONE)	FILTERING
Workforce.DepartmentID	Departments.DepartmentID	oneDirection
Workforce.Date	Calendar.Date	oneDirection

Data handoff: Use data/import-template with exact filenames and headers. Keep client source files in approved private storage; do not commit them. Set DataMode=Folder and DataFolder to the approved location only after validating the inputs.

03 / KPI and DAX glossary

Treat these formulas and definitions as a signed calculation contract.

MEASURE	DAX SPECIFICATION	MEANING
Headcount	VAR LastMonth = MAX(Workforce[Date]) RETURN CALCULATE(SUM(Workforce[ClosingHeadcount]), Workforce[Date] = LastMonth)	Closing headcount at the latest snapshot in the selected period; never sum months.
Average Opening Headcount	AVERAGEX(VALUES(Workforce[Date]), CALCULATE(SUM(Workforce[OpeningHeadcount])))	Average of selected monthly opening headcounts.
Hires	SUM(Workforce[Hires])	Sum of Hires at the recorded grain.
Leavers	SUM(Workforce[Leavers])	Sum of Leavers at the recorded grain.
Net Hiring	[Hires] - [Leavers]	Period hires less leavers.
Period Attrition	DIVIDE([Leavers], [Average Opening Headcount])	Leavers in selected months / average monthly opening headcount. Period rate, not annualized.
Scheduled Hours	SUM(Workforce[ScheduledHours])	Sum of ScheduledHours at the recorded grain.
Absent Hours	SUM(Workforce[AbsentHours])	Sum of AbsentHours at the recorded grain.
Absence Rate	DIVIDE([Absent Hours], [Scheduled Hours])	Absent hours / scheduled hours.
Overtime Hours	SUM(Workforce[OvertimeHours])	Sum of OvertimeHours at the recorded grain.
Payroll	SUM(Workforce[Payroll])	Total payroll over selected months.
Payroll per Employee Month	DIVIDE([Payroll], SUM(Workforce[ClosingHeadcount]))	Payroll / sum of monthly closing headcounts; employee-month cost, not payroll / latest headcount.

Format currency using the client's approved reporting currency. Show rate, margin, attainment, and share measures as percentages. Format units, hours, days, and counts as whole or decimal numbers only where their source supports it.

04 / Build step by step | 1-5

Work through the stages in order and preserve the original demo as your baseline.

1. Confirm the business decisions

Start with: Monitor staffing, period attrition, attendance and payroll without double-counting monthly headcount. Confirm who will use the report and what action each page supports. Agree the reporting period, currency, refresh cadence, data owner, KPI definitions, cutoffs, and acceptance owner. The brief here is inferred from this repository spec, not a signed client requirements document.

2. Request the right source extracts

Request the tables at this grain: Departments: one department, key DepartmentID; Workforce: one department per month-end, key SnapshotID. Use the exact file names, headers, primary keys, and types listed in the data dictionary. Ask for historical periods only where the project scope supports them; do not assume snapshots can reproduce history.

3. Keep data secure and test its quality

Place client files in approved private storage, outside GitHub. Check unique keys, required fields, valid dates, numeric signs, foreign keys, and coverage. Preserve these rules: $\text{ClosingHeadcount} = \text{OpeningHeadcount} + \text{Hires} - \text{Leavers}$. Next month opening equals prior closing. All departments must have the same month coverage. $\text{AbsentHours} \leq \text{ScheduledHours}$. Aggregate, synthetic HR data only; access controls for real employee information must be designed before deployment. The demo is synthetic and is for testing the model, not for client reporting.

4. Open the PBIP source project

Download and extract the full repository, then open power-bi/08-hr-workforce/Dashboard.pbip in Power BI Desktop. Keep the complete folder structure. PBIP saves report and semantic-model definitions as project files that can be versioned [1].

5. Check the known-good demo baseline

Refresh in Demo mode. Review DATA-CONTRACT.md, validation/expected-demo.json, and Model.SemanticModel/DAXQueries/Reconcile.dax. Record the supplied demo totals and click through every page before replacing the source.

05 / Build step by step | 6-10

Connect private data, build the model, and test the finished report.

6. Connect the client's approved data

Copy the matching CSV templates from `power-bi/08-hr-workforce/data/import-template/` to the client's private source folder. In Power Query > Manage Parameters set `DataMode` to `Folder` and `DataFolder` to that absolute path. Keep the required Metrics row. Select Transform Data to inspect types and fix errors before loading [2].

7. Prepare fields and relationships

Use the declared data types, retain one row at the required grain, and handle blanks only as documented. Check these many-to-one links in the model: `Workforce.DepartmentID > Departments.DepartmentID`; `Workforce.Date > Calendar.Date`. Lookup tables should filter facts; avoid fact-to-fact joins that multiply values [3].

8. Add and reconcile measures

Use `measures.dax` and the KPI glossary as the calculation contract. Create explicit DAX measures with approved formats. Test results under each date and business-unit filter; verify totals against an independent calculation. Measures respond to the report filter context [4].

9. Build and review the report pages

Recreate the report blueprint below: exact page purpose, slicers, KPI cards, chart series, and detail rows. Add clear titles, sort time labels chronologically, format currency and percentages, and test interactions. Keep project-specific definitions visible to the report user.

10. Sign off, publish, and hand over

Refresh, reconcile source totals, test edge cases, document KPI ownership, and obtain business sign-off. Keep the PBIP source in version control. If service publishing is in scope, publish to the approved workspace, configure credentials and gateway if needed, schedule refresh, and test permissions [5]. Do not publish confidential data before access/security sign-off.

06 / Report blueprint and acceptance

Implement each page to support a specific decision and trace each number to source data.

PAGE / FILTERS	KPI CARDS	CHARTS / DETAIL TABLE
Workforce overview Filters: Month, Department, Location	Headcount, Hires, Leavers, Period Attrition	Charts: Headcount by Department; Headcount by Month Detail: Department, Headcount, Hires, Leavers, Period Attrition
Retention and hiring Filters: Month, Department, Location	Average Opening Headcount, Hires, Net Hiring, Period Attrition	Charts: Hires and leavers by department; Hires and leavers by month Detail: Department, Average Opening Headcount, Leavers, Period Attrition
Attendance and cost Filters: Month, Department, Location	Payroll, Payroll per Employee Month, Absence Rate, Overtime Hours	Charts: Payroll by Department; Absence Rate by Month Detail: Department, Scheduled Hours, Absent Hours, Absence Rate, Payroll

Acceptance checklist

- Open the PBIP in current Power BI Desktop and refresh all tables without errors.
- Reconcile source counts, key uniqueness, relationships, and every project-specific data rule.
- Compare KPI measures to independently calculated totals and the supplied expected-demo.json.
- Test each slicer, filter interaction, date behavior, chart title, table detail, blank context, and zero denominator.
- Confirm currency, percentage formats, report audiences, privacy, access, refresh ownership, and client sign-off.

Demo acceptance values

METRIC	EXPECTED (SYNTHETIC)
Headcount	290
Hires	125
Leavers	84
Period Attrition	0.32
Absence Rate	3.5%
Payroll	PKR 337,300,000

07 / Handover and references

Use the Microsoft guidance below for product workflows; verify tenant-specific settings at delivery.

- Document approved data owner, source, refresh schedule, and support contact.
- Keep the metric dictionary, data contract, sign-off totals, and known limits with the delivered report.
- For Service deployment, confirm target workspace, credentials, gateway needs, permissions, tenant policies, and applicable license.
- A slicer does not enforce row-level security. Design and test security separately before exposing restricted data.
- This repository contains synthetic examples and a source implementation. Desktop rendering, engine evaluation, Service deployment, and client acceptance are separate release gates.

Microsoft Learn references

[1] Power BI Desktop projects (PBIP) - project format and folders

<https://learn.microsoft.com/en-us/power-bi/developer/projects/projects-overview>

[2] Connect to data in Power BI Desktop - Get Data and Power Query

<https://learn.microsoft.com/en-us/power-bi/connect-data/desktop-connect-to-data>

[3] Understand star schema and the importance for Power BI

<https://learn.microsoft.com/en-us/power-bi/guidance/star-schema>

[4] Tutorial: Create your own measures in Power BI Desktop

<https://learn.microsoft.com/en-us/power-bi/transform-model/desktop-tutorial-create-measures>

[5] Publish semantic models and reports from Power BI Desktop

<https://learn.microsoft.com/en-us/power-bi/create-reports/desktop-upload-desktop-files>

References checked 30 September 2026. Power BI interface labels, preview features, licensing, and tenant controls can change; confirm them in the client's environment.