AtiNAMatiC-Squash — User Manual

Version 0.1.0 | Atij 666 Studio

What It Is

AtiNAMatiC-Squash is a **one-knob feedforward RMS compressor** designed for guitar and bass processing — from subtle bus glue to aggressive, punchy squash. A single **SQUASH** macro knob sets the compression intensity, while three **MODE** characters shape how the compression behaves. A **MIX** control lets you blend the compressed signal in parallel for New York-style compression without touching a ratio or threshold.

Squash is intended to sit after your NAM model and cab sim, adding the final punch and glue that makes a tracked guitar feel controlled and present in the mix without audible pumping.

Signal Chain Placement

```
Guitar -> NAM Model -> Cab Sim -> EQ / FX -> [AtiNAMatiC-Squash] -> DAW track / bus
```

Place Squash **after** your amp sim and cab. It should see the fully processed, speaker-coloured signal. Placing it before the cab will compress the sharp transients before cabinet filtering, which can sound unnatural.

For parallel bus processing, insert Squash on an aux channel and blend using MIX or the host send level.

Controls

Control	Range	Default	Description
SQUASH	Light to Heavy	50%	Main compression intensity macro. Controls threshold, ratio, attack, release, and knee simultaneously.
MODE	Gentle / Standard / Smash	Standard	Selects the compression character.
MIX	0 to 100%	100%	Parallel wet/dry blend. 100% = fully compressed.
OUTPUT	-24 to +24 dB	0 dB	Output trim applied after the compressor and mix blend.

The SQUASH Knob

The SQUASH knob is a smooth macro that scales all five compressor parameters simultaneously. A **smoothstep curve** is applied so the lower half of the travel is more subtle — useful for transparent glue — while the upper half becomes progressively more aggressive.

At **Light (0%)** the plugin is essentially transparent: threshold is high, ratio is minimal, attack is slow, and the soft knee is at its widest.

At **Heavy (100%)** the threshold drops to its lowest point, ratio climbs to the mode maximum, attack tightens to its fastest, and (in Standard and Smash modes) the knee hardens.

Auto makeup gain is applied proportionally: at Light the gain is unity, and it scales up toward Heavy to compensate for perceived loudness reduction. The gain is applied *after* the time-constant smoother so mode switches never cause gain pumping.

Modes

GENTLE

Slow, transparent bus glue with a wide soft knee. Preserves pick dynamics and natural playing feel. Good for clean tones, acoustic processing, and final bus glue.

Parameter	Light (0%)	Heavy (100%)
Threshold	-3 dB	-14 dB
Ratio	1.5 : 1	4 : 1
Attack	50 ms	12 ms
Release	300 ms	80 ms
Knee	8 dB	4 dB

STANDARD

All-purpose character: snappy but musical. Covers the widest range of applications. Good starting point for any source.

Parameter	Light (0%)	Heavy (100%)
Threshold	-6 dB	-22 dB
Ratio	2 : 1	8 : 1
Attack	25 ms	3 ms
Release	200 ms	40 ms
Knee	6 dB	1.5 dB

SMASH

Aggressive, fast, and tight. Very low thresholds, high ratios, near-zero attack. Adds punch and density. Best used with MIX below 100% to keep transient feel (New York parallel style).

Parameter	Light (0%)	Heavy (100%)
Threshold	-9 dB	-30 dB
Ratio	4 : 1	20 : 1
Attack	8 ms	0.5 ms
Release	100 ms	15 ms

Knee	4 dB	0 dB (hard)

GR Meter

The horizontal segmented bar at the bottom of the plugin displays **Gain Reduction** in real time.

- **Range:** 0 to 18 dB GR
- **Colour zones:**
  - Green: 0 to 9 dB GR (normal compression range)
  - Amber: 9 to 13.5 dB GR (medium compression)
  - Red: 13.5 to 18 dB GR (heavy compression)
- **Peak hold** — a bright marker holds at the highest GR reached for ~2 seconds, then decays slowly.
- **Tick marks** at -6 dB, -12 dB, and -18 dB GR.

The meter has **instant attack** and **100 ms visual release**, giving a fast, responsive readout that mirrors what you hear.

System Requirements

	Minimum
OS	Windows 10 (64-bit) / macOS 10.15+ / Linux (Ubuntu 20.04+)
CPU	Any modern x64 processor
RAM	4 GB
DAW	Any VST3 or CLAP host
Formats	VST3, CLAP (Windows/Linux); + AU (macOS)

Installation

Windows - Installer

1. Run **AtiNAMatiC-Squash-Setup-0.1.0.exe**.
2. Select the formats you want (VST3 and/or CLAP).
3. Complete the wizard.
4. Rescan your DAW (see table below).

Windows - Manual

1. Copy `AtiNAMatiC-Squash.vst3` to `C:\Program Files\Common Files\VST3\`
2. Copy `AtiNAMatiC-Squash.clap` to `C:\Program Files\Common Files\CLAP\`
3. Rescan your DAW.

macOS - Manual

1. Copy `AtiNAMatiC-Squash.vst3` to `/Library/Audio/Plug-Ins/VST3/`
2. Copy `AtiNAMatiC-Squash.component` to `/Library/Audio/Plug-Ins/Components/` (AU)
3. Rescan your DAW.

Linux - Manual

1. Copy `AtiNAMatiC-Squash.vst3` to `~/.vst3/` (per-user) or `/usr/lib/vst3/` (system)
2. Copy `AtiNAMatiC-Squash.clap` to `~/.clap/` (per-user) or `/usr/lib/clap/` (system)
3. Rescan your DAW.

DAW Rescan

DAW	Where to rescan
Reaper	Options > Preferences > Plug-ins > VST > Re-scan
Ableton Live	Preferences > Plug-ins > Rescan
Cubase / Nuendo	Studio > VST Plug-in Manager > Update
Bitwig Studio	Settings > Plug-ins > Rescan plug-in locations
Studio One	Options > Locations > VST Plug-ins > Scan
Logic Pro	Restart Logic - AU plug-ins are rescanned automatically

---

Controls Reference

Control	Parameter ID	Type	Range	Default
SQUASH	`squash`	Float	0.0 to 1.0	0.5
MODE	`mode`	Choice	Gentle / Standard / Smash	Standard (1)
MIX	`mix`	Float	0.0 to 1.0	1.0
OUTPUT	`output`	Float (dB)	-24 to +24	0.0

All parameters are fully automatable and support DAW recall and preset saving.

Internal Signal Chain

```
Input (stereo)
  |
  +-> RMS Envelope Detector (10 ms window, stereo-linked: max of L+R)
  |         |
  |         v
  |   Input level in dBFS
  |         |
  |         v
  |   Gain Computer (threshold + soft-knee + ratio set by SQUASH + MODE)
  |         |
  |         v
  |   Per-sample Attack / Release smoother
  |   (both channels track the stereo-linked detector, stereo image preserved)
  |         |
  |         v
```

```
  +-> Apply compression gain
  |         |
  |         v
  |   Auto makeup gain (scaled with SQUASH, applied after smoother)
  |
  +-> Parallel MIX blend (dry x (1 - MIX) + wet x MIX)
  |
  +-> OUTPUT trim
  |
Output (stereo)
```

The compressor uses **stereo linking**: the RMS detector takes the maximum across both channels so both L and R always receive the same gain reduction, preserving the stereo image under heavy compression.

Typical Use Cases

Rhythm guitar glue (GENTLE, 50-70%) — Tightens palm mutes and power chords without audibly clamping the attack. The wide knee and slow attack let the pick transient through before clamping down.

Lead guitar sustain (STANDARD, 60-80%) — Longer notes and bends sustain more evenly. The shorter release at heavier settings keeps the compressor active between phrases, reducing the perception of the signal pumping up between notes.

Parallel drum-room crush (SMASH, 80-100%, MIX 40-60%) — Full SMASH at high SQUASH destroys dynamics and adds density. Blend back with MIX to taste — the dry transients from the parallel path restore punch while the crushed signal adds body and sustain.

DI bass (STANDARD or SMASH, 50-70%) — Controls the dynamic range of bass lines so low notes and high frets sit at the same level in the mix.

Bus finaliser (GENTLE, 30-50%) — Last insert on a guitar bus. Subtle glue that makes multiple guitar tracks feel like they were played in the same room.

Tips

- **Start in STANDARD at 50%.** Adjust SQUASH until the GR meter shows 3-6 dB on peaks, then stop.
- **Use MIX for parallel compression.** SMASH mode at 90% with MIX at 50% is a classic New York compression sound — dense, punchy, still has transient feel.
- **Watch the amber zone (9-13 dB).** For most guitar work, staying in the green is correct; amber and red zones are for intentional effect.
- **GENTLE at 20-30% is nearly invisible** but makes a mix bus sit more consistently. This is the set-it-and-forget-it zone.
- **The peak hold marker** is useful during tracking. Set a phrase, watch where the peak hold lands, then adjust SQUASH so it lands in the 3-6 dB green zone for the loudest moments.
- **OUTPUT after MIX** — OUTPUT is applied after the parallel blend, so adjusting it does not change the compression behaviour, only the final level.

About

AtiNAMatiC-Squash is part of the **One-Knob Series** by Atij 666 Studio — a collection of purpose-built, single-focus audio tools designed for fast, confident sound shaping.

Built with:

- JUCE Framework - Raw Material Software Ltd.
- VST3 SDK - Steinberg Media Technologies GmbH
- CLAP - Free Audio / Alexandre Bique and contributors