

Consolidate and Document Scan Results

Aggregated Findings & Service Mapping Report DEV-355

Project Task Reference: Open Port Scanning and Service Mapping DEV-352

Report Type: Consolidated Scan Findings

Scope: 15 Authorized Systems (anonymized)

Assessment Focus: Open TCP Ports, Detected Services, Service Mapping, and Exposure Observations

1. Executive Summary

This report consolidates the results obtained from the port scanning and service-mapping activities performed against the assigned target systems. The purpose of the exercise was to convert individual scan outputs into a structured inventory showing each target, its exposed TCP ports, and the services identified on those ports.

A total of 15 systems were reviewed. Across these targets, 45 open TCP port instances were identified, representing 19 distinct port numbers. SSH on TCP/22 was the most consistently exposed service, appearing on all 15 targets.

While several systems exposed only SSH, a smaller number of hosts presented a broader service footprint that included web services, database services, service-discovery infrastructure, object storage, and management interfaces. The scan also identified several ports for which the service could not be conclusively determined. These entries have intentionally been retained as unidentified/inconclusive rather than assigning a service based only on the port number.

2. Scope and Objective

The objective of DEV-355 was to aggregate the findings produced during the port-scanning and service-mapping activities into a clear and usable report.

The report specifically covers:

- Target systems included in the scan (anonymized as TARGET-01 to TARGET-15).
- Open TCP ports detected on each target.
- Services identified through service detection.
- Available service/version information from the scan results.
- Repeated and non-standard service exposures.
- Ports where service identification was inconclusive.
- High-level observations and recommended validation areas.

The report is focused on consolidation and documentation rather than performing a complete vulnerability assessment. Therefore, an open port is treated as an observed service exposure and is not automatically classified as a security vulnerability.

3. Source of Findings

The information presented in this report was consolidated from the available port-scan and service-detection results for the assigned targets.

Where service detection provided a clear identification, the detected service and relevant version information have been retained. Where the scanner could not confidently identify the service, the result is recorded as Unidentified, TCP-wrapped, or otherwise described according to the available scan evidence.

This approach prevents assumptions based solely on commonly associated port numbers.

4. Consolidated Target-to-Service Inventory

The following table provides the primary inventory for the assessment. Each row represents an observed open TCP port on a target system. All real IP addresses have been replaced with anonymous TARGET identifiers.

Target ID	Port	Protocol	Detected Service	Version / Details
TARGET-01	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
	54321	TCP	MariaDB	10.6.23
TARGET-02	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
	53	TCP	TCP-wrapped service	Service not exposed for direct identification

	4646	TCP	HTTP / Go service	Go-based HTTP service
	8301	TCP	Unidentified	Service not conclusively identified
	8500	TCP	Consul Agent	Consul service
	8502	TCP	Unidentified	Service not conclusively identified
	8503	TCP	SSL-related service	Exact implementation not confirmed
	8600	TCP	TCP-wrapped service	Service not directly identified
	9000	TCP	MinIO	Object storage service
	9001	TCP	MinIO Console	MinIO management console
TARGET-03	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-04	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-05	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-06	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
	53	TCP	TCP-wrapped service	Service not directly identified
	80	TCP	HTTP	OpenResty
	443	TCP	HTTPS	OpenResty
	7212	TCP	PostgreSQL	PostgreSQL 9.6+
	7213	TCP	Unidentified	Service not conclusively identified
	9111	TCP	Redis	Redis service
	9112	TCP	Go HTTP service	Service fingerprint indicates Go/HTTP
	9180	TCP	HTTP	OpenResty
TARGET-07	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
	53	TCP	TCP-wrapped service	Service not directly identified
	80	TCP	HTTP	OpenResty
	443	TCP	HTTPS	OpenResty
	7212	TCP	PostgreSQL	PostgreSQL 9.6+
	7213	TCP	Unidentified	Service not conclusively identified
	9111	TCP	Redis	Redis service
	9112	TCP	Go HTTP service	Service fingerprint indicates Go/HTTP
	9180	TCP	HTTP	OpenResty
TARGET-08	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-09	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-10	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-11	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-12	22	TCP	SSH	OpenSSH 9.6p1 Ubuntu
	80	TCP	HTTP	nginx 1.31.2
	443	TCP	HTTPS	nginx 1.31.2 / SSL
	8443	TCP	HTTPS-alt	Service implementation not conclusively identified
TARGET-13	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-14	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
TARGET-15	22	TCP	SSH	OpenSSH 8.9p1 Ubuntu
	443	TCP	HTTPS/SSL	Implementation not conclusively identified

5. Service Mapping Overview

The consolidated results show several categories of services across the scanned infrastructure. The distribution is not uniform: most hosts expose only SSH, while a smaller group exposes multiple application, database, or infrastructure services.

5.1 SSH Services

SSH is the most widely observed service in the scan results.

TCP/22 was open on all 15 target systems. Most systems reported OpenSSH 8.9p1 on Ubuntu. One host, TARGET-12, reported OpenSSH 9.6p1 Ubuntu.

The consistent presence of SSH indicates that remote administrative access is a common management mechanism across the scanned systems.

From an operational perspective, SSH exposure should be reviewed against the intended administration model, particularly authentication controls, network restrictions, and whether public accessibility is required.

5.2 Web Services

OpenResty

The following hosts expose OpenResty-based web services:

- TARGET-06
- TARGET-07

Observed ports include: TCP/80 (HTTP), TCP/443 (HTTPS), TCP/9180 (HTTP). This indicates that these systems are providing web-facing or web-based application endpoints through OpenResty.

nginx

Host TARGET-12 exposes: TCP/80 — nginx 1.31.2, TCP/443 — nginx 1.31.2 over SSL/HTTP. The host also exposes TCP/8443, although the exact service implementation was not conclusively identified.

5.3 Database Services

MariaDB

Host TARGET-01 exposes: TCP/54321 — MariaDB 10.6.23

PostgreSQL

The following two hosts expose PostgreSQL:

- TARGET-06 — TCP/7212
- TARGET-07 — TCP/7212

The detected service fingerprint indicates PostgreSQL 9.6+.

Redis

Redis was identified on:

- TARGET-06 — TCP/9111
- TARGET-07 — TCP/9111

The presence of database and data-store services on non-standard ports is particularly relevant for infrastructure inventory because these services may not be immediately apparent from conventional port assumptions.

5.4 Consul and Infrastructure Services

Host TARGET-02 has the broadest service exposure in the collected results.

The following infrastructure-related services were identified:

- TCP/8500 — Consul Agent
- TCP/9000 — MinIO
- TCP/9001 — MinIO Console

Additional ports on the same host include 8301, 8502, 8503, and 8600, but their services were not conclusively identified.

The combination of Consul and MinIO indicates that this host may provide infrastructure or platform-level functionality in addition to application services.

5.5 MinIO

MinIO was identified on TARGET-02:

- TCP/9000 — MinIO (object-storage service)
- TCP/9001 — MinIO Console (management console)

Aggregated Findings & Service Mapping Report DEV-355 (Sanitized)

Because management interfaces can provide administrative capabilities, their intended accessibility should be confirmed as part of normal infrastructure review.

5.6 Redis

Redis was identified on two hosts:

Target ID	Port	Service
TARGET-06	9111	Redis
TARGET-07	9111	Redis

Both systems therefore share a similar service exposure pattern, alongside PostgreSQL and OpenResty services.

6. Port Distribution

Across the 15 scanned targets, the assessment identified:

- 15 target systems
- 45 open TCP port instances
- 19 distinct TCP port numbers
- TCP/22 present on all 15 targets

The distinct observed ports were:

Port	Observed Purpose / Service
22	SSH
53	TCP-wrapped service
80	HTTP / OpenResty / nginx
443	HTTPS / SSL
7212	PostgreSQL
7213	Unidentified
9111	Redis
9112	Go HTTP service
9180	OpenResty HTTP
54321	MariaDB
4646	HTTP / Go service
8301	Unidentified
8500	Consul Agent
8502	Unidentified
8503	SSL-related service
8600	TCP-wrapped service
9000	MinIO
9001	MinIO Console
8443	HTTPS-alt / unidentified implementation

The distribution shows that TCP/22 is the dominant common exposure, while the remaining ports are concentrated on a smaller number of systems.

7. Unidentified and Inconclusive Services

Not every open port could be mapped to a definitive service through the available scan results. These entries have been retained rather than being assigned a service based on assumptions.

The main unresolved ports are:

Target ID	Port	Scan Result
TARGET-02	8301	Unidentified
TARGET-02	8502	Unidentified
TARGET-02	8503	SSL-related / exact service not confirmed
TARGET-02	8600	TCP-wrapped
TARGET-06	7213	Unidentified
TARGET-07	7213	Unidentified

TARGET-12	8443	HTTPS-alt / implementation not confirmed
TARGET-15	443	HTTPS/SSL / implementation not confirmed

These results should not be interpreted as missing scan data. They indicate that the available service-detection evidence was insufficient to make a reliable service identification.

8. Key Aggregated Findings

The consolidated results highlight several important characteristics of the scanned environment:

1. SSH is consistently exposed

All 15 targets have TCP/22 open, making SSH the common administrative service across the scanned infrastructure.

2. Service exposure varies significantly between hosts

Most targets expose only SSH, while a smaller number of systems expose multiple application, database, and infrastructure services.

3. Multiple database services use non-standard ports

MariaDB, PostgreSQL, and Redis were identified on ports 54321, 7212, and 9111 respectively. This is useful for asset and service inventory because standard-port assumptions alone would not provide a complete picture.

4. Infrastructure and management services are concentrated on specific hosts

The scan identified Consul, MinIO, and the MinIO Console on TARGET-02. These services represent infrastructure-level functionality rather than simple application endpoints.

5. Several services require additional validation

Ports such as 7213, 8301, 8502, 8503, and 8443 could not be mapped conclusively. These should be validated before the inventory is treated as final.

9. Data Quality and Mapping Notes

The consolidated inventory in this report is based directly on the system-level scan and service-detection results.

All real IP addresses have been replaced with anonymous TARGET-01 to TARGET-15 labels for public sharing. The TARGET identifier is used as the primary asset identifier throughout the consolidated findings.

This approach maintains the structure and value of the original findings while ensuring no sensitive infrastructure identifiers are exposed.

10. Recommended Follow-up

The following actions are recommended to improve the completeness and operational value of the service inventory:

Area	Recommended Action
Unidentified services	Validate ports 7213, 8301, 8502, 8503 and 8443 with additional controlled service enumeration or the responsible service owners.
Database exposure	Confirm that MariaDB, PostgreSQL, and Redis services are intentionally exposed and restricted to their required network sources.
Management interfaces	Verify that Consul and the MinIO Console are accessible only to authorized users or trusted networks.
SSH exposure	Review whether public SSH access is required and confirm that appropriate authentication and access-control mechanisms are enforced.
Service inventory	Maintain the TARGET-to-port-to-service mapping as the baseline inventory for subsequent infrastructure or security reviews.

These recommendations are intended as validation and hardening follow-up. The presence of an open port alone should not be treated as proof of a vulnerability.

11. Conclusion

The consolidated scan results provide a structured view of the services exposed across the 15 assessed systems. The assessment identified 45 open TCP port instances across 19 distinct ports, with SSH being the only service consistently present across every target.

The remaining service exposure is concentrated across a smaller number of hosts and includes OpenResty, nginx, MariaDB, PostgreSQL, Redis, Consul, MinIO, and MinIO Console, along with several services that require further identification.