

EAPI Dog API Specification

Overview

EAPI Dog API serves as a middleware/pass-through API that integrates with the Dog System API. The EAPI standardizes authentication, request handling, and response formatting for consumers.

Environment URLs

Environment	URL
UAT	https://uat.dogapi-eapi.my-sample-api.com.ph
PROD	https://dogapi-eapi.my-sample-api.com.ph

Authentication

Generate Access Token

Endpoint

POST /dogapi/auth/oauth2/token

Description

Generates an OAuth2 Bearer Token required to access all Dog EAPI endpoints.

Request Headers

Field Name	Value
Content-Type	application/x-www-form-urlencoded

Request Body

Field Name	Sample Value
grant_type	client_credentials
scope	read
client_id	aabbccddeeff112233445566
client_secret	dogapisecret123456

Sample cURL Request

```
curl --location '{{BASE_URL}}/dogapi/auth/oauth2/token' </span>
--header 'Content-Type: application/x-www-form-urlencoded' </span>
--data-urlencode 'grant_type=client_credentials' </span>
--data-urlencode 'scope=read' </span>
--data-urlencode 'client_id=aabbccddeeff112233445566' </span>
--data-urlencode 'client_secret=dogapisecret123456'
```

Response Body

Field Name	Sample Value
token_type	Bearer
access_token	A1BkNeRtgEaCfGe0192
expires_in	1800
consented_on	1739850557
scope	read

Sample Response

```
{
  /* INSERT SAMPLE JSON RESPONSE */
}
```

Common Request Headers

All Dog EAPI endpoints require the following header:

Field Name	Description	Required	Sample
Authorization	Bearer access token from authentication endpoint	Yes	Bearer A1BkNeRtgEaCfGe0192

Example

Authorization: Bearer A1BkNeRtgEaCfGe0192

Standard Response Structure

All successful responses follow the structure below:

```
{  
  "data": {},  
  "message": null,  
  "status": "SUCCESS"  
}
```

Response Fields

Field	Description
data	Requested data payload
message	Additional information or error details
status	SUCCESS or FAILED

APIs

Yes. Based on your example, the response examples should use the **actual EAPI response wrapper** (data, message, status) instead of generic placeholders. Below is the revised API section using your provided JSON structures.

1. Retrieve Random Dog Image

Description

Retrieves a random dog image.

Method

GET

Endpoint

/dogs/random

Sample Request

GET {{BASE_URL}}/dogs/random

Authorization: Bearer {{access_token}}

Sample Response

```
{  
  "data": "https://images.dog.ceo/breeds/sheepdog-english/n02105641_13952.jpg",  
  "message": null,  
  "status": "SUCCESS"  
}
```

Response Fields

Field	Type	Description
data	String	Random dog image URL
message	String / Null	Additional information
status	String	SUCCESS or FAILED

2. Retrieve Random Image by Breed

Description

Retrieves a random image from the specified breed.

Method

GET

Endpoint

/dogs/{breed}

Path Parameters

Parameter	Required	Description	Example
breed	Yes	Dog breed	hound

Sample Request

GET {{BASE_URL}}/dogs/hound

Authorization: Bearer {{access_token}}

Sample Response

```
{
  "data": "https://images.dog.ceo/breeds/hound-afghan/n02088094_1003.jpg",
  "message": null,
  "status": "SUCCESS"
}
```

Response Fields

Field	Type	Description
data	String	Random image URL for specified breed
message	String / Null	Additional information
status	String	SUCCESS or FAILED

3. Retrieve Random Image by Breed and Sub-Breed

Description

Retrieves a random image based on the specified breed and sub-breed.

Method

GET

Endpoint

/dogs/{breed}/{subBreed}

Path Parameters

Parameter	Required	Description	Example
breed	Yes	Dog breed	bulldog
subBreed	Yes	Dog sub-breed	english

Sample Request

GET {{BASE_URL}}/dogs/bulldog/english

Authorization: Bearer {{access_token}}

Sample Response

```
{
  "data": "https://images.dog.ceo/breeds/bulldog-english/jager-1.jpg",
  "message": null,
  "status": "SUCCESS"
}
```

Response Fields

Field	Type	Description
data	String	Random image URL
message	String / Null	Additional information
status	String	SUCCESS or FAILED

4. Retrieve Available Breeds and Sub-Breeds

Description

Retrieves all available breeds and their associated sub-breeds.

Method

GET

Endpoint

/breeds

Sample Request

GET {{BASE_URL}}/breeds

Authorization: Bearer {{access_token}}

Sample Response

```
{
  "data": {
    "breeds": {
      "affenpinscher": [],
      "african": [
        "wild"
      ],
      "airedale": [],
      "akita": [],
```

```
"appenzeller": [],  
"australian": [  
  "kelpie",  
  "shepherd"  
],  
"bakharwal": [  
  "indian"  
]  
}  
,  
"message": null,  
"status": "SUCCESS"  
}
```

Response Fields

Field	Type	Description
data.breeds	Object	Collection of breeds and sub-breeds
message	String / Null	Additional information
status	String	SUCCESS or FAILED

Standard Error Response

All endpoints return errors using the same response structure.

Example: Invalid Breed

```
{  
  "data": null,  
  "message": "Breed not found",  
  "status": "FAILED"  
}
```

Example: Invalid Sub-Breed

```
{
```



```
"data": null,  
"message": "Sub-breed not found",  
"status": "FAILED"  
}
```

Example: Unauthorized Request

```
{  
  "data": null,  
  "message": "Unauthorized access",  
  "status": "FAILED"  
}  
``
```

EAPI to Source API Mapping

EAPI Endpoint	Source Dog API Endpoint
GET /dogs/random	GET /breeds/image/random
GET /dogs/{breed}	GET /breed/{breed}/images/random
GET /dogs/{breed}/{subBreed}	GET /breed/{breed}/{subBreed}/images/random
GET /breeds	GET /breeds/list/all

This format now follows the exact documentation style and response structure from your sample EAPI specifications.

Version History

Version	Date	Description
1.0	[28-SEP-2026]	Initial Draft