

Kuwaiba Open Inventory User's Manual

Neotropic SAS

27.07.2016

System Version **1.0**

Visit **kuwaiba.org** for documentation, latest updates and upcoming events

Contents

Document History	
License	
Introduction	1
Connection to the Server	2
Data Model Manager	4
Containment Manager	7
Navigation Tree	8
Relationship and Special Children Explorer	10
List Type Manager	11
Queries	13
Graphical Query Editor	13
Exporting results	20
Saving and restoring queries	21
Pools Manager	23
Default and Rack Views	26
Physical View	26
Rack View	27
Physical Connections	29
Example 1	29
Example 2	32
Audit Trail	40
Topology Designer	42
Managing Software assets	44
Service Manager	47
Contract Manager	50
Task Manager	52
SDH Networks	55
IP Address Manager	66
User and Group Management	70
Bulk import	71
Load Objects	71
Load List Types	71
Interface	72

Document History

Date	Comments
September 28th 2010	First issue shipped with version 0.1.1
November 26th 2010	Update to cover the new features in 0.2
December 26th 2010	Update to cover the new features in 0.2.1
January 18 th 2001	Changes in version 0.3 alpha
February 3 rd 2011	Changes in version 0.3 beta
March 13 th 2011	Changes in version 0.3 beta 2
May 16th 2011	Changes in version 0.3 stable (the clear button in the graphical query editor)
May 23rd 2012	Adapted to version 0.4
October 23rd 2012	Adapted to version 0.5
June 4 th 2013	Added documentation for Pools module
June 12 th 2013	Added documentation for Data model Manager module and some other minor changes
January 19 th 2015	Adapted manual for version 0.7
November 6 th 2015	Added documentation about bulk upload, software asset management and detailed physical connections
July 27th 2016	Adapted to Kuwaiba version 1.0. LaTeX is now used instead of LibreOffice to create the documentation.

License



This document is published under the terms of a license Creative Commons by-nc-sa. You can find details about it at <http://creativecommons.org/licenses/by-nc-sa/2.0/>



Kuwaiba Server and Client are licensed under EPL v1 and GPL v2. You can find the whole text of this licenses at <http://www.eclipse.org/legal/epl-v10.html>
<http://www.gnu.org/licenses/old-licenses/gpl-2.0.html>

Disclaimer

- This document is provided “as is”, with no warranty at all. Install the software and follow the instructions included at your own risk.
- Kuwaiba uses third-party components with compatible open source licenses (LGPL, BSD-like, etc). You can find a complete list at the project’s web page.

Introduction

Kuwaiba sees an inventory system as a living entity, not growing only in terms of size, but also in structure and intelligence. The main reason is that business requirements change constantly and therefore, the application must be ready to respond to new scenarios. One of the key concepts that can help you unlock the potential of Kuwaiba is the **data model**. It provides a simplified representation of the network and the business from an operational point of view. It can be seen as the skeleton that supports the application, but a skeleton from which you can add, remove and change elements as you go. Later in this document you will be able to see what tools you can use to manage it. For now, just keep in mind that the better you design your data model and the more you get to know it, the more you will take advantage of the application.

Having said that, you will find four types of resources in a typical data model:

- **Physical:** Equipment, pipes, cables, fiber optics, facilities, parts and in general every physical asset from a port to a building.
- **Logical:** These are all the resources related to non-tangible technology assets. In this group fits timeslots, virtual circuits, VLANs, disk space, available bandwidth, etc.
- **Other Non-physical:** mostly software-related assets, such as licenses or virtual machines.
- **Administrative:** These are all those related to administrative tasks, human resources or commercial management. Customers, their services, SLAs (and related parameters like availability or throughput), sales and technical staff assigned to those services, vendors and states belong to this category.

The Kuwaiba desktop client is a set of views (trees, topologies, editors) that allow to put together these elements based on business rules and user-defined models. Kuwaiba extends the concept of **CMDDB** (Configuration Management Database, a place where you store objects that can hold configuration information or be subject to configuration themselves -so called Configuration Items- and their relationships) and enables you to perform network design tasks, support capacity management and provisioning workflows and assist field and customer service teams to improve response times.

Kuwaiba helps you model your network according to your needs, no matter if you're an ISP, a carrier or just a guy with a large (or small!) IT infrastructure to manage. It's open source, under active development and new models are added every release. You can contribute to the project by providing technical insight on a particular technology, testing, translating or just sending your feedback through forums¹ and mailing lists².

¹Forums <https://sourceforge.net/p/kuwaiba/discussion/>

²mailing lists <https://sourceforge.net/p/kuwaiba/mailman/>

Connection to the Server

The first thing you will see when opening the client is the window in the figure 1. The default user and password are **admin/kuwaiba**.




Figure 1: Authentication window

The default connection settings should be enough if the server is running on the same computer the client is. If that's not the case, open the Connection Settings window (figure 2).




Figure 2: Connection Settings window

- **Server Address** Refers to the server IP address or canonical name.
- **Server Port** is the port Glassfish (the application server) is listening to.
- **WSDL Path** is the path within the application server the web service interface definition can be found. Usually this value should remain unchanged.
- Protocol is the transport protocol to be used. By default is HTTP, but is highly advisable to request your administrator to setup a secure connection, otherwise your credentials will be transmitted in plain text over the network.

Except for the password, the last successful settings will be saved upon clicking OK.

Important

If you are unsure if the server is reachable from your location, open a browser and type the address: **http://[server_address]:[server_port]/[wsdl_location]**

You should see a large XML document.

Troubleshooting

- For a **Can't contact backend** error, check the Administrator's Manual Troubleshooting section.

- If you get a **Connection refused** error, check the connection settings and verify that the server is reachable and there isn't a firewall blocking the traffic to it.

Once you are logged in, you will see only the dashboard page and a toolbar (figure 3).



Figure 3: Main toolbar

The toolbar contains the most frequently used tools. Here is an overview of what can you do with them:















	Search objects with the Query Manager
	Refresh the current view
	Refresh local cache
	Physical/Rack View of an object
	Create automation tasks (beta version)
	See the changes made to inventory and application objects
	Manage users and groups
	Change the data model
	Manage how objects can be created inside others
	Create new list types
	Freely design network topologies
	Main tree used to explore physical assets
	Create and manage objects that don't fit in the navigation tree
	Manage client, services and resources associated to them

Table 1: Toolbar items

Data Model Manager

One of the key features of Kuwaiba is that it is completely object-oriented³. It means that every business (Router, City, Port) and application (users, types) element is represented by an **Object** in the application and these objects are in turn product of an reality abstraction called **Class**. Likewise, every attribute is a **Field** in a class. The set of classes, attributes and relationships between them is called data model. There's a default data model, but you can customize it depending on your needs by adding, removing and modifying classes. To achieve this, use the Data Model Manager module (figure 4). The data model is represented as a tree because it's a hierarchical




Figure 4: Part of the data model tree

structure. Technically, it's a class hierarchy⁴. The top of the hierarchy (**InventoryObject**) is the most general type of element in the data model and its subclasses represent all the possible elements that will be treated as inventory assets. As you dig deeper into the tree, the classes become more and more specialized and each level inherits the attributes of the parent classes. This kind of structure has two purposes: First, it helps you to organize your classes based on what characteristics they have in common. Secondly, as you will see later in this manual, you can apply operations over top level classes, and they will be propagated to all subclasses. Another root of the data model tree is **GenericObjectList**, and its subclasses are all possible list types (see more details on the subject in the chapter **List Type Manager**).

Important

The **Properties** window allows you to modify the attributes of a selected object in a tree, list or view. If not already open, it's available from the Windows → Properties menu.

The properties of a class can be edited by using the **Properties** window, selecting the class from the tree (see figure 5). The property sheet is divided in two sections:

- **General:** Contains the intrinsic properties of the class: **name** (can contain only letters and numbers with no special characters or blank spaces). The **display name** of the class, that's how it will be displayed everywhere else (useful for internationalization purposes, for example) and can contain any kind of UTF-8 character. A **description** (useful to document the data model). If the class is **abstract** (abstract classes cannot be instantiated, they're only used to give consistency to the data model). The attribute **countable** is not used currently,

³Object-oriented Programming https://en.wikipedia.org/wiki/Object-oriented_programming

⁴Class Hierarchy https://en.wikipedia.org/wiki/Class_hierarchy




Figure 5: Properties of class **Router**

but it should be used to mark classes whose instances can have graphical representations, but they're not really part of the inventory, such as **Slots**. **In Design Stage** is just a way to mark a class as part of an ongoing data model intervention, and thus, classes with that attribute set to true can not be instantiated. **Color** is the color of the default square icon used to display the object in a tree or view. This icon will be used as long as the **Small Icon** attribute is null. **Small Icon** is the icon that will be used in trees and its size can't exceed 16x16 pixels. **Icon** is the icon used in views, and has a maximum size of 32x32 pixels.

Important

- All user-created classes are set In Design Stage = **true** by default. You won't be able to create objects of these classes until you set it to **false**.
- As a convention, all abstract classes have the prefix **Generic**. Note that a few core classes (like **InventoryObject** or **true**) are abstract are the exception to this rule. You, however, should try to follow this convention as much as possible.

- The second section contains the class fields (attributes). In the figure5, class Router has six attributes: name, state, conditions, vendor, serialNumber and creationDate. Click the button next to the attribute name to customize it (see figure 6).




Figure 6: Properties of attribute **name** in class **Router**

In this window, you can modify the attribute's name, display name, description, type (the drop-down list will show you primitive types -String, Integer, Float, Long, etc- and all available non-abstract list types). When you change an attribute's type, all existing instances will be modified to reflect the change, which means that the values of the modified attribute will be converted to the new type if possible (say, from Integers to Strings). If the conversion is not possible, the new value will be set to null. You can also manage the attribute visibility. Attributes marked as "Administrative" will be shown in a separate tab in the object's property sheet. Sometimes, there are attributes that are used only for administrative purposes and might confuse the end user if mixed with the regular attributes. Finally, you can choose what attributes shouldn't be transferred from one object to another in a copy operation.

Important

- You may lose information when changing an attribute's type. make sure the conversion to the new type is possible before you do it.
- Although there's a Cancel button at the bottom of the window, it does not really work. When you perform a change, it's saved immediately.

You can also create and delete classes and attributes by right-clicking a class node (see figure 7) New subclasses inherit the parent class attributes. Classes with instances or subclasses can not




Figure 7: Class **Router** context menu

be deleted (this is a feature to avoid unintended loss of data). Also, attribute **name** can not be deleted.

Important It's highly recommended **NOT** to rename abstract core classes, as some of them are used internally to support many features and renaming them may turn the system unstable.

Containment Manager

Another key concept in Kuwaiba is containment. It consists of the ability to define what kind of objects can be created within others. For example, a **Country** can be inside a **Continent**, but can't be inside a **Rack**. A **Port** is usually within a **Board**, and not inside a **City**. These business rules can be defined using the Containment Manager.





Figure 8: Containment Manager main window. Zoom in the image to see the details

The main window is divided in two panels (see figure 8, zoom in the image to see the details). The one on the left is a tree that holds all the classes plus the **Navigation Tree Root**. The children of the left-side tree node are the possible classes that can be contained. In the figure 8 there are five nodes expanded: **City**, that has one node inside: **Building**. That means that below a given city, you will only be able to add **Building** objects. Likewise, inside a **Continent** you can only create instances of **Country**, and inside those instances, only objects of class **City**. Under the root of the Navigation Tree, only instances of **Continent** are to be created. Finally, only **OpticalPorts** are supported under **DWDMBoards**. If for your operation Continents are not relevant, or if your routers do not have boards, but only ports, simplify the hierarchy as much as you want to meet your needs. To remove a possible children class, just right-click on it and select “Remove”, and instances from that class will no longer be available to be added under the parent class, though the objects created already will remain linked to the respective parent objects.

Important

- To avoid adding one by one many classes to a parent, you can use the flexibility of the data model as a hierarchical structure. For example, a **Rack** may contain within many types of equipment (routers, DDFs, switches, battery banks, etc). Instead of adding one by one each of these classes, you can add a common super class and all of them will be added automatically. For this example a common super class for most of those classes could be **GenericCommunicationsElement**.
- To search for a particular class, just select any node in the desired side of the panel and type the first letters of the class name. If there are many occurrences of the term, jump from one to another using the F3 key.
- The changes are applied immediately, however, if you happen to not see them reflected, press the Refresh Cache button  in the main toolbar (see table 1).

Navigation Tree

This module presents in a tree fashion the physical objects of your inventory organized according to the containment hierarchy defined with the tool described in the previous chapter (see **Containment Manager**). Just like the Data Model Manager, the Properties window will display




Figure 9: Navigation tree showing objects with default and user-defined icons

the attributes of the object selected in the Navigation Tree. These attributes match the visible attributes defined in the **Containment Manager**. Every change is automatically committed to




Figure 10: Properties of a selected **Rack** object

the database once you hit the Enter key. When editing dates, you need to select another attribute to commit the changes instead of pressing Enter. In the **Containment Manager** you can also configure what labels will be displayed instead of the actual names of the attributes and the help string in the lowest part of the window.

Every node has a set of actions, some will be active for all objects, some depend on the type of element that is selected. In the figure 11 you can see the actions enabled for a **Rack** object.

- **New Object:** The list of object types that can be contained for the selected element type according to the configured Containment Hierarchy. In this case, a **Rack** can only contain **Routers**.
- **Copy:** A plain copy operation.
- **Paste:** A plain paste operation. You can only paste objects where it is allowed according to the configured Containment Hierarchy.
- **Update:** Update the node information. Useful when a changed has made to the object from a external source (e.g. another user) or if you create a new list type affecting one of the




Figure 11: Properties of a selected **Rack** object

attributes of the selected element. In this case, if you, for example, create an instance of **EquipmentVendor** (this will add a new entry to the **vendor** attribute list)

- **Delete:** Deletes the object. This will fail if the object has an incoming relationship, for example, a **Port** connected to a cable.
- **Reports:** The reports associated with this class. In this case, **Rack** has a report called **Rack Usage**. If no reports are associated, the option will appear grayed out.
- **Relate to service:** All inventory objects can be associated to an existing service. See more details in the chapter Service Manager.
- **Release from Service:** Removes the association between an object(resource) and a service. If the object is not related to any service, this option will appear grayed out.
- **Audit Trail:** This will display all the audit trail entries for the selected object, that is, all the changes made to it.
- **Open an Explorer from this Node:** Opens a navigation tree whose root node will be the selected object. Useful when you want to explore an object with many containment levels below.
- **Show Object Id:** Shows the database id of the selected object. Useful for troubleshooting purposes. It will also show the object's complete containment structure.




Figure 12: Object id action on the selected **Rack** object

Important

- Remember that you can always open the Properties window by selecting the main menu option Windows → Properties.
- You can change the name of an object in-line by pressing F2 on a selected node.

Relationship and Special Children Explorer

Apart from the main navigation tree, there are also two explorers that are very useful to navigate through domain-specific models. Both explorers are located in the Tools → Navigation menu.

- **Relationship Explorer:** Allows to see the special relationships of the selected object. When an object makes part of a domain-specific model (SDH, Physical Connections, MPLS, Software Licensing, etc) there are special bounds to other objects called **relationships** they have names documented on model-basis, and they can be seen using this explorer. In the figure 13, it is depicted an **OpticalPort** with two relationships, one called **endpointA** used in the Physical Connections model and it indicates that this port is the endpoint to a physical connection, probably a fiber optic. It also has a relationship called **uses**, which makes part of the Service management model. It indicates that the service called PDH Service-01 uses that port as a resource.




Figure 13: Special relationships of the selected **OpticalPort** object

- **Special Children Explorer:** The special children are children as in the containment hierarchy concept, but used in domain-specific models, which gives them particular behavior depending on the situation (that is, they can't be handled as simple objects in the navigation tree, because, for example, deleting them may require to perform other tasks but just removing the object from the database as they make part of a complex workflow). This is the case of the cables inside a conduit connecting two buildings. You can find more details about this scenario in the chapter **Physical Connections**.




Figure 14: Fibers inside a container between two buildings

List Type Manager

Most of the attributes are primitive types (String, Integer, Booleans, etc), however, there are some more complex that point to another object in the database. This is the case of attributes such as *vendor*, which points to an object holding the information about the vendor of that equipment (support lines, account manager, etc) or *state*, that refers to the current operational state of the equipment (Working, Not Working, Stored, etc) and the state itself is an object, because it may hold information about what's the next allowed states, for example. Many objects in the database will have the same *vendor*, and many other will have the same *state*. In short, list types are those kind of attributes that point to an element in a limited set of objects. In terms of relational databases, you can see it as a many-to-one kind of relationships. To manage the existing list types and its instances, use the **Data Model Manager** and the **List Type Manager**.

To add new list types, add a subclass under GenericObjectList directly or any of its utility sub-classes. List types are like any other class, you can customize them as needed. To create list type




Figure 15: Custom list type

items, use the button  or the menu option Tools → List Type Manager. This module consists of a simple navigation tree similar to the one seen in the past chapter.





Figure 16: Custom list type items

By right-clicking and choosing *New* on a selected list type, you can create new items. The details for every item can be edited using the standard Properties Window as seen in the past chapter.

Important

If the changes are not immediately reflected when editing an object, use the Refresh Cache button  and update the object (Right-click the object node and select the option *Update*).

In the figure 17 you can see the properties of an object of class **Router** modified to have an attribute called *myOwnAttribute* of type **MyOwnListType**.




Figure 17: Object of class **Router** with a custom listy type attribute

Queries

Graphical Query Editor


The query editor let you make a search with a graphical interface, based on nodes to represent the search criteria and connections to express the relationships. Once selected, clicking in the icon  you will get a blank canvas with a toolbar on top with the following elements:



Figure 18: Graphical query editor general tool bar

The toolbar contains the most frequently used tools. Here is an overview of what can you do with them:











	Select the element class you want to search for.
	Open a previously saved query
	Save the current query. The queries are stored in the database using an XML format
	Deletes a saved query
	Cleans the current query
	Edit details about the current query (name, description and owner)
	Organize the nodes automatically
	Executes the current query
	Logical connector used to chain the query predicates, by default AND
	Max number of results per page, default 10, only integer values are allowed

Table 2: Query Toolbar items

When you select a class from the drop-down box, a graphical representation of it will be placed on the canvas, in the figure 19 the class Router was selected, and the corresponding node is created. You can search for a wider range of elements if you select an abstract class (often called GenericSomething). In the example above will search for all Routers in the database, but if you choose GenericPhysicalNode it will search for all physical nodes, this is, all objects that can be connected using a container (see Chapter **Physical Connections** for more information about containers). That includes: buildings, rooms, floors, towers, shelters and facilities. Note that the root class node is colored green.





Figure 19: Node added after selecting a element class

Important

- If you want to see all objects in the database (at least all relevant to the inventory) search for **InventoryObject**, which is the root of all classes related to the inventory. To see the complete hierarchy see related chapter **Data Model Manager**

Back to the original example, if you just leave the router without modifications and execute the query , it will search for all routers available in the database and it will show only a column with the object's display name.




Figure 20: Query results for all the routers

The figure 20 is shown in a new tab and also has a tool bar with the following buttons:





	Export the results to popular formats like CSV, XML
	Previous page
	Next page
	Show all results

Table 3: Query results toolbar items

Now, if we want to see more fields related to the found elements, we should use the "field visibility icons". They're those eyes you can see along with the attributes names. By default none of them are selected, which means that no additional fields will be shown in the result list but the objects themselves. Think of them like the parts of a conventional SQL sentence that follows the SELECT clause: **SELECT** **creationDate**, **serialNumber** **FROM** **Router**, you can obtain a query like this pushing the toggle buttons with the eyes on it beside **serialNumber** and **creationDate** as you can see in the figure 21





Figure 21: creationDate and serialNumber to be shown in the result list

When selected, the visibility icon turns into an eye crossed by a red line. If you don't want this attribute to be shown in the result list, press it again. This is what you will see when you execute the query:



	serialNumber	name	name
ASR1006 Dakar [Router]	01C00C125987	Cisco	Working

Figure 22: Result set showing some fields

Now you may be wondering why the attributes **vendor**, **conditions** and **state** have their visibility icons disabled. That's because they're list type attributes (See for details about list type

attributes). Making again a comparison SQL, these attributes are related to other *tables* (other classes, actually). You have two ways to use these list type attributes as criteria: the first is just selecting the attribute's checkbox and choosing from a list the value that you'd like to use:




Figure 23: Using a list type attribute as filter

Or you can pick manually what fields belonging to the relationship must be included in the result set. To do this, you first have to toggle the simple class node filter (in our example labeled as **Vendor [Filter]**) to a detailed view. You can do by right-clicking on the node's header and choosing the option **Toggle Simple/Detailed view**:




Figure 24: Changing the detail level on a class filter

The result is a node similar to the root one, but colored light orange

You can toggle the node to the original compress view by right-clicking on node's header and choosing the option **Toggle Simple/Detailed view** again.




Figure 25: Expanded class node filter

Example

- We want to search for all routers and we want to see the fields creation date, serial number, vendor and operational state. That would be:
 1. Enabling the visibility icon for the attribute **creationDate**
 2. Checking the checkbox in the attributes **vendor** and state and expanding the resulting nodes (we'll talk about the checkbox later in this chapter)
 3. Enabling the visibility icon for the attribute **name** in both newly spawned nodes.

Let's see the figure 26




Figure 26: Simple query showing three fields from different classes

Resulting in a set like this:

	name	serialNumber	name	name
ASR1006 Dakar [Router]	ASR1006 Dakar	01C00C125987	Cisco	Working
ASR1006 Lisboa [Router]	ASR1006 Lisboa	01C00C190025	Callix	Working

Figure 27: Simple query showing three fields from different classes

Important

The operational states and vendors were created using the List Manager (under Operational-State and Vendor, respectively) and their properties set in the Properties window.

The checkboxes are used to construct the query predicates. Every time you select one of them, a new node is spawned. If the attribute is a basic one (String, Integer, Float, Boolean or Date), you will get a node like these (otherwise you will get the class nodes seen above):

A dialog box titled 'String (Filter)'. It contains a dropdown menu with the word 'EQUAL' selected. Below the dropdown, there is a text input field. The dropdown menu is open, showing the options 'EQUAL' and 'LIKE'.

Figure 28: Filter for String values

Example 2:




Figure 29: Filter for Numeric values




Figure 30: Filter for Date values

- We're going to search for Routers whose **name** contains the string *AS* and the operational **state** is equal to *Working* and have *Cisco* as **vendor**. The fields to be shown must be **creationDate** and **operationalState**. Note that the result limit is set to 1 per page. The query would look like this:







Figure 31: Complex query using an AND logical connector


The condition **Equal to** is case sensitive, while **like** it is not. If you hit the “Next Page” button  you will get the second page of result if there is one and so on, The “Show all” button  will retrieve the full list of results.

Graphical Query Builder x Query Results x			
	serialNumber	name	name
ASR1006 Dakar [Router]	01C00C125987	Cisco	Working


Figure 32: Result set for the complex query

Exporting results

You can export the results in four formats: CSV, XML, Microsoft Word (DOC) and Open Document Text (ODT). So far is only possible to export to CSV and XML. This is done by pressing the Export icon , which will open a window to choose the location of the output file and the format:



Export to ...


Format **CSV - Plain text** 


Range **All**

OK Cancel

Figure 33: Results export options

Export to contains the file destination (once you choose a directory with the file chooser, a random name will be generated, but you can change it as you wish). Note that writing file the extension is not mandatory, since it will detect the type and append the extension before to save the file.

Format to let's you choose the output format. The configure button  lets you set some particular options regarding to the selected format. Currently only CSV has advanced options:



Export Settings x

Separator **Comma (,)**

- Comma (,)
- Tab
- Space
- Pipe (|)
- Tilde (~)

OK Cancel

Figure 34: CSV filter settings

There you can choose the separator character between fields. The available options are: Comma(,), Tab (), Space (), Pipe (—) and Tilde ().

Finally **Range** is used to specify whether whole results should be exported or only the current page.

Note: The XML structure used to export the results can be checked in kuwaiba's wiki⁵.

⁵kuwaiba queries in xml format <http://neotropic.co/kuwaiba/wiki/index.php?title=XML'Documents##To'Save'Queries/>

Saving and restoring queries

The queries can be saved as public or private. It's probable that someone wants to execute the same query on a regular basis and if that's the case for many users, he/she would want to let other users to use the such query. After you design a query, you can save it and this small window will prompt for some basic information:






Figure 35: Setting the query metadata before to save it

Name is the query name. *Description* is the query description. The last check box lets you to make the current query public. By default, the query is private, so you don't pollute the list of available queries for the rest of the users, you can change these settings anytime using the configure button . To open a query, just use the open button , then you will be asked if you want to see only your queries or both your queries and the public ones: *clicking in Cancel will show you both, clicking in Ok will list only those owned by you*




Figure 36: Dialog to choose what queries should be listed

Now you just have to select the one you need and you're done!




Figure 37: list of available queries





Figure 38: list of available queries

Important Please note that when a query is saved the values used to filter won't be saved, since the filter nodes are used as open parameters. For example: in figure 38, the value *Manchester* won't be saved anywhere. Just the structure and the condition (**like**, in this case). The blue box is a parameter. It's supposed that you will fill it with the value you need depending on what you're looking for.

Note 1: Expanding a list type and not selecting anything from it has the same effect as selecting the value **None (null)** in the compact view of the filter.

Note 2: Every time you run a query, a new window with the results will be opened, so don't forget to close those you don't need to save memory.

Pools Manager

This module enables you to manipulate pools of objects. Pools are entities where objects that can't be placed in the standard navigation tree are put. Most of them are logical or administrative elements such as VLANs or VPNs. You can see a pool like a bag where you put things you don't know where else to put. To use this module, click on the icon  in the main toolbar or go to the menu item Tools/Pools. It will open a navigation tree similar to the one used to browse through the containment hierarchy. The first time it will be empty, you can add new pools by right-clicking the root new and selecting "New Pool", as show in the figure below.




Figure 39: Creating a new pool

The dialog box will prompt you for the newly created pool name, its description and what kind of objects do you want to store inside. If you choose, say, "Router", it will let you store only instances of Router. On the other hand, if you choose an abstract class (this is any starting with "Generic" or one of the core classes like InventoryObject or ViewableObject) you will be able to place instances of any subclass of theirs.




Figure 40: Pool creation dialog

Once it's created, you can edit the pool attributes *name* and *description* in the property sheet.




Figure 41: Pool properties

You can add children to it. By right-clicking the corresponding node you can access to all actions associated to it.




Figure 42: Pools Actions

From that moment on, it behaves exactly like the Navigation Tree and you may have multiple containment levels as shown in the figure below in the figure 43.




Figure 43: Pools object properties

Default and Rack Views

Physical View

A view is a graphical representation of an object. There are many types of views, because an object has different perspectives, for example, a service object may have a view showing all the resources associated to it, a second view showing how all those resources are connected and a third showing statistics about such service. All instances (objects) of subclasses of **ViewableObject** have a Physical View that displays the direct children of the selected node. Most objects, except logical and administrative assets and a few physical ones such as slots and ports are subclasses of **ViewableObject**. To access this view, open the Physical View window (see Toolbar items) and select a node in the navigation tree.




Figure 44: Physical View of the selected **Country** object

In the Physical View, you can move and connect the nodes, add a background and export the view. It is particularly useful at Room and City levels, because it will allow you to see how the children elements are located geographically (e.g. buildings) or in an enclosed space (racks in a data center as seen in figure 45).
















Figure 45: Physical View of the selected **Room** object

The figure 46 shows all general purpose tools available in this window.



Figure 46: Physical View toolbar

	Add background
	Remove background
	Format text
	Add background
	Hide/show the labels under the nodes
	Save view
	Add background
	Select/Move tool (selected by default)
	Connect tool (See Physical Connections for more details on how to use it)
	Export to image file
	Refresh view
	View type. Currently, only the Physical (default) and Rack view are available (see Rack View for more details on the latter)

Rack View

This view works only with objects of class **Rack** or its subclasses. It shows how the elements contained within the selected object are organized, based on their positions and number of rack units used.




Figure 47: How to find the rack view in the toolbar

For this view to be correctly built, two conditions must be met:

- The rack must have its **rackUnits** attribute set to a valid integer value. This attribute stores the total number rack units supported by the rack. Typical values are 20, 28, 34, 40 or 45.




Figure 48: Error displayed when the rack does not have a valid value of rack units

- The attributes **rackUnits** and **position** must exist and set to valid values in the elements contained inside the rack. **rackUnits** in this case, makes reference to the number of rack units occupied by the contained element, while **position** is the start position of the contained element, 1-based, numbered from top to bottom. Your equipment vendor usually provides this value.




Figure 49: Attributes correctly set in a DDF contained inside a rack

Important

- The attribute names (**rackUnits**, **position**) are case sensitive and must be integers.
- Some elements you want to create inside a rack **might not** have those attributes by default, so you will need to create them using the Data Model Manager.

If all values are correct, the view should look like this:




Figure 50: Sample rack view

Physical Connections

The Physical Connections toolkit is tightly integrated to the Physical View module. With Kuwaiba you can create physical layer connections using cables, fiber optics or radio links very easily, navigate through the connections and inspect the resources in use.

Before presenting the tools provided by the application, let's first clarify and introduce some concepts. This module deals solely with L1 topologies. It's only about cables, ports, etc. The data model provides four types of entities to represent physical layer elements:

- **Connections:** These are all point-to-point physical links. In the current data model, there are three types of connections: **ElectricalLink** (for electrical connections like coaxial, twisted pairs and the like), **OpticalLink** (for fiber optics) and **RadioLink** (for radio links -Microwave links, mostly-).
- **Containers:** All objects that can be used to contain, wrap and protect connections (understanding *Connection* as defined above). There are two types of containers: **WireContainer** (used to contain all kind of cables -wires and fibers-, like pipes, conduits, ditches, etc) and **WirelessContainer** (used to contain radio channels or carriers).
- **Nodes:** These objects are endpoints to *Containers*. In the default data model you will find classes like: **Tower**, **Warehouse**, **Facility**, **Shelter**, **Building**, **Floor** and **Room**, but in general, any subclass of **GenericPhysicalNode** can be a so called *Node*. **Endpoints:** These objects are endpoints to *Connections*. In practice, they're always some kind of **Port** (in the data model context, this means all subclasses of **GenericPort**).

In summary, you can only connect *Nodes* using *Containers* and *Endpoints* using *Connections*. To create new connections, select in the **Navigation Tree** an element and try to connected the desired children using the Physical View. For example, if you want to connect two buildings, select the city which is the parent for both. Likewise, if you want to connect a router to an ODF, you probably will have to select the room or the rack they are located. In short, select the nearest common parent between the two elements you want to connect.

Important

You can also create power connections with this approach.







	Select the Connection tool
	Create a wire container
	Create a wireless container
	Create an electrical link
	Create an optical link
	Create a wireless link

Table 4: Connection tools

Let's put together all this concepts with some examples.

Example 1

In this example, we will create a direct connection between two routers in the same room, but in different racks using a CAT-5 patch as shown in the figure 51.




Figure 51: Connection diagram for example 1

Let's consider the layout in figure 52




Figure 52: Containment layout for example 1

1. Select the nearest common parent in the navigation tree (in this case the **Room** called Control Center), and using the select tool, change the default position of the nodes




Figure 53: Racks in the room

2. Using the **List Type Manager**, create a list type called *CAT-5* under **ElectricalLinkType**. Following a similar procedure, you can create the different types of electrical connections depending on your network (POTS, coaxial, etc). We will use this later.




Figure 54: Creating the link type

3. Activating the connection tool, click on one node and hold, dragging the mouse until you reach the second node. Make sure you also select the type of connection you want to create, in this case, an **ElectricalLink** (a patch cable).




Figure 55: Creating the connection

4. This will open a wizard where you should select the endpoints of the connection (the end ports)




Figure 56: Connection wizard, step 1

5. In the next step of the wizard, you have to fill in the basic information about the connection: its name and type. Use the type we just created in step 2.




Figure 57: Connection wizard, step 2

And that's it. Double-clicking the connection will add a control point to it. You can add as many as you want, and control its route. The Properties window will get updated accordingly if you select the link or a node.




Figure 58: Final result

Important

Don't forget to save the view using the icon  in the toolbar, so your positioning changes are stored.

Example 2

The second example is more complex. We will connect two buildings with a conduit that contains fibers. In each building there's a router and an ODF, one of the fiber pairs connecting the buildings, will be linking the two ODFs, and then, from the ODF, we'll patch our way the routers.




Figure 59: Connection diagram for example 2

We will use a similar containment layout for this example, just adding a couple ODFs.




Figure 60: Containment layout for example 2

1. First, we must make the initial arrangements. In this case, we will use a Google maps image as background for the city (the nearest common parent) and locate the buildings. We also select the connection tool and the type of connection, which will be a **WireContainer** this time.




Figure 61: Buildings in the city

2. Since this time we are creating a **WireContainer**, the list type for it must be created under **WireContainerType**. Using the List Type Manager, add this entry:



Figure 62: creating a connection type

3. Just like we did in the past example, let's start the connection wizard, but this time the endpoints will be the buildings instead of the ports (remember that we are creating a container here).




Figure 63: Connection wizard, step 1

- In the second step, we fill in the basic fields, but in addition to what we had seen already, it's also necessary to provide information about what's gonna be contained inside the **WireContainer** and how many of those elements are to be created. Since this example is about connecting fibers, we select **OpticalLink** in the field *Children type* and 20 in *Num of children* just for the sake of the example.

Physical Connections Wizard

Steps

1. Choose endpoints
2. **Edit connection settings**

Edit connection settings

Name:

Connection type:

Children type:

Num of children:

< Back Next > Finish Cancel Help

Figure 64: Connection wizard, step 2

- Using the Select tool, modify the route of the connection. Now the container has been created successfully.




Figure 65: Final result

- Once the container has been created, we can now connect a pair of fibers to each side's ODF back port (note the naming used for the ODF ports in the figure 60). To start a wizard to perform this operation, right-click the container and select the option *Connect links...*




Figure 66: Container's contextual menu

- This opens a window divided in three panels. The side panels let you choose what ports you want to connect to the fibers in the container. In this example, we will connect the first pair to the ports labeled as *Back* in the ODFs. You can select multiple ports and fibers and connect them at the same time (use the SHIFT key for multiple selection). Note that it's not necessary to connect both sides. Push the *Connect* button on the lower part of the central panel to finish the procedure.




Figure 67: Connecting links

Important

- In optical connections, Rx and Tx ports are treated as a single port and a pair of fibers, are actually represented as a single **OpticalLink**.

It's possible to explore the contents of a container and see to what fiber the ports are connected to using the explorers in the menu Tools → Navigation. In the figure 68 you will see the Special Children explorer when the container is selected in the view. In the figure 69, the relationship explorer shows the connections of one of the ports in the ODF when selected in the Navigation Tree.




Figure 68: Exploring the container's contents




Figure 69: Exploring the container's relationships




Figure 70: Optical patches between routers and ODFs

8. Now we will create an optical patch on each building between the routers and the 1-Front ports of their respective ODFs in a similar way we did in the **Example 1**.

Important

Remember to use an **OpticalLink**  instead of an **ElectricalLink** .

9. There's still one last step: The ports 1-Front and 1-Back in each ODF are not yet bridged. To do this, we just have to right-click any of the two ports on each ODF and select the option *Connect Mirror Port....* A mirror port is basically a direct connection between two ports. A cable is a separate object in Kuwaiba, a mirror connection is not even an object, is just a relationship between a port and another with the same parent (that is, a sibling). You can see it as a backplane connection.




Figure 71: Mirror connection menu

This will open a window where you can select what port do you want to be mirror of the selected one. Since 1-Front ports only have one sibling (1-Back), that's the only option available.




Figure 72: Mirror connection details

Once the port is mirrored, you can see a new relationship in the relationship explorer when selecting any of the ODF ports in the **Navigation Tree**.




Figure 73: Mirror connection relationship

To release a mirror port, select the option from the context port's context menu.




Figure 74: Release mirror connection menu option

A nice feature in Kuwaiba is the ability to see the path of a physical connection as long as there's continuity. In our example, there is continuity between the port in the router A (RTR-DMT-003) and the port in the Router B (RTR-DMT-004), that is, there are no active elements in between. To see the trace, right-click on any of the ports involved in the connection and select the option *Show physical path*. The figure 76 show the physical path between Router A's port and Router B's




Figure 75: Physical path menu option

port. The port in red is where the trace begins.




Figure 76: Physical path details

And pressing the button  you will get a graphical representation, easier to understand. The





Figure 77: Physical path graphical representation

Properties window will be updated as you select any of the blocks. This view can also be updated.


Audit Trail

Kuwaiba is capable of tracking the changes performed by the users in the database for audit purposes. These changes can be made to inventory objects (equipment, locations, etc) or application objects (pools, tasks, user properties). There are two types of events that are logged: **General events**, that is, those that are not related to any object in particular, like new logins or creation of application objects. **Object-related events**, like property changes or move operations.



Timestamp	Type	User	Property	Old ...	New value	Notes
Tue Jul 26 01:43:36 COT 2016	Update Application Object	admin	name		Cisco	1395
Tue Jul 26 01:44:40 COT 2016	Update Application Object	admin	name		Quest Manufacturing	1397
Tue Jul 26 01:47:55 COT 2016	Update Application Object	admin	name		Phasing Out	1403
Tue Jul 26 01:49:56 COT 2016	Update Application Object	admin	name		Data Center Level	1405
Tue Jul 26 23:40:46 COT 2016	Update Application Object	admin	name		CAT-5	1425
Wed Jul 27 01:16:30 COT 2016	Update Application Object	admin	name		Pipe	1506
Wed Jul 27 16:50:42 COT 2016	Update Application Object	admin	name		Huawei	1488
Wed Jul 27 16:51:05 COT 2016	Update Application Object	admin	name		My Own List Type 1	1490
Wed Jul 27 16:51:16 COT 2016	Update Application Object	admin	name		My Own List Type 2	1492
Wed Jul 27 00:53:04 COT 2016	View Update	admin	structure background			
Wed Jul 27 01:29:58 COT 2016	View Update	admin	structure background			
Wed Jul 27 01:31:51 COT 2016	View Update	admin	structure background			
Wed Jul 27 00:19:56 COT 2016	View Update	admin	structure			
Wed Jul 27 02:29:39 COT 2016	View Update	admin	structure			
Wed Jul 27 03:12:14 COT 2016	View Update	admin	structure			
Wed Jul 27 03:16:34 COT 2016	View Update	admin	structure			
Tue Jul 26 01:18:53 COT 2016	Create Inventory Object	admin				1373
Tue Jul 26 01:18:56 COT 2016	Create Inventory Object	admin				1375
Tue Jul 26 01:19:01 COT 2016	Create Inventory Object	admin				1377
Tue Jul 26 01:21:56 COT 2016	Create Inventory Object	admin				1383
Tue Jul 26 01:23:44 COT 2016	Create Inventory Object	admin				1386
Tue Jul 26 01:24:45 COT 2016	Create Inventory Object	admin				1389
Tue Jul 26 01:24:47 COT 2016	Create Inventory Object	admin				1391
Tue Jul 26 02:43:23 COT 2016	Session Closed	admin				Connected from 127.0.0.1
Tue Jul 26 23:04:38 COT 2016	Session Created	admin				Connected from 127.0.0.1
Tue Jul 26 23:05:39 COT 2016	Create Inventory Object	admin				1411
Tue Jul 26 23:05:42 COT 2016	Create Inventory Object	admin				1413
Tue Jul 26 23:07:19 COT 2016	Move object	admin				[1417] moved to object with id 1386 of class Room
Tue Jul 26 23:59:33 COT 2016	Create Inventory Object	admin				New connection of class ElectricalLink
Wed Jul 27 00:26:33 COT 2016	Move object	admin				[1431] moved to object with id 1383 of class Building
Wed Jul 27 00:27:59 COT 2016	Delete Inventory Object	admin				1 objects deleted
Wed Jul 27 00:28:08 COT 2016	Delete Inventory Object	admin				1 objects deleted
Wed Jul 27 00:28:22 COT 2016	Create Inventory Object	admin				1446
Wed Jul 27 00:28:30 COT 2016	Create Inventory Object	admin				1449
Wed Jul 27 00:32:08 COT 2016	Create Inventory Object	admin				1456
Wed Jul 27 00:37:59 COT 2016	Create Inventory Object	admin				1459
Wed Jul 27 00:38:01 COT 2016	Create Inventory Object	admin				1461
Wed Jul 27 00:38:41 COT 2016	Move object	admin				[1465] moved to object with id 1432 of class Rack
Wed Jul 27 00:39:13 COT 2016	Move object	admin				[1470] moved to object with id 1377 of class City

Figure 78: General events window

The figure 78 shows the window displayed after pressing the **Audit Trail** button  (or selecting the menu option Tools → Audit Trail). It shows the general events, paginated and chronologically sorted from the oldest to the newest event.





	Export to CSV file
	Retrieve all log entries (may take some time depending on the number of records)
	Previous page
	Next page

Table 5: Audit trail toolbar icons

The object-related audit trail window is very similar, but contains only the events related to the selected node. To see the audit trail, select a node in a tree or view, right-click on it and select the *Audit Trail* option.





Figure 79: Audit trail menu option

The result is not paginated, but can be exported to a CSV file.

Audit trail for RTR-DMT-004 [Router]					
Timestamp	Type	User	Property	Old value	New value
Wed Jul 27 00:40:48 COT 2016	Update Inventory Object	admin	name	RTR-DMT-003	RTR-DMT-004
Wed Jul 27 17:00:00 COT 2016	Update Inventory Object	admin	vendor		Cisco-

Figure 80: **Router** object audit trail

Topology Designer

Use this module to make sketches of your network, but using the equipment already created in the inventory. Most people use applications like MS Power Point™, MS Visio™ or a CAD program for this, but here it is already integrated. Use the button  in the main toolbar to open the designer.












	New topology
	Open topology
	Save topology
	Delete topology/Clear canvas
	Export topology to image file
	Select tool
	Connect tool
	Insert cloud
	Insert frame
	Add background
	Remove background

Table 6: Topology Designer toolbar icons

Important

The connections made using this module are not actual inventory objects (unlike those seen in the chapter **Physical Connections**), simply lines linking nodes.

For starters, drag objects from the **Navigation Tree** onto the canvas of the view. You can add equipment (routers, switches, multiplexers) or locations (buildings, outdoor cabinets, poles, etc). If you have previously set the *icon* of the classes the object you have dragged are instance of, it will be used, otherwise, a colored squared will be used instead to represent the nodes. In the figure 81 there are two routers and an object of class **ExternalEquipment**.







Figure 81: Sample topology without connections

You can add nodes that are not inventory objects, but that can help to decorate the topology. If you click the cloud button , a cloud will be added to the topology. If the Selection tool is activated , drag the nodes to position them as needed. You can also add a frame by clicking the frame button . The name of the nodes can be changed by double-clicking them. The label of a frame can also be changed by double-clicking its border.




Figure 82: Same topology, but adding a cloud and a frame

To resize a frame, click on a corner and drag until you get the desired size. To create connections, select the Connection tool and link two nodes as you did in the **Physical Connections** chapter.






Figure 83: Topology with connections

Don't forget to save the topology with pressing the Save button . If saved, this topology can be loaded later using the Open button .

Managing Software assets

With Kuwaiba is possible create software licenses and associate them to existing elements or to keep them in a temporary location until they are actually used. A software license can only be associated to instances of subclasses of class **GenericApplicationElement**




Figure 84: GenericApplicationElement in the the data model

By default the data model you will find the classes in the figure above, but of course, you can create as many more as you want and all of them will be enabled to be associated to software licenses. To customize the properties of a software license, just modify the SoftwareLicense class:




Figure 85: SoftwareLicense in the context of the data model

To associate a software license to an existing element, right click on it on the Navigation Tree and select Create software asset:




Figure 86: Adding a software license

This will open a new window right next to the Properties window with all the existing software assets associated to the element:




Figure 87: Software licenses associated to a given element and some properties

You can also manually open the *Special Children* window by going to the menu Tools *rightarrow* Navigation *rightarrow* Special Children. This explorer window can also be used to other things,

such as seeing the contents of a Physical Container (ducts, ditches, etc).
It's also possible to keep your spare licenses in a pool (see for more details **Pools Manager**)




Figure 88: A new license pool

And you can get something like this





Figure 89: Sample pool of software licenses

Service Manager

The Service Manager allows you to organize all the services in pools, this pools of services belong to customers, these customers are at the same time organized in pools. To open the Services Manager look in the menu for Tools → Service Manager or just click in the icon . To start using the Service Manager you must create a pool of customers, depending of the loaded data model you can create pools of HomeCustomer or CorporateCustomer or any subclass of GenericCustomer (see **Data Model Manager** if you need to create a different kind of customers).




Figure 90: Service Manager root node

Once you create your pool of customers you can create new customers, delete the created pool or show its id; as you can see in the **figure 91** you are able to create new customers of type CorporateCustomer or TelecommunicationsOperator ;why can we create new customers of the class TelecommunicationsOperator if the class of objects of the pool we created was CorporateCustomer? Well we can create customers of that class because TelecommunicationsOperator is a subclass of CorporateCustomer, this is defined in the data model, (see **Data Model Manager** if you need to adjust the model to your needs)




Figure 91: Pools service actions

Now you can create a pool of services inside a customer or delete the customer or show its id.




Figure 92: New service pool dialog

Every pool of service has a name and a description, this properties could be changed later in the property sheet, just selecting the pool of services and editing its the values of its attributes.




Figure 93: New service pool dialog

Once the pool of services had been created you are able to create services in it, just making right-click in the pool and selecting the kind of service you want to add, as we mention before if you need a new kind of service that is not listed just add it to your data model (see **Data Model Manager**).




Figure 94: Create new service

After you finish to create and organize all your customers and services in pools, you can go to the Navigation Tree (see **Navigation Tree**) or to the IP Address Manager (see ??), and relate objects to a service, as you can see in figure 95), just make right click in the object and select the action **Relate to service**,




Figure 95: Related an object to a service

Of course you are also able to release an object from a service, after associate an object to a service if you want to release that relationship you need to make right click in the object and select **Release from service**, if the object has a service associated this will be shown, if you click on it, the object won't be related to that service any more.




Figure 96: Release an object from a service

Every time you relate an object to a service, the object will appear as a son of the service in the Service Manager nodes as you can see in figure 97

Important

You be able to delete an object if the object is associate to a service, if you want to delete that object you should first release the relationship with the service.




Figure 97: Service related to a device

Contract Manager

This small module allows you to organize your contracts in pools and keep track of the expiration dates and service providers. To open it, use the menu option Tools → Advanced → Contract Manager.




Figure 98: Creating a Contract Pool

The contracts are stored in pools, so first, you need to create your contract structure. Right click on the root node and select *New Contract Pool*. Then, inside the pools create the contracts you want, and set their properties.

South Coast SDH Multiplexers [SupportContract] - Properties	
General	
creationDate	July 28, 2016
expirationDate	November 28, 2016
serviceProvider	UniSyx
description	Maintenance contracts for SDH multiplexers
startDate	May 27, 2016
name	South May 2016

	Sun	Mon	Tue	Wed	Thu	Fri	Sat
19	1	2	3	4	5	6	7
20	8	9	10	11	12	13	14
21	15	16	17	18	19	20	21
22	22	23	24	25	26	27	28
23	29	30	31				

Figure 99: Editing a contract

Important

If you are editing a date, so it can be set correctly, instead of just hitting the Enter key, change the focus to other attribute in the property sheet (that is, select another property with the mouse).

To create a service provider for the contracts, go to the **List Type Manager** and create an entry under **ServiceProvider**.



Figure 100: New service provider

Any inventory object can be subject to a contract. You can associate an element to an existing contract, right click on it and select the option *Associate to contract...* and select the desired one as shown in the figure 102.




Figure 101: Associate to contract option



Figure 102: Contract list

The new elements associated to a contract are also available in the Contract Manager window.




Figure 103: Elements associated to a contract

This association can be undone either from the **Navigation Tree** or the **Contract Manager** using the node's context menu.





Figure 104: Removing the association

Task Manager

The Task Manager is the early release of a complete automation and notification module. At this stage, you can create tasks, edit a script that will be executed and execute this task either on demand or associated to a Dashboard widget that will be loaded at user login time. To open the Task Manager, select the menu option Tools → Task Manager or press the button  in the main toolbar. Right-clicking the root node of the task tree will present a menu to create tasks. A task




Figure 105: Creating a new task

object has the following attributes

It is possible to subscribe users, so that they receive notifications with the result of the execution. Right-click on the task node, select the option *Subscribe users...* and pick a user from the list.




Figure 106: Subscribing a user

It is out of the scope of this document to teach how to code scripts, however, in the directory **scripts** of the client installer, you will find some samples to guide you through. It's important to note, though, that most of the times, the scripts will require input parameters. This parameters can be easily added to the task so the user can fill them in before to run the task. To create parameters, right-click the task node and select the option *Add Parameter...*




Figure 107: Adding a parameter

Once added, it will be immediately available in the property sheet, under the category *Task Parameters*.

name	The name of the task.
description	The description of the task.
enabled	Is this task enabled?
script	The Groovy script to be executed by this task.
startTime	The exact time and date this task should start its execution. Applicable only to tasks with <i>executionType</i> set to Loop. Not used yet.
everyXMinutes	After the start time, every how many minutes should this task be executed? Applicable only to tasks with <i>executionType</i> set to Loop. Not used yet.
executionType	How should the task be executed. <ul style="list-style-type: none"> • On Demand: Run only if the user executes it manually. • User Login: Run upon subscribed users login. • Loop: Run on a periodic basis, using the parameters described above. • System Startup: Run when the system goes up. <p>Currently, only <i>On Demand</i> and <i>User Login</i> are used</p>
email	The email of the person or group that will receive the notification. Optional. Not used yet.
notificationType	What type of notification should the subscribed users receive? <ul style="list-style-type: none"> • No Notification: No notification. • Client Managed: The client that executes the task decides how to notify. • Email: Send an email to the address described above. <p>Not used yet.</p>




Figure 108: Subscribing a user

Tasks can also be executed on-demand. To do that, select the *Execute Task* option from the task node's context menu.




Figure 109: Task execution

Important

The full set of methods available in a script can be found at
<http://kuwaiba.org/javadoc/persistence/org/kuwaiba/apis/persistence/interfaces/ApplicationEntityManager.html>

SDH Networks

This module allows to create end-to-end virtual circuits and all other logical entities required by the SDH protocol⁶. Let's introduce some concepts first. See figure 110 for sample connection that illustrate the following terms.

1. **TransportLink:** A point-to-point logical connection that represents a single STMX. By default, the **TransportLinks** included in Kuwaiba are SMT1, STM4, STM16, STM64 and STM256.
2. **ContainerLink:** It's a logical connection that may or may not have multiple hops and connects ports within the boundaries of the transport network. A **ContainerLink** ends where at least one **TransportLink** ends, but in its path, the **ContainerLink** may have used many **TransportLinks**. In simple terms, a ContainerLink is an SDH virtual circuit. By default there are defined 5 types of ContainerLinks: VC12, VC3, VC4, VC4x4 and VC4x16. The latter two provide support for concatenation.
3. **TributaryLink:** Objects of this types are not circuits themselves, they rather use actual virtual circuits (ContainerLinks) and end in the ports where the SDH service is delivered to the customer (usually tributary ports).

In short, Transport and ContainerLinks provide the foundations for the hierarchy, while the TributaryLinks provide information about where the circuits are delivered (that is, what are the end-points of the connections). Detailed information about the data model portion devoted to SDH, read the document *SDH Model and Tools*.

⁶SDH Graphical Overview <http://www.cisco.com/c/en/us/support/docs/optical/synchronous-digital-hierarchy-sdh/28327-sdh-28327.html>




Figure 110: Sample multi-hop SDH circuit and its relationships with services, customers and physical resources

To create an SDH topology, go to the menu option Tols → Advanced → SDH Networks. This will open an empty canvas similar to the Topology Designer.











	New topology
	Open topology
	Save topology
	Delete topology/Clear canvas
	Export topology to image file
	Select tool
	Connect tool
	Create a TransportLink
	Create a ContainerLink
	Create TributaryLink

Table 7: SDH module toolbar icons

Drag and drop the equipment you need from the Navigation Tree and place them on the canvas.




Figure 111: Some routers and multiplexers in an SDH topology

Let’s consider this 4 equipment topology. What we are going to do, is to create a ring using STM-4 on one branch and SMT-1 on the other. We will create a VC12 between **SDH-87** and **Router 1**. Each equipment has the same board/port layout: Two boards, a tributary and an aggregate one, with two ports each.






Figure 112: Port/board layout

First, we have to create the most basic support, that is the TransportLinks (STMX). Use the Connect tool  and press the Create TransportLink button . Then, just like the Topology Designer and the Physical Connections, drag a line from one equipment to the other. That will start a wizard.

To change the connection color, use the Data Model Manager. Select the class corresponding to the desired TransportLink and change the attribute *color*.




Figure 113: Changing the color for STM1 links

The first step of the wizard will request for the basic information: name and type




Figure 114: Creating a TransporLink, step 1

The second will request for the the connection endpoints, which will always be aggregate ports.




Figure 115: Creating a TransporLink, step 2

After repeating the procedure three more time, the ring will be finished. In the figure 116, the SMT4 links are colored light purple, while the SMT1 ones are blue.




Figure 116: SDH ring


The next level in the hierarchy is the set of structured high-order circuits (VC4) that will contain the E1s that we will add later. We will create three VC4: One long, **from SDH-87 to Router 1**, other short, from **SDH-87 to Router 2**, and finally another short between **Router 2 and Router 1**. This will provide two paths to route the E1s later on. To create the VC4 connections (a.k.a. ContainerLinks), we will leave the Connection tool selected and press the *Create ContainerLink* button . To create the first ContainerLink, let's drag a line between the **SDH-87** and the **Router 1**. That will start a wizard.

Figure 117: New ContainerLink, step 1

Again, the first step is about basic information: Container name and type. We will create a simple VC4. The next step is about routes. You will find two routes. In the center panel, the detail of the chosen route will be displayed.

Steps

1. Fill in the general information
2. Choose the route
3. Choose positions

Choose a route

Route 2 - 2 hops

▼

SDH-87 [SDHMux]
STM4 SDH-87 - Router 2 [STM4]
Router 2 [Router]
STM 4 Router 2 - Router 1 [STM4]
Router 1 [Router]

< Back

Next >

Finish

Cancel

Help

Figure 118: New ContainerLink, step 2

For this example, we're going to use the lower branch composed by the STM1 TransportLinks. The next step will ask you to define what timeslots will you use from each TransportLink in the route (figure 119). Since the TransportLinks are STM1, there will be only one slot available. To select the timeslot, double-click the desired STM, and select the timeslot from the list (figure 120).

Steps

1. Fill in the general information
2. Choose the route
3. Choose positions

Double click on a transport link to choose a position for this container

STM 1 SDH-87 - SDH-12 [STM1] - NA
STM1 SDH-12 - Router 1 [STM1] - NA

Figure 119: New ContainerLink, step 3

This list will be populated with the available timeslots, but besides, it will inform you what timeslots are already in use and who's using them.





Figure 120: New ContainerLink, step 2

Note that after choosing a timeslot the label next to the STM's name will change from *NA* to the number you chose. It's not necessary to select any endpoint ports, since they're taken from the underlying TransportLinks. Once created, you won't see anything different in the view, since the only connections to be displayed are the TransportLinks.

The last step is to create a TributaryLink, that is, the actual E1 to be delivered. For that, we have to press the Create Tributary button . As usual, drag a line between the end equipment, in this case, SDH-87 and Router 1. This will open another wizard.




Figure 121: New TributaryLink, step 1

In the next step, it's requested to pick a route. Note that the STM4-based route won't be offered, as it doesn't have ContainerLinks to transport the TributaryLink.




Figure 122: New TributaryLink, step 2

The third step consists of choosing the timeslot in the ContainerLink (VC4)




Figure 123: New TributaryLink, step 3

Again, by double-clicking the ContainerLink, you can pick a timeslot



Figure 124: Picking a timeslot from all the available ones in the ContainerLink(VC4)

The next step is choosing the endpoints. For this example, we're going to end the SDH connection in a tributary port of a PDHBoard. It, of course, could end in any port of any board, however this is the most common scenario.




Figure 125: Picking a timeslot from all the available ones in the ContainerLink(VC4)

Finally, as an option, you can associate the newly created TributaryLink to a service instance. Note that this list will be populated **only** with objects of subclasses of **GenericSDHService** previously created in the Service Manager, as seen in the figure 127.




Figure 126: Optionally, relating the circuit to a service

To see the resources used by the circuit, right-click on it either in the search results or the service manager and select the option Reports → TributaryLink Resources.




Figure 127: SDH service in the Service Manager and report execution

The result shows the timeslots, TransportLinks involved, end ports, services associated and optionally, demarcation points (next physically connected ports, usually in an ODF/DDF)

Tributary Link Details Report for E1 SDH-87 - Router 1



Name	E1 SDH-87 - Router 1
Type	VC12TributaryLink
Endpoint A	Router 1 [Router]:1
Endpoint B	SDH-87 [SDHMux]:1
Demarcation Points	
Service	Test SDH Service
Customer	Orange

Structured Name	Structured Position	Transport Links
STR SDH-87 - Router 1 [VC4]	29	1 - STM1 SDH-12 - Router 1 [STM1] 1 - STM 1 SDH-87 - SDH-12 [STM1]

This report is powered by [Kuwaiba Open Network Inventory](#)

Figure 128: Report results (zoom in to read better)

Important

As an exercise for the reader, create Container and TributaryLinks using the alternate STM4-based route.

IP Address Manager

The IP Address Manager(IPAM) let you store and manage your subnets and their IP addresses, kuwaiba let you integrate your IPAM to the whole network inventory allowing to relate the created subnets to existing VLANs or services, also allow you to associate the IP addresses of a subnet to an existing network device or service.

Once you open the IPAM manager you will finds two default nodes IPv4 and IPv6. These nodes has two actions you can create subnets or folders.




Figure 129: IP address manager root nodes actions

A folder is a way to store several subnetworks, you can create as many folders as you want, you can also create a folder inside other folder.




Figure 130: Create a new folder

Once you create a folder, you could edit its attributes, **name** and **description** in the property sheet just like any other element in kuwaiba




Figure 131: Folder actions

To add a new subnet IPv4 or IPv6 you should type the subnet in the Classless Inter-Domain Routing (CIDR) Format⁷.

For IPv4 address you could use 182.5.13.0/26 and will be accepted, remember de CIDR Format.

For a IPv6 address you could use a compress or a expand notation for example you could use 2000::/3 or 2000:0000:0000:0000:0000:0000:0000/3 both will be accepted.

⁷CIDR Format <http://ip2cidr.com/cidr.php>




Figure 132: Add Subnet

Once you have created a subnet you could add IP addresses




Figure 133: Subnet actions

Kuwaiba will put by default in text box the next no used ip address of the subnet, but you could type any IP address that belongs the subnet range, kuwaiba won't let you add the network IP or de broadcast IP.




Figure 134: Add IP address

The subnets can be associate to VLANs, just make right-click in the subnet and select *Relate to a VLAN* then kuwaiba will display a text dialog with a list of all the existing VLANs.

The subnets and the IP addresses can be associate to services, just make right-click in the subnet or the IP address and select *Relate to a service* then kuwaiba will display a dialog with a list of all the existing services (see **Service Manager**)

Note It won't be possible delete a subnet or an IP address if are associate to something else like a VLAN a service or a network device.




Figure 135: Available VLANs




Figure 136: Available Services

An IP addresses can be associate to network devices, just make right-click in the IP address and select *Relate to a device* then kuwaiba will display a text dialog with a list of all the existing network devices than had been created.




Figure 137: Available Devices

Once you create your folders, subnets and IP addresses and after associate them to services, VLANs or network devices, you generate a report about the subnet in the subnet's action menu, this report will give you a detail resume of the subnet usage, the services and VLANs associate to the subnet and every IP address added, the network devices associate to them.




Figure 138: Subnet usage report

User and Group Management

This feature lets you define new application users and relate/unrelate them from application groups. By default there is only one user (**admin**, password **kuwaiba**) and no groups. You can edit everything, even its username. The module shows three buttons at its own toolbar: **Add user:**




Figure 139: User/Group Management main window

Adds a new user. It's placed at the end of the list and its name is a composition of the string “user” and a random number between 0 and 10000. **Add groups:** Adds a new group. It's placed at the end of the list and its name is a composition of the string “group” and a random number between 0 and 10000. **Refresh:** Refreshes the selected tab (users or groups)





Figure 140: Deleting an user

If you want to delete an user or a group, just right click the element and choose *Delete*. Deleting a group won't delete the related users. If you want to change a user's password, click the button  in the *Password* or *Group* column and a custom editor will be shown.





Figure 141: Changing a password

If you want to change a user's password, click the button  in the “Password” or “Group” column and a custom editor will be shown.




Figure 142: Changing an user user group association

Currently is only possible to add/remove groups to/from a user (not vice versa)

Bulk import

Kuwaiba provides a way to import objects and list types from CVS text files with a define format. This module can be found at *Tools* → *Bulk Import*. Examples of these files are included in the client installer bundle under the directory *Samples*.

Load Objects

CLASS_N	P_CLASS_N	P_DIST_ATT_DEF	[ATT1_DEF]	[ATT2_DEF]	...
---------	-----------	----------------	------------	------------	-----

Table 8: File format to load objects

Important

- The separator between fields is the fixed string "~".
- All class and attribute names are case sensitive.
- You can comment lines using the fixed character "#" at the beginning of the line.

CLASS_N: Name of the class the object is instance of. **Example**: if you want to create a router, use *Router*.

P_CLASS_N: Name of the class the object will be created under. If the object should be created under the Navigation tree root, use the fixed string *root*. **Example**: If you want to create an object under a country, use *Country*.

P_DIST_ATT_DEF: The definition of the attribute used to search for the parent of the object. This field is composed by two parts: the name of the attribute of the parent and its value. These parts are separated by the fixed string "~" and the attribute can't be a list type because they are not used to uniquely identify an element. **Example**: if you want to create an object whose parent is, say, the country Germany, use "name~c~Germany".

The following fields are optional, and consist of the definition of the value of the attributes of the object:

ATTX_DEF: These fields are composed by two parts: the name of the attribute to be set and its value. These parts are separated by the fixed string "~". The second part (value) can be either a primitive type (string, number, boolean) or a reference to a list type. In this case, the value can be the name of such type or its id (a number).

Example 1: name~c~Atomium~t~owner~c~Government

Example 2: name~c~Atomium~t~owner~c~1002

Example 3: name~c~Port 1~t~enabled~c~true

Sample lines: Country~t~root~t~name~c~root~t~acronym~c~DE

#This is a comment

Router~t~Building~t~name~c~Build 1~t~serialNumber~c~123456

Important

If you plan to use the bulk import feature, avoid using numbers as list type names because they can be mistaken for ids.

Load List Types

The separator between fields is the fixed string "~". **CLASS_N**: Name of the class the listtype is instance of. **Example**: if you want to create a new type of cable, use *ElectricalLink*. For all

CLASS_N	[ATT1_DEF]	[ATT2_DEF]	...
---------	------------	------------	-----

Table 9: File format to load list types

possible values, refer to the Data Model Manager, under the class `GenenericObjectList`. The following fields are optional, and consist of the definition of the value of the attributes of the object:

ATTX_DEF: These fields are composed by two parts: the name of the attribute to be set and its value. These parts are separated by the fixed string `"~c~"`. The second part (value) can be either a primitive type (string, number, boolean) or a reference to a list type. In this case, the value can be the name of such type or its id (a number).

Sample line: `SoftwareType~t~name~c~Database~t~displayName~c~Database Engine`

Interface




Figure 143: Bulk import interface

The interface to upload the file has two tabs: One to import objects and the other to import list types: First select the file using the *Select file* button, then, to process the data, click on *Process file*. This can take from a few seconds to some minutes depending on the size of the file and the I/O constraints of your server. The result will be shown in the *Output* window. This window will be opened automatically, but if you close it by mistake, it's possible to reopen it from the menu option Window Output Output or by hitting CTRL+4

Only the errors and relevant information messages will be displayed. The output can be easily processed since the fields (message type, line number and message) are separated by tabs so it can be opened as a CSV file in a spreadsheet editor.




Figure 144: Import process output sample

Important

- The lines with no errors will be committed into the database. Make sure to comment out the lines uploaded correctly to avoid creating the same object many times.
- If you perform changes in file after loading it (that is, after pressing *Select file*), you will have to select it again so it can take the changes, otherwise, it will process the old file instead. To save the output messages, right-click the window.