

ATL-140

GNSS | GSM

Discover the power of the ATL-140, an ICAT certified AIS-140 vehicle tracker built to transform fleet management. With seamless Bluetooth connectivity, robust RS232 and CAN interfaces, 4 digital inputs, 3 digital outputs, and 2 analog inputs, it delivers end to end vehicle monitoring. Featuring internal high-gain GNSS and GSM antennas, 5 LED indicators, eSIM support, and memory for 80,000 log packets, the ATL-140 ensures reliable performance, optimized routes, reduced downtime, and effortless compliance across logistics, public transport, emergency services, and rental fleets.



Multiple IOs

**Internal High Gain
GSM & GNSS Antenna**

BLE 5.0 Powered*

IP65 Casing

1000mAh Battery

8-36V DC



Theft
Prevention



Security and
Surveillance



Vehicle Health
Parameter Monitoring



Logistics and
Supply Chain

INTERFACE

Digital Input	4
Digital Output	3
Analog Input	2
CAN	1*
RS232	1
GNSS & GSM Antenna	Internal High Gain Antennas
Indicators	5 LEDs (Power, Charging, GSM, GPS, MCU)
SIM	eSIM
Memory	80,000 Log Packets

NAVIGATION

GNSS	GPS, IRNSS, GLONASS, GALILEO, BDS, QZSS
Horizontal Position Autonomous	<1m CEP @Open Sky
SBAS	Supported
Tracking Sensitivity	-162 dBm
Re-acquisition Sensitivity	-158 dBm
Velocity	0.1 m/s CEP
Hot Start	1 sec
Warm Start	10 sec
Cold Start	30 sec

CELLULAR NETWORK

Technology	GSM
2G Band	850/900/1800/1900 MHz
RF Power	Class 4 (2W@850/900 MHz), Class 1 (1W@1800/1900 MHz)
Coding Scheme	CS 1, 2, 3, 4
SMS	Point to point MO & MT, SMS cell broadcast, Text and PDU mode

POWER

Voltage Range	8-36 V DC
Battery	1000 mAh Li-Po 3.7 V

BLUETOOTH

Specification	BLE 5.0*
Supported Peripherals	Temperature and Humidity sensor, Universal BLE sensors support, Beacons*

OPERATING ENVIRONMENT

Working Current	Sleep Mode < 5mA, Active Mode < 180mA
Operating Temperature	-20 °C to +60 °C (With Battery), -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C
Ingress Protection Rating	IP65

PHYSICAL SPECIFICATION

Dimensions	108 x 98 x 33 mm (L x W x H)
Weight	193 g

FEATURES

Sensors	3D Accelerometer & 3D Gyroscope
Scenarios	Overspeed detection, Manual Geofence, Unplug detection, Harsh Acceleration, Harsh Braking, Rush turning, Cabinet tamper detection, Battery low, Parameter setting alerts, SOS alerts
Sleep modes	Deep Sleep
Configuration and firmware update	FOTA Web, FOTA
SMS	Configuration, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Fuel monitoring	LLS (Analog, BLE & RS232)
Time Synchronization	GPS

*represents optional