

ATL-440

GNSS | LTE | BLE

ATL-440 is a next-generation 4G vehicle tracking device engineered for intelligent and uninterrupted fleet visibility. Featuring Bluetooth 5.0, wide high-voltage support, and IP67-rated protection, it delivers reliable performance in demanding conditions. With multiple I/O interfaces and AIS-140 compliance, it is ideal for logistics, public transport, heavy fleets, mining, construction, and regulated transportation operations.



Multiple IOs

**Internal High Gain
LTE & GNSS Antenna**

BLE 5.0 Powered

IP67 Casing

1000mAh Battery

9-90V DC



Heavy Construction
Machinery



Security and
Surveillance



Vehicle Health
Parameter Monitoring



Logistics and
Supply Chain

INTERFACE

DI, DO, AI	4, 4, 2
1-RPM/ Wire	1*
CAN	1
RS232	1
RS485	1*
GNSS/ LTE Antenna	Internal High Gain Antennas
Indicators	5 LEDs (Power, Charging, GSM, GPS, MCU)
SIM	eSIM
Memory	41,000 Log Packets

NAVIGATION

GNSS	GPS, IRNSS, GLONASS, GALILEO, BDS, QZSS
Horizontal Position Autonomous	<1m CEP @ Open Sky
SBAS	Supported
Tracking Sensitivity	-162 dBm
Re-acquisition Sensitivity	-158 dBm
Velocity	0.1 m/s CEP
Hot Start	<1 sec
Warm Start	< 10 sec
Cold Start	<30 Sec

CELLULAR NETWORK

2G Band	850,900,1800,1900 MHz
4G Band	B1,B3,B5,B7,B8,B20,B28,B38,B40,41
RF Power	Class 4 (2W@850/900 MHz), Class 1 (1W@1800/1900 MHz)
Coding Scheme	CS 1, 2, 3, 4
SMS	Point to point MO & MT, SMS cell broadcast

POWER

Voltage Range	9-90 V DC with overvoltage and reverse polarity protection
Battery	1000 mAh Li-Ion battery, 3.7 V (0.63 Wh)

BLUETOOTH

Specification	BLE 5.0
Supported Peripherals	All BLE Sensors Supported

OPERATING ENVIRONMENT

Working Current	Sleep Mode < 10mA, Active Mode < 180mA
Operating Temperature	-20 °C to +60 °C (With Battery), -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C
Ingress Protection Rating	IP67

PHYSICAL SPECIFICATION

Dimensions & Weight	90 x 112 x 41 mm (L x B x H) & 264g
---------------------	-------------------------------------

FEATURES

Sensors	3D Accelerometer & 3D Gyroscope
Scenarios	Overspeed detection, Manual Geofence, Unplug detection, Harsh Acceleration, Harsh Braking, Rush turning, Cabinet tamper detection, Battery low, Parameter setting alerts, SOS alerts
Sleep modes	Deep Sleep
Configuration and firmware update	FOTA Web, FOTA
SMS	Configuration, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GPS
Fuel monitoring	LLS (Analog, BLE & RS232)
Ignition detection	Digital Input1

*Optional