

E-101

GNSS | GSM

The E-101 Vehicle Tracker is a versatile and reliable device designed to simplify fleet management, vehicle security, and logistics operations. Ideal for transportation, taxi services, car rentals, and delivery fleets, it delivers accurate, real-time tracking and seamless system integration. With robust performance and easy deployment, the E-101 helps businesses improve operational efficiency, enhance security, and maintain complete control over their vehicle operations.



**HA / HB
Detection**

250 mAh Battery

**More than 15,000
Log Packets**

GSM Technology

Motion Sensor

8-36V Power Supply



**Theft
Prevention**



**Security and
Surveillance**



**Gig Worker
Tracking**



**Logistics and
Supply Chain**

INTERFACE

Digital Input	1
Digital Output	1
GNSS Antenna	Internal High Gain GNSS
Cellular Antenna	Internal High Gain GSM
Indicators	4 LEDs (Power, Charging, GSM, GPS)
SIM	Micro SIM
Memory	15,000+ Log Packets

NAVIGATION

GNSS	GPS, GAGAN, QZSS, BeiDou
Channels	32 tracking channels, 96 capture channels, 210 PRN channels
Horizontal Position Autonomous	< 2.5m CEP
SBAS	Supported
Tracking Sensitivity	-158 dBm
Re-acquisition Sensitivity	-156 dBm
Velocity	0.1m/s
Hot Start	< 1 sec
Warm Start	< 10 sec
Cold Start	< 35 sec

CELLULAR NETWORK

Technology	GSM
2G Band	850/900/1800/1900 MHz
RF Power	Class 4 (2W@850/900MHz), Class 1 (1W@1800/1900MHz)
Coding Scheme	CS 1, 2, 3, 4
SMS	Text
Data	GPRS Multislot Class

POWER

Voltage Range	8-36V DC
Battery	250mAh Li-Po 3.7V

OPERATING ENVIRONMENT

Working Current	Sleep Mode < 5mA, Active Mode < 100mA
Operating Temperature	-20 °C to +60 °C (With Battery) -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C

PHYSICAL SPECIFICATION

Dimensions	91 x 51 x 19 mm (L x B x H)
Weight	64 g

FEATURES

Sensors	Motion Sensor
Scenarios	Overspeeding, DOUT, Idling data
Configuration and firmware update	FOTA, SMS, GPRS Commands
SMS	Configuration, Events, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GPS
Ignition detection	Digital input 1

*represents optional