

EL-100

GNSS | GSM | BLE

The power-packed 2G vehicle tracking device is purpose-built for electric vehicle (EV) fleets, delivering reliable performance and intelligent insights. Featuring BLE connectivity, advanced battery analytics, and CAN bus support, it enables deep visibility into vehicle health, energy usage, and operational efficiency. With a wide 9–90V operating voltage range, the device supports diverse EV platforms and configurations. Designed for high-performance tracking and monitoring, it empowers fleet operators with real-time data, improved battery management, and greater control over EV fleet operations.



Multiple IO's

9-90V DC Voltage

BLE 5.0 Powered

**Internal High Gain
GSM & GNSS Antenna**

IP54 Casing

CAN Enabled



Energy Storage
System (ESS)



EV Fleet Management



Charging
Infrastructure



Smart Logistics

INTERFACE

Digital Input	2
Digital Output	2
Analog Input	1
CAN	1
1-Wire / 1-RPM	1
GNSS & GPS Antenna	Internal High Gain Antennas
USB	2.0 Micro USB
Indicators	4 LEDs (Charging, Power, GSM, GPS)
SIM	Micro SIM
Memory	32 Mb (17,000 packets on single IP)
CAN Protocol Support	All legislated OBD-II Protocols, Non-Legislated OBD Protocols & Heavy-Duty

NAVIGATION

GNSS	GPS, GAGAN, QZSS, BeiDou
Receiver	32 tracking channels, 96 capture channels, 210 PRN channels
Horizontal Position Autonomous	<2.5m CEP
SBAS	Supported
Tracking Sensitivity	-158 dbm
Re-acquisition Sensitivity	-156 dbm
Velocity	0.1 m/s
Hot Start, Warm Start, Cold Start	<1 sec, 10 sec, <35 sec

CELLULAR NETWORK

Technology	GSM
2G Band	850/900/1800/1900 MHz
RF Power	Class 4 (2W@850/900MHz), Class 1 (1W@1800/1900MHz)
Coding Scheme	CS 1, 2, 3, 4
SMS	Text

POWER

Voltage Range	9-90V DC
Battery	250mAh Li-Po 3.7V

BLUETOOTH

Specification	BLE 5.0
Supported Peripherals	Universal BLE sensors support, Beacons

OPERATING ENVIRONMENT

Working Current	Sleep Mode <25mA, Active Mode < 180mA
Operating Temperature	-20 °C to +60 °C (With Battery), -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C
Ingress Protection Rating	IP54

PHYSICAL SPECIFICATION

Dimensions	88x45x15 mm (LxBxH)
Weight	110g

FEATURES

Sensors	Accelerometer Supported
Scenarios	Overspeeding, DOUT, Unplug detection (Other alerts like excessive Idling, towing, geofence can be integrated)
Configuration and firmware update	FOTA, FOTA Web, Configuration over USB & BLE
SMS	Configuration, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GPS
Ignition detection	Digital Input1