

EL-400

GNSS | LTE | BLE

The EL-400 is a power-packed 4G LTE Cat-1 vehicle tracking device designed specifically for electric vehicle (EV) fleets. With advanced 4G connectivity, 2G fallback, and Bluetooth support, it ensures reliable, uninterrupted data transmission across diverse operating conditions. Featuring a wide high-voltage operating range and CAN bus support, the EL-400 delivers deep insights into battery performance, energy usage, and vehicle health. Built for high-performance EV tracking, it empowers fleet operators with real-time visibility, smarter battery management, and greater control over their electric mobility operations.



Multiple IO's

9-90V DC Voltage

BLE 5.0 Powered

**Internal High Gain
LTE & GNSS Antenna**

IP54 Casing

CAN Enabled



Energy Storage
System (ESS)



EV Fleet Management



Charging
Infrastructure



Smart Logistics

INTERFACE

Digital Input	3
Digital Output	2
Analog Input	1
CAN	1
1-Wire	1
RS232	1
GNSS & LTE Antenna	Internal High Gain Antennas
USB	2.0 Micro USB
Indicators	4 LEDs (Power, GSM, GNSS, Charging)
SIM	Nano SIM
Memory	64Mb
CAN Protocol Support	All legislated OBD-II Protocols, Non-Legislated OBD Protocols & Heavy-Duty

NAVIGATION

GNSS Constellations	GPS, GLONASS, BeiDou, QZSS, GALILEO
Channels	47 Tracking Channels
Horizontal Position Autonomous	1.5m CEP
Tracking Sensitivity	-166 dBm
Re-acquisition Sensitivity	-159 dBm
Velocity	0.1 m/s
Hot Start	1 sec
Warm Start	2 sec
Cold Start	15 sec

CELLULAR NETWORK

Technology	LTE CAT1, GSM
2G Band	EG915U-CN (900/1800 MHz), EG915U-EU (850/900/1800/1900 MHz), EG915U-LA (850/900/1800/1900 MHz)
4G LTE Bands	EG915U-CN : LTE FDD: B1/B3/B5/B8, LTE TDD: B34/B38/B39/B40/B41; EG915U-EU : LTE-FDD: B1/ 3/ 5/ 7/ 8/ 20/ 28; EG915U-LA : LTE-FDD: B2/3/4/5/7/8/28/66
RF Power	EG915U-CN (EGSM900: Class 4 (33 dBm $\pm$ 2 dB), DCS1800: Class 1 (30 dBm $\pm$ 2 dB), LTE-FDD: Class 3 (23 dBm $\pm$ 2 dB), LTE-TDD: Class 3 (23 dBm $\pm$ 2 dB)); EG915U-EU & LA (GSM850/EGSM900: Class 4 (33 dBm $\pm$ 2 dB), DCS1800/PCS 1900: Class 1 (30 dBm $\pm$ 2 dB), LTE-FDD: Class 3 (23 dBm $\pm$ 2 dB))
Coding Scheme	CS 1, 2, 3, 4

POWER

Voltage Range	9-90V DC
Internal Battery	260mAh Li-Po 3.7V

BLUETOOTH

Specification	BLE 5.0
Supported Peripherals	Universal BLE sensors support, Beacons

OPERATING ENVIRONMENT

Working Current	Sleep Mode < 25mA, Active Mode < 160mA @ 12V
Operating Temperature	-20 °C to +60 °C (With Battery), -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C
Ingress Protection Rating	IP54

PHYSICAL SPECIFICATION

Dimensions & Weight	88x45x15 mm (LxBxH) & 71g
---------------------	---------------------------

FEATURES

Sensors	Accelerometer Supported
Sleep modes	Deep Sleep
Configuration and firmware update	FOTA Web, FOTA, Configuration Tool(USB, BLE)
SMS	Configuration, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GPS
Fuel Sensors	LLS (Analog/BLE/RS232), Built-in CAN

*represents optional