

EL-440

GNSS | LTE | BLE

The EL-440 is a top-spec vehicle tracking device built around advanced CAN capability, enabling deep access to vehicle data across multiple CAN protocols. With 4G connectivity, Bluetooth, and high-gain internal GNSS and LTE antennas, it ensures reliable real-time data transmission and monitoring. Designed for modern fleet and vehicle intelligence applications, the EL-440 delivers precise insights, stability, and performance where a wide range of vehicle parameters are required to be monitored.



Multiple IOs

9-90V DC Voltage

BLE 5.0 Powered

**Internal High Gain
LTE & GNSS Antenna**

IP67 Casing

1000mAh Battery



Heavy Construction
Machinery



Security and
Surveillance



Vehicle Health
Parameter Monitoring



Logistics and
Supply Chain

INTERFACE

DI, DO, AI	4, 4, 2
CAN	2
1-Wire	1
RS232/RS485	1/1*
GNSS & LTE Antenna	Internal High Gain Antennas
USB	2.0 Micro USB
Indicators	4 LEDs (Power, LTE, GPS, Charging)
SIM	Micro SIM or eSIM
Memory	64Mb

NAVIGATION

GNSS	GPS, GLONASS, GALILEO, BeiDou, QZSS
Channels	47 Tracking Channels
Horizontal Position Autonomous	1.5m
SBAS	Supported
Tracking Sensitivity	-166 dBm
Re-acquisition Sensitivity	-159 dBm
Velocity	0.1m/s
Hot Start	1 sec
Warm Start	2 sec
Cold Start	15 sec

CELLULAR NETWORK

Technology	LTE CAT1, GSM
2G Band	EG915U-CN(900/1800 MHz), EG915U-EU(850/900/1800/1900 MHz), EG915U-NA(850/900/1800/1900 MHz)
4G LTE Bands	EG915U-CN: LTE FDD: B1/B3/B5/B8, LTE TDD: B34/B38/B39/B40/B41; EG915U-EU: LTE-FDD: B1/ 3/ 5/ 7/ 8/ 20/ 28; EG915U-NA: LTE-FDD: B2/3/4/5/7/8/28/66
RF Power	EG915U-CN(EGSM900: Class 4 (33 dBm $\pm$ 2 dB),DCS1800: Class 1 (30 dBm $\pm$ 2 dB), LTE-FDD: Class 3 (23 dBm $\pm$ 2 dB), LTE-TDD: Class 3 (23 dBm $\pm$ 2 dB)); EG915U-EU & NA(GSM850/EGSM900: Class 4 (33 dBm $\pm$ 2 dB), DCS1800/PCS 1900: Class 1 (30 dBm $\pm$ 2 dB), LTE-FDD: Class 3 (23 dBm $\pm$ 2 dB))
Coding Scheme	CS 1, 2, 3, 4
SMS	Point to point MO & MT, SMS cell broadcast

POWER

Voltage Range	9-90V DC
Battery	1000mAh Li-Po 3.7V

BLUETOOTH

Specification	BLE 5.0
Supported Peripherals	Temperature & Humidity sensor, Universal BLE sensors support, Beacons

OPERATING ENVIRONMENT

Operating Temperature	-20 °C to +60 °C (With Battery), -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C
Ingress Protection Rating	IP67
Battery charge temperature	0 °C to +45 °C
Battery discharge temperature	-20 °C to +60 °C
Battery storage temperature	-20 °C to +45 °C for 1 month, -20 °C to +35 °C for 6 months

PHYSICAL SPECIFICATION

Dimensions & Weight	90x112x41 mm (LxBxH), 210 g
---------------------	-----------------------------

FEATURES

Sensors	3D Accelerometer & 3D Gyroscope
Scenarios	Overspeed detection, Manual Geofence, Unplug detection, Harsh Acceleration, Harsh Braking, Rush turning, Cabinet tamper detection, Battery low, Parameter setting alerts, SOS alerts
Sleep modes	Deep Sleep

*represents optional