

GWC-100

IOT Gateway

GWC-100 is a robust IoT gateway engineered for reliable data communication and device integration. Featuring LTE, GNSS, Wi-Fi, and BLE connectivity, along with CAN support, an Ethernet interface, wide high-voltage operating range, and extended battery life, it delivers stable performance for connected mobility and industrial IoT environments.



**2 USB Ports:
Type-C and Type-B**

**LTE, BLE & WIFI
Connectivity**

2000 mAh Battery

9-90V DC Voltage

IP65 Casing

Ethernet Port



Logistics and
Supply Chain



Gensets
Monitoring



Energy Storage
System (ESS)



Mobile Tower
Data Monitoring

INTERFACE

CAN	CAN FD – All protocol standards supported
USB	2 USB Ports: Type-C and Type-B
Antenna	Internal antennas for LTE, GNSS, Wi-Fi, BLE
SIM	Plastic SIM, Optional eSIM

NAVIGATION

GNSS	GPS, BeiDou
Frequency	L1 Frequency

POWER

Voltage Range	9-90V DC
Battery	2000mAh @ 3.7V

PHYSICAL SPECIFICATION

Dimensions & Weight	90 × 32 × 120 mm (L × B × H) & 150 g
---------------------	--------------------------------------

CONNECTIVITY

Technology	CAT LTE with 2G fallback
4G Band	LTE-FDD Bands: B1/B3/B5/B8 LTE-TDD Bands: B34/B38/B39/B40/B41
2G Band	B3/B8
Wi-Fi	2.4 GHz, 802.11b (RX supported)
Bluetooth	BLE 5.0 supported – Compatible with all kinds of sensors
Ethernet	Supported

FEATURES

FOTA (Firmware Over the Air)	Supported
Built-in HSM	Yes (for secure cryptographic operations)
Tracking	GNSS Based Live Tracking
WIFI	Hotspot Supported*
ELD Feature	Supported*
OTA	Supported

*represents optional