

L-400

GNSS | LTE | BLE

Discover advanced 4G vehicle telematics with the L-400 Tracking Device, built for enhanced visibility and control. Featuring reliable 4G connectivity, bluetooth support, and a durable IP54-rated casing, it is ideal for fleet management, supply chain optimization, cold chain logistics, and vehicle tracking. With 4 digital inputs, 1 digital output, 1 ADC, and 1-Wire/RS232/RS485 support, the L-400 enables easy integration with vehicle systems and sensors. Designed for industries such as e-commerce, pharmaceuticals, food and beverage, agriculture, and healthcare, it delivers accurate, real-time location monitoring and operational efficiency.



Multiple IOs

**Internal High Gain
LTE & GNSS Antenna**

BLE 5.0

8-55V Power Supply

**250mAh Li-Po 3.7V
Battery**

IP54 Rugged Casing



Emergency
Vehicles



Boiler Monitoring
System



Industrial
IOT Solutions



Cold Chain
Supply Management

INTERFACE

Digital Input	4
Digital Output	1
ADC	1
1-Wire/RS232/RS485	1*
GNSS & LTE Antenna	Internal High Gain Antennas
Indicators	4 LEDs (Power, GSM, GPS, Charging)
SIM	Micro SIM
USB	2.0 Micro USB
Memory	25,000+ Log Packets

NAVIGATION

GNSS	GPS, GLONASS, BeiDou
Horizontal Position Autonomous	< 2m CEP
SBAS	Supported
Tracking Sensitivity	-161 dBm
Re-acquisition Sensitivity	-158 dBm
Velocity	< 0.1 m/s
Hot Start	< 1 sec
Warm Start	< 30 sec
Cold Start	< 40 sec

CELLULAR NETWORK

Technology	LTE with 2G fallback
4G Band	B1,B3,B5,B8,B34,B38,B39,B40,B41
2G Band	900/1800MHz
RF Power	EGSM900: Class 4(33dBm $\pm$ 2dB) , DCS1800: Class 1(30dBm $\pm$ 2dB) , LTE Power Level 3(23dBm $\pm$ 2.7dB)
Coding Scheme	CS 1, 2, 3, 4

POWER

Voltage Range	8-55V DC
Battery	250mAh Li-Po 3.7V

BLUETOOTH

Specification	BLE 5.0
Supported Peripherals	TPMS, FLS, Beacons, Etc.

OPERATING ENVIRONMENT

Working Current	Active Mode < 120mA
Operating Temperature	-20 °C to +60 °C (With Battery), -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C
Ingress Protection Rating	IP54

PHYSICAL SPECIFICATION

Dimensions	100 x 54 x 17 mm (L x B x H)
Weight	79 g

FEATURES

Sensors	Supported
Scenarios	Overspeeding, DOUT, Unplug detection
Configuration and firmware update	FOTA, Configuration over USB & BLE
SMS	Configuration, Events, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GPS, NTP
Fuel monitoring	LLS

*represents optional