

LC-401

GNSS | LTE

The LC-401 Smart Vehicle Tracker delivers reliable vehicle security, tracking, and fleet management in a compact, high-performance design. With mutiple IOs, it allows monitoring of ignition or AC status and remote immobilization for enhanced control. Equipped with a high-gain internal antenna, the LC-401 ensures accurate real-time tracking, making it an essential tool for modern fleet operations.



**Monitoring
Harsh Braking**

**Monitoring
Harsh Acceleration**

**More than 4500
Log Packets**

Multiple IOs

**Internal High Gain
LTE & GNSS Antenna**

9-90V Power Supply



Fleet Management &
Route Monitoring



Security and
Surveillance



Gig Worker
Tracking



Logistics and
Supply Chain

INTERFACE

Digital Input	2+1*
Digital Output	1
ADC	1
GNSS Antenna	Internal High Gain GNSS
Cellular Antenna	Internal High Gain LTE
Indicators	2 LED's (Green: GSM, Blue: GPS)
SIM	Micro SIM & eSIM*
Memory	4500+ data packet

NAVIGATION

GNSS	GPS, GLONASS, BeiDou, Galileo, QZSS
Horizontal Position Autonomous	2m
Tracking Sensitivity	-165 dBm
Re acquisition Sensitivity	-157 dBm
Hot Start	2 sec
Cold Start	28 sec

CELLULAR NETWORK

Technology	LTE CAT 1
4G Band	FDD LTE: B1, B3, B5, B8, B34, TDD LTE: B38, B39, B40, B41
Output Power	LTE-TDD: Class 3 (23dBm ±2dB) , LTE-FDD: Class 3(23dBm ±2dB)

POWER

Voltage Range	9-90V DC
Battery	45mAh Li-Po 3.7V

OPERATING ENVIRONMENT

Working Current	Active Mode 60mA
Operating Temperature	-20 °C to +60 °C (With Battery), -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C

PHYSICAL SPECIFICATION

Dimensions	91 x 52 x 19.5 mm (L x B x H)
Weight	65 g

FEATURES

Scenarios	Rash Driving, Over Speeding detection, DOUT Control , Idling detection, Unplug detection, Trip
Configuration and firmware update	FOTA Web, FOTA, Configuration Tool (USB)
SMS	Configuration, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GPS